



OASIS ebXML Messaging Services 3.0 Conformance Profiles

Committee Specification 01

24 April 2010

Specification URIs:

This Version:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cs-01.pdf>
(Authoritative)

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cs-01.html>

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cs-01.odt>

Previous Version:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cd-04.pdf>
(Authoritative)

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cd-04.html>

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles-cd-04.odt>

Latest Version:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles.pdf>

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles.html>

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/profiles/200707/ebms3-confprofiles.odt>

Technical Committee:

OASIS ebXML Messaging Services TC

Chair:

Ian Jones, British Telecommunications plc <ian.c.jones@bt.com>

Editor:

Jacques Durand, Fujitsu Computer Systems <jdurand@us.fujitsu.com>

Related Work:

This specification is related to:

- [OASIS ebXML Messaging Services Version 3.0: Part 1, Core Specification](#)

Declared XML Namespace:

<http://docs.oasis-open.org/ebxml-msg/ns/ebms/v3.0/profiles/200707>

32 **Abstract:**

33 This document is a **supplement** to the ebMS-3 specification [ebMS3]. It defines some
34 conformance profiles that support specific messaging styles or context of use. Future releases of
35 this document are likely to be augmented with additional conformance profiles that reflect the
36 choices or needs of user communities. As a pre-condition to interoperability it is necessary for
37 two implementations to agree on which common conformance profile, or which compatible
38 conformance profiles, they will comply with. This document and its future releases is intended as
39 a medium to publish conformance profiles that users and products will claim compliance with.

40 **Status:**

41 This document was last revised or approved by the ebXML Messaging Services Committee on
42 the above date. The level of approval is also listed above. Check the "Latest Version" or "Latest
43 Approved Version" location noted above for possible later revisions of this document.

44 Technical Committee members should send comments on this specification to the Technical
45 Committee's email list. Others should send comments to the Technical Committee by using the
46 "Send A Comment" button on the Technical Committee's web page at
47 <http://www.oasis-open.org/committees/ebxml-msg/>

48 For information on whether any patents have been disclosed that may be essential to
49 implementing this specification, and any offers of patent licensing terms, please refer to the
50 Intellectual Property Rights section of the Technical Committee web page at
51 <http://www.oasis-open.org/committees/ebxml-msg/ipr.php>

52 The non-normative errata page for this specification is located at
53 <http://www.oasis-open.org/committees/ebxml-msg/>

Notices

54

55 Copyright © OASIS® 2010. All Rights Reserved.

56 All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual
57 Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website.

58 This document and translations of it may be copied and furnished to others, and derivative works that
59 comment on or otherwise explain it or assist in its implementation may be prepared, copied, published,
60 and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice
61 and this section are included on all such copies and derivative works. However, this document itself may
62 not be modified in any way, including by removing the copyright notice or references to OASIS, except as
63 needed for the purpose of developing any document or deliverable produced by an OASIS Technical
64 Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be
65 followed) or as required to translate it into languages other than English.

66 The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors
67 or assigns.

68 This document and the information contained herein is provided on an "AS IS" basis and OASIS
69 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY
70 WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY
71 OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A
72 PARTICULAR PURPOSE.

73 OASIS requests that any OASIS Party or any other party that believes it has patent claims that would
74 necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard,
75 to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to
76 such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that
77 produced this specification.

78 OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of
79 any patent claims that would necessarily be infringed by implementations of this specification by a patent
80 holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR
81 Mode of the OASIS Technical Committee that produced this specification. OASIS may include such
82 claims on its website, but disclaims any obligation to do so.

83 OASIS takes no position regarding the validity or scope of any intellectual property or other rights that
84 might be claimed to pertain to the implementation or use of the technology described in this document or
85 the extent to which any license under such rights might or might not be available; neither does it
86 represent that it has made any effort to identify any such rights. Information on OASIS' procedures with
87 respect to rights in any document or deliverable produced by an OASIS Technical Committee can be
88 found on the OASIS website. Copies of claims of rights made available for publication and any
89 assurances of licenses to be made available, or the result of an attempt made to obtain a general license
90 or permission for the use of such proprietary rights by implementers or users of this OASIS Committee
91 Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no
92 representation that any information or list of intellectual property rights will at any time be complete, or
93 that any claims in such list are, in fact, Essential Claims.

94 The names "OASIS", ebXML, ebXML Messaging Services, ebMS are trademarks of [OASIS](http://www.oasis-open.org), the owner
95 and developer of this specification, and should be used only to refer to the organization and its official
96 outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving
97 the right to enforce its marks against misleading uses. Please see
98 <http://www.oasis-open.org/who/trademark.php> for above guidance.

99

Table of Contents

100	1 Introduction.....	5
101	1.1 Terminology.....	6
102	1.2 Normative References.....	6
103	1.3 Non-normative References.....	7
104	2 The Gateway Conformance Profile.....	8
105	2.1 Purpose.....	8
106	2.2 Conformance Profile: Gateway RM V3.....	8
107	2.2.1 Feature Set.....	8
108	2.2.2 WS-I Conformance Requirements.....	10
109	2.2.3 Processing Mode Parameters.....	11
110	2.3 Conformance Profile: Gateway RX V3.....	14
111	2.3.1 Feature Set.....	14
112	2.3.2 WS-I Conformance Requirements.....	14
113	2.3.3 Processing Mode Parameters.....	15
114	2.4 Conformance Profile: Gateway RM V2/3.....	15
115	2.4.1 Feature Set.....	15
116	2.4.2 WS-I Conformance Requirements.....	18
117	2.4.3 Processing Mode Parameters.....	18
118	2.5 Conformance Profile: Gateway RX V2/3.....	18
119	2.5.1 Feature Set.....	18
120	2.5.2 WS-I Conformance Requirements.....	19
121	2.5.3 Processing Mode Parameters.....	19
122	3 Examples of Alternate Conformance Profiles.....	20
123	3.1 Purpose.....	20
124	3.2 Conformance Profile: Light Handler (LH-RM CP).....	20
125	3.2.1 Feature Set.....	20
126	3.2.2 WS-I Conformance Requirements.....	21
127	3.3 Conformance Profile: Activity Monitor (AM-CP).....	21
128	3.3.1 Feature Set.....	21
129	3.3.2 WS-I Conformance Requirements.....	22
130	Appendix A Conformance Profile Template and Terminology.....	23
131	Appendix B Acknowledgments.....	25
132	Appendix C Revision History.....	26
133		

134

1 Introduction

135

136 The intent of the core ebMS-3 specification [ebMS3] is to provide a stable, normative framework for
137 developers to work with, but is not sufficient for guaranteeing “out-of-the-box” interoperability between
138 conforming implementations. The specification contains options and makes use of third-party
139 specifications for which more than one alternative may exist (e.g. SOAP 1.1 vs SOAP 1.2).
140 Implementations of ebMS-3 must generally settle on some of these options in order to interoperate. The
141 main specification intentionally does not prescribe which ones should be used by an implementation: it is
142 the role of conformance profiles to do so. The notion of conformance profile used here has been defined
143 in [QAFrameW].

144 Different user communities may elect to use different conformance profiles, reflecting different sets of
145 options. Or, they may decide to use different versions of referred third-party specifications that are still in
146 transition at the time the core specification is written (e.g. SOAP, and WSS). These elections – which may
147 evolve over time and are more dependent on usage patterns than the core specification - are captured by
148 conformance profiles. Because conformance profiles are dependent on the needs and choices of user
149 communities, and because they may evolve faster than the underlying core specification (here ebMS-3) -
150 i.e. some profiles will get deprecated, or new ones will appear - it is preferable that they are not defined
151 in the core specification which is expected to remain a stable reference. Instead, conformance profiles are
152 specified in a separate document that is not part of the standard and is easier to update.

153 Future releases of the present document are likely to be augmented with additional conformance profiles
154 that reflect the choices or needs of user communities. This document intends to serve as a medium for
155 publishing such conformance profiles. Conformance profiles only refer to selected options and features
156 that are already described in a normative way in the ebMS-3 specification: **it is possible to conform to the
157 core ebMS-3 specification without conforming to one of its profiles, but conforming to one of the profiles
158 described here implies conformance to the core ebMS-3 specification.**

159 Section 2 introduces a conformance profile – the “Gateway profile” that lists the features expected of a
160 Message Service Handler (MSH) acting as e-Business or e-Government gateway to back-end systems.

161 Although wide-scale interoperability is best served by having all users adopt a single profile, at the time
162 this document is written there are two transitional aspects that call for temporary definitions of some
163 variants of the Gateway profile:

- 164 ● There is today a significant user base for ebMS V2. Given the disruptive leap from V2 to V3
165 (largely due to convergence with Web services protocols), there is a need for a multi-version
166 profile supporting both (V2+V3). Conforming implementations will be able to interact both with
167 partners using V2 and partners using V3.
- 168 ● There exist two largely equivalent specifications for reliable messaging: (a) WS-Reliability 1.1 and
169 (b) WS-ReliableMessaging. (a) has been an OASIS standard for several years, has been tested
170 and implemented by communities of users, notably in Asia. (b) is a more recent standard, still
171 awaiting for WS-I interoperability guidance, but enjoying a broad support among US-based
172 companies.

173 These transitional aspects are likely to vanish in the long run, but they call for supportive conformance
174 profiles for the time being. As a result, the following variants of the gateway profile are defined here:

175

- 176 ● **Gateway RM V2/3:** supporting both ebMS V2 and V3, using WS-Reliability1.1 (produced by the
177 WSRM OASIS TC) as reliable messaging specification.
- 178 ● **Gateway RM V3:** supporting ebMS V3 exactly in the same way as the previous RM V2/3 profile,
179 but not requiring support for V2. Conformance to Gateway RM V2/3 implies conformance to
180 Gateway RM V3.

- 181 ● **Gateway RX V2/3:** supporting both ebMS V2 and V3 with same features as Gateway RM V2/3,
182 except that it uses WS-ReliableMessaging (produced by the WS-RX OASIS TC) as reliable
183 messaging specification.
- 184 ● **Gateway RX V3:** supporting ebMS V3 exactly in the same way as the previous RX V2/3 profile,
185 but not requiring support for V2. Conformance to Gateway RX V2/3 implies conformance to
186 Gateway RX V3.

187

188 *NOTE: It is certainly possible for an implementation or product to support all these conformance profiles*
189 *simultaneously. As already mentioned, a product conforming to Gateway RM V2/3 or RX V2/3 will*
190 *automatically conform respectively to Gateway RM V3 or RX V3. In addition, an MSH implementation can*
191 *conform to both Gateway RM V2/3 and Gateway RX V2/3, by simply alternating at run-time between the*
192 *two reliability modules used for RM and RX. This run-time assignment may be implemented in various*
193 *ways, e.g. by using a different URL, or by associating a particular reliability processing with specific user*
194 *data (e.g. originating party ID). The P-Mode would be the place where to specify which reliability mode is*
195 *to be associated with a particular message content.*

196 Prior experience in diverse communication sectors (e.g. TVs, cell phones and messaging middleware)
197 has shown that adoption is best promoted by facilitating local or “regional” interoperability first – i.e. by
198 recognizing that different communities of users may have different requirements and therefore adoption
199 paths. These would be served by different conformance profiles. Then in a second phase, global
200 interoperability needs will push for some consolidation, meaning convergence toward a core conformance
201 profile elected by all.

202 In addition to defining an e-Business / e-Government Gateway profile and its transitional variants, the
203 role of this document is to provide some framework and notation for defining additional profiles, a couple
204 of which are provided as examples.

205 1.1 Terminology

206 The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD
207 NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this specification are to be interpreted as
208 described in IETF RFC 2119.

209 1.2 Normative References

- | | | |
|-----|-------------------|---|
| 210 | [ebMS2] | OASIS Standard, <i>OASIS ebXML Message Service Specification Version 2.0</i> ,
211 April 1, 2002. <a href="http://www.oasis-open.org/committees/ebxml-
msg/documents/ebMS_v2_0.pdf">http://www.oasis-open.org/committees/ebxml-
msg/documents/ebMS_v2_0.pdf |
| 213 | [ebMS3] | OASIS Standard, <i>OASIS ebXML Messaging Services, Version 3.0: Part 1, Core
214 Features</i> , 2007. <a href="http://docs.oasis-open.org/ebxml-
msg/ebms/v3.0/core/ebms_core-3.0-spec.pdf">http://docs.oasis-open.org/ebxml-
msg/ebms/v3.0/core/ebms_core-3.0-spec.pdf |
| 216 | [RFC 2119] | S. Bradner. <i>Key words for use in RFCs to Indicate Requirement Levels</i> . IETF
217 RFC 2119, March 1997. http://www.ietf.org/rfc/rfc2119.txt |
| 218 | [UCC-MS2] | <i>UCC/EAN Basic Reliable ebXML Messaging v2.0 Interoperability Testing</i> , 2002. |
| 219 | [WSIAP10] | <i>WS-I Attachment Profile V1.0</i> , Web-Services Interoperability Consortium, 2007.
220 http://www.ws-i.org/deliverables/workinggroup.aspx?wg=basicprofile |
| 221 | [WSIBP12] | <i>WS-I Basic Profile V1.2 (draft)</i> , Web-Services Interoperability Consortium, 2007.
222 http://www.ws-i.org/deliverables/workinggroup.aspx?wg=basicprofile |
| 223 | [WSIBSP11] | Abbie Barbir, et al, eds, <i>Basic Security Profile Version 1.1</i> , Web-Services
224 Interoperability Consortium, 2006.
225 http://www.wsi.org/Profiles/BasicSecurityProfile-1.1.html |

226 **[ebBP-SIG]** OASIS ebXML Business Process TC, *ebXML Business Signals Schema*, 2006.
227 <http://docs.oasis-open.org/ebxml-bp/ebbp-signals-2.0>
228

229 **1.3 Non-normative References**

230 **[QAFrameW]** Karl Dubost, et al, eds, *QA Framework: Specification Guidelines*, 2005.
231 <http://www.w3.org/TR/qaframe-spec/>
232

233

2 The Gateway Conformance Profile

234

2.1 Purpose

235 The *Gateway* conformance profile (or G-CP) is the baseline for conducting electronic business. G-CP
236 addresses the messaging requirements of most enterprise e-Business or e-Government gateways.

237 It is expected that user communities will generate variants of the G-CP profile that differ by their
238 interoperability parameters, e.g. a variant that uses a transport other than HTTP. Also, the Gateway
239 messaging function may evolve over time to reflect an evolution of the enterprise gateway requirements
240 among the user community. A line of evolution is along the versions of the underlying specifications used
241 by ebMS V3.0, in particular SOAP and WSS. After careful consideration at the time the ebMS V3.0
242 specification is finalized, the following versions have been selected for G-CP:

- 243 • SOAP 1.2 has been selected because of support by most SOAP stacks (most of these stacks
244 also support SOAP 1.1).
- 245 • Both WSS 1.0 and WSS 1.1. Although 1.1 is too recent to be broadly supported by implementers,
246 this version supports security of attachments. While G-CP mandates support for both, the version
247 to be used for a particular exchange or with a particular partner can still be specified in the
248 processing mode (P-Mode). This makes it possible for a partially conforming implementation to
249 interoperate with others.

250 As mentioned in the introduction, G-CP comes in four variants, called here transitional variants. The first
251 one to be described here is Gateway RM V3, based on the WS-Reliability1.1 standard for reliable
252 messaging.

253

2.2 Conformance Profile: Gateway RM V3

254 The Gateway RM V3 is identified by the URI:

255 <http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/gateway-rmv3>

256 **This section identifies the requirements for conforming to this profile.**

257

2.2.1 Feature Set

258 Gateway RM V3 is defined as follows, using the table template and terminology provided in Appendix F
259 (“Conformance”) of the core ebXML Messaging Services V3.0 specification [ebMS3].

260

Conformance Profile: Gateway RM V3	Profile summary: <“Sending+Receiving” / “ gateway-rmv3” / Level 1 / HTTP1.1 + SOAP 1.2 + WSS1.1 + WS-Reliability 1.1 >
Functional Aspects	Profile Feature Set
ebMS MEP	<p>The implementation MUST support all ebMS simple MEPs, in either Sender or Receiver role:</p> <ul style="list-style-type: none"> • One-way / Push, • One-way / Pull,

	<ul style="list-style-type: none"> • Two-way / Sync (both Initiator and Responder roles) <p>Regardless of which MEP is used, the sending of an eb:Receipt message MUST be supported:</p> <ul style="list-style-type: none"> • For the One-way / Push, both “response” and “callback” reply patterns MUST be supported. • For the One-way / Pull, the “callback” pattern is the only viable option. The sender of the User message MUST accept (i.e. must not Fault and must process as expected) an eb:Receipt either piggybacked on a PullRequest, or sent separately. The User message receiver MUST be able to send an eb:Receipt separately from the PullRequest. • For the Two-way / Sync, both “response” and “callback” reply patterns must be supported for the first leg. The “callback” pattern is the only viable option for the second leg. The reply sender MUST accept an eb:Receipt either piggybacked on another User message, or sent separately. The reply receiver MUST be able to send an eb:Receipt separately. <p>Use of the ebbpsig:NonRepudiationInformation element (as defined in [ebBP-SIG]) MUST be supported as content for the eb:Receipt message, both by sender and receiver.</p>
Reliability	<p>The following message reliability features MUST be supported:</p> <ul style="list-style-type: none"> • Sender and Receiver MSH MUST support the following QoS features for pushed or pulled ebMS messages: at-least-once, at-most-once, exactly-once. • Receiver MSH MUST be able to acknowledge pulled messages (AtLeastOnce.Contract.AckResponse="true"). • Receiver MSH MUST supports Acknowledgments on delivery (supports P-Mode with Reliability.AtLeastOnce.Contract.AckOnDelivery="true") • Sender and Receiver MSH MUST support the following reply patterns for acknowledgments (P-Mode AtLeastOnce.ReplyPattern): either “response”, or “callback” (no support for polling required)
Security	<p>The following message security features MUST be supported:</p> <ul style="list-style-type: none"> • Sender and Receiver MSH MUST support username / password token, digital signatures and encryption. • Sender and Receiver MSH MUST support content-only transforms. • Sender and Receiver MSH MUST support security of attachments as required. • Sender and Receiver MSH MUST support message authorization at P-Mode level (see 7.10 in [ebMS3]) using wsse:UsernameToken profile. Authorization of the Pull signal - for a particular MPC - must be supported at minimum. <p>NOTE on XMLDsig: XMLDsig allows arbitrary XSLT Transformations when constructing the plaintext over which a signature or reference is created.</p>

	<p>Conforming applications that allow use of XSLT transformations when verifying either signatures or references are encouraged to maintain lists of “safe” transformations for a given partner, service, action and role combination. Static analysis of XSLT expressions with a human user audit is encouraged for trusting a given expression as “safe”</p>
Error generation and reporting	<p>The following error handling features MUST be supported:</p> <ul style="list-style-type: none"> • Capability of the Receiving MSH to report errors from message processing, either as ebMS error messages or as Faults to the Sending MSH. The following modes of reporting to Sending MSH are supported: (a) sending error as a separate request (ErrorHandling.Report.ReceiverErrorsTo=<URL of Sending MSH>), (b) sending error on the back channel of underlying protocol (ErrorHandling.Report.AsResponse="true"). • Capability to report to a third-party address (ErrorHandling.Report.ReceiverErrorsTo=<other address>). • Capability of Sending MSH to report generated errors as notifications to the message producer (support for Report.ProcessErrorNotifyProducer="true") (e.g. delivery failure). • Generated errors: All specified errors MUST be generated when applicable, except for EBMS:0010: On Receiving MSH, no requirement to generate error EBMS:0010 for discrepancies between message header and the following P-Mode features: P-Mode.reliability and P-Mode.security, but requirement to generate such error for other discrepancies.
Message Partition Channels	<p>Support for additional message channels beside the default is REQUIRED, so that selective pulling by a partner MSH is possible.</p>
Message packaging	<p>The following message packaging features MUST be supported:</p> <ul style="list-style-type: none"> • Support for attachments is REQUIRED. • Support for MessageProperties is REQUIRED. • Ability to process messages that contain both a signal message unit (eb:SignalMessage) and a user message unit (eb:UserMessage) is REQUIRED.
Interoperability Parameters	<p>Transport: HTTP 1.1</p> <p>SOAP version: 1.2</p> <p>Reliability Specification: WS-Reliability 1.1. Only “Response” or “Callback” ReplyPattern values are required to be supported.</p> <p>Security Specification: WSS1.0 and WSS 1.1. When using the One-way / Pull MEP or the Two-way / Sync MEP, the response message must use by default the same WSS version as the request message. Otherwise, the version to be applied to a message is specified in the P-Mode.security</p>

261

262 2.2.2 WS-I Conformance Requirements

263 The Web-Services Interoperability consortium has defined guidelines for interoperability of SOAP
264 messaging implementations. In order to ensure maximal interoperability across different SOAP stacks,
265 MIME and HTTP implementations, this conformance profile requires compliance with the following WS-I
266 profiles:

- 267 ● Basic Security Profile (BSP) 1.1 [WSIBSP11]
- 268 ● Attachment Profile (AP) 1.0, [WSIAP10] with regard to the use of MIME and SwA.

269 Notes:

- 270 – Compliance with AP1.0 would normally require compliance with BP1.1, which in turn requires the
271 absence of SOAP Envelope in the HTTP response of a One-Way (R2714). However, recent BP
272 versions such as BP1.2 [WSIBP12] override this requirement. Consequently, the Gateway
273 conformance profile does not require conformance to these deprecated requirements inherited from
274 BP1.1 (R2714, R1143) regarding the use of HTTP.
 - 275 – The above WS-I profiles must be complied with within the scope of features exhibited by the Gateway
276 RM V3 ebMS conformance profile. For example, since only SOAP 1.2 is required by Gateway RM V3,
277 the requirements from BSP 1.1 that depend on SOAP 1.1 would not apply. Similarly, none of the
278 requirements for DESCRIPTION (WSDL) or REGDATA (UDDI) apply here, as these are not used.
- 279 This conformance profile may be refined in a future version to require conformance to the following WS-I
280 profiles, once approved and published by WS-I:

- 281 ● Basic Profile 2.0 (BP2.0)jui

282

283 2.2.3 Processing Mode Parameters

284 Summary of P-Mode parameters that must be supported by an implementation conforming to this profile.
285 For each parameter, either:

- 286 – full support is required: an implementation is supposed to support the possible options for this
287 parameter.
- 288 – Support for a subset of values is required.
- 289 – No support is required: an implementation is not required to support the features controlled by this
290 parameter, and therefore not required to understand this parameter.

291

292 0. General PMode parameters:

- 293 • **(PMode.ID:** support not required)
- 294 • **(PMode.Agreement:** support not required)
- 295 • **PMode.MEP:** support for: <http://www.oasis-open.org/committees/ebxml-msg/>
296 {one-way, two-way}

- 297 • **PMode.MEPbinding:** support for: <http://www.oasis-open.org/committees/ebxml->
298 [msg/{ push, pull, sync}](#)
- 299 • **PMode.Initiator.Party:** support required.
- 300 • **PMode.Initiator.Role:** support required.
- 301 • **PMode.Initiator.Authorization.username** and
302 **PMode.Initiator.Authorization.password:** support for: wsse:UsernameToken.
- 303 • **PMode.Responder.Party:** support required.
- 304 • **PMode.Responder.Role:** support required.
- 305 • **PMode.Responder.Authorization.username** and
306 **PMode.Responder.Authorization.password:** support for: wsse:UsernameToken.

307

308 **1. PMode[1].Protocol:**

- 309 • **PMode[1].Protocol.Address:** support for "http" scheme.
- 310 • **PMode[1].Protocol.SOAPVersion:** support for SOAP 1.2.

311

312 **2.PMode[1].BusinessInfo:**

- 313 • **PMode[1].BusinessInfo.Service:** support required.
- 314 • **PMode[1].BusinessInfo.Action:** support required.
- 315 • **PMode[1].BusinessInfo.Properties[]:** support required.
- 316 • **(PMode[1].BusinessInfo.PayloadProfile[]: not required)**
- 317 • **(PMode[1].BusinessInfo.PayloadProfile.maxSize: not required)**
- 318 • **PMode[1].BusinessInfo.MPC:** support required.

319

320 **3. PMode[1].ErrorHandling:**

- 321 • **(PMode[1].ErrorHandling.Report.SenderErrorsTo:** support not required)
- 322 • **PMode[1].ErrorHandling.Report.ReceiverErrorsTo:** support required (for address of
323 the MSH sending the message in error or for third-party).
- 324 • **PMode[1].ErrorHandling.Report.AsResponse:** support required (true/false).
- 325 • **(PMode[1].ErrorHandling.Report.ProcessErrorNotifyConsumer** support not required)
- 326 • **PMode[1].ErrorHandling.Report.ProcessErrorNotifyProducer:** support required
327 (true/false)
- 328 • **PMode[1].ErrorHandling.Report.DeliveryFailuresNotifyProducer:** support required
329 (true/false)

330

331 **4. PMode[1].Reliability:**

- 332 • **PMode[1].Reliability.AtLeastOnce.Contract:** support required (true/false)
- 333 • **PMode[1].Reliability.AtLeastOnce.Contract.AckOnDelivery:** true/false
- 334 • **PMode[1].Reliability.AtLeastOnce.Contract.AcksTo:** support required.
- 335 • **PMode[1].Reliability.AtLeastOnce.Contract.AckResponse:** support required
- 336 (true/false)
- 337 • **PMode[1].Reliability.AtLeastOnce.ReplyPattern:** support required for: {Response,
- 338 Callback}.
- 339 • **PMode[1].Reliability.AtMostOnce.Contract:** support required (true/false)
- 340 • **(PMode[1].Reliability.InOrder.Contract:** support not required)
- 341 • **(PMode[1].Reliability.StartGroup:** support not required)
- 342 • **(PMode[1].Reliability.Correlation:** support not required)
- 343 • **(PMode[1].Reliability.TerminateGroup:** support not required)

344

345 **5. PMode[1].Security:**

- 346 • **PMode[1].Security.WSSVersion:** support required for: {1.0 , 1.1 }
- 347 • **PMode[1].Security.X509.Sign:** support required.
- 348 • **PMode[1].Security.X509.Signature.Certificate:** support required.
- 349 • **PMode[1].Security.X509.Signature.HashFunction:** support required.
- 350 • **PMode[1].Security.X509.Signature.Algorithm:** support required.
- 351 • **PMode[1].Security.X509.Encryption.Encrypt:** support required.
- 352 • **PMode[1].Security.X509.Encryption.Certificate:** support required.
- 353 • **PMode[1].Security.X509.Encryption.Algorithm:** support required.
- 354 • **(PMode[1].Security.X509.Encryption.MinimumStrength:** support not required)
- 355 • **PMode[1].Security.UsernameToken.username:** support required.
- 356 • **PMode[1].Security.UsernameToken.password:** support required.
- 357 • **PMode[1].Security.UsernameToken.Digest:** support required (true/false)
- 358 • **(PMode[1].Security.UsernameToken.Nonce:** not required)
- 359 • **PMode[1].Security.UsernameToken.Created:** support required.
- 360 • **PMode[1].Security.PModeAuthorize:** support required (true/false)

- **PMode[1].Security.SendReceipt**: support required (true/false)
- **Pmode[1].Security.SendReceipt.ReplyPattern**: support required (both "response" and "callback")

2.3 Conformance Profile: Gateway RX V3

The Gateway RX V3 is identified by the URI:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/gateway-rxv3>

This section identifies the requirements for conforming to this profile.

2.3.1 Feature Set

Gateway RX V3 is equivalent to the RM V3 conformance profile feature-wise.

The only difference is about the way messaging reliability is ensured. This profile relies on WS-ReliableMessaging1.1 instead of WS-Reliability1.1.

The feature set is therefor the same as in RM V3 except for the last table row:

Conformance Profile: Gateway RX V3	Profile summary: <"Sending+Receiving" / " gateway-rxv3" / Level 1 / HTTP1.1 + SOAP 1.2 + WSS1.1 + WS-ReliableMessaging1.1 >
Functional Aspects	Profile Feature Set
ebMS MEP	[same as in Gateway RM V3]
Reliability	[same as in Gateway RM V3, except for the following feature:] <ul style="list-style-type: none"> • No support required for Acknowledgments on delivery (supports P-Mode with Reliability.AtLeastOnce.Contract.AckOnDelivery="false")
Security	[same as in Gateway RM V3]
Error generation and reporting	[same as in Gateway RM V3]
Message Partition Channels	[same as in Gateway RM V3]
Message packaging	[same as in Gateway RM V3]
Interoperability Parameters	<p>Transport: HTTP 1.1</p> <p>SOAP version: 1.2</p> <p>Reliability Specification: WS-ReliableMessaging 1.1. Only "Response" or "Callback" ReplyPattern values are required to be supported.</p> <p>Security Specification: WSS1.0 and WSS 1.1.</p>

375 **2.3.2 WS-I Conformance Requirements**

376 The Web-Services Interoperability consortium has defined guidelines for interoperability of SOAP
377 messaging implementations. In order to ensure interoperability across different SOAP stacks, MIME and
378 HTTP implementations, this conformance profile requires compliance with the following WS-I profiles.

- 379 • Basic Security Profile (BSP) 1.1 [WSIBSP11]
- 380 • Attachment Profile (AP) 1.0, [WSIAP10] with regard to the use of MIME and SwA.

381 Note: the above WS-I profiles must be complied with within the scope of features exhibited by the
382 Gateway RX V3 ebMS conformance profile. For example, since only SOAP 1.2 is required by Gateway
383 RX V3, the requirements from BSP 1.1 that depend on SOAP 1.1 would not apply. Also, same
384 observations apply to compliance to AP1.0, regarding inherited BP1.1 requirements (R2714, R1143), as
385 in Gateway RM V3.

386 The Gateway RX V3 may be refined in a future version to require conformance to the following WS-I
387 profiles, once approved and published by WS-I:

- 388 • Basic Profile 2.0
- 389 • Reliable and Secure Profile (RSP) 1.1

390 **2.3.3 Processing Mode Parameters**

391 The P-Mode parameters to be supported are same as in Gateway RM V3, except for the following:

- 392 • **PMODE[1].Reliability.AtLeastOnce.Contract.AckOnDelivery**: “false” only needs be supported.

393 **2.4 Conformance Profile: Gateway RM V2/3**

394 The Gateway RM V2/3 is identified by the URI:

395 <http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/gateway-rmv2v3>

396 **This section identifies the requirements for conforming to this profile.**

397 **2.4.1 Feature Set**

398 Gateway RM V2/3 is defined as an extension of RM V3. As far as V3 is concerned, the features to be
399 supported by this conformance profile are exactly the same as in RM V3.

400 Regarding ebMS V2, the features to be supported for RM V2/3 are those required in the test profile:
401 **“UCC/EAN Basic Reliable ebXML Messaging v2.0”** defined in “UCC Global Interoperability
402 Program for ebXML MS” [UCC-MS2]. RM V2/3 requires the following restrictions – or tolerates the
403 following relaxations – on the UCC test profile:

- 404 • Only the HTTP1.1 + HTTP/S protocols must be used – SMTP is not part of RM V2/3.
- 405 • The value “signalsAndResponse” as well “responseOnly” do not need be supported for
406 SyncReplyMode. This means that “synchronous” request-responses do not need be supported.
- 407 • The Message Services (Ping, Status) tests H as defined in the above UCC test profile, do not
408 need be supported.
- 409 • The following capabilities, already optional in the UCC test profile, do not need be supported:
410 Encrypted File Transfer (Test G), Other Languages (Test I).

411 NOTE: An additional row has been added to the table: “portability parameters”, which associates a
 412 particular processing mode (P-Mode in V3) representation with the profile so that implementations
 413 supporting this profile can process the same processing mode representation.

414

Conformance Profile: Gateway RM V2/3	Profile summary: <“Sending+Receiving” / “gateway-rmv2v3” / Level 1 / HTTP1.1 + SOAP 1.2 + WSS1.1 + WS-Reliability 1.1 > + < “Sending+Receiving” / UCC-EAN V2 handler / Level 1 / HTTP1.1>
Functional Aspects	Profile Feature Set for ebMS V2 (to add to those for V3 in RM V3)
EbMS V2 MEP	Support for the following MEPs (in either Sender or Receiver role) is REQUIRED: <ul style="list-style-type: none"> • One-way / Push, defined as exchanges controlled by SyncReplyMode values: “mshSignalsOnly”, “signalsOnly” or “none”.
V2 Reliability	Support for reliable messaging, as specified in UCC test profile under Test E and Test J, is REQUIRED: Test E Acknowledgments E1. Unsigned Data/Unsigned Ack E2. Unsigned Data/Signed Ack E3. Signed Data/Unsigned Ack E4. Signed Data/Signed Ack E5. Signed Data/Signed Ack Secure Channel Test J Single-Hop Reliable Messaging J1. Once and Only Once Profile – Successful Retries, RetryInterval J2. Duplicate Detection - Original Acknowledgement to Duplicate Request J3. Delivery Failure Notification J4. Long Running Conversation
V2 Security	Support for secure messaging, as specified by UCC test profile under Test A , Test B and Test D, is REQUIRED: Test A Certificate Exchange A1. Personal Certificate Test B Simple Data Transfer B2. HTTP/S Data Transfer Test D Data Security D1. Signed Data

	D2. Signed Data Secure Channel (HTTP/S) D3. Client Authentication - Signed Data Secure Channel (HTTP/S)
V2 Error generation and reporting	Support for error handling, as specified by UCC test profile under Test K, is REQUIRED: Test K Error Handling K1. SOAP:Fault K2. ValueNotRecognized K3. NotSupported K4. Inconsistent Sync K5. Inconsistent Signature K6. Inconsistent Acknowledgment Signature K7. SecurityFailure K8. TimeToLiveExpired K10. MessageHeader format K11. Missing Payload
V2 Message Partition Channels	Not applicable.
V2 Message packaging	Support for the following packaging patterns, as specified by UCC test profile under Test B, Test C and Test F, is REQUIRED: Test B Simple Data Transfer B1. HTTP Data Transfer Test C Large File Transfer C1. HTTP Large File Send Test F Multiple Payload Handling F1. Multiple Payload Transfer – two payloads F2. Multiple Payload Transfer – five payloads F3. Multiple Payload Signed – two payloads F4. Multiple Payload Signed with Signed Acknowledgment – five payloads – secure channel
V2 Interoperability Parameters	Transport: HTTP 1.1 and HTTP/S
V2 processing mode	Processing mode representation: CPPA 2.0 or CPPA 1.0

415

- 416 This conformance profile combines ebMS V2 and V3 in the following way:
- 417 • Each one of the two messaging versions is operating separately as within two separate message
418 handlers, without any requirement for each handler to be aware of the other handler.
 - 419 • The P-Mode is a notion that has been defined only for V3. This conformance profile does not
420 define the equivalent for V2 and there is no requirement in this profile to extend it to V2.
 - 421 • This conformance profile does not extend the notion of MEP as defined in V3. No MEP is defined
422 or supported that makes use of both V2 and V3 messages.
 - 423 • Message Ids must however be unique across V2 and V3.
 - 424 • Although common header elements may be used to correlate V2 messages and V3 messages –
425 e.g. ConversationID, RefToMessageId – this conformance profile does not require a handler to
426 support any correlation semantics across V2 and V3. A V3 message referencing a V2 message
427 cannot be considered as part of a V3 MEP as defined in the V3 specification.

428 2.4.2 WS-I Conformance Requirements

429 The same compliance rules as for RM V3 apply. Only ebMS V3 messages are concerned with these
430 rules.

431 2.4.3 Processing Mode Parameters

432 The P-Mode parameters to be supported for the V3 capability are same as in Gateway RM V3.

433 2.5 Conformance Profile: Gateway RX V2/3

434 The Gateway RX V2/3 is identified by the URI:

435 <http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/gateway-rxv2v3>

436 **This section identifies the requirements for conforming to this profile.**

437 2.5.1 Feature Set

438 Gateway RX V2/3 is equivalent to the RX V3 conformance profile feature-wise.

439 The only difference is about the way messaging reliability is ensured. This profile relies on WS-
440 ReliableMessaging1.1 instead of WS-Reliability1.1. The same difference in V3 feature set table between
441 RM V3 and RX V3, applies here. The feature set for the V2 part is the same as in RM V2/3.

442

Conformance Profile: Gateway RX V2/3	Profile summary: <"Sending+Receiving" / " gateway-rxv2v3" / Level 1 / HTTP1.1 + SOAP 1.2 + WSS1.1 + WS-ReliableMessaging 1.1 > + < "Sending+Receiving" / UCC-EAN V2 handler / Level 1 / HTTP1.1>
Functional Aspects	Profile Feature Set
V2 Functional Aspects (same as in RM V2/3)	(same as in RM V2/3)

V3 Functional Aspects (same as in RX V3)	(same as in RX V3)
--	--------------------

443

444 **2.5.2 WS-I Conformance Requirements**

445 The same compliance rules as for RX V3 apply. Only ebMS V3 messages are concerned with these rules.

446 **2.5.3 Processing Mode Parameters**

447 The P-Mode parameters to be supported for the V3 capability are same as in Gateway RM V2/3, except
448 for the following:

- 449 • **PMode[1].Reliability.AtLeastOnce.Contract.AckOnDelivery**: “false” only needs be supported.

450

3 Examples of Alternate Conformance Profiles

3.1 Purpose

Some MSH implementations may have to operate under conditions where the full capabilities of the above Gateway conformance profile (G-CP) are not only unnecessary, but also not appropriate due to limited resources. In such cases, specific conformance profiles may need be defined as an alternate baseline for interoperability. Examples of such profiles (LH-CP and AM-CP) are given below.

The conformance profile below is intended to apply to messaging devices that do not have the ability to receive incoming requests (e.g. HTTP requests), due to a lack of static IP address or firewall restrictions. These message handlers also are supposed to be limited in storage capability. It is named LH-CP, meaning Light Handler.

3.2 Conformance Profile: Light Handler (LH-RM CP)

The Light Handler CP is identified by the URI:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/lighthandler-rm>

NOTE: For consistency with the notations used in the previous Gateway conformance profiles, an alternative light handler profile using WS-ReliableMessaging instead of WS-Reliability would be named:

<http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/lighthandler-rx>

but such profile is not defined here.

3.2.1 Feature Set

Conformance Profile: LHRM-CP	Profile summary: <“Sending+Receiving” / “ lighthandler-rm” / Level 1 / HTTP1.1 + SOAP 1.1 + WS-Reliability 1.1>
Functional Aspects	Profile Feature Set
ebMS MEP	Support for One-way / Push (as initiator), and One-way / Pull (as initiator).
Reliability	Support for guaranteed delivery only: must be able to receive reliability acks on the SOAP response to the Push, and to resend a pushed message. Must be able to resend a non-acknowledged Pull signal. No requirement to acknowledge a pulled message.
Security	Support for username / password token
Error reporting	Support for error notification to the local message producer (e.g. reported failure to deliver pushed messages). Ability to report message processing errors for pulled messages to the remote party via Error messages (such an error may be bundled with another pushed message or a Pull signal.).
Message Partition Channels	Sending on default message partition flow channel (no support for additional message partitions required.)
Message packaging	No support for attachments required – i.e. the payload will use the SOAP body-, no support for MessageProperties required.
Interop Parameters	Transport: HTTP 1.1 SOAP version: 1.1

	WSS: none
	Reliability Specification: WS-Reliability 1.1

469

470 3.2.2 WS-I Conformance Requirements

471 This conformance profile will require compliance with the following WS-I profile, once formally approved
472 by WS-I (currently in Board approval draft status):

- 473 • Basic Profile 1.2 [WSIBP12]

474 Note: the above WS-I profile must be complied with within the scope of features exhibited by the Light
475 Handler ebMS conformance profile.

476 3.3 Conformance Profile: Activity Monitor (AM-CP)

477 The Activity Monitor CP is identified by the URI:

478 <http://docs.oasis-open.org/ebxml-msg/ebms/v3.0/ns/cprofiles/200707/activity-monitor>

479 3.3.1 Feature Set

480 The following conformance profile is even more restricted in capability. It is intended to match the
481 capability of a monitoring component that is supposed to only send messages (Sending role only), e.g. for
482 some type of business activity monitoring where reliability is not required as the loss of one of some
483 messages can be offset by subsequent messages.

484

Conformance Profile: AM-CP	Profile summary: <“Sending” / “activity-monitor” / Level 1 / HTTP1.1 + SOAP 1.1 >
Functional Aspects	Profile Feature Set
ebMS MEP	Support for One-way / Push (initiator)
Reliability	None.
Security	none
Error reporting	Support for generating errors associated with sending user messages, and notifying remote party via messages. Support for error reporting by notifying its own party (e.g. inability to open a connection).
Message Partition Channels	default message partition channel.
Message packaging	No support for attachments required, no support for MessageProperties required.
Interop Parameters	Transport: HTTP 1.1 SOAP version: 1.1 WSS: none Reliability Specification: none

485

486 **3.3.2 WS-I Conformance Requirements**

487 This conformance profile requires compliance with the following WS-I profiles.

- 488 • Basic Profile 1.2 [WSIBP12]

489 Note: the above WS-I profile must be complied with within the scope of features exhibited by the Activity
490 Monitor conformance profile.

491

492 4 Conformance Clauses

493 4.1 Gateway RM V3 Conformance Clause

494 In order to conform to the **Gateway RM V3** Profile, an implementation must comply with all normative
495 statements and requirements in Section 2.2.

496 In particular, it must:

- 497 - implement the set of features as required in the Feature Set table of Section 2.2.1.
- 498 - comply with WS-I requirements listed in Section 2.2.2.
- 499 - support the required PMode parameters described in Section 2.2.3.

500

501 4.2 Gateway RX V3 Conformance Clause

502 In order to conform to the **Gateway RX V3** Profile, an implementation must comply with all normative
503 statements and requirements in Section 2.3.

504 In particular, it must:

- 505 - implement the set of features as required in the Feature Set table of Section 2.3.1.
- 506 - comply with WS-I requirements listed in Section 2.3.2.
- 507 - support the required PMode parameters described in Section 2.3.3.

508

509 4.3 Gateway RM V2/3 Conformance Clause

510 In order to conform to the **Gateway RM V2/3** Profile, an implementation must comply with all normative
511 statements and requirements in Section 2.4.

512 In particular, it must:

- 513 - implement the set of features as required in the Feature Set table of Section 2.4.1.
- 514 - comply with WS-I requirements listed in Section 2.4.2.
- 515 - support the required PMode parameters described in Section 2.4.3.

516

517 4.4 Gateway RX V2/3 Conformance Clause

518 In order to conform to the **Gateway RX V2/3** Profile, an implementation must comply with all normative
519 statements and requirements in Section 2.5.

520 In particular, it must:

- 521 - implement the set of features as required in the Feature Set table of Section 2.5.1.
- 522 - comply with WS-I requirements listed in Section 2.5.2.

523 - support the required PMode parameters described in Section 2.5.3.

524

Appendix A Conformance Profile Template and Terminology

525

526 In order to facilitate the definition and comparison of conformance profiles, it is recommended to use the
527 following template for describing a conformance profile.

528 In each entry of this table (column 2) specify which features are REQUIRED or RECOMMENDED by this
529 profile (this applies also to the absence of features).

Conformance Profile: <name>		Profile summary: [list of:] < ebMS Role(s) / DeploymentType / Level / InteroperabilityParameters >
Functional Aspects		Profile Feature Set
ebMS MEP		
Reliability		
Security		
Error reporting		
Message Partition Channels		
Message packaging		
Interop. Parameters	Transport and version	
	SOAP version	
	Reliability specification and version	
	Security specification and version	

530

531 Terminology:

532 A conformance profile is primarily associated with a common type of deployment or usage of an MSH
533 implementation. It identifies a set of features that must be implemented in order for an MSH to support
534 this type of deployment.

535 A conformance profile for ebMS is expressed using the following terms:

536 **Role:** This property refers to any possible role a message handler could take (see Section 2 in [ebMS3],
537 which defines Sending and Receiving.)

538 **Deployment Type:** A deployment type characterizes a context in which the implementation operates and
539 the expected functional use for this implementation. For example, the following deployment types are
540 expected to be among the most common, nonexclusive from others:

- 541 1. "resource-constrained handler". This characterizes an implementation that generally is not always
542 connected, may not be directly addressable, may have no static IP address, has limited persistent
543 capability, and is not subject to high-volume traffic.
- 544 2. "B2B or G2G gateway". This characterizes an implementation that generally is acting as the
545 gateway for an enterprise or government agency. It has a fixed address; it may have connectivity
546 restrictions due to security; and it must support various types of connectivity with diverse
547 partners.

548 **Level:** This property represents a level of capability for this conformance profile, expressed as a positive
549 integer (starting from 1). All other properties being equal, an implementation that is conforming to a profile
550 at level N (with N>1) is also conforming to the same profile at level N-1.

551 **Interoperability parameters:** This property is a composed property. It is a vector of parameters that must
552 (in general) be similar pairwise between two implementations in order for them to interoperate. Three
553 parameters are identified here, not exclusive from others. Some are only relevant to ebMS V3:

- 554 1. The transport protocol supported, for which a non-exhaustive list of values is: HTTP, SMTP,
555 HTTPS.
- 556 2. SOAP version: either SOAP 1.1 or SOAP 1.2.
- 557 3. The reliability specification supported, either WS-Reliability or WS-ReliableMessaging.

558 **Conformance Profile:** A conformance profile is then fully identified by one or more quadruples of the
559 form: < Role / DeploymentType / Level / InteropParameters>, or <R / D / L / P>, which is called the *profile*
560 *summary*.

561 **Functional Aspect:** A conformance profile will impose specific requirements on different aspects of the
562 specification, that are called here functional aspects. A set of (non-exhaustive) functional aspects is:

563 Message Exchange Patterns, Error Reporting, Reliability, Security, Message Partition Flows, Message
564 Packaging, Transport.

565 **Profile Feature Set:** The set of specification requirements associated with a conformance profile. This set
566 is partitioned using the functional aspects listed for the specification: it can be expressed as a list of
567 functional aspects, annotated with the required features of each aspect.

568

569 **Appendix B Acknowledgments**

570 The following individuals have participated in the creation of this specification and are gratefully
571 acknowledged.

572 **Participants:**

573 Jacques Durand, Fujitsu Software <jdurand@us.fujitsu.com>

574 Ric Emery, Axway Inc. <remery@us.axway.com>

575 Kazunori Iwasa, Fujitsu Limited <kiwasa@jp.fujitsu.com>

576 Ian Jones, British Telecommunications plc <ian.c.jones@bt.com>

577 Dale Moberg, Axway Inc. <dmoberg@us.axway.com>

578

Appendix C Revision History

579

Rev	Date	By Whom	What
CD 02	25 Jul 2007	J. Durand	Candidate draft for CD
CD 03	28 Oct 2008	J. Durand	Missing subsection 2.2.1, more specific profiling of eb:Receipt, more specific message authorization requirements.
CD 04	10/03/09	J. Durand	Addressed public comments for Candidate CD4

580