



KMIP Storage Array with Self-Encrypting Drives Profile Version 1.0

Committee Specification Draft 02

19 June 2014

Specification URIs

This version:

<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csd02/kmip-sa-sed-profile-v1.0-csd02.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csd02/kmip-sa-sed-profile-v1.0-csd02.html>
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csd02/kmip-sa-sed-profile-v1.0-csd02.pdf>

Previous version:

<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csprd01/kmip-sa-sed-profile-v1.0-csprd01.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csprd01/kmip-sa-sed-profile-v1.0-csprd01.html>
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csprd01/kmip-sa-sed-profile-v1.0-csprd01.pdf>

Latest version:

<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/kmip-sa-sed-profile-v1.0.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/kmip-sa-sed-profile-v1.0.html>
<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/kmip-sa-sed-profile-v1.0.pdf>

Technical Committee:

OASIS Key Management Interoperability Protocol (KMIP) TC

Chairs:

Subhash Sankuratripati (Subhash.Sankuratripati@netapp.com), NetApp
Saikat Saha (saikat.saha@oracle.com), Oracle

Editors:

Tim Hudson (tjh@cryptsoft.com), Cryptsoft Pty Ltd.
Mahadev Karadigudda (mahadev@netapp.com), NetApp

Related work:

This specification is related to:

- *Key Management Interoperability Protocol Profiles Version 1.0*. Edited by Robert Griffin and Subhash Sankuratripati. 01 October 2010. OASIS Standard. <http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.html>.
- *Key Management Interoperability Protocol Specification Version 1.1*. Edited by Robert Haas and Indra Fitzgerald. 24 January 2013. OASIS Standard. <http://docs.oasis-open.org/kmip/spec/v1.1/os/kmip-spec-v1.1-os.html>.

- *Key Management Interoperability Protocol Specification Version 1.2*. Edited by Kiran Thota and Kelley Burgin. Latest version: <http://docs.oasis-open.org/kmip/spec/v1.2/kmip-spec-v1.2.html>.

Abstract:

Describes a profile for Storage Arrays with Self-Encrypting Drives as KMIP clients interacting with KMIP servers

Status:

This document was last revised or approved by the OASIS Key Management Interoperability Protocol (KMIP) TC on the above date. The level of approval is also listed above. Check the "Latest version" location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <https://www.oasis-open.org/committees/kmip/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<https://www.oasis-open.org/committees/kmip/ipr.php>).

Citation format:

When referencing this specification the following citation format should be used:

[kmip-sa-sed-v1.0]

KMIP Storage Array with Self-Encrypting Drives Profile Version 1.0. Edited by Tim Hudson and Mahadev Karadigudda. 19 June 2014. OASIS Committee Specification Draft 02.

<http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/csd02/kmip-sa-sed-profile-v1.0-csd02.html>. Latest version: <http://docs.oasis-open.org/kmip/kmip-sa-sed-profile/v1.0/kmip-sa-sed-profile-v1.0.html>.

Notices

Copyright © OASIS Open 2014. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

Table of Contents

1	Introduction	5
1.1	Terminology	5
1.2	Normative References	5
2	Storage Array with Self-Encrypting Drives Profile	6
2.1	Authentication Suite	6
2.2	Storage Array with Self-Encrypting Drives - Client	6
2.3	Storage Array with Self-Encrypting Drives - Server	6
3	Storage Array with Self-Encrypting Drives Test Cases	8
3.1	Mandatory Test Cases KMIP v1.0	8
3.1.1	SASED-M-1-10 - Configuration	8
3.1.2	SASED-M-2-10 - Register the authentication key	9
3.1.3	SASED-M-3-10 - Retrieve Authentication Key	12
3.2	Mandatory Test Cases KMIP v1.1	17
3.2.1	SASED-M-1-11 - Configuration	17
3.2.2	SASED-M-2-11 - Register the authentication key	18
3.2.3	SASED-M-3-11 - Retrieve Authentication Key	22
3.3	Mandatory Test Cases KMIP v1.2	27
3.3.1	SASED-M-1-12 - Configuration	27
3.3.2	SASED-M-2-12 - Register the authentication key	28
3.3.3	SASED-M-3-12 - Retrieve Authentication Key	31
4	Conformance	37
4.1	Storage Array with Self Encrypting Drive Client KMIP v1.0 Profile Conformance	37
4.2	Storage Array with Self Encrypting Drive Client KMIP v1.1 Profile Conformance	37
4.3	Storage Array with Self Encrypting Drive Client KMIP v1.2 Profile Conformance	37
4.4	Storage Array with Self Encrypting Drive Server KMIP v1.0 Profile Conformance	37
4.5	Storage Array with Self Encrypting Drive Server KMIP v1.1 Profile Conformance	37
4.6	Storage Array with Self Encrypting Drive Server KMIP v1.2 Profile Conformance	37
4.7	Permitted Test Case Variations	38
4.7.1	Variable Items	38
4.7.2	Variable behavior	39
Appendix A.	Acknowledgments	40
Appendix B.	KMIP Specification Cross Reference	43
Appendix C.	Revision History	48

1 Introduction

For normative definition of the elements of KMIP see the [KMIP Specification](#) [KMIP-SPEC] and the [KMIP Profiles](#) [KMIP-PROF].

This profile defines the necessary KMIP functionality that a Storage Array with Self-Encrypting Drives operating as a KMIP client SHALL use and a KMIP server conforming to this profile SHALL support in order to interoperate in conformance with this profile.

1.1 Terminology

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

Authentication Key	A secret used by self-encrypting drives to verify authenticity of the client before allowing the drive to perform sensitive operations.
--------------------	---

1.2 Normative References

- [RFC2119] Bradner, S., “Key words for use in RFCs to Indicate Requirement Levels”, BCP 14, RFC 2119, March 1997. <http://www.ietf.org/rfc/rfc2119.txt>.
- [KMIP-ENCODE] [URL](#)
Candidate OASIS Standard 01. [DD MMM YYYY](#).
- [KMIP-SPEC] One or more of [KMIP-SPEC-1_0], [KMIP-SPEC-1_1], [KMIP-SPEC-1_2]
- [KMIP-SPEC-1_0] Key Management Interoperability Protocol Specification Version 1.0
<http://docs.oasis-open.org/kmip/spec/v1.0/os/kmip-spec-1.0-os.doc>
OASIS Standard, October 2010.
- [KMIP-SPEC-1_1] *Key Management Interoperability Protocol Specification Version 1.1*.
<http://docs.oasis-open.org/kmip/spec/v1.1/os/kmip-spec-v1.1-os.doc>
OASIS Standard. 24 January 2013.
- [KMIP-SPEC-1_2] *Key Management Interoperability Protocol Specification Version 1.2*.
[URL](#)
Candidate OASIS Standard 01. [DD MMM YYYY](#).
- [KMIP-PROF] One or more of [KMIP-PROF-1_0], [KMIP-PROF-1_1], [KMIP-PROF-1_2]
- [KMIP-PROF-1_0] *Key Management Interoperability Protocol Profiles Version 1.0*. <http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc>
OASIS Standard. 1 October 2010.
- [KMIP-PROF-1_1] *Key Management Interoperability Protocol Profiles Version 1.1*
<http://docs.oasis-open.org/kmip/profiles/v1.1/os/kmip-profiles-v1.1-os.doc>
OASIS Standard 01. 24 January 2013.
- [KMIP-PROF-1_2] *Key Management Interoperability Protocol Profiles Version 1.2*.
[URL](#)
Candidate OASIS Standard 01. [DD MMM YYYY](#).

2 Storage Array with Self-Encrypting Drives Profile

The Storage Array with Self-Encrypting Drives Profile is a storage array containing self-encrypting drives operating as a KMIP client interacting with a KMIP server.

2.1 Authentication Suite

Implementations conformant to this profile SHALL support at least one of the Authentication Suites defined within [KMIP-PROF]. The establishment of the trust relationship between the KMIP client and the KMIP server is the same as the defined base profiles for the version of the profile supported.

2.2 Storage Array with Self-Encrypting Drives - Client

KMIP clients conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the [KMIP-SPEC-1_0]

KMIP clients conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Client Clause* (section 5.12) of [KMIP-PROF-1_1]

KMIP clients conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Client* (section 5.2) of [KMIP-PROF-1_2]

KMIP clients conformant to this profile:

4. SHOULD NOT use a *Custom Attribute* [KMIP-SPEC] that duplicates information that is already in standard *Attributes* [KMIP-SPEC]

2.3 Storage Array with Self-Encrypting Drives - Server

KMIP servers conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the *Conformance clauses for a KMIP Server* (section 12.1) of [KMIP-SPEC-1_0]

KMIP servers conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Server Clause* (section 5.2) of [KMIP-PROF-1_1]

KMIP servers conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Server* (section 5.1) of [KMIP-PROF-1_2]

KMIP servers conformant to this profile SHALL:

4. SHALL support the following *Objects* [KMIP-SPEC]
 - a. *Template* [KMIP-SPEC]
 - b. *Secret Data* [KMIP-SPEC]
5. SHALL support the following *Attributes* [KMIP-SPEC]
 - c. *Custom Attribute* [KMIP SPEC]
6. SHALL support the following client-to-server operations:
 - d. *Register* [KMIP-SPEC]
7. SHALL support the following *Message Encoding* [KMIP-SPEC]:
 - e. *Secret Data Type Enumeration* [KMIP-SPEC] value:
 - i. Password
 - f. *Object Type Enumeration* [KMIP-SPEC] values:
 - i. Secret Data

- 78 ii. Template
- 79 g. *Name Type Enumeration* [KMIP-SPEC] value:
- 80 i. Uninterpreted Text String
- 81 8. SHALL support *Custom Attribute* [KMIP-SPEC] with the following data types and properties:
- 82 h. TextString
- 83 9. SHALL support a minimum length of 64 characters for *Custom Attribute* [KMIP-SPEC] and *Name*
- 84 [KMIP-SPEC] values where the attribute type is of variable length.
- 85 10. SHALL support a minimum of 10 *Custom Attribute* [KMIP-SPEC] per managed object
- 86 11. SHALL support a minimum of 64 characters in *Custom Attribute* [KMIP-SPEC] names
- 87 12. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause
- 88 within this section 2.2
- 89 13. MAY support extensions outside the scope of this standard (e.g., vendor extensions,
- 90 conformance clauses) that do not contradict any KMIP requirements.

3 Storage Array with Self-Encrypting Drives Test Cases

The test cases define a number of request-response pairs for KMIP operations. Each test case is provided in the XML format specified in [KMIP-ENCODE] intended to be both human-readable and usable by automated tools. The time sequence (starting from 0) for each request-response pair is noted and line numbers are provided for ease of cross-reference for a given test sequence.

Each test case has a unique label (the section name) which includes indication of mandatory (-M-) or optional (-O-) status and the protocol version major and minor numbers as part of the identifier.

The test cases may depend on a specific configuration of a KMIP client and server being configured in a manner consistent with the test case assumptions.

Where possible the flow of unique identifiers between tests, the date-time values, and other dynamic items are indicated using symbolic identifiers – in actual request and response messages these dynamic values will be filled in with valid values.

Note: the values for the returned items and the custom attributes are illustrative. Actual values from a real client system may vary as specified in section 4.7.

3.1 Mandatory Test Cases KMIP v1.0

3.1.1 SASSED-M-1-10 - Configuration

Determine server configuration details including operations supported (only the mandatory operations are listed in the response example), objects supported (only the mandatory objects types are listed in the response example), and optional server information.

```
# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="0"/>
0006     </ProtocolVersion>
0007     <BatchCount type="Integer" value="1"/>
0008   </RequestHeader>
0009   <BatchItem>
0010     <Operation type="Enumeration" value="Query"/>
0011     <RequestPayload>
0012       <QueryFunction type="Enumeration" value="QueryOperations"/>
0013       <QueryFunction type="Enumeration" value="QueryObjects"/>
0014       <QueryFunction type="Enumeration"
0015       value="QueryServerInformation"/>
0016     </RequestPayload>
0017   </BatchItem>
0018 </RequestMessage>
0019 <ResponseMessage>
0020   <ResponseHeader>
0021     <ProtocolVersion>
0022       <ProtocolVersionMajor type="Integer" value="1"/>
0023       <ProtocolVersionMinor type="Integer" value="0"/>
0024     </ProtocolVersion>
0025     <TimeStamp type="DateTime" value="2013-04-25T16:53:03+00:00"/>
0026     <BatchCount type="Integer" value="1"/>
0027   </ResponseHeader>
```



```

0027     <BatchItem>
0028         <Operation type="Enumeration" value="Query"/>
0029         <ResultStatus type="Enumeration" value="Success"/>
0030         <ResponsePayload>
0031             <Operation type="Enumeration" value="Query"/>
0032             <Operation type="Enumeration" value="Locate"/>
0033             <Operation type="Enumeration" value="Destroy"/>
0034             <Operation type="Enumeration" value="Get"/>
0035             <Operation type="Enumeration" value="Register"/>
0036             <Operation type="Enumeration" value="GetAttributes"/>
0037             <Operation type="Enumeration" value="GetAttributeList"/>
0038             <Operation type="Enumeration" value="AddAttribute"/>
0039             <ObjectType type="Enumeration" value="SecretData"/>
0040             <ObjectType type="Enumeration" value="Template"/>
0041             <VendorIdentification type="TextString" value="server-
vendor.com"/>
0042             <ServerInformation>
0043             </ServerInformation>
0044         </ResponsePayload>
0045     </BatchItem>
0046 </ResponseMessage>

```

111

112 3.1.2 SASSED-M-2-10 - Register the authentication key

113 A template is created and the secret data for the authentication key is then registered. The server must
114 allow the registration of managed objects for Object Groups either by allowed arbitrary values for Object
115 Groups or by pre-configuration of specific Object Groups prior to the storage array registering the
116 authentication key. The authentication key may be a new authentication key or a replacement
117 authentication key.

118

```

# TIME 0
0001 <RequestMessage>
0002 <RequestHeader>
0003     <ProtocolVersion>
0004         <ProtocolVersionMajor type="Integer" value="1"/>
0005         <ProtocolVersionMinor type="Integer" value="0"/>
0006     </ProtocolVersion>
0007     <BatchCount type="Integer" value="1"/>
0008 </RequestHeader>
0009 <BatchItem>
0010     <Operation type="Enumeration" value="Locate"/>
0011     <RequestPayload>
0012         <Attribute>
0013             <AttributeName type="TextString" value="Name"/>
0014             <AttributeValue>
0015                 <NameValue type="TextString" value="SASED-M-2-10-
templatel"/>
0016                 <NameType type="Enumeration"
value="UninterpretedTextString"/>
0017             </AttributeValue>
0018         </Attribute>
0019         <Attribute>
0020             <AttributeName type="TextString" value="Object Type"/>
0021             <AttributeValue type="Enumeration" value="Template"/>
0022         </Attribute>
0023     </RequestPayload>

```

0024	</BatchItem>
0025	</RequestMessage>
0026	<ResponseMessage>
0027	<ResponseHeader>
0028	<ProtocolVersion>
0029	<ProtocolVersionMajor type="Integer" value="1"/>
0030	<ProtocolVersionMinor type="Integer" value="0"/>
0031	</ProtocolVersion>
0032	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0033	<BatchCount type="Integer" value="1"/>
0034	</ResponseHeader>
0035	<BatchItem>
0036	<Operation type="Enumeration" value="Locate"/>
0037	<ResultStatus type="Enumeration" value="Success"/>
0038	<ResponsePayload>
0039	</ResponsePayload>
0040	</BatchItem>
0041	</ResponseMessage>
	# TIME 1
0042	<RequestMessage>
0043	<RequestHeader>
0044	<ProtocolVersion>
0045	<ProtocolVersionMajor type="Integer" value="1"/>
0046	<ProtocolVersionMinor type="Integer" value="0"/>
0047	</ProtocolVersion>
0048	<BatchCount type="Integer" value="1"/>
0049	</RequestHeader>
0050	<BatchItem>
0051	<Operation type="Enumeration" value="Register"/>
0052	<RequestPayload>
0053	<ObjectType type="Enumeration" value="Template"/>
0054	<TemplateAttribute>
0055	</TemplateAttribute>
0056	<Template>
0057	<Attribute>
0058	<AttributeName type="TextString" value="Object Group"/>
0059	<AttributeValue type="TextString" value="SASED-M-2-10-
0060	group"/>
0061	</Attribute>
0062	<Attribute>
0063	<AttributeName type="TextString" value="x-
0064	CustomAttribute1"/>
0065	<AttributeValue type="TextString" value="CustomValue1"/>
0066	</Attribute>
0067	<Attribute>
0068	<AttributeName type="TextString" value="x-
0069	CustomAttribute2"/>
0070	<AttributeValue type="TextString" value="CustomValue2"/>
0071	</Attribute>
0072	<Attribute>
0073	<AttributeName type="TextString" value="Name"/>
0074	<AttributeValue>
0075	<NameValue type="TextString" value="SASED-M-2-10-
	templatel"/>
	<NameType type="Enumeration"
	value="UninterpretedTextString"/>
	</AttributeValue>
	</Attribute>

0076	</Template>
0077	</RequestPayload>
0078	</BatchItem>
0079	</RequestMessage>
0080	<ResponseMessage>
0081	<ResponseHeader>
0082	<ProtocolVersion>
0083	<ProtocolVersionMajor type="Integer" value="1"/>
0084	<ProtocolVersionMinor type="Integer" value="0"/>
0085	</ProtocolVersion>
0086	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0087	<BatchCount type="Integer" value="1"/>
0088	</ResponseHeader>
0089	<BatchItem>
0090	<Operation type="Enumeration" value="Register"/>
0091	<ResultStatus type="Enumeration" value="Success"/>
0092	<ResponsePayload>
0093	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0094	</ResponsePayload>
0095	</BatchItem>
0096	</ResponseMessage>
	# TIME 2
0097	<RequestMessage>
0098	<RequestHeader>
0099	<ProtocolVersion>
0100	<ProtocolVersionMajor type="Integer" value="1"/>
0101	<ProtocolVersionMinor type="Integer" value="0"/>
0102	</ProtocolVersion>
0103	<BatchCount type="Integer" value="1"/>
0104	</RequestHeader>
0105	<BatchItem>
0106	<Operation type="Enumeration" value="Register"/>
0107	<RequestPayload>
0108	<ObjectType type="Enumeration" value="SecretData"/>
0109	<TemplateAttribute>
0110	<Name>
0111	<NameValue type="TextString" value="SASED-M-2-10-templatel"/>
0112	<NameType type="Enumeration" value="UninterpretedTextString"/>
0113	</Name>
0114	<Attribute>
0115	<AttributeName type="TextString" value="x-CustomAttribute3"/>
0116	<AttributeValue type="TextString" value="CustomValue3"/>
0117	</Attribute>
0118	<Attribute>
0119	<AttributeName type="TextString" value="x-CustomAttribute4"/>
0120	<AttributeValue type="TextString" value="CustomValue4"/>
0121	</Attribute>
0122	<Attribute>
0123	<AttributeName type="TextString" value="Name"/>
0124	<AttributeValue>
0125	<NameValue type="TextString" value="SASED-M-2-10-name"/>
0126	<NameType type="Enumeration" value="UninterpretedTextString"/>

[illegible]

119

120 3.1.3 SASSED-M-3-10 - Retrieve Authentication Key

121 Locate and retrieve the previously registered authentication key and finally destroy both the
122 authentication key and the template.

```

0001 # TIME 0
0002 <RequestMessage>
0003   <RequestHeader>
0004     <ProtocolVersion>
0005       <ProtocolVersionMajor type="Integer" value="1"/>
0006       <ProtocolVersionMinor type="Integer" value="0"/>
0007     </ProtocolVersion>
0008     <BatchCount type="Integer" value="1"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Locate"/>
0012     <RequestPayload>
0013       <Attribute>
0014         <AttributeName type="TextString" value="Object Group"/>
0015         <AttributeValue type="TextString" value="SASED-M-2-10-
group"/>

```

0015	</Attribute>
0016	<Attribute>
0017	<AttributeName type="TextString" value="Object Type"/>
0018	<AttributeValue type="Enumeration" value="SecretData"/>
0019	</Attribute>
0020	</RequestPayload>
0021	</BatchItem>
0022	</RequestMessage>
0023	<ResponseMessage>
0024	<ResponseHeader>
0025	<ProtocolVersion>
0026	<ProtocolVersionMajor type="Integer" value="1"/>
0027	<ProtocolVersionMinor type="Integer" value="0"/>
0028	</ProtocolVersion>
0029	<TimeStamp type="DateTime" value="2013-04-25T16:53:13+00:00"/>
0030	<BatchCount type="Integer" value="1"/>
0031	</ResponseHeader>
0032	<BatchItem>
0033	<Operation type="Enumeration" value="Locate"/>
0034	<ResultStatus type="Enumeration" value="Success"/>
0035	<ResponsePayload>
0036	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0037	</ResponsePayload>
0038	</BatchItem>
0039	</ResponseMessage>
0040	# TIME 1
0040	<RequestMessage>
0041	<RequestHeader>
0042	<ProtocolVersion>
0043	<ProtocolVersionMajor type="Integer" value="1"/>
0044	<ProtocolVersionMinor type="Integer" value="0"/>
0045	</ProtocolVersion>
0046	<BatchCount type="Integer" value="1"/>
0047	</RequestHeader>
0048	<BatchItem>
0049	<Operation type="Enumeration" value="GetAttributes"/>
0050	<RequestPayload>
0051	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0052	<AttributeName type="TextString" value="x-CustomAttribute4"/>
0053	</RequestPayload>
0054	</BatchItem>
0055	</RequestMessage>
0056	<ResponseMessage>
0057	<ResponseHeader>
0058	<ProtocolVersion>
0059	<ProtocolVersionMajor type="Integer" value="1"/>
0060	<ProtocolVersionMinor type="Integer" value="0"/>
0061	</ProtocolVersion>
0062	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0063	<BatchCount type="Integer" value="1"/>
0064	</ResponseHeader>
0065	<BatchItem>
0066	<Operation type="Enumeration" value="GetAttributes"/>
0067	<ResultStatus type="Enumeration" value="Success"/>
0068	<ResponsePayload>
0069	<UniqueIdentifier type="TextString"

0070	value="\$UNIQUE_IDENTIFIER_0"/>
0071	<Attribute>
	<AttributeName type="TextString" value="x-
0072	CustomAttribute4"/>
0073	<AttributeValue type="TextString" value="CustomValue4"/>
0074	</Attribute>
0075	</ResponsePayload>
0076	</BatchItem>
	</ResponseMessage>
0077	# TIME 2
0078	<RequestMessage>
0079	<RequestHeader>
0080	<ProtocolVersion>
0081	<ProtocolVersionMajor type="Integer" value="1"/>
0082	<ProtocolVersionMinor type="Integer" value="0"/>
0083	</ProtocolVersion>
0084	<BatchCount type="Integer" value="1"/>
0085	</RequestHeader>
0086	<BatchItem>
0087	<Operation type="Enumeration" value="GetAttributes"/>
0088	<RequestPayload>
	<UniqueIdentifier type="TextString"
0089	value="\$UNIQUE_IDENTIFIER_0"/>
0090	<AttributeName type="TextString" value="x-CustomAttribute3"/>
0091	</RequestPayload>
0092	</BatchItem>
	</RequestMessage>
0093	<ResponseMessage>
0094	<ResponseHeader>
0095	<ProtocolVersion>
0096	<ProtocolVersionMajor type="Integer" value="1"/>
0097	<ProtocolVersionMinor type="Integer" value="0"/>
0098	</ProtocolVersion>
0099	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0100	<BatchCount type="Integer" value="1"/>
0101	</ResponseHeader>
0102	<BatchItem>
0103	<Operation type="Enumeration" value="GetAttributes"/>
0104	<ResultStatus type="Enumeration" value="Success"/>
0105	<ResponsePayload>
0106	<UniqueIdentifier type="TextString"
0107	value="\$UNIQUE_IDENTIFIER_0"/>
0108	<Attribute>
	<AttributeName type="TextString" value="x-
0109	CustomAttribute3"/>
0110	<AttributeValue type="TextString" value="CustomValue3"/>
0111	</Attribute>
0112	</ResponsePayload>
0113	</BatchItem>
	</ResponseMessage>
0114	# TIME 3
0115	<RequestMessage>
0116	<RequestHeader>
0117	<ProtocolVersion>
0118	<ProtocolVersionMajor type="Integer" value="1"/>
0119	<ProtocolVersionMinor type="Integer" value="0"/>
0120	</ProtocolVersion>
	<BatchCount type="Integer" value="1"/>

[illegible]

0173	<ProtocolVersion>
0174	<ProtocolVersionMajor type="Integer" value="1"/>
0175	<ProtocolVersionMinor type="Integer" value="0"/>
0176	</ProtocolVersion>
0177	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0178	<BatchCount type="Integer" value="1"/>
0179	</ResponseHeader>
0180	<BatchItem>
0181	<Operation type="Enumeration" value="Destroy"/>
0182	<ResultStatus type="Enumeration" value="Success"/>
0183	<ResponsePayload>
0184	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0185	</ResponsePayload>
0186	</BatchItem>
0187	</ResponseMessage>
	# TIME 5
0188	<RequestMessage>
0189	<RequestHeader>
0190	<ProtocolVersion>
0191	<ProtocolVersionMajor type="Integer" value="1"/>
0192	<ProtocolVersionMinor type="Integer" value="0"/>
0193	</ProtocolVersion>
0194	<BatchCount type="Integer" value="1"/>
0195	</RequestHeader>
0196	<BatchItem>
0197	<Operation type="Enumeration" value="Locate"/>
0198	<RequestPayload>
0199	<Attribute>
0200	<AttributeName type="TextString" value="Name"/>
0201	<AttributeValue>
0202	<NameValue type="TextString" value="SASED-M-2-10-
	template1"/>
0203	<NameType type="Enumeration"
	value="UninterpretedTextString"/>
0204	</AttributeValue>
0205	</Attribute>
0206	<Attribute>
0207	<AttributeName type="TextString" value="Object Type"/>
0208	<AttributeValue type="Enumeration" value="Template"/>
0209	</Attribute>
0210	</RequestPayload>
0211	</BatchItem>
0212	</RequestMessage>
0213	<ResponseMessage>
0214	<ResponseHeader>
0215	<ProtocolVersion>
0216	<ProtocolVersionMajor type="Integer" value="1"/>
0217	<ProtocolVersionMinor type="Integer" value="0"/>
0218	</ProtocolVersion>
0219	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0220	<BatchCount type="Integer" value="1"/>
0221	</ResponseHeader>
0222	<BatchItem>
0223	<Operation type="Enumeration" value="Locate"/>
0224	<ResultStatus type="Enumeration" value="Success"/>
0225	<ResponsePayload>
0226	<UniqueIdentifier type="TextString"

0227	value="\$UNIQUE_IDENTIFIER_1"/>
0228	</ResponsePayload>
0229	</BatchItem>
	</ResponseMessage>
0230	# TIME 6
0231	<RequestMessage>
0232	<RequestHeader>
0233	<ProtocolVersion>
0234	<ProtocolVersionMajor type="Integer" value="1"/>
0235	<ProtocolVersionMinor type="Integer" value="0"/>
0236	</ProtocolVersion>
0237	<BatchCount type="Integer" value="1"/>
0238	</BatchCount>
0239	<Operation type="Enumeration" value="Destroy"/>
0240	<RequestPayload>
0241	<UniqueIdentifier type="TextString"
0242	value="\$UNIQUE_IDENTIFIER_1"/>
0243	</UniqueIdentifier>
0244	</RequestPayload>
0245	</BatchItem>
0246	</RequestMessage>
0247	<ResponseMessage>
0248	<ResponseHeader>
0249	<ProtocolVersion>
0250	<ProtocolVersionMajor type="Integer" value="1"/>
0251	<ProtocolVersionMinor type="Integer" value="0"/>
0252	</ProtocolVersion>
0253	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0254	<BatchCount type="Integer" value="1"/>
0255	</BatchCount>
0256	<Operation type="Enumeration" value="Destroy"/>
0257	<ResultStatus type="Enumeration" value="Success"/>
0258	<ResponsePayload>
0259	<UniqueIdentifier type="TextString"
0260	value="\$UNIQUE_IDENTIFIER_1"/>
0261	</UniqueIdentifier>
	</ResponsePayload>
	</BatchItem>
	</ResponseMessage>

123

124 3.2 Mandatory Test Cases KMIP v1.1

125 3.2.1 SASSED-M-1-11 - Configuration

126 Determine server configuration details including operations supported (only the mandatory operations are
 127 listed in the response example), objects supported (only the mandatory objects types are listed in the
 128 response example), and optional server information.

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="1"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>

0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	<QueryFunction type="Enumeration"
	value="QueryServerInformation"/>
0015	</RequestPayload>
0016	</BatchItem>
0017	</RequestMessage>
0018	<ResponseMessage>
0019	<ResponseHeader>
0020	<ProtocolVersion>
0021	<ProtocolVersionMajor type="Integer" value="1"/>
0022	<ProtocolVersionMinor type="Integer" value="1"/>
0023	</ProtocolVersion>
0024	<TimeStamp type="DateTime" value="2013-04-25T16:53:03+00:00"/>
0025	<BatchCount type="Integer" value="1"/>
0026	</ResponseHeader>
0027	<BatchItem>
0028	<Operation type="Enumeration" value="Query"/>
0029	<ResultStatus type="Enumeration" value="Success"/>
0030	<ResponsePayload>
0031	<Operation type="Enumeration" value="Query"/>
0032	<Operation type="Enumeration" value="Locate"/>
0033	<Operation type="Enumeration" value="Destroy"/>
0034	<Operation type="Enumeration" value="Get"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<ObjectType type="Enumeration" value="SecretData"/>
0040	<ObjectType type="Enumeration" value="Template"/>
0041	<VendorIdentification type="TextString" value="server-
	vendor.com"/>
0042	<ServerInformation>
0043	</ServerInformation>
0044	</ResponsePayload>
0045	</BatchItem>
0046	</ResponseMessage>

129

130 3.2.2 SASSED-M-2-11 - Register the authentication key

131 A template is created and the secret data for the authentication key is then registered. The server must
132 allow the registration of managed objects for Object Groups either by allowed arbitrary values for Object
133 Groups or by pre-configuration of specific Object Groups prior to the storage array registering the
134 authentication key. The authentication key may be a new authentication key or a replacement
135 authentication key.

136

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="1"/>

0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Locate"/>
0011	<RequestPayload>
0012	<Attribute>
0013	<AttributeName type="TextString" value="Name"/>
0014	<AttributeValue>
0015	<NameValue type="TextString" value="SASED-M-2-11- templatel"/>
0016	<NameType type="Enumeration" value="UninterpretedTextString"/>
0017	</AttributeValue>
0018	</Attribute>
0019	<Attribute>
0020	<AttributeName type="TextString" value="Object Type"/>
0021	<AttributeValue type="Enumeration" value="Template"/>
0022	</Attribute>
0023	</RequestPayload>
0024	</BatchItem>
0025	</RequestMessage>
0026	<ResponseMessage>
0027	<ResponseHeader>
0028	<ProtocolVersion>
0029	<ProtocolVersionMajor type="Integer" value="1"/>
0030	<ProtocolVersionMinor type="Integer" value="1"/>
0031	</ProtocolVersion>
0032	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0033	<BatchCount type="Integer" value="1"/>
0034	</ResponseHeader>
0035	<BatchItem>
0036	<Operation type="Enumeration" value="Locate"/>
0037	<ResultStatus type="Enumeration" value="Success"/>
0038	<ResponsePayload>
0039	</ResponsePayload>
0040	</BatchItem>
0041	</ResponseMessage>
	# TIME 1
0042	<RequestMessage>
0043	<RequestHeader>
0044	<ProtocolVersion>
0045	<ProtocolVersionMajor type="Integer" value="1"/>
0046	<ProtocolVersionMinor type="Integer" value="1"/>
0047	</ProtocolVersion>
0048	<BatchCount type="Integer" value="1"/>
0049	</RequestHeader>
0050	<BatchItem>
0051	<Operation type="Enumeration" value="Register"/>
0052	<RequestPayload>
0053	<ObjectType type="Enumeration" value="Template"/>
0054	<TemplateAttribute>
0055	</TemplateAttribute>
0056	<Template>
0057	<Attribute>
0058	<AttributeName type="TextString" value="Object Group"/>
0059	<AttributeValue type="TextString" value="SASED-M-2-11- group"/>

0060	</Attribute>
0061	<Attribute>
0062	<AttributeName type="TextString" value="x-CustomAttribute1"/>
0063	<AttributeValue type="TextString" value="CustomValue1"/>
0064	</Attribute>
0065	<Attribute>
0066	<AttributeName type="TextString" value="x-CustomAttribute2"/>
0067	<AttributeValue type="TextString" value="CustomValue2"/>
0068	</Attribute>
0069	<Attribute>
0070	<AttributeName type="TextString" value="Name"/>
0071	<AttributeValue>
0072	<NameValue type="TextString" value="SASED-M-2-11-templatel"/>
0073	<NameType type="Enumeration" value="UninterpretedTextString"/>
0074	</AttributeValue>
0075	</Attribute>
0076	</Template>
0077	</RequestPayload>
0078	</BatchItem>
0079	</RequestMessage>
0080	<ResponseMessage>
0081	<ResponseHeader>
0082	<ProtocolVersion>
0083	<ProtocolVersionMajor type="Integer" value="1"/>
0084	<ProtocolVersionMinor type="Integer" value="1"/>
0085	</ProtocolVersion>
0086	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0087	<BatchCount type="Integer" value="1"/>
0088	</ResponseHeader>
0089	<BatchItem>
0090	<Operation type="Enumeration" value="Register"/>
0091	<ResultStatus type="Enumeration" value="Success"/>
0092	<ResponsePayload>
0093	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0094	</ResponsePayload>
0095	</BatchItem>
0096	</ResponseMessage>
0097	# TIME 2 <RequestMessage>
0098	<RequestHeader>
0099	<ProtocolVersion>
0100	<ProtocolVersionMajor type="Integer" value="1"/>
0101	<ProtocolVersionMinor type="Integer" value="1"/>
0102	</ProtocolVersion>
0103	<BatchCount type="Integer" value="1"/>
0104	</RequestHeader>
0105	<BatchItem>
0106	<Operation type="Enumeration" value="Register"/>
0107	<RequestPayload>
0108	<ObjectType type="Enumeration" value="SecretData"/>
0109	<TemplateAttribute>
0110	<Name>
0111	<NameValue type="TextString" value="SASED-M-2-11-

0112
0113
0114
0115

0116
0117
0118
0119

0120
0121
0122
0123
0124
0125
0126

0127
0128
0129
0130
0131
0132
0133
0134
0135

0136
0137
0138
0139
0140
0141
0142
0143
0144
0145
0146
0147
0148
0149
0150
0151
0152
0153
0154
0155

0156
0157
0158

138 3.2.3 SASSED-M-3-11 - Retrieve Authentication Key

139 Locate and retrieve the previously registered authentication key and finally destroy both the
140 authentication key and the template.

0001	# TIME 0
0002	<RequestMessage>
0003	<RequestHeader>
0004	<ProtocolVersion>
0005	<ProtocolVersionMajor type="Integer" value="1"/>
0006	<ProtocolVersionMinor type="Integer" value="1"/>
0007	</ProtocolVersion>
0008	<BatchCount type="Integer" value="1"/>
0009	</RequestHeader>
0010	<BatchItem>
0011	<Operation type="Enumeration" value="Locate"/>
0012	<RequestPayload>
0013	<Attribute>
0014	<AttributeName type="TextString" value="Object Group"/>
0015	<AttributeValue type="TextString" value="SASSED-M-2-11-
0016	group"/>
0017	</Attribute>
0018	<Attribute>
0019	<AttributeName type="TextString" value="Object Type"/>
0020	<AttributeValue type="Enumeration" value="SecretData"/>
0021	</Attribute>
0022	</RequestPayload>
0023	</BatchItem>
0024	</RequestMessage>
0025	<ResponseMessage>
0026	<ResponseHeader>
0027	<ProtocolVersion>
0028	<ProtocolVersionMajor type="Integer" value="1"/>
0029	<ProtocolVersionMinor type="Integer" value="1"/>
0030	</ProtocolVersion>
0031	<TimeStamp type="DateTime" value="2013-04-25T16:53:13+00:00"/>
0032	<BatchCount type="Integer" value="1"/>
0033	</ResponseHeader>
0034	<BatchItem>
0035	<Operation type="Enumeration" value="Locate"/>
0036	<ResultStatus type="Enumeration" value="Success"/>
0037	<ResponsePayload>
0038	<UniqueIdentifier type="TextString"
0039	value="\$UNIQUE_IDENTIFIER_0"/>
0040	</ResponsePayload>
0041	</BatchItem>
0042	</ResponseMessage>
0043	# TIME 1
0044	<RequestMessage>
0045	<RequestHeader>
0046	<ProtocolVersion>
0047	<ProtocolVersionMajor type="Integer" value="1"/>
0048	<ProtocolVersionMinor type="Integer" value="1"/>
0049	</ProtocolVersion>
	<BatchCount type="Integer" value="1"/>
	</RequestHeader>
	<BatchItem>
	<Operation type="Enumeration" value="GetAttributes"/>

0050	<RequestPayload>
0051	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0052	<AttributeName type="TextString" value="x-CustomAttribute4"/>
0053	</RequestPayload>
0054	</BatchItem>
0055	</RequestMessage>
0056	<ResponseMessage>
0057	<ResponseHeader>
0058	<ProtocolVersion>
0059	<ProtocolVersionMajor type="Integer" value="1"/>
0060	<ProtocolVersionMinor type="Integer" value="1"/>
0061	</ProtocolVersion>
0062	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0063	<BatchCount type="Integer" value="1"/>
0064	</ResponseHeader>
0065	<BatchItem>
0066	<Operation type="Enumeration" value="GetAttributes"/>
0067	<ResultStatus type="Enumeration" value="Success"/>
0068	<ResponsePayload>
0069	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0070	<Attribute>
0071	<AttributeName type="TextString" value="x-
	CustomAttribute4"/>
0072	<AttributeValue type="TextString" value="CustomValue4"/>
0073	</Attribute>
0074	</ResponsePayload>
0075	</BatchItem>
0076	</ResponseMessage>
	# TIME 2
0077	<RequestMessage>
0078	<RequestHeader>
0079	<ProtocolVersion>
0080	<ProtocolVersionMajor type="Integer" value="1"/>
0081	<ProtocolVersionMinor type="Integer" value="1"/>
0082	</ProtocolVersion>
0083	<BatchCount type="Integer" value="1"/>
0084	</RequestHeader>
0085	<BatchItem>
0086	<Operation type="Enumeration" value="GetAttributes"/>
0087	<RequestPayload>
0088	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0089	<AttributeName type="TextString" value="x-CustomAttribute3"/>
0090	</RequestPayload>
0091	</BatchItem>
0092	</RequestMessage>
0093	<ResponseMessage>
0094	<ResponseHeader>
0095	<ProtocolVersion>
0096	<ProtocolVersionMajor type="Integer" value="1"/>
0097	<ProtocolVersionMinor type="Integer" value="1"/>
0098	</ProtocolVersion>
0099	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0100	<BatchCount type="Integer" value="1"/>
0101	</ResponseHeader>
0102	<BatchItem>

0154	</BatchItem>
0155	</ResponseMessage>
0156	# TIME 4
0157	<RequestMessage>
0158	<RequestHeader>
0159	<ProtocolVersion>
0160	<ProtocolVersionMajor type="Integer" value="1"/>
0161	<ProtocolVersionMinor type="Integer" value="1"/>
0162	</ProtocolVersion>
0163	<BatchCount type="Integer" value="1"/>
0164	</RequestHeader>
0165	<BatchItem>
0166	<Operation type="Enumeration" value="Destroy"/>
0167	<RequestPayload>
0168	<UniqueIdentifier type="TextString"
0169	value="\$UNIQUE_IDENTIFIER_0"/>
0170	</RequestPayload>
0171	</BatchItem>
0172	</RequestMessage>
0173	<ResponseMessage>
0174	<ResponseHeader>
0175	<ProtocolVersion>
0176	<ProtocolVersionMajor type="Integer" value="1"/>
0177	<ProtocolVersionMinor type="Integer" value="1"/>
0178	</ProtocolVersion>
0179	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0180	<BatchCount type="Integer" value="1"/>
0181	</ResponseHeader>
0182	<BatchItem>
0183	<Operation type="Enumeration" value="Destroy"/>
0184	<ResultStatus type="Enumeration" value="Success"/>
0185	<ResponsePayload>
0186	<UniqueIdentifier type="TextString"
0187	value="\$UNIQUE_IDENTIFIER_0"/>
0188	</ResponsePayload>
0189	</BatchItem>
0190	</ResponseMessage>
0191	# TIME 5
0192	<RequestMessage>
0193	<RequestHeader>
0194	<ProtocolVersion>
0195	<ProtocolVersionMajor type="Integer" value="1"/>
0196	<ProtocolVersionMinor type="Integer" value="1"/>
0197	</ProtocolVersion>
0198	<BatchCount type="Integer" value="1"/>
0199	</RequestHeader>
0200	<BatchItem>
0201	<Operation type="Enumeration" value="Locate"/>
0202	<RequestPayload>
0203	<Attribute>
0204	<AttributeName type="TextString" value="Name"/>
0205	<AttributeValue>
	<NameValue type="TextString" value="SASED-M-2-11-
	template1"/>
	<NameType type="Enumeration"
	value="UninterpretedTextString"/>
	</AttributeValue>
	</Attribute>

0206	<Attribute>
0207	<AttributeName type="TextString" value="Object Type"/>
0208	<AttributeValue type="Enumeration" value="Template"/>
0209	</Attribute>
0210	</RequestPayload>
0211	</BatchItem>
0212	</RequestMessage>
0213	<ResponseMessage>
0214	<ResponseHeader>
0215	<ProtocolVersion>
0216	<ProtocolVersionMajor type="Integer" value="1"/>
0217	<ProtocolVersionMinor type="Integer" value="1"/>
0218	</ProtocolVersion>
0219	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0220	<BatchCount type="Integer" value="1"/>
0221	</ResponseHeader>
0222	<BatchItem>
0223	<Operation type="Enumeration" value="Locate"/>
0224	<ResultStatus type="Enumeration" value="Success"/>
0225	<ResponsePayload>
0226	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_1"/>
0227	</ResponsePayload>
0228	</BatchItem>
0229	</ResponseMessage>
0230	# TIME 6
0230	<RequestMessage>
0231	<RequestHeader>
0232	<ProtocolVersion>
0233	<ProtocolVersionMajor type="Integer" value="1"/>
0234	<ProtocolVersionMinor type="Integer" value="1"/>
0235	</ProtocolVersion>
0236	<BatchCount type="Integer" value="1"/>
0237	</RequestHeader>
0238	<BatchItem>
0239	<Operation type="Enumeration" value="Destroy"/>
0240	<RequestPayload>
0241	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_1"/>
0242	</RequestPayload>
0243	</BatchItem>
0244	</RequestMessage>
0245	<ResponseMessage>
0246	<ResponseHeader>
0247	<ProtocolVersion>
0248	<ProtocolVersionMajor type="Integer" value="1"/>
0249	<ProtocolVersionMinor type="Integer" value="1"/>
0250	</ProtocolVersion>
0251	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0252	<BatchCount type="Integer" value="1"/>
0253	</ResponseHeader>
0254	<BatchItem>
0255	<Operation type="Enumeration" value="Destroy"/>
0256	<ResultStatus type="Enumeration" value="Success"/>
0257	<ResponsePayload>
0258	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_1"/>
0259	</ResponsePayload>

0260	</BatchItem>
0261	</ResponseMessage>

141

142 3.3 Mandatory Test Cases KMIP v1.2

143 3.3.1 SASSED-M-1-12 - Configuration

144 Determine server configuration details including operations supported (only the mandatory operations are
 145 listed in the response example), objects supported (only the mandatory objects types are listed in the
 146 response example), and optional server information.

0001	# TIME 0
0002	<RequestMessage>
0003	<RequestHeader>
0004	<ProtocolVersion>
0005	<ProtocolVersionMajor type="Integer" value="1"/>
0006	<ProtocolVersionMinor type="Integer" value="2"/>
0007	</ProtocolVersion>
0008	<BatchCount type="Integer" value="1"/>
0009	</RequestHeader>
0010	<BatchItem>
0011	<Operation type="Enumeration" value="Query"/>
0012	<RequestPayload>
0013	<QueryFunction type="Enumeration" value="QueryOperations"/>
0014	<QueryFunction type="Enumeration" value="QueryObjects"/>
0015	<QueryFunction type="Enumeration" value="QueryServerInformation"/>
0016	</RequestPayload>
0017	</BatchItem>
0018	</RequestMessage>
0019	<ResponseMessage>
0020	<ResponseHeader>
0021	<ProtocolVersion>
0022	<ProtocolVersionMajor type="Integer" value="1"/>
0023	<ProtocolVersionMinor type="Integer" value="2"/>
0024	</ProtocolVersion>
0025	<TimeStamp type="DateTime" value="2013-04-25T16:53:03+00:00"/>
0026	<BatchCount type="Integer" value="1"/>
0027	</ResponseHeader>
0028	<BatchItem>
0029	<Operation type="Enumeration" value="Query"/>
0030	<ResultStatus type="Enumeration" value="Success"/>
0031	<ResponsePayload>
0032	<Operation type="Enumeration" value="Query"/>
0033	<Operation type="Enumeration" value="Locate"/>
0034	<Operation type="Enumeration" value="Destroy"/>
0035	<Operation type="Enumeration" value="Get"/>
0036	<Operation type="Enumeration" value="Register"/>
0037	<Operation type="Enumeration" value="GetAttributes"/>
0038	<Operation type="Enumeration" value="GetAttributeList"/>
0039	<Operation type="Enumeration" value="AddAttribute"/>
0040	<ObjectType type="Enumeration" value="SecretData"/>
0041	<ObjectType type="Enumeration" value="Template"/>
0042	<VendorIdentification type="TextString" value="server-vendor.com"/>
0043	<ServerInformation>
0044	</ServerInformation>

0044	</ResponsePayload>
0045	</BatchItem>
0046	</ResponseMessage>

147

148 3.3.2 SASSED-M-2-12 - Register the authentication key

149 A template is created and the secret data for the authentication key is then registered. The server must
150 allow the registration of managed objects for Object Groups either by allowed arbitrary values for Object
151 Groups or by pre-configuration of specific Object Groups prior to the storage array registering the
152 authentication key. The authentication key may be a new authentication key or a replacement
153 authentication key.

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="2"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Locate"/>
0011	<RequestPayload>
0012	<Attribute>
0013	<AttributeName type="TextString" value="Name"/>
0014	<AttributeValue>
0015	<NameValue type="TextString" value="SASED-M-2-12- template1"/>
0016	<NameType type="Enumeration" value="UninterpretedTextString"/>
0017	</AttributeValue>
0018	</Attribute>
0019	<Attribute>
0020	<AttributeName type="TextString" value="Object Type"/>
0021	<AttributeValue type="Enumeration" value="Template"/>
0022	</Attribute>
0023	</RequestPayload>
0024	</BatchItem>
0025	</RequestMessage>
0026	<ResponseMessage>
0027	<ResponseHeader>
0028	<ProtocolVersion>
0029	<ProtocolVersionMajor type="Integer" value="1"/>
0030	<ProtocolVersionMinor type="Integer" value="2"/>
0031	</ProtocolVersion>
0032	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0033	<BatchCount type="Integer" value="1"/>
0034	</ResponseHeader>
0035	<BatchItem>
0036	<Operation type="Enumeration" value="Locate"/>
0037	<ResultStatus type="Enumeration" value="Success"/>
0038	<ResponsePayload>
0039	</ResponsePayload>
0040	</BatchItem>
0041	</ResponseMessage>
	# TIME 1

0042	<RequestMessage>
0043	<RequestHeader>
0044	<ProtocolVersion>
0045	<ProtocolVersionMajor type="Integer" value="1"/>
0046	<ProtocolVersionMinor type="Integer" value="2"/>
0047	</ProtocolVersion>
0048	<BatchCount type="Integer" value="1"/>
0049	</RequestHeader>
0050	<BatchItem>
0051	<Operation type="Enumeration" value="Register"/>
0052	<RequestPayload>
0053	<ObjectType type="Enumeration" value="Template"/>
0054	<TemplateAttribute>
0055	<Attribute>
0056	<AttributeName type="TextString" value="Name"/>
0057	<AttributeValue>
0058	<NameValue type="TextString" value="SASED-M-2-12-
0059	templatel"/>
0060	<NameType type="Enumeration"
0061	value="UninterpretedTextString"/>
0062	</AttributeValue>
0063	</Attribute>
0064	</TemplateAttribute>
0065	<Template>
0066	<Attribute>
0067	<AttributeName type="TextString" value="Object Group"/>
0068	<AttributeValue type="TextString" value="SASED-M-2-12-
0069	group"/>
0070	</Attribute>
0071	<Attribute>
0072	<AttributeName type="TextString" value="x-
0073	CustomAttribute1"/>
0074	<AttributeValue type="TextString" value="CustomValue1"/>
0075	</Attribute>
0076	<Attribute>
0077	<AttributeName type="TextString" value="x-
0078	CustomAttribute2"/>
0079	<AttributeValue type="TextString" value="CustomValue2"/>
0080	</Attribute>
0081	</Template>
0082	</RequestPayload>
0083	</BatchItem>
0084	</RequestMessage>
0085	<ResponseMessage>
0086	<ResponseHeader>
0087	<ProtocolVersion>
0088	<ProtocolVersionMajor type="Integer" value="1"/>
0089	<ProtocolVersionMinor type="Integer" value="2"/>
0090	</ProtocolVersion>
0091	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0092	<BatchCount type="Integer" value="1"/>
0093	</ResponseHeader>
0094	<BatchItem>
0095	<Operation type="Enumeration" value="Register"/>
0096	<ResultStatus type="Enumeration" value="Success"/>
0097	<ResponsePayload>
0098	<UniqueIdentifier type="TextString"
0099	value="\$UNIQUE_IDENTIFIER 0"/>

0144	<ProtocolVersion>
0145	<ProtocolVersionMajor type="Integer" value="1"/>
0146	<ProtocolVersionMinor type="Integer" value="2"/>
0147	</ProtocolVersion>
0148	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0149	<BatchCount type="Integer" value="1"/>
0150	</ResponseHeader>
0151	<BatchItem>
0152	<Operation type="Enumeration" value="Register"/>
0153	<ResultStatus type="Enumeration" value="Success"/>
0154	<ResponsePayload>
0155	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_1"/>
0156	</ResponsePayload>
0157	</BatchItem>
0158	</ResponseMessage>

154

155 3.3.3 SASSED-M-3-12 - Retrieve Authentication Key

156 Locate and retrieve the previously registered authentication key and finally destroy both the
157 authentication key and the template.

# TIME 0	
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="2"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Locate"/>
0011	<RequestPayload>
0012	<Attribute>
0013	<AttributeName type="TextString" value="Object Group"/>
0014	<AttributeValue type="TextString" value="SASED-M-2-12-
	group"/>
0015	</Attribute>
0016	<Attribute>
0017	<AttributeName type="TextString" value="Object Type"/>
0018	<AttributeValue type="Enumeration" value="SecretData"/>
0019	</Attribute>
0020	</RequestPayload>
0021	</BatchItem>
0022	</RequestMessage>
0023	<ResponseMessage>
0024	<ResponseHeader>
0025	<ProtocolVersion>
0026	<ProtocolVersionMajor type="Integer" value="1"/>
0027	<ProtocolVersionMinor type="Integer" value="2"/>
0028	</ProtocolVersion>
0029	<TimeStamp type="DateTime" value="2013-04-25T16:53:13+00:00"/>
0030	<BatchCount type="Integer" value="1"/>
0031	</ResponseHeader>
0032	<BatchItem>
0033	<Operation type="Enumeration" value="Locate"/>

0034	<ResultStatus type="Enumeration" value="Success"/>
0035	<ResponsePayload>
0036	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0037	</ResponsePayload>
0038	</BatchItem>
0039	</ResponseMessage>
	# TIME 1
0040	<RequestMessage>
0041	<RequestHeader>
0042	<ProtocolVersion>
0043	<ProtocolVersionMajor type="Integer" value="1"/>
0044	<ProtocolVersionMinor type="Integer" value="2"/>
0045	</ProtocolVersion>
0046	<BatchCount type="Integer" value="1"/>
0047	</RequestHeader>
0048	<BatchItem>
0049	<Operation type="Enumeration" value="GetAttributes"/>
0050	<RequestPayload>
0051	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0052	<AttributeName type="TextString" value="x-CustomAttribute4"/>
0053	</RequestPayload>
0054	</BatchItem>
0055	</RequestMessage>
0056	<ResponseMessage>
0057	<ResponseHeader>
0058	<ProtocolVersion>
0059	<ProtocolVersionMajor type="Integer" value="1"/>
0060	<ProtocolVersionMinor type="Integer" value="2"/>
0061	</ProtocolVersion>
0062	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0063	<BatchCount type="Integer" value="1"/>
0064	</ResponseHeader>
0065	<BatchItem>
0066	<Operation type="Enumeration" value="GetAttributes"/>
0067	<ResultStatus type="Enumeration" value="Success"/>
0068	<ResponsePayload>
0069	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0070	<Attribute>
0071	<AttributeName type="TextString" value="x-
	CustomAttribute4"/>
0072	<AttributeValue type="TextString" value="CustomValue4"/>
0073	</Attribute>
0074	</ResponsePayload>
0075	</BatchItem>
0076	</ResponseMessage>
	# TIME 2
0077	<RequestMessage>
0078	<RequestHeader>
0079	<ProtocolVersion>
0080	<ProtocolVersionMajor type="Integer" value="1"/>
0081	<ProtocolVersionMinor type="Integer" value="2"/>
0082	</ProtocolVersion>
0083	<BatchCount type="Integer" value="1"/>
0084	</RequestHeader>
0085	<BatchItem>

0086	<Operation type="Enumeration" value="GetAttributes"/>
0087	<RequestPayload>
0088	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0089	<AttributeName type="TextString" value="x-CustomAttribute3"/>
0090	</RequestPayload>
0091	</BatchItem>
0092	</RequestMessage>
0093	<ResponseMessage>
0094	<ResponseHeader>
0095	<ProtocolVersion>
0096	<ProtocolVersionMajor type="Integer" value="1"/>
0097	<ProtocolVersionMinor type="Integer" value="2"/>
0098	</ProtocolVersion>
0099	<TimeStamp type="DateTime" value="2013-04-25T16:53:14+00:00"/>
0100	<BatchCount type="Integer" value="1"/>
0101	</ResponseHeader>
0102	<BatchItem>
0103	<Operation type="Enumeration" value="GetAttributes"/>
0104	<ResultStatus type="Enumeration" value="Success"/>
0105	<ResponsePayload>
0106	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0107	<Attribute>
0108	<AttributeName type="TextString" value="x-
	CustomAttribute3"/>
0109	<AttributeValue type="TextString" value="CustomValue3"/>
0110	</Attribute>
0111	</ResponsePayload>
0112	</BatchItem>
0113	</ResponseMessage>
0114	# TIME 3
0115	<RequestMessage>
0116	<RequestHeader>
0117	<ProtocolVersion>
0118	<ProtocolVersionMajor type="Integer" value="1"/>
0119	<ProtocolVersionMinor type="Integer" value="2"/>
0120	</ProtocolVersion>
0121	<BatchCount type="Integer" value="1"/>
0122	</RequestHeader>
0123	<BatchItem>
0124	<Operation type="Enumeration" value="Get"/>
0125	<RequestPayload>
0126	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0127	</RequestPayload>
0128	</BatchItem>
0129	</RequestMessage>
0130	<ResponseMessage>
0131	<ResponseHeader>
0132	<ProtocolVersion>
0133	<ProtocolVersionMajor type="Integer" value="1"/>
0134	<ProtocolVersionMinor type="Integer" value="2"/>
0135	</ProtocolVersion>
0136	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0137	<BatchCount type="Integer" value="1"/>
0138	</ResponseHeader>
	<BatchItem>

[illegible]

0190	<ProtocolVersion>
0191	<ProtocolVersionMajor type="Integer" value="1"/>
0192	<ProtocolVersionMinor type="Integer" value="2"/>
0193	</ProtocolVersion>
0194	<BatchCount type="Integer" value="1"/>
0195	</RequestHeader>
0196	<BatchItem>
0197	<Operation type="Enumeration" value="Locate"/>
0198	<RequestPayload>
0199	<Attribute>
0200	<AttributeName type="TextString" value="Name"/>
0201	<AttributeValue>
0202	<NameValue type="TextString" value="SASED-M-2-12- template1"/>
0203	<NameType type="Enumeration" value="UninterpretedTextString"/>
0204	</AttributeValue>
0205	</Attribute>
0206	<Attribute>
0207	<AttributeName type="TextString" value="Object Type"/>
0208	<AttributeValue type="Enumeration" value="Template"/>
0209	</Attribute>
0210	</RequestPayload>
0211	</BatchItem>
0212	</RequestMessage>
0213	<ResponseMessage>
0214	<ResponseHeader>
0215	<ProtocolVersion>
0216	<ProtocolVersionMajor type="Integer" value="1"/>
0217	<ProtocolVersionMinor type="Integer" value="2"/>
0218	</ProtocolVersion>
0219	<TimeStamp type="DateTime" value="2013-04-25T16:53:08+00:00"/>
0220	<BatchCount type="Integer" value="1"/>
0221	</ResponseHeader>
0222	<BatchItem>
0223	<Operation type="Enumeration" value="Locate"/>
0224	<ResultStatus type="Enumeration" value="Success"/>
0225	<ResponsePayload>
0226	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_1"/>
0227	</ResponsePayload>
0228	</BatchItem>
0229	</ResponseMessage>
# TIME 6	
0230	<RequestMessage>
0231	<RequestHeader>
0232	<ProtocolVersion>
0233	<ProtocolVersionMajor type="Integer" value="1"/>
0234	<ProtocolVersionMinor type="Integer" value="2"/>
0235	</ProtocolVersion>
0236	<BatchCount type="Integer" value="1"/>
0237	</RequestHeader>
0238	<BatchItem>
0239	<Operation type="Enumeration" value="Destroy"/>
0240	<RequestPayload>
0241	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_1"/>
0242	</RequestPayload>

0243	</BatchItem>
0244	</RequestMessage>
0245	<ResponseMessage>
0246	<ResponseHeader>
0247	<ProtocolVersion>
0248	<ProtocolVersionMajor type="Integer" value="1"/>
0249	<ProtocolVersionMinor type="Integer" value="2"/>
0250	</ProtocolVersion>
0251	<TimeStamp type="DateTime" value="2013-04-25T17:01:41+00:00"/>
0252	<BatchCount type="Integer" value="1"/>
0253	</ResponseHeader>
0254	<BatchItem>
0255	<Operation type="Enumeration" value="Destroy"/>
0256	<ResultStatus type="Enumeration" value="Success"/>
0257	<ResponsePayload>
0258	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_1"/>
0259	</ResponsePayload>
0260	</BatchItem>
0261	</ResponseMessage>

158

159

4 Conformance

4.1 Storage Array with Self Encrypting Drive Client KMIP v1.0 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Client conditions (2.2)
3. SHALL support all the Mandatory Test Cases KMIP v1.0 (3.1)

4.2 Storage Array with Self Encrypting Drive Client KMIP v1.1 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Client conditions (2.2)
3. SHALL support all the Mandatory Test Cases KMIP v1.1 (3.2)

4.3 Storage Array with Self Encrypting Drive Client KMIP v1.2 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Client conditions (2.2)
3. SHALL support all the Mandatory Test Cases KMIP v1.2 (3.3)

4.4 Storage Array with Self Encrypting Drive Server KMIP v1.0 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Server conditions (2.3)
3. SHALL support all the Mandatory Test Cases KMIP v1.0 (3.1)

4.5 Storage Array with Self Encrypting Drive Server KMIP v1.1 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Server conditions (2.3)
3. SHALL support all the Mandatory Test Cases KMIP v1.1 (3.2)

4.6 Storage Array with Self Encrypting Drive Server KMIP v1.2 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions (2.1)
2. SHALL support the Storage Array with Self-Encrypting Drives - Server conditions (2.3)
3. SHALL support all the Mandatory Test Cases KMIP v1.2 (3.3)

4.7 Permitted Test Case Variations

Whilst the test cases provided in this Profile define the allowed request and response content, some inherent variations MAY occur and are permitted within a successfully completed test case.

Each test case MAY include allowed variations in the description of the test case in addition to the variations noted in this section.

Other variations not explicitly noted in this Profile SHALL be deemed non-conformant.

4.7.1 Variable Items

An implementation conformant to this Profile MAY vary the following values:

1. UniqueIdentifier
2. PrivateKeyUniqueIdentifier
3. PublicKeyUniqueIdentifier
4. UniqueBatchItemIdentifier
5. AsynchronousCorrelationValue
6. TimeStamp
7. KeyValue / KeyMaterial including:
 - a. key material content returned for managed cryptographic objects which are generated by the server
 - b. wrapped versions of keys where the wrapping key is dynamic or the wrapping contains variable output for each wrap operation
8. For response containing the output of cryptographic operation in Data / SignatureData/ MACData / IVCounterNonce where:
 - a. the managed object is generated by the server; or
 - b. the operation inherently contains variable output
9. For the following DateTime attributes where the value is not specified in the request as a fixed DateTime value:
 - a. ActivationDate
 - b. ArchiveDate
 - c. CompromiseDate
 - d. CompromiseOccurrenceDate
 - e. DeactivationDate
 - f. DestroyDate
 - g. InitialDate
 - h. LastChangeDate
 - i. ProtectStartDate
 - j. ProcessStopDate
 - k. ValidityDate
 - l. OriginalCreationDate
10. LinkedObjectIdentifier
11. DigestValue

- a. For those managed cryptographic objects which are dynamically generated
- 12. KeyFormatType
 - a. The key format type selected by the server when it creates managed objects
- 13. Digest
 - a. The HashingAlgorithm selected by the server when it calculates the digest for a managed object for which it has access to the key material
 - b. The Digest Value
- 14. Extensions reported in Query for ExtensionList and ExtensionMap
- 15. Application Namespaces reported in Query
- 16. Object Types reported in Query other than those noted as required in this profile
- 17. Operation Types reported in Query other than those noted as required in this profile (or any referenced profile documents)
- 18. For TextString attribute values containing test identifiers:
 - a. Additional vendor or application prefixes
- 19. Additional attributes beyond those noted in the response

An implementation conformant to this Profile MAY allow the following response variations:

1. Object Group values – May or may not return one or more Object Group values not included in the requests
2. y-CustomAttributes – May or may not include additional server-specific associated attributes not included in requests
3. Message Extensions – May or may not include additional (non-critical) vendor extensions
4. TemplateAttribute – May or may not be included in responses where the Template Attribute response is noted as optional in [KMIP-SPEC]
5. AttributeIndex – May or may not include Attribute Index value where the Attribute Index value is 0 for Protocol Versions 1.1 and above.
6. ResultMessage – May or may not be included in responses and the value (if included) may vary from the text contained within the test case.
7. The list of Protocol Versions returned in a DiscoverVersion response may include additional protocol versions if the request has not specified a list of client supported Protocol Versions.
8. VendorIdentification - The value (if included) may vary from the text contained within the test case.

4.7.2 Variable behavior

An implementation conformant to this Profile SHALL allow variation of the following behavior:

1. A test MAY omit the clean-up requests and responses (containing Revoke and/or Destroy) at the end of the test provided there is a separate mechanism to remove the created objects during testing.
2. A test MAY omit the test identifiers if the client is unable to include them in requests. This includes the following attributes:
 - a. Name; and
 - b. x-ID
3. A test MAY perform requests with multiple batch items or as multiple requests with a single batch item provided the sequence of operations are equivalent
4. A request MAY contain an optional *Authentication* [KMIP_SPEC] structure within each request

Appendix A. Acknowledgments

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

Participants:

281 Hal Aldridge, Sypris Electronics
282 Mike Allen, Symantec
283 Gordon Arnold, IBM
284 Todd Arnold, IBM
285 Richard Austin, Hewlett-Packard
286 Lars Bagnert, PrimeKey
287 Elaine Barker, NIST
288 Peter Bartok, Venafi, Inc.
289 Tom Benjamin, IBM
290 Anthony Berglas, Cryptsoft
291 Mathias Björkqvist, IBM
292 Kevin Bocket, Venafi
293 Anne Bolgert, IBM
294 Alan Brown, Thales e-Security
295 Tim Bruce, CA Technologies
296 Chris Burchett, Credant Technologies, Inc.
297 Kelley Burgin, National Security Agency
298 Robert Burns, Thales e-Security
299 Chuck Castleton, Venafi
300 Kenli Chong, QuintessenceLabs
301 John Clark, Hewlett-Packard
302 Tom Clifford, Symantec Corp.
303 Doron Cohen, SafeNet, Inc
304 Tony Cox, Cryptsoft
305 Russell Dietz, SafeNet, Inc
306 Graydon Dodson, Lexmark International Inc.
307 Vinod Duggirala, EMC Corporation
308 Chris Dunn, SafeNet, Inc.
309 Michael Duren, Sypris Electronics
310 James Dzierzanowski, American Express CCoE
311 Faisal Faruqui, Thales e-Security
312 Stan Feather, Hewlett-Packard
313 David Finkelstein, Symantec Corp.
314 James Fitzgerald, SafeNet, Inc.
315 Indra Fitzgerald, Hewlett-Packard
316 Judith Furlong, EMC Corporation
317 Susan Gleeson, Oracle
318 Robert Griffin, EMC Corporation
319 Paul Grojean, Individual
320 Robert Haas, IBM
321 Thomas Hardjono, M.I.T.
322 ChengDong He, Huawei Technologies Co., Ltd.
323 Steve He, Vormetric
324 Kurt Heberlein, Hewlett-Packard
325 Larry Hofer, Emulex Corporation
326 Maryann Hondo, IBM
327 Walt Hubis, NetApp
328 Tim Hudson, Cryptsoft
329 Jonas Iggbom, Venafi, Inc.

330 Sitaram Inguva, American Express CCoE
331 Jay Jacobs, Target Corporation
332 Glen Jaquette, IBM
333 Mahadev Karadiguddi, NetApp
334 Greg Kazmierczak, Wave Systems Corp.
335 Marc Kenig, SafeNet, Inc.
336 Mark Knight, Thales e-Security
337 Kathy Kriese, Symantec Corporation
338 Mark Lambiase, SecureAuth
339 John Leiseboer, Quintessence Labs
340 Hal Lockhart, Oracle Corporation
341 Robert Lockhart, Thales e-Security
342 Anne Luk, Cryptsoft
343 Sairam Manidi, Freescale
344 Luther Martin, Voltage Security
345 Neil McEvoy, iFOSSF
346 Marina Milshtein, Individual
347 Dale Moberg, Axway Software
348 Jishnu Mukeri, Hewlett-Packard
349 Bryan Olson, Hewlett-Packard
350 John Peck, IBM
351 Rob Philpott, EMC Corporation
352 Denis Pochuev, SafeNet, Inc.
353 Reid Poole, Venafi, Inc.
354 Ajai Puri, SafeNet, Inc.
355 Saravanan Ramalingam, Thales e-Security
356 Peter Reed, SafeNet, Inc.
357 Bruce Rich, IBM
358 Christina Richards, American Express CCoE
359 Warren Robbins, Dell
360 Peter Robinson, EMC Corporation
361 Scott Rotondo, Oracle
362 Saikat Saha, SafeNet, Inc.
363 Anil Saldhana, Red Hat
364 Subhash Sankuratipati, NetApp
365 Boris Schumperli, Cryptomathic
366 Greg Singh, QuintessenceLabs
367 David Smith, Venafi, Inc
368 Brian Spector, Certivox
369 Terence Spies, Voltage Security
370 Deborah Steckroth, RouteOne LLC
371 Michael Stevens, QuintessenceLabs
372 Marcus Streets, Thales e-Security
373 Satish Sundar, IBM
374 Kiran Thota, VMware
375 Somanchi Trinath, Freescale Semiconductor, Inc.
376 Nathan Turajski, Thales e-Security
377 Sean Turner, IECA, Inc.
378 Paul Turner, Venafi, Inc.
379 Rod Wideman, Quantum Corporation
380 Steven Wierenga, Hewlett-Packard
381 Jin Wong, QuintessenceLabs
382 Sameer Yami, Thales e-Security
383 Peter Yee, EMC Corporation
384 Krishna Yellepeddy, IBM
385 Catherine Ying, SafeNet, Inc.
386 Tatu Ylonen, SSH Communications Security (Tectia Corp)

387 Michael Yoder, Vormetric. Inc.
388 Magda Zdunkiewicz, Cryptsoft
389 Peter Zelechowski, Election Systems & Software

Appendix B. KMIP Specification Cross Reference

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
1 Introduction			
<i>Non-Normative References</i>	1.3.	1.3.	1.3.
<i>Normative References</i>	1.2.	1.2.	1.2.
<i>Terminology</i>	1.1.	1.1.	1.1.
2 Objects			
<i>Attribute</i>	2.1.1.	2.1.1.	2.1.1.
<i>Base Objects</i>	2.1.	2.1.	2.1.
<i>Certificate</i>	2.2.1.	2.2.1.	2.2.1.
<i>Credential</i>	2.1.2.	2.1.2.	2.1.2.
<i>Data</i>	-	-	2.1.10.
<i>Data Length</i>	-	-	2.1.11.
<i>Extension Information</i>	-	2.1.9.	2.1.9.
<i>Key Block</i>	2.1.3.	2.1.3.	2.1.3.
<i>Key Value</i>	2.1.4.	2.1.4.	2.1.4.
<i>Key Wrapping Data</i>	2.1.5.	2.1.5.	2.1.5.
<i>Key Wrapping Specification</i>	2.1.6.	2.1.6.	2.1.6.
<i>MAC Data</i>	-	-	2.1.13.
<i>Managed Objects</i>	2.2.	2.2.	2.2.
<i>Nonce</i>	-	-	2.1.14.
<i>Opaque Object</i>	2.2.8.	2.2.8.	2.2.8.
<i>PGP Key</i>	-	-	2.2.9.
<i>Private Key</i>	2.2.4.	2.2.4.	2.2.4.
<i>Public Key</i>	2.2.3.	2.2.3.	2.2.3.
<i>Secret Data</i>	2.2.7.	2.2.7.	2.2.7.
<i>Signature Data</i>	-	-	2.1.12.
<i>Split Key</i>	2.2.5.	2.2.5.	2.2.5.
<i>Symmetric Key</i>	2.2.2.	2.2.2.	2.2.2.
<i>Template</i>	2.2.6.	2.2.6.	2.2.6.
<i>Template-Attribute Structures</i>	2.1.8.	2.1.8.	2.1.8.
<i>Transparent DH Private Key</i>	2.1.7.6.	2.1.7.6.	2.1.7.6.
<i>Transparent DH Public Key</i>	2.1.7.7.	2.1.7.7.	2.1.7.7.
<i>Transparent DSA Private Key</i>	2.1.7.2.	2.1.7.2.	2.1.7.2.
<i>Transparent DSA Public Key</i>	2.1.7.3.	2.1.7.3.	2.1.7.3.
<i>Transparent ECDH Private Key</i>	2.1.7.10.	2.1.7.10.	2.1.7.10.
<i>Transparent ECDH Public Key</i>	2.1.7.11.	2.1.7.11.	2.1.7.11.
<i>Transparent ECDSA Private Key</i>	2.1.7.8.	2.1.7.8.	2.1.7.8.
<i>Transparent ECDSA Public Key</i>	2.1.7.9.	2.1.7.9.	2.1.7.9.
<i>Transparent ECMQV Private Key</i>	2.1.7.12.	2.1.7.12.	2.1.7.12.
<i>Transparent ECMQV Public Key</i>	2.1.7.13.	2.1.7.13.	2.1.7.13.
<i>Transparent Key Structures</i>	2.1.7.	2.1.7.	2.1.7.
<i>Transparent RSA Private Key</i>	2.1.7.4.	2.1.7.4.	2.1.7.4.
<i>Transparent RSA Public Key</i>	2.1.7.5.	2.1.7.5.	2.1.7.5.
<i>Transparent Symmetric Key</i>	2.1.7.1.	2.1.7.1.	2.1.7.1.
3 Attributes			
<i>Activation Date</i>	3.19.	3.24.	3.24.
<i>Alternative Name</i>	-	-	3.40.
<i>Application Specific Information</i>	3.30.	3.36.	3.36.
<i>Archive Date</i>	3.27.	3.32.	3.32.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Attributes</i>	3	3	3
<i>Certificate Identifier</i>	3.9.	3.13.	3.13.
<i>Certificate Issuer</i>	3.11.	3.15.	3.15.
<i>Certificate Length</i>	-	3.9.	3.9.
<i>Certificate Subject</i>	3.10.	3.14.	3.14.
<i>Certificate Type</i>	3.8.	3.8.	3.8.
<i>Compromise Date</i>	3.25.	3.30.	3.30.
<i>Compromise Occurrence Date</i>	3.24.	3.29.	3.29.
<i>Contact Information</i>	3.31.	3.37.	3.37.
<i>Cryptographic Algorithm</i>	3.4.	3.4.	3.4.
<i>Cryptographic Domain Parameters</i>	3.7.	3.7.	3.7.
<i>Cryptographic Length</i>	3.5.	3.5.	3.5.
<i>Cryptographic Parameters</i>	3.6.	3.6.	3.6.
<i>Custom Attribute</i>	3.33.	3.39.	3.39.
<i>Deactivation Date</i>	3.22.	3.27.	3.27.
<i>Default Operation Policy</i>	3.13.2.	3.18.2.	3.18.2.
<i>Default Operation Policy for Certificates and Public Key Objects</i>	3.13.2.2.	3.18.2.2.	3.18.2.2.
<i>Default Operation Policy for Secret Objects</i>	3.13.2.1.	3.18.2.1.	3.18.2.1.
<i>Default Operation Policy for Template Objects</i>	3.13.2.3.	3.18.2.3.	3.18.2.3.
<i>Destroy Date</i>	3.23.	3.28.	3.28.
<i>Digest</i>	3.12.	3.17.	3.17.
<i>Digital Signature Algorithm</i>	-	3.16.	3.16.
<i>Fresh</i>	-	3.34.	3.34.
<i>Initial Date</i>	3.18.	3.23.	3.23.
<i>Key Value Location</i>	-	-	3.42.
<i>Key Value Present</i>	-	-	3.41.
<i>Last Change Date</i>	3.32.	3.38.	3.38.
<i>Lease Time</i>	3.15.	3.20.	3.20.
<i>Link</i>	3.29.	3.35.	3.35.
<i>Name</i>	3.2.	3.2.	3.2.
<i>Object Group</i>	3.28.	3.33.	3.33.
<i>Object Type</i>	3.3.	3.3.	3.3.
<i>Operation Policy Name</i>	3.13.	3.18.	3.18.
<i>Operations outside of operation policy control</i>	3.13.1.	3.18.1.	3.18.1.
<i>Original Creation Date</i>	-	-	3.43.
<i>Process Start Date</i>	3.20.	3.25.	3.25.
<i>Protect Stop Date</i>	3.21.	3.26.	3.26.
<i>Revocation Reason</i>	3.26.	3.31.	3.31.
<i>State</i>	3.17.	3.22.	3.22.
<i>Unique Identifier</i>	3.1.	3.1.	3.1.
<i>Usage Limits</i>	3.16.	3.21.	3.21.
<i>X.509 Certificate Identifier</i>	-	3.10.	3.10.
<i>X.509 Certificate Issuer</i>	-	3.12.	3.12.
<i>X.509 Certificate Subject</i>	-	3.11.	3.11.
4 Client-to-Server Operations			
<i>Activate</i>	4.18.	4.19.	4.19.
<i>Add Attribute</i>	4.13.	4.14.	4.14.
<i>Archive</i>	4.21.	4.22.	4.22.
<i>Cancel</i>	4.25.	4.27.	4.27.
<i>Certify</i>	4.6.	4.7.	4.7.
<i>Check</i>	4.9.	4.10.	4.10.
<i>Create</i>	4.1.	4.1.	4.1.
<i>Create Key Pair</i>	4.2.	4.2.	4.2.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Create Split Key</i>	-	-	4.38.
<i>Decrypt</i>	-	-	4.30.
<i>Delete Attribute</i>	4.15.	4.16.	4.16.
<i>Derive Key</i>	4.5.	4.6.	4.6.
<i>Destroy</i>	4.20.	4.21.	4.21.
<i>Discover Versions</i>	-	4.26.	4.26.
<i>Encrypt</i>	-	-	4.29.
<i>Get</i>	4.10.	4.11.	4.11.
<i>Get Attribute List</i>	4.12.	4.13.	4.13.
<i>Get Attributes</i>	4.11.	4.12.	4.12.
<i>Get Usage Allocation</i>	4.17.	4.18.	4.18.
<i>Hash</i>	-	-	4.37.
<i>Join Split Key</i>	-	-	4.39.
<i>Locate</i>	4.8.	4.9.	4.9.
<i>MAC</i>	-	-	4.33.
<i>MAC Verify</i>	-	-	4.34.
<i>Modify Attribute</i>	4.14.	4.15.	4.15.
<i>Obtain Lease</i>	4.16.	4.17.	4.17.
<i>Poll</i>	4.26.	4.28.	4.28.
<i>Query</i>	4.24.	4.25.	4.25.
<i>Re-certify</i>	4.7.	4.8.	4.8.
<i>Recover</i>	4.22.	4.23.	4.23.
<i>Register</i>	4.3.	4.3.	4.3.
<i>Re-key</i>	4.4.	4.4.	4.4.
<i>Re-key Key Pair</i>	-	4.5.	4.5.
<i>Revoke</i>	4.19.	4.20.	4.20.
<i>RNG Retrieve</i>	-	-	4.35.
<i>RNG Seed</i>	-	-	4.36.
<i>Sign</i>	-	-	4.31.
<i>Signature Verify</i>	-	-	4.32.
<i>Validate</i>	4.23.	4.24.	4.24.
5 Server-to-Client Operations			
<i>Notify</i>	5.1.	5.1.	5.1.
<i>Put</i>	5.2.	5.2.	5.2.
6 Message Contents			
<i>Asynchronous Correlation Value</i>	6.8.	6.8.	6.8.
<i>Asynchronous Indicator</i>	6.7.	6.7.	6.7.
<i>Attestation Capable Indicator</i>	-	-	6.17.
<i>Batch Count</i>	6.14.	6.14.	6.14.
<i>Batch Error Continuation Option</i>	6.13.	6.13.	6.13.
<i>Batch Item</i>	6.15.	6.15.	6.15.
<i>Batch Order Option</i>	6.12.	6.12.	6.12.
<i>Maximum Response Size</i>	6.3.	6.3.	6.3.
<i>Message Extension</i>	6.16.	6.16.	6.16.
<i>Operation</i>	6.2.	6.2.	6.2.
<i>Protocol Version</i>	6.1.	6.1.	6.1.
<i>Result Message</i>	6.11.	6.11.	6.11.
<i>Result Reason</i>	6.10.	6.10.	6.10.
<i>Result Status</i>	6.9.	6.9.	6.9.
<i>Time Stamp</i>	6.5.	6.5.	6.5.
<i>Unique Batch Item ID</i>	6.4.	6.4.	6.4.
7 Message Format			

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Message Structure</i>	7.1.	7.1.	7.1.
<i>Operations</i>	7.2.	7.2.	7.2.
8 Authentication			
<i>Authentication</i>	8	8	8
9 Message Encoding			
<i>Alternative Name Type Enumeration</i>	-	-	9.1.3.2.34.
<i>Attestation Type Enumeration</i>	-	-	9.1.3.2.36.
<i>Batch Error Continuation Option Enumeration</i>	9.1.3.2.29.	9.1.3.2.30.	9.1.3.2.30.
<i>Bit Masks</i>	9.1.3.3.	9.1.3.3.	9.1.3.3.
<i>Block Cipher Mode Enumeration</i>	9.1.3.2.13.	9.1.3.2.14.	9.1.3.2.14.
<i>Cancellation Result Enumeration</i>	9.1.3.2.24.	9.1.3.2.25.	9.1.3.2.25.
<i>Certificate Request Type Enumeration</i>	9.1.3.2.21.	9.1.3.2.22.	9.1.3.2.22.
<i>Certificate Type Enumeration</i>	9.1.3.2.6.	9.1.3.2.6.	9.1.3.2.6.
<i>Credential Type Enumeration</i>	9.1.3.2.1.	9.1.3.2.1.	9.1.3.2.1.
<i>Cryptographic Algorithm Enumeration</i>	9.1.3.2.12.	9.1.3.2.13.	9.1.3.2.13.
<i>Cryptographic Usage Mask</i>	9.1.3.3.1.	9.1.3.3.1.	9.1.3.3.1.
<i>Defined Values</i>	9.1.3.	9.1.3.	9.1.3.
<i>Derivation Method Enumeration</i>	9.1.3.2.20.	9.1.3.2.21.	9.1.3.2.21.
<i>Digital Signature Algorithm Enumeration</i>	-	9.1.3.2.7.	9.1.3.2.7.
<i>Encoding Option Enumeration</i>	-	9.1.3.2.32.	9.1.3.2.32.
<i>Enumerations</i>	9.1.3.2.	9.1.3.2.	9.1.3.2.
<i>Examples</i>	9.1.2.	9.1.2.	9.1.2.
<i>Hashing Algorithm Enumeration</i>	9.1.3.2.15.	9.1.3.2.16.	9.1.3.2.16.
<i>Item Length</i>	9.1.1.3.	9.1.1.3.	9.1.1.3.
<i>Item Tag</i>	9.1.1.1.	9.1.1.1.	9.1.1.1.
<i>Item Type</i>	9.1.1.2.	9.1.1.2.	9.1.1.2.
<i>Item Value</i>	9.1.1.4.	9.1.1.4.	9.1.1.4.
<i>Key Compression Type Enumeration</i>	9.1.3.2.2.	9.1.3.2.2.	9.1.3.2.2.
<i>Key Format Type Enumeration</i>	9.1.3.2.3.	9.1.3.2.3.	9.1.3.2.3.
<i>Key Role Type Enumeration</i>	9.1.3.2.16.	9.1.3.2.17.	9.1.3.2.17.
<i>Key Value Location Type Enumeration</i>	-	-	9.1.3.2.35.
<i>Link Type Enumeration</i>	9.1.3.2.19.	9.1.3.2.20.	9.1.3.2.20.
<i>Name Type Enumeration</i>	9.1.3.2.10.	9.1.3.2.11.	9.1.3.2.11.
<i>Object Group Member Enumeration</i>	-	9.1.3.2.33.	9.1.3.2.33.
<i>Object Type Enumeration</i>	9.1.3.2.11.	9.1.3.2.12.	9.1.3.2.12.
<i>Opaque Data Type Enumeration</i>	9.1.3.2.9.	9.1.3.2.10.	9.1.3.2.10.
<i>Operation Enumeration</i>	9.1.3.2.26.	9.1.3.2.27.	9.1.3.2.27.
<i>Padding Method Enumeration</i>	9.1.3.2.14.	9.1.3.2.15.	9.1.3.2.15.
<i>Put Function Enumeration</i>	9.1.3.2.25.	9.1.3.2.26.	9.1.3.2.26.
<i>Query Function Enumeration</i>	9.1.3.2.23.	9.1.3.2.24.	9.1.3.2.24.
<i>Recommended Curve Enumeration for ECDSA, ECDH, and ECMQV</i>	9.1.3.2.5.	9.1.3.2.5.	9.1.3.2.5.
<i>Result Reason Enumeration</i>	9.1.3.2.28.	9.1.3.2.29.	9.1.3.2.29.
<i>Result Status Enumeration</i>	9.1.3.2.27.	9.1.3.2.28.	9.1.3.2.28.
<i>Revocation Reason Code Enumeration</i>	9.1.3.2.18.	9.1.3.2.19.	9.1.3.2.19.
<i>Secret Data Type Enumeration</i>	9.1.3.2.8.	9.1.3.2.9.	9.1.3.2.9.
<i>Split Key Method Enumeration</i>	9.1.3.2.7.	9.1.3.2.8.	9.1.3.2.8.
<i>State Enumeration</i>	9.1.3.2.17.	9.1.3.2.18.	9.1.3.2.18.
<i>Storage Status Mask</i>	9.1.3.3.2.	9.1.3.3.2.	9.1.3.3.2.
<i>Tags</i>	9.1.3.1.	9.1.3.1.	9.1.3.1.
<i>TTLV Encoding</i>	9.1.	9.1.	9.1.
<i>TTLV Encoding Fields</i>	9.1.1.	9.1.1.	9.1.1.
<i>Usage Limits Unit Enumeration</i>	9.1.3.2.30.	9.1.3.2.31.	9.1.3.2.31.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Validity Indicator Enumeration</i>	9.1.3.2.22.	9.1.3.2.23.	9.1.3.2.23.
<i>Wrapping Method Enumeration</i>	9.1.3.2.4.	9.1.3.2.4.	9.1.3.2.4.
<i>XML Encoding</i>	9.2.	-	-
10 Transport			
<i>Transport</i>	10	10	10
12 KMIP Server and Client Implementation Conformance			
<i>Conformance clauses for a KMIP Server</i>	12.1.	-	-
<i>KMIP Client Implementation Conformance</i>	-	12.2.	12.2.
<i>KMIP Server Implementation Conformance</i>	-	12.1.	12.1.

Appendix C. Revision History

Revision	Date	Editor	Changes Made
wd01	21-May-2013	Tim Hudson / Mahadev Karadigudda	Converted from draft proposal to OASIS template with minor rewording and inclusion of references to KMIP 1.2 documents
wd02	25-June-2013	Tim Hudson	Updated test cases and changed how multiple versions of the specification are referenced and added test cases for all versions.
wd03	6-August-2013	Tim Hudson	Updated to include Permitted Test Case Variations and updated Test Cases based on July 2013 Interop
wd04	10-August-2013	Tim Hudson	Updated Permitted Test Case Variations
wd04a	24-October-2013	Tim Hudson	Editorial update to include VendorIdentification in the list of allowed variations as per TC motion.
pr01update	11-June-2014	Tim Hudson	Updated following Public Review

391