

## KMIP Tape Library Profile Version 1.0

### Committee Specification Draft 02 / Public Review Draft 02

19 June 2014

#### Specification URIs

##### This version:

<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd02/kmip-tape-lib-profile-v1.0-csprd02.doc> (Authoritative)  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd02/kmip-tape-lib-profile-v1.0-csprd02.html>  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd02/kmip-tape-lib-profile-v1.0-csprd02.pdf>

##### Previous version:

<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd01/kmip-tape-lib-profile-v1.0-csprd01.doc> (Authoritative)  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd01/kmip-tape-lib-profile-v1.0-csprd01.html>  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd01/kmip-tape-lib-profile-v1.0-csprd01.pdf>

##### Latest version:

<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/kmip-tape-lib-profile-v1.0.doc> (Authoritative)  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/kmip-tape-lib-profile-v1.0.html>  
<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/kmip-tape-lib-profile-v1.0.pdf>

#### Technical Committee:

OASIS Key Management Interoperability Protocol (KMIP) TC

#### Chairs:

Subhash Sankuratripati ([Subhash.Sankuratripati@netapp.com](mailto:Subhash.Sankuratripati@netapp.com)), NetApp  
Saikat Saha ([saikat.saha@oracle.com](mailto:saikat.saha@oracle.com)), Oracle

#### Editors:

Tim Hudson ([tjh@cryptsoft.com](mailto:tjh@cryptsoft.com)), Cryptsoft  
Stan Feather ([stan.feather@hp.com](mailto:stan.feather@hp.com)), Hewlett-Packard  
Rod Wideman ([rod.wideman@quantum.com](mailto:rod.wideman@quantum.com)), Quantum

#### Related work:

This specification is related to:

- *Key Management Interoperability Protocol Profiles Version 1.0*. Edited by Robert Griffin and Subhash Sankuratripati. 01 October 2010. OASIS Standard. <http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.html>.
- *Key Management Interoperability Protocol Specification Version 1.1*. Edited by Robert Haas and Indra Fitzgerald. 24 January 2013. OASIS Standard. <http://docs.oasis-open.org/kmip/spec/v1.1/os/kmip-spec-v1.1-os.html>.

- *Key Management Interoperability Protocol Specification Version 1.2*. Edited by Kiran Thota and Kelley Burgin. Latest version: <http://docs.oasis-open.org/kmip/spec/v1.2/kmip-spec-v1.2.html>.

**Abstract:**

Describes a profile for Tape Libraries as KMIP clients interacting with KMIP servers.

**Status:**

This document was last revised or approved by the OASIS Key Management Interoperability Protocol (KMIP) TC on the above date. The level of approval is also listed above. Check the “Latest version” location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee’s email list. Others should send comments to the Technical Committee by using the “Send A Comment” button on the Technical Committee’s web page at <https://www.oasis-open.org/committees/kmip/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<https://www.oasis-open.org/committees/kmip/ipr.php>).

**Citation format:**

When referencing this specification the following citation format should be used:

**[kmip-tape-lib-v1.0]**

*KMIP Tape Library Profile Version 1.0*. Edited by Tim Hudson, Stan Feather, and Rod Wideman. 19 June 2014. OASIS Committee Specification Draft 02 / Public Review Draft 02.

<http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/csprd02/kmip-tape-lib-profile-v1.0-csprd02.html>. Latest version: <http://docs.oasis-open.org/kmip/kmip-tape-lib-profile/v1.0/kmip-tape-lib-profile-v1.0.html>.

---

# Notices

Copyright © OASIS Open 2014. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

---

# Table of Contents

1	Introduction.....	5
1.1	Terminology.....	5
1.2	Normative References.....	5
2	Tape Library Profile.....	7
2.1	Authentication Suite.....	7
2.2	Baseline Tape Library - Client.....	7
2.3	Baseline Tape Library - Server.....	7
2.4	Using Application Specific Information for Key Identifiers.....	9
2.5	Using Alternative Name for tape media barcode.....	10
3	Tape Library Profile Test Cases.....	11
3.1	Mandatory Test Cases KMIP v1.0.....	11
3.1.1	TL-M-1-10 - Configuration.....	11
3.1.2	TL-M-2-10 - Write with new (created) key.....	12
3.1.3	TL-M-3-10 - Read an encrypted tape.....	15
3.2	Mandatory Test Cases KMIP v1.1.....	23
3.2.1	TL-M-1-11 - Configuration.....	23
3.2.2	TL-M-2-11 - Write with new (created) key.....	24
3.2.3	TL-M-3-11 - Read an encrypted tape.....	26
3.3	Mandatory Test Cases KMIP v1.2.....	35
3.3.1	TL-M-1-12 - Configuration.....	35
3.3.2	TL-M-2-12 - Write with new (created) key.....	36
3.3.3	TL-M-3-12 - Read an encrypted tape.....	39
4	Conformance.....	48
4.1	Tape Library Client KMIP v1.0 Conformance.....	48
4.2	Tape Library Client KMIP v1.1 Conformance.....	48
4.3	Tape Library Client KMIP v1.2 Conformance.....	48
4.4	Tape Library Server KMIP v1.0 Conformance.....	48
4.5	Tape Library Server KMIP v1.1 Conformance.....	48
4.6	Tape Library Server KMIP v1.2 Conformance.....	49
4.7	Permitted Test Case Variations.....	49
4.7.1	Variable Items.....	49
4.7.2	Variable behavior.....	50
Appendix A.	Acknowledgments.....	52
Appendix B.	KMIP Specification Cross Reference.....	55
Appendix C.	Revision History.....	60

# 1 Introduction

For normative definition of the elements of KMIP see the [KMIP Specification](#) [KMIP-SPEC] and the [KMIP Profiles](#) [KMIP-PROF].

This profile defines the necessary KMIP functionality that a Tape Library operating as a KMIP client SHALL use and a KMIP server conforming to this profile SHALL support in order to interoperate in conformance with this profile.

## 1.1 Terminology

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in [RFC2119].

Key Associated Data (KAD)	Part of the tape format. May be segmented into authenticated and unauthenticated fields. KAD usage is detailed in the SCSI SSC-3 standard from the T10 organization available as ANSI INCITS 335-2000.
Hexadecimal Numeric Characters	Case-sensitive, printable, single byte ASCII characters representing the numbers 0 through 9 and uppercase alpha A through F. (US-ASCII characters 30h-39h and 41h-46h). Each byte (single 8-bit numeric value) is represented as two hexadecimal numeric characters with the high-nibble represented by the first (left-most) hexadecimal numeric character and the low-nibble represented by the second (right-most) hexadecimal numeric character.
N(a)	The maximum number of bytes in the tape authenticated KAD field. For LTO4, N(a) is 12 bytes. For LTO5, N(a) is 60 bytes. For LTO6, N(a) is 60 bytes.
N(u)	The maximum number of bytes in the tape unauthenticated KAD field. For LTO4, N(u) is 32 bytes. For LTO5, N(u) is 32 bytes. For LTO6, N(u) is 32 bytes.
N(k)	The maximum number of bytes in the tape format KAD fields – i.e. N(a) + N(u). For LTO4, N(k) is 44 bytes. For LTO5, N(k) is 92 bytes. For LTO6, N(k) is 92 bytes.

## 1.2 Normative References

- [RFC2119] Bradner, S., “Key words for use in RFCs to Indicate Requirement Levels”, BCP 14, RFC 2119, March 1997. <http://www.ietf.org/rfc/rfc2119.txt>.
- [KMIP-ENCODE] [KMIP Additional Message Encodings Version 1.0](#).  
[URL](#)  
Candidate OASIS Standard 01. **DD MMM YYYY**

19 **[KMIP-SPEC]** One or more of [KMIP-SPEC-1\_0], [KMIP-SPEC-1\_1], [KMIP-SPEC-1\_2]  
20 **[KMIP-SPEC-1\_0]** Key Management Interoperability Protocol Specification Version 1.0  
21 <http://docs.oasis-open.org/kmip/spec/v1.0/os/kmip-spec-1.0-os.doc>  
22 OASIS Standard, October 2010.  
23 **[KMIP-SPEC-1\_1]** *Key Management Interoperability Protocol Specification Version 1.1.*  
24 <http://docs.oasis-open.org/kmip/spec/v1.1/os/kmip-spec-v1.1-os.doc>  
25 OASIS Standard. 24 January 2013.  
26 **[KMIP-SPEC-1\_2]** *Key Management Interoperability Protocol Specification Version 1.2.*  
27 **URL**  
28 Candidate OASIS Standard 01. **DD MMM YYYY.**  
29 **[KMIP-PROF]** One or more of [KMIP-PROF-1\_0], [KMIP-PROF-1\_1], [KMIP-PROF-1\_2]  
30 **[KMIP-PROF-1\_0]** *Key Management Interoperability Protocol Profiles Version 1.0.* [http://docs.oasis-](http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc)  
31 [open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc](http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc)  
32 OASIS Standard. 1 October 2010.  
33 **[KMIP-PROF-1\_1]** *Key Management Interoperability Protocol Profiles Version 1.1.*  
34 <http://docs.oasis-open.org/kmip/profiles/v1.1/os/kmip-profiles-v1.1-os.doc>  
35 OASIS Standard 01. 24 January 2013.  
36 **[KMIP-PROF-1\_2]** *Key Management Interoperability Protocol Profiles Version 1.2.*  
37 **URL**  
38 Candidate OASIS Standard 01. **DD MMM YYYY.**

---

## 39 2 Tape Library Profile

40 The Tape Library Profile specifies the behavior of a tape library operating as a KMIP client interacting with  
41 a KMIP server.

### 42 2.1 Authentication Suite

43 Implementations conformant to this profile SHALL support at least one of the Authentication Suites  
44 defined within [KMIP-PROF].

### 45 2.2 Baseline Tape Library - Client

46 KMIP clients conformant to this profile under [KMIP-SPEC-1\_0]:

47 1. SHALL conform to the [KMIP-SPEC-1\_0]

48 KMIP clients conformant to this profile under [KMIP-SPEC-1\_1]:

49 2. SHALL conform to the *Baseline Client Clause* (section 5.12) of [KMIP-PROF-1\_1]

50 KMIP clients conformant to this profile under [KMIP-SPEC-1\_2]:

51 3. SHALL conform to the *Baseline Client* (section 5.2) of [KMIP-PROF-1\_2]

52 KMIP clients conformant to this profile

53 4. SHOULD support *Application Specific Information* [KMIP-SPEC] with Application Data provided  
54 by the client in accordance with section 2.4

55 5. SHOULD NOT use a *Custom Attribute* [KMIP-SPEC] that duplicates information that is already in  
56 standard *Attributes* [KMIP-SPEC]

57 6. MAY use x-Barcode as a *Custom Attribute* [KMIP-SPEC] of type Text String to store the barcode

58 7. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause  
59 within this section 2.2

60 8. MAY support extensions outside the scope of this standard (e.g., vendor extensions,  
61 conformance clauses) that do not conflict with any KMIP requirements

62 KMIP clients conformant to this profile under [KMIP-SPEC-1\_2]:

63 9. SHALL support the following *Attributes* [KMIP-SPEC]

64 a. *Alternative Name* [KMIP-SPEC-1\_2]

65 10. SHALL support the following *Message Encoding* [KMIP-SPEC-1\_2]:

66 a. *Alternative Name Type Enumeration* [KMIP-SPEC-1\_2] value:

67 i. Uninterpreted Text String

68 11. SHALL store the media barcode information in an *Alternative Name* [KMIP-SPEC-1\_2] *Attribute*  
69 [KMIP-SPEC-1\_2] in accordance with section 2.5

### 70 2.3 Baseline Tape Library - Server

71 KMIP servers conformant to this profile under [KMIP-SPEC-1\_0]:

72 1. SHALL conform to the [KMIP-SPEC-1\_0]

73 KMIP servers conformant to this profile under [KMIP-SPEC-1\_1]:

74 2. SHALL conform to the *Baseline Server* of [KMIP-PROF-1\_1]

75 KMIP servers conformant to this profile under [KMIP-SPEC-1\_2]:

76 3. SHALL conform to the *Baseline Server* of [KMIP-PROF-1\_2]

77 KMIP servers conformant to this profile:

- 78 4. SHALL support the following *Objects* [KMIP-SPEC]  
79 a. *Symmetric Key* [KMIP-SPEC]  
80 5. SHALL support the following *Attributes* [KMIP-SPEC]:  
81 a. *Name* [KMIP-SPEC]  
82 b. *Cryptographic Algorithm* [KMIP-SPEC]  
83 c. *Custom Attribute* [KMIP SPEC]  
84 d. *Application Specific Information* [KMIP SPEC]  
85 6. SHALL support the following *Client-to-Server Operations* [KMIP-SPEC]:  
86 a. *Create* [KMIP-SPEC]  
87 7. SHALL support the following *Message Contents* [KMIP-SPEC]:  
88 a. *Batch Order Option* [KMIP-SPEC] value:  
89 i. True  
90 b. *Batch Count* [KMIP-SPEC] value:  
91 i. 1 to 32  
92 8. SHALL support the following *Message Encoding* [KMIP-SPEC]:  
93 a. *Cryptographic Algorithm Enumeration* [KMIP-SPEC] value:  
94 i. AES  
95 b. *Object Type Enumeration* [KMIP-SPEC] value:  
96 i. Symmetric Key  
97 c. *Key Format Type Enumeration* [KMIP-SPEC] value:  
98 i. Raw  
99 d. *Cryptographic Length* [KMIP-SPEC] value :  
100 i. 256-bit  
101 e. *Name Type Enumeration* [KMIP-SPEC] value:  
102 i. Uninterpreted Text String  
103 9. SHALL support *Custom Attribute* [KMIP-SPEC] with the following data types and properties:  
104 a. Text String  
105 b. Integer  
106 c. Date Time  
107 10. SHALL support a minimum length of 256 characters for *Custom Attribute* [KMIP-SPEC] and  
108 *Name* [KMIP-SPEC] values where the attribute type is of variable length  
109 11. SHALL support a minimum of 30 *Custom Attribute* [KMIP-SPEC] per managed object  
110 12. SHALL support a minimum of 64 characters in *Custom Attribute* [KMIP-SPEC] names  
111 13. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause  
112 within this section 2.2  
113 14. MAY support extensions outside the scope of this standard (e.g., vendor extensions,  
114 conformance clauses) that do not conflict with any KMIP requirements  
115  
116 KMIP servers conformant to this profile under [KMIP-SPEC-1\_2]:  
117 15. SHALL support the following *Attributes* [KMIP-SPEC]  
118 a. *Alternative Name* [KMIP-SPEC-1\_2]  
119 16. SHALL support the following *Message Encoding* [KMIP-SPEC-1\_2]:  
120 a. *Alternative Name Type Enumeration* [KMIP-SPEC-1\_2] value:



## 122 2.4 Using Application Specific Information for Key Identifiers

123 This information applies to Tape Libraries that use the *Application Specific Information* [KMIP-SPEC]  
 124 attribute to store key identifiers. KMIP clients are not required to use *Application Specific Information*  
 125 [KMIP-SPEC] however KMIP servers are required to support KMIP clients that use *Application Specific*  
 126 *Information* [KMIP-SPEC] and KMIP clients that do not use *Application Specific Information* [KMIP-  
 127 SPEC].

128 The *Application Specific Information* [KMIP-SPEC] MAY be used to store data that is specific to the  
 129 application (Tape Library) using the object.

130 The following Application Namespaces SHOULD be used in the Application Namespace field of the  
 131 *Application Specific Information* [KMIP-SPEC]:

- 132 • LIBRARY-LTO, LIBRARY-LTO4, LIBRARY-LTO5, and LIBRARY-LTO6

133 For backwards compatibility with deployed Tape Library implementations, servers MAY support  
 134 VENDOR-LIBRARY-LTO as an Application Namespace, where VENDOR is an ASCII string that SHALL  
 135 NOT be further interpreted and SHALL be handled by the server as if the Application Namespace was set  
 136 to LIBRARY-LTO.

137 *Application Specific Information* [KMIP-SPEC] supports key identifiers being created either on the server  
 138 or on the client (Tape Library), but not both. This profile specifies key identifiers created by the client.

139 The *Application Specific Information* [KMIP-SPEC] method of key identification relies on the ability to  
 140 uniquely identify a key based only on its Application Data (preferably), or (alternatively) on some  
 141 combination of Application Data and *Custom Attributes* [KMIP-SPEC], which the key creator guarantees  
 142 to be unique within the Application Namespace.

143 Key identifiers stored in the KMIP server's *Application Specific Information* [KMIP-SPEC] are in ASCII  
 144 format. Key identifiers stored in the KMIP client's tape format KAD fields are numeric format. The  
 145 specific algorithm for converting between text and numeric formats is specified below.

146 All information contained in the tape format's KAD fields is converted to an ASCII string consisting of  
 147 hexadecimal numeric character pairs as follows:

- 148 1. The unauthenticated KAD is converted to text;
- 149 2. The authenticated KAD is converted to text and;
- 150 3. The converted authenticated KAD text is concatenated to the end of the converted  
 151 unauthenticated KAD text.

152 If the implementation uses client-created key identifiers, then the client generates a new identifier in  
 153 ASCII format that SHALL be unique within the chosen namespace. The source material for generating the  
 154 string is dependent on client policy. The numeric representation of this identifier SHALL be no larger than  
 155 the N(k) bytes of the KAD for the tape media being used.

156 For KMIP clients and servers conforming to this profile, *Application Specific Information* [KMIP-SPEC]  
 157 SHALL be created by the Tape Library KMIP client based on the tape format's KAD fields as follows:

- 158 1. Define an empty output buffer sufficient to contain a string with a maximum length of 2\*N(k)  
 159 bytes.
- 160 2. Copy the tape format's unauthenticated KAD (if present) to the output buffer, converting each  
 161 byte value to exactly two Hexadecimal Numeric Characters. The first byte (i.e., byte 0) of the  
 162 output buffer is the first byte of unauthenticated KAD.
- 163 3. Concatenate the tape format's authenticated KAD to the output buffer, converting each byte value  
 164 to exactly two Hexadecimal Numeric Characters.

165

166 Note: the contents of the unauthenticated KAD and authenticated KAD fields may be less than the  
 167 maximum permitted lengths; the implementation provides the correct length values to use in the algorithm  
 168 rather than using fixed maximum length fields.

169 If *Application Specific Information* [KMIP-SPEC] is supported, then it SHALL be used by the client for  
170 locating the object for the purpose of encrypting and decrypting data on tape. The *Application Specific*  
171 *Information* [KMIP-SPEC] value SHALL solely be used for this purpose.

## 172 **2.5 Using Alternative Name for tape media barcode**

173 The Tape Library client SHALL assign a text (i.e., human-readable) representation of the media barcode  
174 to the *Alternative Name* [KMIP-SPEC-1\_2] of the object. This SHALL occur on first use of the object for  
175 encryption, which normally is when the library requests the server to create the object.

176  
177 The relationship between key identifiers in *Application Specific Information* [KMIP-SPEC] and *Alternative*  
178 *Name* [KMIP-SPEC-1\_2] is as follows:

- 179 a) The values for both are provided by the client
- 180 b) The identifier in *Alternative Name* [KMIP-SPEC-1\_2] (i.e., the barcode) SHALL be used by the  
181 server administrator for finding keys associated with specific tape media (e.g., a server  
182 administrator may want to find the key(s) associated with a missing tape cartridge, where the  
183 barcode of that tape cartridge is known).
- 184 c) The *Alternative Name* [KMIP-SPEC-1\_2] SHALL NOT be used by a client for locating the object  
185 to encrypt or decrypt data, since the value (barcode) is not required to be unique and therefore  
186 does not ensure retrieval of the correct key.

## 187 3 Tape Library Profile Test Cases

188 The test cases define a number of request-response pairs for KMIP operations. Each test case is  
189 provided in the XML format specified in [KMIP-ENCODE] intended to be both human-readable and usable  
190 by automated tools. The time sequence (starting from 0) for each request-response pair is noted and line  
191 numbers are provided for ease of cross-reference for a given test sequence.

192 Each test case has a unique label (the section name) which includes indication of mandatory (-M-) or  
193 optional (-O-) status and the protocol version major and minor numbers as part of the identifier.

194 The test cases may depend on a specific configuration of a KMIP client and server being configured in a  
195 manner consistent with the test case assumptions.

196 Where possible the flow of unique identifiers between tests, the date-time values, and other dynamic  
197 items are indicated using symbolic identifiers – in actual request and response messages these dynamic  
198 values will be filled in with valid values.

199 Note: the values for the returned items and the custom attributes are illustrative. Actual values from a real  
200 client system may vary as specified in section 4.7.

### 201 3.1 Mandatory Test Cases KMIP v1.0

#### 202 3.1.1 TL-M-1-10 - Configuration

203 Determine server configuration details including operations supported (only the mandatory operations are  
204 listed in the response example), objects supported (only the mandatory objects types are listed in the  
205 response example), optional server information, and optional list of application name spaces.

```
0001 # TIME 0
0002 <RequestMessage>
0003   <RequestHeader>
0004     <ProtocolVersion>
0005       <ProtocolVersionMajor type="Integer" value="1"/>
0006       <ProtocolVersionMinor type="Integer" value="0"/>
0007     </ProtocolVersion>
0008     <BatchCount type="Integer" value="1"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Query"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <QueryFunction type="Enumeration" value="QueryOperations"/>
0015       <QueryFunction type="Enumeration" value="QueryObjects"/>
0016       <QueryFunction type="Enumeration" value="QueryServerInformation"/>
0017       <QueryFunction type="Enumeration" value="QueryApplicationNamespaces"/>
0018     </RequestPayload>
0019   </BatchItem>
0020 </RequestMessage>
0021 <ResponseMessage>
0022   <ResponseHeader>
0023     <ProtocolVersion>
0024       <ProtocolVersionMajor type="Integer" value="1"/>
0025       <ProtocolVersionMinor type="Integer" value="0"/>
0026     </ProtocolVersion>
0027     <TimeStamp type="DateTime" value="2012-10-05T21:35:17+00:00"/>
0028     <BatchCount type="Integer" value="1"/>
```

```

0028 </ResponseHeader>
0029 <BatchItem>
0030   <Operation type="Enumeration" value="Query"/>
0031   <UniqueBatchItemID type="ByteString" value="01"/>
0032   <ResultStatus type="Enumeration" value="Success"/>
0033   <ResponsePayload>
0034     <Operation type="Enumeration" value="Query"/>
0035     <Operation type="Enumeration" value="Locate"/>
0036     <Operation type="Enumeration" value="Destroy"/>
0037     <Operation type="Enumeration" value="Get"/>
0038     <Operation type="Enumeration" value="Create"/>
0039     <Operation type="Enumeration" value="Register"/>
0040     <Operation type="Enumeration" value="GetAttributes"/>
0041     <Operation type="Enumeration" value="GetAttributeList"/>
0042     <Operation type="Enumeration" value="AddAttribute"/>
0043     <Operation type="Enumeration" value="ModifyAttribute"/>
0044     <Operation type="Enumeration" value="DeleteAttribute"/>
0045     <Operation type="Enumeration" value="Activate"/>
0046     <Operation type="Enumeration" value="Revoke"/>
0047     <Operation type="Enumeration" value="Check"/>
0048     <ObjectType type="Enumeration" value="SymmetricKey"/>
0049     <ObjectType type="Enumeration" value="Template"/>
0050     <VendorIdentification type="TextString" value="server-
vendor.com"/>
0051     <ServerInformation>
0052     </ServerInformation>
0053   </ResponsePayload>
0054 </BatchItem>
0055 </ResponseMessage>

```

206

### 207 3.1.2 TL-M-2-10 - Write with new (created) key

208 This case may occur when the Write operation starts with the first block on a tape. The implementation  
209 may choose which Write operations qualify for creation of a new key. Regardless of the initiating  
210 circumstances, the Tape Library requests the server to create a new AES-256 symmetric key with  
211 appropriate identifying information which is unique within the Application Namespace.

212 Additional custom attributes MAY be specified in order to:

- 213 - ensure uniqueness of the key identifier when later Locating the key via ASI
- 214 - provide human-readable information (such as the tape Barcode value)
- 215 - provide information to support client-specific purposes

```

# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="0"/>
0006     </ProtocolVersion>
0007     <BatchOrderOption type="Boolean" value="true"/>
0008     <BatchCount type="Integer" value="2"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Create"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <ObjectType type="Enumeration" value="SymmetricKey"/>

```

```

0015     <TemplateAttribute>
0016     <Attribute>
0017         <AttributeName type="TextString" value="x-ID"/>
0018         <AttributeValue type="TextString" value="TL-M-2-10"/>
0019     </Attribute>
0020     <Attribute>
0021         <AttributeName type="TextString" value="Name"/>
0022         <AttributeValue>
0023             <NameValue type="TextString"
value="AAAAAAA1A1AA12345678901234567"/>
0024             <NameType type="Enumeration"
value="UninterpretedTextString"/>
0025         </AttributeValue>
0026     </Attribute>
0027     <Attribute>
0028         <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0029         <AttributeValue type="Enumeration" value="AES"/>
0030     </Attribute>
0031     <Attribute>
0032         <AttributeName type="TextString" value="Cryptographic
Length"/>
0033         <AttributeValue type="Integer" value="256"/>
0034     </Attribute>
0035     <Attribute>
0036         <AttributeName type="TextString" value="Cryptographic
Usage Mask"/>
0037         <AttributeValue type="Integer" value="Decrypt Encrypt"/>
0038     </Attribute>
0039     <Attribute>
0040         <AttributeName type="TextString" value="Application
Specific Information"/>
0041         <AttributeValue>
0042             <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0043             <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0044         </AttributeValue>
0045     </Attribute>
0046     <Attribute>
0047         <AttributeName type="TextString" value="x-Barcode"/>
0048         <AttributeValue type="TextString" value="XXA012A1"/>
0049     </Attribute>
0050     <Attribute>
0051         <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0052         <AttributeValue type="TextString" value="XXA012A1"/>
0053     </Attribute>
0054     <Attribute>
0055         <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0056         <AttributeValue type="Integer" value="0"/>
0057     </Attribute>
0058     <Attribute>
0059         <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0060         <AttributeValue type="DateTime" value="2012-10-

```



### 217 3.1.3 TL-M-3-10 - Read an encrypted tape

218 The Tape Library constructs an identifier string based on the method in 2.3, then requests the server to  
 219 Locate that string via ASI. A Get is then requested based on the key's unique identifier. The Tape Library  
 220 MAY update attributes associated with the Symmetric Key Managed Object. The following test case  
 221 shows extensive use of custom attributes. Custom attributes are not required if the Application Name is  
 222 unique within the Application Namespace. An implementation may also use custom attributes for vendor-  
 223 unique purposes, or to improve usability.

224 The test case destroys the key created in the previous test case to clean up after the test. Tape Library  
 225 implementations may elect to not perform this step.

226

```

# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="0"/>
0006     </ProtocolVersion>
0007     <BatchOrderOption type="Boolean" value="true"/>
0008     <BatchCount type="Integer" value="2"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Locate"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <Attribute>
0015         <AttributeName type="TextString" value="Object Type"/>
0016         <AttributeValue type="Enumeration" value="SymmetricKey"/>
0017       </Attribute>
0018       <Attribute>
0019         <AttributeName type="TextString" value="Application Specific
Information"/>
0020         <AttributeValue>
0021           <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0022           <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF123400
000"/>
0023         </AttributeValue>
0024       </Attribute>
0025     </RequestPayload>
0026   </BatchItem>
0027   <BatchItem>
0028     <Operation type="Enumeration" value="Get"/>
0029     <UniqueBatchItemID type="ByteString" value="02"/>
0030     <RequestPayload>
0031     </RequestPayload>
0032   </BatchItem>
0033 </RequestMessage>
0034 <ResponseMessage>
0035   <ResponseHeader>
0036     <ProtocolVersion>
0037       <ProtocolVersionMajor type="Integer" value="1"/>
0038       <ProtocolVersionMinor type="Integer" value="0"/>
0039     </ProtocolVersion>
0040     <TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0041     <BatchCount type="Integer" value="2"/>
  
```





```

0093     value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
0094     000"/>
0095         </AttributeValue>
0096     </Attribute>
0097 </RequestPayload>
0098 </BatchItem>
0099 <BatchItem>
0100     <Operation type="Enumeration" value="GetAttributeList"/>
0101     <UniqueBatchItemID type="ByteString" value="02"/>
0102     <RequestPayload>
0103 </RequestPayload>
0104 </BatchItem>
0105 </RequestMessage>
0106 <ResponseMessage>
0107     <ResponseHeader>
0108         <ProtocolVersion>
0109             <ProtocolVersionMajor type="Integer" value="1"/>
0110             <ProtocolVersionMinor type="Integer" value="0"/>
0111         </ProtocolVersion>
0112         <TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0113         <BatchCount type="Integer" value="2"/>
0114     </ResponseHeader>
0115     <BatchItem>
0116         <Operation type="Enumeration" value="Locate"/>
0117         <UniqueBatchItemID type="ByteString" value="01"/>
0118         <ResponseStatus type="Enumeration" value="Success"/>
0119         <ResponsePayload>
0120             <UniqueIdentifier type="TextString"
0121             value="$UNIQUE IDENTIFIER 0"/>
0122         </ResponsePayload>
0123     </BatchItem>
0124     <BatchItem>
0125         <Operation type="Enumeration" value="GetAttributeList"/>
0126         <UniqueBatchItemID type="ByteString" value="02"/>
0127         <ResponseStatus type="Enumeration" value="Success"/>
0128         <ResponsePayload>
0129             <UniqueIdentifier type="TextString"
0130             value="$UNIQUE_IDENTIFIER_0"/>
0131             <AttributeName type="TextString" value="x-ID"/>
0132             <AttributeName type="TextString" value="x-Barcode"/>
0133             <AttributeName type="TextString" value="x-VendorAttribute1"/>
0134             <AttributeName type="TextString" value="x-VendorAttribute2"/>
0135             <AttributeName type="TextString" value="x-VendorAttribute3"/>
0136             <AttributeName type="TextString" value="Unique Identifier"/>
0137             <AttributeName type="TextString" value="Object Type"/>
0138             <AttributeName type="TextString" value="Cryptographic
0139             Algorithm"/>
0140             <AttributeName type="TextString" value="Cryptographic
0141             Length"/>
0142             <AttributeName type="TextString" value="Application Specific
0143             Information"/>
0144             <AttributeName type="TextString" value="Cryptographic Usage
0145             Mask"/>
0146             <AttributeName type="TextString" value="Digest"/>
0147             <AttributeName type="TextString" value="Initial Date"/>
0148             <AttributeName type="TextString" value="Last Change Date"/>
0149             <AttributeName type="TextString" value="Lease Time"/>
0150             <AttributeName type="TextString" value="Name"/>

```

0143	<AttributeName type="TextString" value="State"/>
0144	</ResponsePayload>
0145	</BatchItem>
0146	</ResponseMessage>
	# TIME 2
0147	<RequestMessage>
0148	<RequestHeader>
0149	<ProtocolVersion>
0150	<ProtocolVersionMajor type="Integer" value="1"/>
0151	<ProtocolVersionMinor type="Integer" value="0"/>
0152	</ProtocolVersion>
0153	<BatchOrderOption type="Boolean" value="true"/>
0154	<BatchCount type="Integer" value="2"/>
0155	</RequestHeader>
0156	<BatchItem>
0157	<Operation type="Enumeration" value="Locate"/>
0158	<UniqueBatchItemID type="ByteString" value="01"/>
0159	<RequestPayload>
0160	<Attribute>
0161	<AttributeName type="TextString" value="Object Type"/>
0162	<AttributeValue type="Enumeration" value="SymmetricKey"/>
0163	</Attribute>
0164	<Attribute>
0165	<AttributeName type="TextString" value="Application Specific Information"/>
0166	<AttributeValue>
0167	<ApplicationNamespace type="TextString" value="LIBRARY-LTO"/>
0168	<ApplicationData type="TextString" value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000"/>
0169	</AttributeValue>
0170	</Attribute>
0171	</RequestPayload>
0172	</BatchItem>
0173	<BatchItem>
0174	<Operation type="Enumeration" value="GetAttributes"/>
0175	<UniqueBatchItemID type="ByteString" value="02"/>
0176	<RequestPayload>
0177	</RequestPayload>
0178	</BatchItem>
0179	</RequestMessage>
0180	<ResponseMessage>
0181	<ResponseHeader>
0182	<ProtocolVersion>
0183	<ProtocolVersionMajor type="Integer" value="1"/>
0184	<ProtocolVersionMinor type="Integer" value="0"/>
0185	</ProtocolVersion>
0186	<TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0187	<BatchCount type="Integer" value="2"/>
0188	</ResponseHeader>
0189	<BatchItem>
0190	<Operation type="Enumeration" value="Locate"/>
0191	<UniqueBatchItemID type="ByteString" value="01"/>
0192	<ResultStatus type="Enumeration" value="Success"/>
0193	<ResponsePayload>
0194	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER 0"/>

```

0195     </ResponsePayload>
0196 </BatchItem>
0197 <BatchItem>
0198   <Operation type="Enumeration" value="GetAttributes"/>
0199   <UniqueBatchItemID type="ByteString" value="02"/>
0200   <ResultStatus type="Enumeration" value="Success"/>
0201   <ResponsePayload>
0202     <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0203     <Attribute>
0204       <AttributeName type="TextString" value="x-ID"/>
0205       <AttributeValue type="TextString" value="TL-M-2-10"/>
0206     </Attribute>
0207     <Attribute>
0208       <AttributeName type="TextString" value="x-Barcode"/>
0209       <AttributeValue type="TextString" value="XXA012A1"/>
0210     </Attribute>
0211     <Attribute>
0212       <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0213       <AttributeValue type="TextString" value="XXA012A1"/>
0214     </Attribute>
0215     <Attribute>
0216       <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0217       <AttributeValue type="Integer" value="0"/>
0218     </Attribute>
0219     <Attribute>
0220       <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0221       <AttributeValue type="DateTime" value="2012-10-
05T22:08:19+00:00"/>
0222     </Attribute>
0223     <Attribute>
0224       <AttributeName type="TextString" value="Unique Identifier"/>
0225       <AttributeValue type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0226     </Attribute>
0227     <Attribute>
0228       <AttributeName type="TextString" value="Object Type"/>
0229       <AttributeValue type="Enumeration" value="SymmetricKey"/>
0230     </Attribute>
0231     <Attribute>
0232       <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0233       <AttributeValue type="Enumeration" value="AES"/>
0234     </Attribute>
0235     <Attribute>
0236       <AttributeName type="TextString" value="Cryptographic
Length"/>
0237       <AttributeValue type="Integer" value="256"/>
0238     </Attribute>
0239     <Attribute>
0240       <AttributeName type="TextString" value="Application Specific
Information"/>
0241       <AttributeValue>
0242         <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>

```

0243	<ApplicationData type="TextString" value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000000"/>
0244	</AttributeValue>
0245	</Attribute>
0246	<Attribute>
0247	<AttributeName type="TextString" value="Cryptographic Usage Mask"/>
0248	<AttributeValue type="Integer" value="Decrypt Encrypt"/>
0249	</Attribute>
0250	<Attribute>
0251	<AttributeName type="TextString" value="Digest"/>
0252	<AttributeValue>
0253	<HashingAlgorithm type="Enumeration" value="SHA_256"/>
0254	<DigestValue type="ByteString" value="0bd3d7ada745e4eb34cc9d26cc84d4852a15906b2f77f80d01fc31c28108c49b"/>
0255	</AttributeValue>
0256	</Attribute>
0257	<Attribute>
0258	<AttributeName type="TextString" value="Initial Date"/>
0259	<AttributeValue type="DateTime" value="2012-10-05T21:41:46+00:00"/>
0260	</Attribute>
0261	<Attribute>
0262	<AttributeName type="TextString" value="Last Change Date"/>
0263	<AttributeValue type="DateTime" value="2012-10-05T21:41:46+00:00"/>
0264	</Attribute>
0265	<Attribute>
0266	<AttributeName type="TextString" value="Lease Time"/>
0267	<AttributeValue type="Interval" value="3600"/>
0268	</Attribute>
0269	<Attribute>
0270	<AttributeName type="TextString" value="Name"/>
0271	<AttributeValue>
0272	<NameValue type="TextString" value="AAAAAAA1A1AA12345678901234567"/>
0273	<NameType type="Enumeration" value="UninterpretedTextString"/>
0274	</AttributeValue>
0275	</Attribute>
0276	<Attribute>
0277	<AttributeName type="TextString" value="State"/>
0278	<AttributeValue type="Enumeration" value="PreActive"/>
0279	</Attribute>
0280	</ResponsePayload>
0281	</BatchItem>
0282	</ResponseMessage>
0283	# TIME 3 <RequestMessage>
0284	<RequestHeader>
0285	<ProtocolVersion>
0286	<ProtocolVersionMajor type="Integer" value="1"/>
0287	<ProtocolVersionMinor type="Integer" value="0"/>
0288	</ProtocolVersion>
0289	<BatchOrderOption type="Boolean" value="true"/>
0290	<BatchCount type="Integer" value="3"/>

```

0291 </RequestHeader>
0292 <BatchItem>
0293   <Operation type="Enumeration" value="Locate"/>
0294   <UniqueBatchItemID type="ByteString" value="01"/>
0295   <RequestPayload>
0296     <Attribute>
0297       <AttributeName type="TextString" value="Object Type"/>
0298       <AttributeValue type="Enumeration" value="SymmetricKey"/>
0299     </Attribute>
0300     <Attribute>
0301       <AttributeName type="TextString" value="Application Specific
Information"/>
0302       <AttributeValue>
0303         <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0304         <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0305       </AttributeValue>
0306     </Attribute>
0307   </RequestPayload>
0308 </BatchItem>
0309 <BatchItem>
0310   <Operation type="Enumeration" value="ModifyAttribute"/>
0311   <UniqueBatchItemID type="ByteString" value="02"/>
0312   <RequestPayload>
0313     <Attribute>
0314       <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0315       <AttributeValue type="DateTime" value="2012-10-
05T22:27:06+00:00"/>
0316     </Attribute>
0317   </RequestPayload>
0318 </BatchItem>
0319 <BatchItem>
0320   <Operation type="Enumeration" value="ModifyAttribute"/>
0321   <UniqueBatchItemID type="ByteString" value="03"/>
0322   <RequestPayload>
0323     <Attribute>
0324       <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0325       <AttributeValue type="Integer" value="1"/>
0326     </Attribute>
0327   </RequestPayload>
0328 </BatchItem>
0329 </RequestMessage>
0330 <ResponseMessage>
0331   <ResponseHeader>
0332     <ProtocolVersion>
0333       <ProtocolVersionMajor type="Integer" value="1"/>
0334       <ProtocolVersionMinor type="Integer" value="0"/>
0335     </ProtocolVersion>
0336     <TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0337     <BatchCount type="Integer" value="3"/>
0338   </ResponseHeader>
0339   <BatchItem>
0340     <Operation type="Enumeration" value="Locate"/>
0341     <UniqueBatchItemID type="ByteString" value="01"/>

```

0342	<ResultStatus type="Enumeration" value="Success"/>
0343	<ResponsePayload>
0344	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0345	</ResponsePayload>
0346	</BatchItem>
0347	<BatchItem>
0348	<Operation type="Enumeration" value="ModifyAttribute"/>
0349	<UniqueBatchItemID type="ByteString" value="02"/>
0350	<ResultStatus type="Enumeration" value="Success"/>
0351	<ResponsePayload>
0352	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0353	<Attribute>
0354	<AttributeName type="TextString" value="x-
	VendorAttribute2"/>
0355	<AttributeValue type="DateTime" value="2012-10-
	05T22:27:06+00:00"/>
0356	</Attribute>
0357	</ResponsePayload>
0358	</BatchItem>
0359	<BatchItem>
0360	<Operation type="Enumeration" value="ModifyAttribute"/>
0361	<UniqueBatchItemID type="ByteString" value="03"/>
0362	<ResultStatus type="Enumeration" value="Success"/>
0363	<ResponsePayload>
0364	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0365	<Attribute>
0366	<AttributeName type="TextString" value="x-
	VendorAttribute3"/>
0367	<AttributeValue type="Integer" value="1"/>
0368	</Attribute>
0369	</ResponsePayload>
0370	</BatchItem>
0371	</ResponseMessage>
	<i># TIME 4</i>
0372	<RequestMessage>
0373	<RequestHeader>
0374	<ProtocolVersion>
0375	<ProtocolVersionMajor type="Integer" value="1"/>
0376	<ProtocolVersionMinor type="Integer" value="0"/>
0377	</ProtocolVersion>
0378	<BatchCount type="Integer" value="1"/>
0379	</RequestHeader>
0380	<BatchItem>
0381	<Operation type="Enumeration" value="Destroy"/>
0382	<RequestPayload>
0383	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0384	</RequestPayload>
0385	</BatchItem>
0386	</RequestMessage>
0387	<ResponseMessage>
0388	<ResponseHeader>
0389	<ProtocolVersion>
0390	<ProtocolVersionMajor type="Integer" value="1"/>
0391	<ProtocolVersionMinor type="Integer" value="0"/>

```

0392     </ProtocolVersion>
0393     <TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0394     <BatchCount type="Integer" value="1"/>
0395 </ResponseHeader>
0396 <BatchItem>
0397     <Operation type="Enumeration" value="Destroy"/>
0398     <ResultStatus type="Enumeration" value="Success"/>
0399     <ResponsePayload>
0400         <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0401     </ResponsePayload>
0402 </BatchItem>
0403 </ResponseMessage>

```

227

## 228 3.2 Mandatory Test Cases KMIP v1.1

### 229 3.2.1 TL-M-1-11 - Configuration

230 Determine server configuration details including operations supported (only the mandatory operations are  
231 listed in the response example), objects supported (only the mandatory objects types are listed in the  
232 response example), optional server information, and optional list of application name spaces.

```

0001 # TIME 0
0002 <RequestMessage>
0003     <RequestHeader>
0004         <ProtocolVersion>
0005             <ProtocolVersionMajor type="Integer" value="1"/>
0006             <ProtocolVersionMinor type="Integer" value="1"/>
0007         </ProtocolVersion>
0008         <BatchCount type="Integer" value="1"/>
0009     </RequestHeader>
0010     <BatchItem>
0011         <Operation type="Enumeration" value="Query"/>
0012         <UniqueBatchItemID type="ByteString" value="01"/>
0013         <RequestPayload>
0014             <QueryFunction type="Enumeration" value="QueryOperations"/>
0015             <QueryFunction type="Enumeration"
value="QueryServerInformation"/>
0016             <QueryFunction type="Enumeration"
value="QueryApplicationNamespaces"/>
0017         </RequestPayload>
0018     </BatchItem>
0019 </RequestMessage>
0020 <ResponseMessage>
0021     <ResponseHeader>
0022         <ProtocolVersion>
0023             <ProtocolVersionMajor type="Integer" value="1"/>
0024             <ProtocolVersionMinor type="Integer" value="1"/>
0025         </ProtocolVersion>
0026         <TimeStamp type="DateTime" value="2012-10-05T21:35:17+00:00"/>
0027         <BatchCount type="Integer" value="1"/>
0028     </ResponseHeader>
0029     <BatchItem>
0030         <Operation type="Enumeration" value="Query"/>
0031         <UniqueBatchItemID type="ByteString" value="01"/>
0032         <ResultStatus type="Enumeration" value="Success"/>

```

```

0033     <ResponsePayload>
0034         <Operation type="Enumeration" value="Query"/>
0035         <Operation type="Enumeration" value="Locate"/>
0036         <Operation type="Enumeration" value="Destroy"/>
0037         <Operation type="Enumeration" value="Get"/>
0038         <Operation type="Enumeration" value="Create"/>
0039         <Operation type="Enumeration" value="Register"/>
0040         <Operation type="Enumeration" value="GetAttributes"/>
0041         <Operation type="Enumeration" value="GetAttributeList"/>
0042         <Operation type="Enumeration" value="AddAttribute"/>
0043         <Operation type="Enumeration" value="ModifyAttribute"/>
0044         <Operation type="Enumeration" value="DeleteAttribute"/>
0045         <Operation type="Enumeration" value="Activate"/>
0046         <Operation type="Enumeration" value="Revoke"/>
0047         <Operation type="Enumeration" value="Check"/>
0048         <ObjectType type="Enumeration" value="SymmetricKey"/>
0049         <ObjectType type="Enumeration" value="Template"/>
0050         <VendorIdentification type="TextString" value="server-
vendor.com"/>
0051     <ServerInformation>
0052     </ServerInformation>
0053 </ResponsePayload>
0054 </BatchItem>
0055 </ResponseMessage>

```

233

### 234 3.2.2 TL-M-2-11 - Write with new (created) key

235 This case may occur when the Write operation starts with the first block on a tape. The implementation  
236 may choose which Write operations qualify for creation of a new key. Regardless of the initiating  
237 circumstances, the Tape Library requests the server to create a new AES-256 symmetric key with  
238 appropriate identifying information which is unique within the Application Namespace.

239 Additional custom attributes MAY be specified in order to:

- 240 - ensure uniqueness of the key identifier when later Locating the key via ASI
- 241 - provide human-readable information (such as the tape Barcode value)
- 242 - provide information to support client-specific purposes

```

# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="1"/>
0006     </ProtocolVersion>
0007     <BatchOrderOption type="Boolean" value="true"/>
0008     <BatchCount type="Integer" value="2"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Create"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <ObjectType type="Enumeration" value="SymmetricKey"/>
0015       <TemplateAttribute>
0016         <Attribute>
0017           <AttributeName type="TextString" value="x-ID"/>
0018           <AttributeValue type="TextString" value="TL-M-2-11"/>
0019         </Attribute>

```



```

0020     <Attribute>
0021         <AttributeName type="TextString" value="Name"/>
0022         <AttributeValue>
0023             <NameValue type="TextString"
value="AAAAAAA1A1AA12345678901234567"/>
0024             <NameType type="Enumeration"
value="UninterpretedTextString"/>
0025         </AttributeValue>
0026     </Attribute>
0027     <Attribute>
0028         <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0029         <AttributeValue type="Enumeration" value="AES"/>
0030     </Attribute>
0031     <Attribute>
0032         <AttributeName type="TextString" value="Cryptographic
Length"/>
0033         <AttributeValue type="Integer" value="256"/>
0034     </Attribute>
0035     <Attribute>
0036         <AttributeName type="TextString" value="Cryptographic
Usage Mask"/>
0037         <AttributeValue type="Integer" value="Decrypt Encrypt"/>
0038     </Attribute>
0039     <Attribute>
0040         <AttributeName type="TextString" value="Application
Specific Information"/>
0041         <AttributeValue>
0042             <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0043             <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0044         </AttributeValue>
0045     </Attribute>
0046     <Attribute>
0047         <AttributeName type="TextString" value="x-Barcode"/>
0048         <AttributeValue type="TextString" value="XXA012A1"/>
0049     </Attribute>
0050     <Attribute>
0051         <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0052         <AttributeValue type="TextString" value="XXA012A1"/>
0053     </Attribute>
0054     <Attribute>
0055         <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0056         <AttributeValue type="Integer" value="0"/>
0057     </Attribute>
0058     <Attribute>
0059         <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0060         <AttributeValue type="DateTime" value="2012-10-
05T22:08:19+00:00"/>
0061     </Attribute>
0062 </TemplateAttribute>
0063 </RequestPayload>
0064 </BatchItem>

```



249 unique within the Application Namespace. An implementation may also use custom attributes for vendor-  
250 unique purposes, or to improve usability.

251 The test case destroys the key created in the previous test case to clean up after the test. Tape Library  
252 implementations may elect to not perform this step.

253

```
0001 # TIME 0
0002 <RequestMessage>
0003   <RequestHeader>
0004     <ProtocolVersion>
0005       <ProtocolVersionMajor type="Integer" value="1"/>
0006       <ProtocolVersionMinor type="Integer" value="1"/>
0007     </ProtocolVersion>
0008     <BatchOrderOption type="Boolean" value="true"/>
0009     <BatchCount type="Integer" value="2"/>
0010   </RequestHeader>
0011   <BatchItem>
0012     <Operation type="Enumeration" value="Locate"/>
0013     <UniqueBatchItemID type="ByteString" value="01"/>
0014     <RequestPayload>
0015       <Attribute>
0016         <AttributeName type="TextString" value="Object Type"/>
0017         <AttributeValue type="Enumeration" value="SymmetricKey"/>
0018       </Attribute>
0019       <Attribute>
0020         <AttributeName type="TextString" value="Application Specific
0021 Information"/>
0022         <AttributeValue>
0023           <ApplicationNamespace type="TextString" value="LIBRARY-
0024 LTO"/>
0025           <ApplicationData type="TextString"
0026 value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
0027 000"/>
0028         </AttributeValue>
0029       </Attribute>
0030     </RequestPayload>
0031   </BatchItem>
0032   <BatchItem>
0033     <Operation type="Enumeration" value="Get"/>
0034     <UniqueBatchItemID type="ByteString" value="02"/>
0035     <RequestPayload>
0036     </RequestPayload>
0037   </BatchItem>
0038 </RequestMessage>
0039 <ResponseMessage>
0040   <ResponseHeader>
0041     <ProtocolVersion>
0042       <ProtocolVersionMajor type="Integer" value="1"/>
0043       <ProtocolVersionMinor type="Integer" value="1"/>
0044     </ProtocolVersion>
0045     <TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0046     <BatchCount type="Integer" value="2"/>
0047   </ResponseHeader>
0048   <BatchItem>
0049     <Operation type="Enumeration" value="Locate"/>
0050     <UniqueBatchItemID type="ByteString" value="01"/>
0051     <ResultStatus type="Enumeration" value="Success"/>
0052   </BatchItem>
0053 </ResponseMessage>
```



0097	<BatchItem>
0098	<Operation type="Enumeration" value="GetAttributeList"/>
0099	<UniqueBatchItemID type="ByteString" value="02"/>
0100	<RequestPayload>
0101	</RequestPayload>
0102	</BatchItem>
0103	</RequestMessage>
0104	<ResponseMessage>
0105	<ResponseHeader>
0106	<ProtocolVersion>
0107	<ProtocolVersionMajor type="Integer" value="1"/>
0108	<ProtocolVersionMinor type="Integer" value="1"/>
0109	</ProtocolVersion>
0110	<TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0111	<BatchCount type="Integer" value="2"/>
0112	</ResponseHeader>
0113	<BatchItem>
0114	<Operation type="Enumeration" value="Locate"/>
0115	<UniqueBatchItemID type="ByteString" value="01"/>
0116	<ResultStatus type="Enumeration" value="Success"/>
0117	<ResponsePayload>
0118	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0119	</ResponsePayload>
0120	</BatchItem>
0121	<BatchItem>
0122	<Operation type="Enumeration" value="GetAttributeList"/>
0123	<UniqueBatchItemID type="ByteString" value="02"/>
0124	<ResultStatus type="Enumeration" value="Success"/>
0125	<ResponsePayload>
0126	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0127	<AttributeName type="TextString" value="x-ID"/>
0128	<AttributeName type="TextString" value="x-Barcode"/>
0129	<AttributeName type="TextString" value="x-VendorAttribute1"/>
0130	<AttributeName type="TextString" value="x-VendorAttribute2"/>
0131	<AttributeName type="TextString" value="x-VendorAttribute3"/>
0132	<AttributeName type="TextString" value="Unique Identifier"/>
0133	<AttributeName type="TextString" value="Object Type"/>
0134	<AttributeName type="TextString" value="Cryptographic
	Algorithm"/>
0135	<AttributeName type="TextString" value="Cryptographic
	Length"/>
0136	<AttributeName type="TextString" value="Application Specific
	Information"/>
0137	<AttributeName type="TextString" value="Cryptographic Usage
	Mask"/>
0138	<AttributeName type="TextString" value="Digest"/>
0139	<AttributeName type="TextString" value="Initial Date"/>
0140	<AttributeName type="TextString" value="Last Change Date"/>
0141	<AttributeName type="TextString" value="Lease Time"/>
0142	<AttributeName type="TextString" value="Name"/>
0143	<AttributeName type="TextString" value="State"/>
0144	</ResponsePayload>
0145	</BatchItem>
0146	</ResponseMessage>
0147	# TIME 2 <RequestMessage>

```

0148 <RequestHeader>
0149   <ProtocolVersion>
0150     <ProtocolVersionMajor type="Integer" value="1"/>
0151     <ProtocolVersionMinor type="Integer" value="1"/>
0152   </ProtocolVersion>
0153   <BatchOrderOption type="Boolean" value="true"/>
0154   <BatchCount type="Integer" value="2"/>
0155 </RequestHeader>
0156 <BatchItem>
0157   <Operation type="Enumeration" value="Locate"/>
0158   <UniqueBatchItemID type="ByteString" value="01"/>
0159   <RequestPayload>
0160     <Attribute>
0161       <AttributeName type="TextString" value="Object Type"/>
0162       <AttributeValue type="Enumeration" value="SymmetricKey"/>
0163     </Attribute>
0164     <Attribute>
0165       <AttributeName type="TextString" value="Application Specific
0166 Information"/>
0167       <AttributeValue>
0168         <ApplicationNamespace type="TextString" value="LIBRARY-
0169 LTO"/>
0170         <ApplicationData type="TextString"
0171 value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
0172 000"/>
0173       </AttributeValue>
0174     </Attribute>
0175   </RequestPayload>
0176 </BatchItem>
0177 <BatchItem>
0178   <Operation type="Enumeration" value="GetAttributes"/>
0179   <UniqueBatchItemID type="ByteString" value="02"/>
0180   <RequestPayload>
0181   </RequestPayload>
0182 </BatchItem>
0183 </RequestMessage>
0184 <ResponseMessage>
0185   <ResponseHeader>
0186     <ProtocolVersion>
0187       <ProtocolVersionMajor type="Integer" value="1"/>
0188       <ProtocolVersionMinor type="Integer" value="1"/>
0189     </ProtocolVersion>
0190     <TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0191     <BatchCount type="Integer" value="2"/>
0192   </ResponseHeader>
0193   <BatchItem>
0194     <Operation type="Enumeration" value="Locate"/>
0195     <UniqueBatchItemID type="ByteString" value="01"/>
0196     <ResultStatus type="Enumeration" value="Success"/>
0197   <ResponsePayload>
0198     <UniqueIdentifier type="TextString"
0199 value="$UNIQUE_IDENTIFIER_0"/>
0200   </ResponsePayload>
0201 </BatchItem>
0202 <BatchItem>
0203   <Operation type="Enumeration" value="GetAttributes"/>
0204   <UniqueBatchItemID type="ByteString" value="02"/>
0205   <ResultStatus type="Enumeration" value="Success"/>

```

```

0201     <ResponsePayload>
0202     <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0203     <Attribute>
0204         <AttributeName type="TextString" value="x-ID"/>
0205         <AttributeValue type="TextString" value="TL-M-2-11"/>
0206     </Attribute>
0207     <Attribute>
0208         <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0209         <AttributeValue type="TextString" value="XXA012A1"/>
0210     </Attribute>
0211     <Attribute>
0212         <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0213         <AttributeValue type="Integer" value="0"/>
0214     </Attribute>
0215     <Attribute>
0216         <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0217         <AttributeValue type="DateTime" value="2012-10-
05T22:08:19+00:00"/>
0218     </Attribute>
0219     <Attribute>
0220         <AttributeName type="TextString" value="Unique Identifier"/>
0221         <AttributeValue type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0222     </Attribute>
0223     <Attribute>
0224         <AttributeName type="TextString" value="Object Type"/>
0225         <AttributeValue type="Enumeration" value="SymmetricKey"/>
0226     </Attribute>
0227     <Attribute>
0228         <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0229         <AttributeValue type="Enumeration" value="AES"/>
0230     </Attribute>
0231     <Attribute>
0232         <AttributeName type="TextString" value="Cryptographic
Length"/>
0233         <AttributeValue type="Integer" value="256"/>
0234     </Attribute>
0235     <Attribute>
0236         <AttributeName type="TextString" value="Application Specific
Information"/>
0237         <AttributeValue>
0238             <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0239             <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0240         </AttributeValue>
0241     </Attribute>
0242     <Attribute>
0243         <AttributeName type="TextString" value="Cryptographic Usage
Mask"/>
0244         <AttributeValue type="Integer" value="Decrypt Encrypt"/>
0245     </Attribute>

```

0246	<Attribute>
0247	<AttributeName type="TextString" value="Digest"/>
0248	<AttributeValue>
0249	<HashingAlgorithm type="Enumeration" value="SHA_256"/>
0250	<DigestValue type="ByteString"
	value="0bd3d7ada745e4eb34cc9d26cc84d4852a15906b2f77f80d01fc31c28108c
	49b"/>
0251	<KeyFormatType type="Enumeration" value="Raw"/>
0252	</AttributeValue>
0253	</Attribute>
0254	<Attribute>
0255	<AttributeName type="TextString" value="Fresh"/>
0256	<AttributeValue type="Boolean" value="false"/>
0257	</Attribute>
0258	<Attribute>
0259	<AttributeName type="TextString" value="Initial Date"/>
0260	<AttributeValue type="DateTime" value="2012-10-
	05T21:41:46+00:00"/>
0261	</Attribute>
0262	<Attribute>
0263	<AttributeName type="TextString" value="Last Change Date"/>
0264	<AttributeValue type="DateTime" value="2012-10-
	05T21:41:46+00:00"/>
0265	</Attribute>
0266	<Attribute>
0267	<AttributeName type="TextString" value="Lease Time"/>
0268	<AttributeValue type="Interval" value="3600"/>
0269	</Attribute>
0270	<Attribute>
0271	<AttributeName type="TextString" value="Name"/>
0272	<AttributeValue>
0273	<NameValue type="TextString"
	value="AAAAAAA1A1AA12345678901234567"/>
0274	<NameType type="Enumeration"
	value="UninterpretedTextString"/>
0275	</AttributeValue>
0276	</Attribute>
0277	<Attribute>
0278	<AttributeName type="TextString" value="State"/>
0279	<AttributeValue type="Enumeration" value="PreActive"/>
0280	</Attribute>
0281	</ResponsePayload>
0282	</BatchItem>
0283	</ResponseMessage>
	<i># TIME 3</i>
0284	<RequestMessage>
0285	<RequestHeader>
0286	<ProtocolVersion>
0287	<ProtocolVersionMajor type="Integer" value="1"/>
0288	<ProtocolVersionMinor type="Integer" value="1"/>
0289	</ProtocolVersion>
0290	<BatchOrderOption type="Boolean" value="true"/>
0291	<BatchCount type="Integer" value="3"/>
0292	</RequestHeader>
0293	<BatchItem>
0294	<Operation type="Enumeration" value="Locate"/>
0295	<UniqueBatchItemID type="ByteString" value="01"/>
0296	<RequestPayload>



```

0297     <Attribute>
0298         <AttributeName type="TextString" value="Object Type"/>
0299         <AttributeValue type="Enumeration" value="SymmetricKey"/>
0300     </Attribute>
0301     <Attribute>
0302         <AttributeName type="TextString" value="Application Specific
Information"/>
0303         <AttributeValue>
0304             <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0305             <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0306         </AttributeValue>
0307     </Attribute>
0308 </RequestPayload>
0309 </BatchItem>
0310 <BatchItem>
0311     <Operation type="Enumeration" value="ModifyAttribute"/>
0312     <UniqueBatchItemID type="ByteString" value="02"/>
0313     <RequestPayload>
0314         <Attribute>
0315             <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0316             <AttributeValue type="DateTime" value="2012-10-
05T22:27:06+00:00"/>
0317         </Attribute>
0318     </RequestPayload>
0319 </BatchItem>
0320 <BatchItem>
0321     <Operation type="Enumeration" value="ModifyAttribute"/>
0322     <UniqueBatchItemID type="ByteString" value="03"/>
0323     <RequestPayload>
0324         <Attribute>
0325             <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0326             <AttributeValue type="Integer" value="1"/>
0327         </Attribute>
0328     </RequestPayload>
0329 </BatchItem>
0330 </RequestMessage>
0331 <ResponseMessage>
0332     <ResponseHeader>
0333         <ProtocolVersion>
0334             <ProtocolVersionMajor type="Integer" value="1"/>
0335             <ProtocolVersionMinor type="Integer" value="1"/>
0336         </ProtocolVersion>
0337         <TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0338         <BatchCount type="Integer" value="3"/>
0339     </ResponseHeader>
0340     <BatchItem>
0341         <Operation type="Enumeration" value="Locate"/>
0342         <UniqueBatchItemID type="ByteString" value="01"/>
0343         <ResultStatus type="Enumeration" value="Success"/>
0344         <ResponsePayload>
0345             <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0346         </ResponsePayload>

```

0347	</BatchItem>
0348	<BatchItem>
0349	<Operation type="Enumeration" value="ModifyAttribute"/>
0350	<UniqueBatchItemID type="ByteString" value="02"/>
0351	<ResultStatus type="Enumeration" value="Success"/>
0352	<ResponsePayload>
0353	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0354	<Attribute>
0355	<AttributeName type="TextString" value="x- VendorAttribute2"/>
0356	<AttributeValue type="DateTime" value="2012-10- 05T22:27:06+00:00"/>
0357	</Attribute>
0358	</ResponsePayload>
0359	</BatchItem>
0360	<BatchItem>
0361	<Operation type="Enumeration" value="ModifyAttribute"/>
0362	<UniqueBatchItemID type="ByteString" value="03"/>
0363	<ResultStatus type="Enumeration" value="Success"/>
0364	<ResponsePayload>
0365	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0366	<Attribute>
0367	<AttributeName type="TextString" value="x- VendorAttribute3"/>
0368	<AttributeValue type="Integer" value="1"/>
0369	</Attribute>
0370	</ResponsePayload>
0371	</BatchItem>
0372	</ResponseMessage>
	<i># TIME 4</i>
0373	<RequestMessage>
0374	<RequestHeader>
0375	<ProtocolVersion>
0376	<ProtocolVersionMajor type="Integer" value="1"/>
0377	<ProtocolVersionMinor type="Integer" value="1"/>
0378	</ProtocolVersion>
0379	<BatchCount type="Integer" value="1"/>
0380	</RequestHeader>
0381	<BatchItem>
0382	<Operation type="Enumeration" value="Destroy"/>
0383	<RequestPayload>
0384	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0385	</RequestPayload>
0386	</BatchItem>
0387	</RequestMessage>
0388	<ResponseMessage>
0389	<ResponseHeader>
0390	<ProtocolVersion>
0391	<ProtocolVersionMajor type="Integer" value="1"/>
0392	<ProtocolVersionMinor type="Integer" value="1"/>
0393	</ProtocolVersion>
0394	<TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0395	<BatchCount type="Integer" value="1"/>
0396	</ResponseHeader>
0397	<BatchItem>

0398	<Operation type="Enumeration" value="Destroy"/>
0399	<ResultStatus type="Enumeration" value="Success"/>
0400	<ResponsePayload>
0401	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0402	</ResponsePayload>
0403	</BatchItem>
0404	</ResponseMessage>

254

## 255 3.3 Mandatory Test Cases KMIP v1.2

### 256 3.3.1 TL-M-1-12 - Configuration

257 Determine server configuration details including operations supported (only the mandatory operations are  
 258 listed in the response example), objects supported (only the mandatory objects types are listed in the  
 259 response example), optional server information, and optional list of application name spaces.

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="2"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<UniqueBatchItemID type="ByteString" value="01"/>
0012	<RequestPayload>
0013	<QueryFunction type="Enumeration" value="QueryOperations"/>
0014	<QueryFunction type="Enumeration" value="QueryObjects"/>
0015	<QueryFunction type="Enumeration"
	value="QueryServerInformation"/>
0016	<QueryFunction type="Enumeration"
	value="QueryApplicationNamespaces"/>
0017	</RequestPayload>
0018	</BatchItem>
0019	</RequestMessage>
0020	<ResponseMessage>
0021	<ResponseHeader>
0022	<ProtocolVersion>
0023	<ProtocolVersionMajor type="Integer" value="1"/>
0024	<ProtocolVersionMinor type="Integer" value="2"/>
0025	</ProtocolVersion>
0026	<TimeStamp type="DateTime" value="2012-10-05T21:35:17+00:00"/>
0027	<BatchCount type="Integer" value="1"/>
0028	</ResponseHeader>
0029	<BatchItem>
0030	<Operation type="Enumeration" value="Query"/>
0031	<UniqueBatchItemID type="ByteString" value="01"/>
0032	<ResultStatus type="Enumeration" value="Success"/>
0033	<ResponsePayload>
0034	<Operation type="Enumeration" value="Query"/>
0035	<Operation type="Enumeration" value="Locate"/>
0036	<Operation type="Enumeration" value="Destroy"/>
0037	<Operation type="Enumeration" value="Get"/>

```

0038     <Operation type="Enumeration" value="Create"/>
0039     <Operation type="Enumeration" value="Register"/>
0040     <Operation type="Enumeration" value="GetAttributes"/>
0041     <Operation type="Enumeration" value="GetAttributeList"/>
0042     <Operation type="Enumeration" value="AddAttribute"/>
0043     <Operation type="Enumeration" value="ModifyAttribute"/>
0044     <Operation type="Enumeration" value="DeleteAttribute"/>
0045     <Operation type="Enumeration" value="Activate"/>
0046     <Operation type="Enumeration" value="Revoke"/>
0047     <Operation type="Enumeration" value="Check"/>
0048     <ObjectType type="Enumeration" value="SymmetricKey"/>
0049     <ObjectType type="Enumeration" value="Template"/>
0050     <VendorIdentification type="TextString" value="server-
vendor.com"/>
0051     <ServerInformation>
0052     </ServerInformation>
0053     </ResponsePayload>
0054     </BatchItem>
0055 </ResponseMessage>

```

260

### 261 3.3.2 TL-M-2-12 - Write with new (created) key

262 This case may occur when the Write operation starts with the first block on a tape. The implementation  
263 may choose which Write operations qualify for creation of a new key. Regardless of the initiating  
264 circumstances, the Tape Library requests the server to create a new AES-256 symmetric key with  
265 appropriate identifying information which is unique within the Application Namespace.

266 Additional custom attributes MAY be specified in order to:

- 267 - ensure uniqueness of the key identifier when later Locating the key via ASI
- 268 - provide human-readable information (such as the tape Barcode value)
- 269 - provide information to support client-specific purposes

```

# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="2"/>
0006     </ProtocolVersion>
0007     <BatchOrderOption type="Boolean" value="true"/>
0008     <BatchCount type="Integer" value="2"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Create"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <ObjectType type="Enumeration" value="SymmetricKey"/>
0015       <TemplateAttribute>
0016         <Attribute>
0017           <AttributeName type="TextString" value="x-ID"/>
0018           <AttributeValue type="TextString" value="TL-M-2-12"/>
0019         </Attribute>
0020         <Attribute>
0021           <AttributeName type="TextString" value="Alternative
Name"/>
0022           <AttributeValue>
0023             <AlternativeNameValue type="TextString"

```

```

0024 value="XXA012A1"/>
      <AlternativeNameType type="Enumeration"
0025 value="UninterpretedTextString"/>
      </AttributeValue>
0026 </Attribute>
0027 <Attribute>
0028 <AttributeName type="TextString" value="Name"/>
0029 <AttributeValue>
0030 <NameValue type="TextString"
value="AAAAAAA1A1AA12345678901234567"/>
0031 <NameType type="Enumeration"
value="UninterpretedTextString"/>
0032 </AttributeValue>
0033 </Attribute>
0034 <Attribute>
0035 <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0036 <AttributeValue type="Enumeration" value="AES"/>
0037 </Attribute>
0038 <Attribute>
0039 <AttributeName type="TextString" value="Cryptographic
Length"/>
0040 <AttributeValue type="Integer" value="256"/>
0041 </Attribute>
0042 <Attribute>
0043 <AttributeName type="TextString" value="Cryptographic
Usage Mask"/>
0044 <AttributeValue type="Integer" value="Decrypt Encrypt"/>
0045 </Attribute>
0046 <Attribute>
0047 <AttributeName type="TextString" value="Application
Specific Information"/>
0048 <AttributeValue>
0049 <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0050 <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0051 </AttributeValue>
0052 </Attribute>
0053 <Attribute>
0054 <AttributeName type="TextString" value="x-Barcode"/>
0055 <AttributeValue type="TextString" value="XXA012A1"/>
0056 </Attribute>
0057 <Attribute>
0058 <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0059 <AttributeValue type="TextString" value="XXA012A1"/>
0060 </Attribute>
0061 <Attribute>
0062 <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0063 <AttributeValue type="Integer" value="0"/>
0064 </Attribute>
0065 <Attribute>
0066 <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0067 <AttributeValue type="DateTime" value="2012-10-

```



271 **3.3.3 TL-M-3-12 - Read an encrypted tape**

272 The Tape Library constructs an identifier string based on the method in 2.3, then requests the server to  
 273 Locate that string via ASI. A Get is then requested based on the key's unique identifier. The Tape Library  
 274 MAY update attributes associated with the Symmetric Key Managed Object. The following test case  
 275 shows extensive use of custom attributes. Custom attributes are not required if the Application Name is  
 276 unique within the Application Namespace. An implementation may also use custom attributes for vendor-  
 277 unique purposes, or to improve usability.

278 The test case destroys the key created in the previous test case to clean up after the test. Tape Library  
 279 implementations may elect to not perform this step.

280

```

# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="2"/>
0006     </ProtocolVersion>
0007     <BatchOrderOption type="Boolean" value="true"/>
0008     <BatchCount type="Integer" value="2"/>
0009   </RequestHeader>
0010   <BatchItem>
0011     <Operation type="Enumeration" value="Locate"/>
0012     <UniqueBatchItemID type="ByteString" value="01"/>
0013     <RequestPayload>
0014       <Attribute>
0015         <AttributeName type="TextString" value="Object Type"/>
0016         <AttributeValue type="Enumeration" value="SymmetricKey"/>
0017       </Attribute>
0018       <Attribute>
0019         <AttributeName type="TextString" value="Application Specific
Information"/>
0020         <AttributeValue>
0021           <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0022           <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF123400
000"/>
0023         </AttributeValue>
0024       </Attribute>
0025     </RequestPayload>
0026   </BatchItem>
0027   <BatchItem>
0028     <Operation type="Enumeration" value="Get"/>
0029     <UniqueBatchItemID type="ByteString" value="02"/>
0030     <RequestPayload>
0031     </RequestPayload>
0032   </BatchItem>
0033 </RequestMessage>
0034 <ResponseMessage>
0035   <ResponseHeader>
0036     <ProtocolVersion>
0037       <ProtocolVersionMajor type="Integer" value="1"/>
0038       <ProtocolVersionMinor type="Integer" value="2"/>
0039     </ProtocolVersion>
0040     <TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0041     <BatchCount type="Integer" value="2"/>
  
```





```

0093     value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
0094     000"/>
0095         </AttributeValue>
0096     </Attribute>
0097 </RequestPayload>
0098 </BatchItem>
0099 <BatchItem>
0100     <Operation type="Enumeration" value="GetAttributeList"/>
0101     <UniqueBatchItemID type="ByteString" value="02"/>
0102     <RequestPayload>
0103 </RequestPayload>
0104 </BatchItem>
0105 </RequestMessage>
0106 <ResponseMessage>
0107     <ResponseHeader>
0108         <ProtocolVersion>
0109             <ProtocolVersionMajor type="Integer" value="1"/>
0110             <ProtocolVersionMinor type="Integer" value="2"/>
0111         </ProtocolVersion>
0112         <TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0113         <BatchCount type="Integer" value="2"/>
0114     </ResponseHeader>
0115     <BatchItem>
0116         <Operation type="Enumeration" value="Locate"/>
0117         <UniqueBatchItemID type="ByteString" value="01"/>
0118         <ResultStatus type="Enumeration" value="Success"/>
0119         <ResponsePayload>
0120             <UniqueIdentifier type="TextString"
0121 value="$UNIQUE_IDENTIFIER 0"/>
0122         </ResponsePayload>
0123 </BatchItem>
0124 <BatchItem>
0125         <Operation type="Enumeration" value="GetAttributeList"/>
0126         <UniqueBatchItemID type="ByteString" value="02"/>
0127         <ResultStatus type="Enumeration" value="Success"/>
0128         <ResponsePayload>
0129             <UniqueIdentifier type="TextString"
0130 value="$UNIQUE_IDENTIFIER_0"/>
0131             <AttributeName type="TextString" value="x-ID"/>
0132             <AttributeName type="TextString" value="x-Barcode"/>
0133             <AttributeName type="TextString" value="x-VendorAttribute1"/>
0134             <AttributeName type="TextString" value="x-VendorAttribute2"/>
0135             <AttributeName type="TextString" value="x-VendorAttribute3"/>
0136             <AttributeName type="TextString" value="Unique Identifier"/>
0137             <AttributeName type="TextString" value="Object Type"/>
0138             <AttributeName type="TextString" value="Cryptographic
0139 Algorithm"/>
0140             <AttributeName type="TextString" value="Cryptographic
0141 Length"/>
0142             <AttributeName type="TextString" value="Application Specific
0143 Information"/>
0144             <AttributeName type="TextString" value="Cryptographic Usage
0145 Mask"/>
0146             <AttributeName type="TextString" value="Digest"/>
0147             <AttributeName type="TextString" value="Initial Date"/>
0148             <AttributeName type="TextString" value="Last Change Date"/>
0149             <AttributeName type="TextString" value="Lease Time"/>
0150             <AttributeName type="TextString" value="Name"/>

```

0143	<AttributeName type="TextString" value="Original Creation Date"/>
0144	<AttributeName type="TextString" value="State"/>
0145	</ResponsePayload>
0146	</BatchItem>
0147	</ResponseMessage>
	# TIME 2
0148	<RequestMessage>
0149	<RequestHeader>
0150	<ProtocolVersion>
0151	<ProtocolVersionMajor type="Integer" value="1"/>
0152	<ProtocolVersionMinor type="Integer" value="2"/>
0153	</ProtocolVersion>
0154	<BatchOrderOption type="Boolean" value="true"/>
0155	<BatchCount type="Integer" value="2"/>
0156	</RequestHeader>
0157	<BatchItem>
0158	<Operation type="Enumeration" value="Locate"/>
0159	<UniqueBatchItemID type="ByteString" value="01"/>
0160	<RequestPayload>
0161	<Attribute>
0162	<AttributeName type="TextString" value="Object Type"/>
0163	<AttributeValue type="Enumeration" value="SymmetricKey"/>
0164	</Attribute>
0165	<Attribute>
0166	<AttributeName type="TextString" value="Application Specific Information"/>
0167	<AttributeValue>
0168	<ApplicationNamespace type="TextString" value="LIBRARY-LTO"/>
0169	<ApplicationData type="TextString" value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000"/>
0170	</AttributeValue>
0171	</Attribute>
0172	</RequestPayload>
0173	</BatchItem>
0174	<BatchItem>
0175	<Operation type="Enumeration" value="GetAttributes"/>
0176	<UniqueBatchItemID type="ByteString" value="02"/>
0177	<RequestPayload>
0178	</RequestPayload>
0179	</BatchItem>
0180	</RequestMessage>
0181	<ResponseMessage>
0182	<ResponseHeader>
0183	<ProtocolVersion>
0184	<ProtocolVersionMajor type="Integer" value="1"/>
0185	<ProtocolVersionMinor type="Integer" value="2"/>
0186	</ProtocolVersion>
0187	<TimeStamp type="DateTime" value="2012-10-05T22:00:32+00:00"/>
0188	<BatchCount type="Integer" value="2"/>
0189	</ResponseHeader>
0190	<BatchItem>
0191	<Operation type="Enumeration" value="Locate"/>
0192	<UniqueBatchItemID type="ByteString" value="01"/>
0193	<ResultStatus type="Enumeration" value="Success"/>
0194	<ResponsePayload>

```

0195     <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0196     </ResponsePayload>
0197     </BatchItem>
0198     <BatchItem>
0199         <Operation type="Enumeration" value="GetAttributes"/>
0200         <UniqueBatchItemID type="ByteString" value="02"/>
0201         <ResultStatus type="Enumeration" value="Success"/>
0202         <ResponsePayload>
0203             <UniqueIdentifier type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0204             <Attribute>
0205                 <AttributeName type="TextString" value="x-ID"/>
0206                 <AttributeValue type="TextString" value="TL-M-2-12"/>
0207             </Attribute>
0208             <Attribute>
0209                 <AttributeName type="TextString" value="x-Barcode"/>
0210                 <AttributeValue type="TextString" value="XXA012A1"/>
0211             </Attribute>
0212             <Attribute>
0213                 <AttributeName type="TextString" value="x-
VendorAttribute1"/>
0214                 <AttributeValue type="TextString" value="XXA012A1"/>
0215             </Attribute>
0216             <Attribute>
0217                 <AttributeName type="TextString" value="x-
VendorAttribute2"/>
0218                 <AttributeValue type="Integer" value="0"/>
0219             </Attribute>
0220             <Attribute>
0221                 <AttributeName type="TextString" value="x-
VendorAttribute3"/>
0222                 <AttributeValue type="DateTime" value="2012-10-
05T22:08:19+00:00"/>
0223             </Attribute>
0224             <Attribute>
0225                 <AttributeName type="TextString" value="Unique Identifier"/>
0226                 <AttributeValue type="TextString"
value="$UNIQUE_IDENTIFIER_0"/>
0227             </Attribute>
0228             <Attribute>
0229                 <AttributeName type="TextString" value="Object Type"/>
0230                 <AttributeValue type="Enumeration" value="SymmetricKey"/>
0231             </Attribute>
0232             <Attribute>
0233                 <AttributeName type="TextString" value="Cryptographic
Algorithm"/>
0234                 <AttributeValue type="Enumeration" value="AES"/>
0235             </Attribute>
0236             <Attribute>
0237                 <AttributeName type="TextString" value="Cryptographic
Length"/>
0238                 <AttributeValue type="Integer" value="256"/>
0239             </Attribute>
0240             <Attribute>
0241                 <AttributeName type="TextString" value="Alternative Name"/>
0242                 <AttributeValue>
0243                     <AlternativeNameValue type="TextString" value="XXA012A1"/>

```

```

0244     <AlternativeNameType type="Enumeration"
value="UninterpretedTextString"/>
0245     </AttributeValue>
0246     </Attribute>
0247     <Attribute>
0248         <AttributeName type="TextString" value="Application Specific
Information"/>
0249         <AttributeValue>
0250             <ApplicationNamespace type="TextString" value="LIBRARY-
LTO"/>
0251             <ApplicationData type="TextString"
value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF1234000
000"/>
0252             </AttributeValue>
0253             </Attribute>
0254             <Attribute>
0255                 <AttributeName type="TextString" value="Cryptographic Usage
Mask"/>
0256                 <AttributeValue type="Integer" value="Decrypt Encrypt"/>
0257                 </Attribute>
0258                 <Attribute>
0259                     <AttributeName type="TextString" value="Digest"/>
0260                     <AttributeValue>
0261                         <HashingAlgorithm type="Enumeration" value="SHA_256"/>
0262                         <DigestValue type="ByteString"
value="0bd3d7ada745e4eb34cc9d26cc84d4852a15906b2f77f80d01fc31c28108c
49b"/>
0263                         <KeyFormatType type="Enumeration" value="Raw"/>
0264                         </AttributeValue>
0265                     </Attribute>
0266                     <Attribute>
0267                         <AttributeName type="TextString" value="Fresh"/>
0268                         <AttributeValue type="Boolean" value="false"/>
0269                     </Attribute>
0270                     <Attribute>
0271                         <AttributeName type="TextString" value="Initial Date"/>
0272                         <AttributeValue type="DateTime" value="2012-10-
05T21:41:46+00:00"/>
0273                     </Attribute>
0274                     <Attribute>
0275                         <AttributeName type="TextString" value="Last Change Date"/>
0276                         <AttributeValue type="DateTime" value="2012-10-
05T21:41:46+00:00"/>
0277                     </Attribute>
0278                     <Attribute>
0279                         <AttributeName type="TextString" value="Lease Time"/>
0280                         <AttributeValue type="Interval" value="3600"/>
0281                     </Attribute>
0282                     <Attribute>
0283                         <AttributeName type="TextString" value="Name"/>
0284                         <AttributeValue>
0285                             <NameValue type="TextString"
value="AAAAAAA1A1AA12345678901234567"/>
0286                             <NameType type="Enumeration"
value="UninterpretedTextString"/>
0287                             </AttributeValue>
0288                         </Attribute>
0289                     </Attribute>

```

0290	<AttributeName type="TextString" value="Original Creation
0291	Date"/>
0292	<AttributeValue type="DateTime" value="2012-10-
0293	05T21:41:46+00:00"/>
0294	</Attribute>
0295	<AttributeName type="TextString" value="State"/>
0296	<AttributeValue type="Enumeration" value="PreActive"/>
0297	</Attribute>
0298	</ResponsePayload>
0299	</BatchItem>
0300	</ResponseMessage>
0301	# TIME 3
0302	<RequestMessage>
0303	<RequestHeader>
0304	<ProtocolVersion>
0305	<ProtocolVersionMajor type="Integer" value="1"/>
0306	<ProtocolVersionMinor type="Integer" value="2"/>
0307	</ProtocolVersion>
0308	<BatchOrderOption type="Boolean" value="true"/>
0309	<BatchCount type="Integer" value="3"/>
0310	</RequestHeader>
0311	<BatchItem>
0312	<Operation type="Enumeration" value="Locate"/>
0313	<UniqueBatchItemID type="ByteString" value="01"/>
0314	<RequestPayload>
0315	<Attribute>
0316	<AttributeName type="TextString" value="Object Type"/>
0317	<AttributeValue type="Enumeration" value="SymmetricKey"/>
0318	</Attribute>
0319	<Attribute>
0320	<AttributeName type="TextString" value="Application Specific
0321	Information"/>
0322	<AttributeValue>
0323	<ApplicationNamespace type="TextString" value="LIBRARY-
0324	LTO"/>
0325	<ApplicationData type="TextString"
0326	value="123456789ABCDEF123456789123456789ABCDEF123456789ABCDEF123400
0327	000"/>
0328	</AttributeValue>
0329	</Attribute>
0330	</RequestPayload>
0331	</BatchItem>
0332	<BatchItem>
0333	<Operation type="Enumeration" value="ModifyAttribute"/>
0334	<UniqueBatchItemID type="ByteString" value="02"/>
0335	<RequestPayload>
0336	<Attribute>
0337	<AttributeName type="TextString" value="x-
0338	VendorAttribute3"/>
	<AttributeValue type="DateTime" value="2012-10-
	05T22:27:06+00:00"/>
	</Attribute>
	</RequestPayload>
	</BatchItem>
	<BatchItem>
	<Operation type="Enumeration" value="ModifyAttribute"/>
	<UniqueBatchItemID type="ByteString" value="03"/>

0339	<RequestPayload>
0340	<Attribute>
0341	<AttributeName type="TextString" value="x- VendorAttribute2"/>
0342	<AttributeValue type="Integer" value="1"/>
0343	</Attribute>
0344	</RequestPayload>
0345	</BatchItem>
0346	</RequestMessage>
0347	<ResponseMessage>
0348	<ResponseHeader>
0349	<ProtocolVersion>
0350	<ProtocolVersionMajor type="Integer" value="1"/>
0351	<ProtocolVersionMinor type="Integer" value="2"/>
0352	</ProtocolVersion>
0353	<TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0354	<BatchCount type="Integer" value="3"/>
0355	</ResponseHeader>
0356	<BatchItem>
0357	<Operation type="Enumeration" value="Locate"/>
0358	<UniqueBatchItemID type="ByteString" value="01"/>
0359	<ResultStatus type="Enumeration" value="Success"/>
0360	<ResponsePayload>
0361	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0362	</ResponsePayload>
0363	</BatchItem>
0364	<BatchItem>
0365	<Operation type="Enumeration" value="ModifyAttribute"/>
0366	<UniqueBatchItemID type="ByteString" value="02"/>
0367	<ResultStatus type="Enumeration" value="Success"/>
0368	<ResponsePayload>
0369	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0370	<Attribute>
0371	<AttributeName type="TextString" value="x- VendorAttribute3"/>
0372	<AttributeValue type="DateTime" value="2012-10- 05T22:27:06+00:00"/>
0373	</Attribute>
0374	</ResponsePayload>
0375	</BatchItem>
0376	<BatchItem>
0377	<Operation type="Enumeration" value="ModifyAttribute"/>
0378	<UniqueBatchItemID type="ByteString" value="03"/>
0379	<ResultStatus type="Enumeration" value="Success"/>
0380	<ResponsePayload>
0381	<UniqueIdentifier type="TextString" value="\$UNIQUE_IDENTIFIER_0"/>
0382	<Attribute>
0383	<AttributeName type="TextString" value="x- VendorAttribute2"/>
0384	<AttributeValue type="Integer" value="1"/>
0385	</Attribute>
0386	</ResponsePayload>
0387	</BatchItem>
0388	</ResponseMessage>
	# TIME 4

0389	<RequestMessage>
0390	<RequestHeader>
0391	<ProtocolVersion>
0392	<ProtocolVersionMajor type="Integer" value="1"/>
0393	<ProtocolVersionMinor type="Integer" value="2"/>
0394	</ProtocolVersion>
0395	<BatchCount type="Integer" value="1"/>
0396	</RequestHeader>
0397	<BatchItem>
0398	<Operation type="Enumeration" value="Destroy"/>
0399	<RequestPayload>
0400	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0401	</RequestPayload>
0402	</BatchItem>
0403	</RequestMessage>
0404	<ResponseMessage>
0405	<ResponseHeader>
0406	<ProtocolVersion>
0407	<ProtocolVersionMajor type="Integer" value="1"/>
0408	<ProtocolVersionMinor type="Integer" value="2"/>
0409	</ProtocolVersion>
0410	<TimeStamp type="DateTime" value="2012-10-05T22:00:33+00:00"/>
0411	<BatchCount type="Integer" value="1"/>
0412	</ResponseHeader>
0413	<BatchItem>
0414	<Operation type="Enumeration" value="Destroy"/>
0415	<ResultStatus type="Enumeration" value="Success"/>
0416	<ResponsePayload>
0417	<UniqueIdentifier type="TextString"
	value="\$UNIQUE_IDENTIFIER_0"/>
0418	</ResponsePayload>
0419	</BatchItem>
0420	</ResponseMessage>

281

---

## 282 4 Conformance

### 283 4.1 Tape Library Client KMIP v1.0 Conformance

284 KMIP client implementations conformant to this profile:

- 285 1. SHALL support the Authentication Suite conditions (2.1);
- 286 2. SHALL support the Baseline Tape Library - Client conditions (2.2);
- 287 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 288 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and
- 289 5. SHALL support all the Mandatory Test Cases KMIP v1.0 (3.1).

### 290 4.2 Tape Library Client KMIP v1.1 Conformance

291 KMIP client implementations conformant to this profile:

- 292 1. SHALL support the Authentication Suite conditions (2.1);
- 293 2. SHALL support the Baseline Tape Library - Client conditions (2.2);
- 294 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 295 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and
- 296 5. SHALL support all the Mandatory Test Cases KMIP v1.1 (3.2).

### 297 4.3 Tape Library Client KMIP v1.2 Conformance

298 KMIP client implementations conformant to this profile:

- 299 1. SHALL support the Authentication Suite conditions (2.1);
- 300 2. SHALL support the Baseline Tape Library - Client conditions (2.2);
- 301 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 302 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and
- 303 5. SHALL support all the Mandatory Test Cases KMIP v1.2 (3.3).

### 304 4.4 Tape Library Server KMIP v1.0 Conformance

305 KMIP server implementations conformant to this profile:

- 306 1. SHALL support the Authentication Suite conditions (2.1);
- 307 2. SHALL support the Baseline Tape Library - Server conditions (2.3);
- 308 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 309 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and
- 310 5. SHALL support all the Mandatory Test Cases KMIP v1.0 (3.1).

### 311 4.5 Tape Library Server KMIP v1.1 Conformance

312 KMIP server implementations conformant to this profile:

- 313 1. SHALL support the Authentication Suite conditions (2.1);
- 314 2. SHALL support the Baseline Tape Library - Server conditions (2.3);
- 315 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 316 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and



317 5. SHALL support all the Mandatory Test Cases KMIP v1.1 (3.2).

## 318 **4.6 Tape Library Server KMIP v1.2 Conformance**

319 KMIP server implementations conformant to this profile:

- 320 1. SHALL support the Authentication Suite conditions (2.1);
- 321 2. SHALL support the Baseline Tape Library - Server conditions (2.3);
- 322 3. SHALL support the Using Application Specific Information for Key Identifiers conditions (2.4);
- 323 4. SHALL support the Using Alternative Name for tape media barcode conditions (2.5); and
- 324 5. SHALL support all the Mandatory Test Cases KMIP v1.2 (3.3).

## 325 **4.7 Permitted Test Case Variations**

326 Whilst the test cases provided in this Profile define the allowed request and response content, some  
327 inherent variations MAY occur and are permitted within a successfully completed test case.

328 Each test case MAY include allowed variations in the description of the test case in addition to the  
329 variations noted in this section.

330 Other variations not explicitly noted in this Profile SHALL be deemed non-conformant.

### 331 **4.7.1 Variable Items**

332 An implementation conformant to this Profile MAY vary the following values:

- 333 1. UniqueIdentifier
- 334 2. PrivateKeyUniqueIdentifier
- 335 3. PublicKeyUniqueIdentifier
- 336 4. UniqueBatchItemIdentifier
- 337 5. AsynchronousCorrelationValue
- 338 6. TimeStamp
- 339 7. KeyValue / KeyMaterial including:
  - 340 a. key material content returned for managed cryptographic objects which are generated by
  - 341 the server
  - 342 b. wrapped versions of keys where the wrapping key is dynamic or the wrapping contains
  - 343 variable output for each wrap operation
- 344 8. For response containing the output of cryptographic operation in Data / SignatureData/ MACData  
345 / IVCounterNonce where:
  - 346 a. the managed object is generated by the server; or
  - 347 b. the operation inherently contains variable output
- 348 9. For the following DateTime attributes where the value is not specified in the request as a fixed  
349 DateTime value:
  - 350 a. ActivationDate
  - 351 b. ArchiveDate
  - 352 c. CompromiseDate
  - 353 d. CompromiseOccurrenceDate
  - 354 e. DeactivationDate
  - 355 f. DestroyDate
  - 356 g. InitialDate
  - 357 h. LastChangeDate

- 358 i. ProtectStartDate
- 359 j. ProcessStopDate
- 360 k. ValidityDate
- 361 l. OriginalCreationDate
- 362 10. LinkedObjectIdentifier
- 363 11. DigestValue
  - 364 a. For those managed cryptographic objects which are dynamically generated
- 365 12. KeyFormatType
  - 366 a. The key format type selected by the server when it creates managed objects
- 367 13. Digest
  - 368 a. The HashingAlgorithm selected by the server when it calculates the digest for a managed
  - 369 object for which it has access to the key material
  - 370 b. The Digest Value
- 371 14. Extensions reported in Query for ExtensionList and ExtensionMap
- 372 15. Application Namespaces reported in Query
- 373 16. Object Types reported in Query other than those noted as required in this profile
- 374 17. Operation Types reported in Query other than those noted as required in this profile (or any
- 375 referenced profile documents)
- 376 18. For TextString attribute values containing test identifiers:
  - 377 a. Additional vendor or application prefixes
- 378 19. Additional attributes beyond those noted in the response

379

An implementation conformant to this Profile MAY allow the following response variations:

- 381 20. Object Group values – May or may not return one or more Object Group values not included in
- 382 the requests
- 383 21. y-CustomAttributes – May or may not include additional server-specific associated attributes not
- 384 included in requests
- 385 22. Message Extensions – May or may not include additional (non-critical) vendor extensions
- 386 23. TemplateAttribute – May or may not be included in responses where the Template Attribute
- 387 response is noted as optional in [KMIP-SPEC]
- 388 24. AttributeIndex – May or may not include Attribute Index value where the Attribute Index value is 0
- 389 for Protocol Versions 1.1 and above.
- 390 25. ResultMessage – May or may not be included in responses and the value (if included) may vary
- 391 from the text contained within the test case.
- 392 26. The list of Protocol Versions returned in a DiscoverVersion response may include additional
- 393 protocol versions if the request has not specified a list of client supported Protocol Versions.
- 394 27. VendorIdentification - The value (if included) may vary from the text contained within the test
- 395 case.

## 396 4.7.2 Variable behavior

397 An implementation conformant to this Profile SHALL allow variation of the following behavior:

- 398 1. A test may omit the clean-up requests and responses (containing Revoke and/or Destroy) at the
- 399 end of the test provided there is a separate mechanism to remove the created objects during
- 400 testing.
- 401 2. A test may omit the test identifiers if the client is unable to include them in requests. This includes
- 402 the following attributes:

- 403                   a. Name; and  
404                   b. x-ID
- 405           3. A test MAY perform requests with multiple batch items or as multiple requests with a single batch  
406           item provided the sequence of operations are equivalent
- 407           4. A request MAY contain an optional *Authentication* [KMIP\_SPEC] structure within each request  
408

---

## Appendix A. Acknowledgments

409 The following individuals have participated in the creation of this specification and are gratefully  
410 acknowledged:

411 **Participants:**

412 Hal Aldridge, Sypris Electronics  
413 Mike Allen, Symantec  
414 Gordon Arnold, IBM  
415 Todd Arnold, IBM  
416 Richard Austin, Hewlett-Packard  
417 Lars Bagnert, PrimeKey  
418 Elaine Barker, NIST  
419 Peter Bartok, Venafi, Inc.  
420 Tom Benjamin, IBM  
421 Anthony Berglas, Cryptsoft  
422 Mathias Björkqvist, IBM  
423 Kevin Bocket, Venafi  
424 Anne Bolgert, IBM  
425 Alan Brown, Thales e-Security  
426 Tim Bruce, CA Technologies  
427 Chris Burchett, Credant Technologies, Inc.  
428 Kelley Burgin, National Security Agency  
429 Robert Burns, Thales e-Security  
430 Chuck Castleton, Venafi  
431 Kenli Chong, QuintessenceLabs  
432 John Clark, Hewlett-Packard  
433 Tom Clifford, Symantec Corp.  
434 Doron Cohen, SafeNet, Inc  
435 Tony Cox, Cryptsoft  
436 Russell Dietz, SafeNet, Inc  
437 Graydon Dodson, Lexmark International Inc.  
438 Vinod Duggirala, EMC Corporation  
439 Chris Dunn, SafeNet, Inc.  
440 Michael Duren, Sypris Electronics  
441 James Dzierzanowski, American Express CCoE  
442 Faisal Faruqui, Thales e-Security  
443 Stan Feather, Hewlett-Packard  
444 David Finkelstein, Symantec Corp.  
445 James Fitzgerald, SafeNet, Inc.  
446 Indra Fitzgerald, Hewlett-Packard  
447 Judith Furlong, EMC Corporation  
448 Susan Gleeson, Oracle  
449 Robert Griffin, EMC Corporation  
450 Paul Grojean, Individual  
451 Robert Haas, IBM  
452 Thomas Hardjono, M.I.T.  
453 ChengDong He, Huawei Technologies Co., Ltd.  
454 Steve He, Vormetric  
455 Kurt Heberlein, Hewlett-Packard  
456 Larry Hofer, Emulex Corporation  
457 Maryann Hondo, IBM  
458 Walt Hubis, NetApp  
459 Tim Hudson, Cryptsoft  
460 Jonas Iggbom, Venafi, Inc.

461 Sitaram Inguva, American Express CcoE  
462 Jay Jacobs, Target Corporation  
463 Glen Jaquette, IBM  
464 Mahadev Karadiguddi, NetApp  
465 Greg Kazmierczak, Wave Systems Corp.  
466 Marc Kenig, SafeNet, Inc.  
467 Mark Knight, Thales e-Security  
468 Kathy Kriese, Symantec Corporation  
469 Mark Lambiase, SecureAuth  
470 John Leiseboer, Quintessence Labs  
471 Hal Lockhart, Oracle Corporation  
472 Robert Lockhart, Thales e-Security  
473 Anne Luk, Cryptsoft  
474 Sairam Manidi, Freescale  
475 Luther Martin, Voltage Security  
476 Neil McEvoy, iFOSSF  
477 Marina Milshtein, Individual  
478 Dale Moberg, Axway Software  
479 Jishnu Mukeri, Hewlett-Packard  
480 Bryan Olson, Hewlett-Packard  
481 John Peck, IBM  
482 Rob Philpott, EMC Corporation  
483 Denis Pochuev, SafeNet, Inc.  
484 Reid Poole, Venafi, Inc.  
485 Ajai Puri, SafeNet, Inc.  
486 Saravanan Ramalingam, Thales e-Security  
487 Peter Reed, SafeNet, Inc.  
488 Bruce Rich, IBM  
489 Christina Richards, American Express CcoE  
490 Warren Robbins, Dell  
491 Peter Robinson, EMC Corporation  
492 Scott Rotondo, Oracle  
493 Saikat Saha, SafeNet, Inc.  
494 Anil Saldhana, Red Hat  
495 Subhash Sankuratripati, NetApp  
496 Boris Schumperli, Cryptomathic  
497 Greg Singh, QuintessenceLabs  
498 David Smith, Venafi, Inc  
499 Brian Spector, Certivox  
500 Terence Spies, Voltage Security  
501 Deborah Steckroth, RouteOne LLC  
502 Michael Stevens, QuintessenceLabs  
503 Marcus Streets, Thales e-Security  
504 Satish Sundar, IBM  
505 Kiran Thota, Vmware  
506 Somanchi Trinath, Freescale Semiconductor, Inc.  
507 Nathan Turajski, Thales e-Security  
508 Sean Turner, IECA, Inc.  
509 Paul Turner, Venafi, Inc.  
510 Rod Wideman, Quantum Corporation  
511 Steven Wierenga, Hewlett-Packard  
512 Jin Wong, QuintessenceLabs  
513 Sameer Yami, Thales e-Security  
514 Peter Yee, EMC Corporation  
515 Krishna Yellepeddy, IBM  
516 Catherine Ying, SafeNet, Inc.  
517 Tatu Ylonen, SSH Communications Security (Tectia Corp)

518 Michael Yoder, Vormetric. Inc.  
519 Magda Zdunkiewicz, Cryptsoft  
520 Peter Zelechowski, Election Systems & Software

## Appendix B. KMIP Specification Cross Reference

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<b>1 Introduction</b>			
<i>Non-Normative References</i>	1.3.	1.3.	1.3.
<i>Normative References</i>	1.2.	1.2.	1.2.
<i>Terminology</i>	1.1.	1.1.	1.1.
<b>2 Objects</b>			
<i>Attribute</i>	2.1.1.	2.1.1.	2.1.1.
<i>Base Objects</i>	2.1.	2.1.	2.1.
<i>Certificate</i>	2.2.1.	2.2.1.	2.2.1.
<i>Credential</i>	2.1.2.	2.1.2.	2.1.2.
<i>Data</i>	-	-	2.1.10.
<i>Data Length</i>	-	-	2.1.11.
<i>Extension Information</i>	-	2.1.9.	2.1.9.
<i>Key Block</i>	2.1.3.	2.1.3.	2.1.3.
<i>Key Value</i>	2.1.4.	2.1.4.	2.1.4.
<i>Key Wrapping Data</i>	2.1.5.	2.1.5.	2.1.5.
<i>Key Wrapping Specification</i>	2.1.6.	2.1.6.	2.1.6.
<i>MAC Data</i>	-	-	2.1.13.
<i>Managed Objects</i>	2.2.	2.2.	2.2.
<i>Nonce</i>	-	-	2.1.14.
<i>Opaque Object</i>	2.2.8.	2.2.8.	2.2.8.
<i>PGP Key</i>	-	-	2.2.9.
<i>Private Key</i>	2.2.4.	2.2.4.	2.2.4.
<i>Public Key</i>	2.2.3.	2.2.3.	2.2.3.
<i>Secret Data</i>	2.2.7.	2.2.7.	2.2.7.
<i>Signature Data</i>	-	-	2.1.12.
<i>Split Key</i>	2.2.5.	2.2.5.	2.2.5.
<i>Symmetric Key</i>	2.2.2.	2.2.2.	2.2.2.
<i>Template</i>	2.2.6.	2.2.6.	2.2.6.
<i>Template-Attribute Structures</i>	2.1.8.	2.1.8.	2.1.8.
<i>Transparent DH Private Key</i>	2.1.7.6.	2.1.7.6.	2.1.7.6.
<i>Transparent DH Public Key</i>	2.1.7.7.	2.1.7.7.	2.1.7.7.
<i>Transparent DSA Private Key</i>	2.1.7.2.	2.1.7.2.	2.1.7.2.
<i>Transparent DSA Public Key</i>	2.1.7.3.	2.1.7.3.	2.1.7.3.
<i>Transparent ECDH Private Key</i>	2.1.7.10.	2.1.7.10.	2.1.7.10.
<i>Transparent ECDH Public Key</i>	2.1.7.11.	2.1.7.11.	2.1.7.11.
<i>Transparent ECDSA Private Key</i>	2.1.7.8.	2.1.7.8.	2.1.7.8.
<i>Transparent ECDSA Public Key</i>	2.1.7.9.	2.1.7.9.	2.1.7.9.
<i>Transparent ECMQV Private Key</i>	2.1.7.12.	2.1.7.12.	2.1.7.12.
<i>Transparent ECMQV Public Key</i>	2.1.7.13.	2.1.7.13.	2.1.7.13.
<i>Transparent Key Structures</i>	2.1.7.	2.1.7.	2.1.7.
<i>Transparent RSA Private Key</i>	2.1.7.4.	2.1.7.4.	2.1.7.4.
<i>Transparent RSA Public Key</i>	2.1.7.5.	2.1.7.5.	2.1.7.5.
<i>Transparent Symmetric Key</i>	2.1.7.1.	2.1.7.1.	2.1.7.1.
<b>3 Attributes</b>			
<i>Activation Date</i>	3.19.	3.24.	3.24.
<i>Alternative Name</i>	-	-	3.40.
<i>Application Specific Information</i>	3.30.	3.36.	3.36.
<i>Archive Date</i>	3.27.	3.32.	3.32.

<b>Reference Term</b>	<b>KMIP 1.0</b>	<b>KMIP 1.1</b>	<b>KMIP 1.2</b>
<i>Attributes</i>	3	3	3
<i>Certificate Identifier</i>	3.9.	3.13.	3.13.
<i>Certificate Issuer</i>	3.11.	3.15.	3.15.
<i>Certificate Length</i>	-	3.9.	3.9.
<i>Certificate Subject</i>	3.10.	3.14.	3.14.
<i>Certificate Type</i>	3.8.	3.8.	3.8.
<i>Compromise Date</i>	3.25.	3.30.	3.30.
<i>Compromise Occurrence Date</i>	3.24.	3.29.	3.29.
<i>Contact Information</i>	3.31.	3.37.	3.37.
<i>Cryptographic Algorithm</i>	3.4.	3.4.	3.4.
<i>Cryptographic Domain Parameters</i>	3.7.	3.7.	3.7.
<i>Cryptographic Length</i>	3.5.	3.5.	3.5.
<i>Cryptographic Parameters</i>	3.6.	3.6.	3.6.
<i>Custom Attribute</i>	3.33.	3.39.	3.39.
<i>Deactivation Date</i>	3.22.	3.27.	3.27.
<i>Default Operation Policy</i>	3.13.2.	3.18.2.	3.18.2.
<i>Default Operation Policy for Certificates and Public Key Objects</i>	3.13.2.2.	3.18.2.2.	3.18.2.2.
<i>Default Operation Policy for Secret Objects</i>	3.13.2.1.	3.18.2.1.	3.18.2.1.
<i>Default Operation Policy for Template Objects</i>	3.13.2.3.	3.18.2.3.	3.18.2.3.
<i>Destroy Date</i>	3.23.	3.28.	3.28.
<i>Digest</i>	3.12.	3.17.	3.17.
<i>Digital Signature Algorithm</i>	-	3.16.	3.16.
<i>Fresh</i>	-	3.34.	3.34.
<i>Initial Date</i>	3.18.	3.23.	3.23.
<i>Key Value Location</i>	-	-	3.42.
<i>Key Value Present</i>	-	-	3.41.
<i>Last Change Date</i>	3.32.	3.38.	3.38.
<i>Lease Time</i>	3.15.	3.20.	3.20.
<i>Link</i>	3.29.	3.35.	3.35.
<i>Name</i>	3.2.	3.2.	3.2.
<i>Object Group</i>	3.28.	3.33.	3.33.
<i>Object Type</i>	3.3.	3.3.	3.3.
<i>Operation Policy Name</i>	3.13.	3.18.	3.18.
<i>Operations outside of operation policy control</i>	3.13.1.	3.18.1.	3.18.1.
<i>Original Creation Date</i>	-	-	3.43.
<i>Process Start Date</i>	3.20.	3.25.	3.25.
<i>Protect Stop Date</i>	3.21.	3.26.	3.26.
<i>Revocation Reason</i>	3.26.	3.31.	3.31.
<i>State</i>	3.17.	3.22.	3.22.
<i>Unique Identifier</i>	3.1.	3.1.	3.1.
<i>Usage Limits</i>	3.16.	3.21.	3.21.
<i>X.509 Certificate Identifier</i>	-	3.10.	3.10.
<i>X.509 Certificate Issuer</i>	-	3.12.	3.12.
<i>X.509 Certificate Subject</i>	-	3.11.	3.11.
<b>4 Client-to-Server Operations</b>			
<i>Activate</i>	4.18.	4.19.	4.19.
<i>Add Attribute</i>	4.13.	4.14.	4.14.
<i>Archive</i>	4.21.	4.22.	4.22.
<i>Cancel</i>	4.25.	4.27.	4.27.
<i>Certify</i>	4.6.	4.7.	4.7.
<i>Check</i>	4.9.	4.10.	4.10.
<i>Create</i>	4.1.	4.1.	4.1.
<i>Create Key Pair</i>	4.2.	4.2.	4.2.



<b>Reference Term</b>	<b>KMIP 1.0</b>	<b>KMIP 1.1</b>	<b>KMIP 1.2</b>
<i>Create Split Key</i>	-	-	4.38.
<i>Decrypt</i>	-	-	4.30.
<i>Delete Attribute</i>	4.15.	4.16.	4.16.
<i>Derive Key</i>	4.5.	4.6.	4.6.
<i>Destroy</i>	4.20.	4.21.	4.21.
<i>Discover Versions</i>	-	4.26.	4.26.
<i>Encrypt</i>	-	-	4.29.
<i>Get</i>	4.10.	4.11.	4.11.
<i>Get Attribute List</i>	4.12.	4.13.	4.13.
<i>Get Attributes</i>	4.11.	4.12.	4.12.
<i>Get Usage Allocation</i>	4.17.	4.18.	4.18.
<i>Hash</i>	-	-	4.37.
<i>Join Split Key</i>	-	-	4.39.
<i>Locate</i>	4.8.	4.9.	4.9.
<i>MAC</i>	-	-	4.33.
<i>MAC Verify</i>	-	-	4.34.
<i>Modify Attribute</i>	4.14.	4.15.	4.15.
<i>Obtain Lease</i>	4.16.	4.17.	4.17.
<i>Poll</i>	4.26.	4.28.	4.28.
<i>Query</i>	4.24.	4.25.	4.25.
<i>Re-certify</i>	4.7.	4.8.	4.8.
<i>Recover</i>	4.22.	4.23.	4.23.
<i>Register</i>	4.3.	4.3.	4.3.
<i>Re-key</i>	4.4.	4.4.	4.4.
<i>Re-key Key Pair</i>	-	4.5.	4.5.
<i>Revoke</i>	4.19.	4.20.	4.20.
<i>RNG Retrieve</i>	-	-	4.35.
<i>RNG Seed</i>	-	-	4.36.
<i>Sign</i>	-	-	4.31.
<i>Signature Verify</i>	-	-	4.32.
<i>Validate</i>	4.23.	4.24.	4.24.
<b>5 Server-to-Client Operations</b>			
<i>Notify</i>	5.1.	5.1.	5.1.
<i>Put</i>	5.2.	5.2.	5.2.
<b>6 Message Contents</b>			
<i>Asynchronous Correlation Value</i>	6.8.	6.8.	6.8.
<i>Asynchronous Indicator</i>	6.7.	6.7.	6.7.
<i>Attestation Capable Indicator</i>	-	-	6.17.
<i>Batch Count</i>	6.14.	6.14.	6.14.
<i>Batch Error Continuation Option</i>	6.13.	6.13.	6.13.
<i>Batch Item</i>	6.15.	6.15.	6.15.
<i>Batch Order Option</i>	6.12.	6.12.	6.12.
<i>Maximum Response Size</i>	6.3.	6.3.	6.3.
<i>Message Extension</i>	6.16.	6.16.	6.16.
<i>Operation</i>	6.2.	6.2.	6.2.
<i>Protocol Version</i>	6.1.	6.1.	6.1.
<i>Result Message</i>	6.11.	6.11.	6.11.
<i>Result Reason</i>	6.10.	6.10.	6.10.
<i>Result Status</i>	6.9.	6.9.	6.9.
<i>Time Stamp</i>	6.5.	6.5.	6.5.
<i>Unique Batch Item ID</i>	6.4.	6.4.	6.4.
<b>7 Message Format</b>			

<b>Reference Term</b>	<b>KMIP 1.0</b>	<b>KMIP 1.1</b>	<b>KMIP 1.2</b>
<i>Message Structure</i>	7.1.	7.1.	7.1.
<i>Operations</i>	7.2.	7.2.	7.2.
<b>8 Authentication</b>			
<i>Authentication</i>	8	8	8
<b>9 Message Encoding</b>			
<i>Alternative Name Type Enumeration</i>	-	-	9.1.3.2.34.
<i>Attestation Type Enumeration</i>	-	-	9.1.3.2.36.
<i>Batch Error Continuation Option Enumeration</i>	9.1.3.2.29.	9.1.3.2.30.	9.1.3.2.30.
<i>Bit Masks</i>	9.1.3.3.	9.1.3.3.	9.1.3.3.
<i>Block Cipher Mode Enumeration</i>	9.1.3.2.13.	9.1.3.2.14.	9.1.3.2.14.
<i>Cancellation Result Enumeration</i>	9.1.3.2.24.	9.1.3.2.25.	9.1.3.2.25.
<i>Certificate Request Type Enumeration</i>	9.1.3.2.21.	9.1.3.2.22.	9.1.3.2.22.
<i>Certificate Type Enumeration</i>	9.1.3.2.6.	9.1.3.2.6.	9.1.3.2.6.
<i>Credential Type Enumeration</i>	9.1.3.2.1.	9.1.3.2.1.	9.1.3.2.1.
<i>Cryptographic Algorithm Enumeration</i>	9.1.3.2.12.	9.1.3.2.13.	9.1.3.2.13.
<i>Cryptographic Usage Mask</i>	9.1.3.3.1.	9.1.3.3.1.	9.1.3.3.1.
<i>Defined Values</i>	9.1.3.	9.1.3.	9.1.3.
<i>Derivation Method Enumeration</i>	9.1.3.2.20.	9.1.3.2.21.	9.1.3.2.21.
<i>Digital Signature Algorithm Enumeration</i>	-	9.1.3.2.7.	9.1.3.2.7.
<i>Encoding Option Enumeration</i>	-	9.1.3.2.32.	9.1.3.2.32.
<i>Enumerations</i>	9.1.3.2.	9.1.3.2.	9.1.3.2.
<i>Examples</i>	9.1.2.	9.1.2.	9.1.2.
<i>Hashing Algorithm Enumeration</i>	9.1.3.2.15.	9.1.3.2.16.	9.1.3.2.16.
<i>Item Length</i>	9.1.1.3.	9.1.1.3.	9.1.1.3.
<i>Item Tag</i>	9.1.1.1.	9.1.1.1.	9.1.1.1.
<i>Item Type</i>	9.1.1.2.	9.1.1.2.	9.1.1.2.
<i>Item Value</i>	9.1.1.4.	9.1.1.4.	9.1.1.4.
<i>Key Compression Type Enumeration</i>	9.1.3.2.2.	9.1.3.2.2.	9.1.3.2.2.
<i>Key Format Type Enumeration</i>	9.1.3.2.3.	9.1.3.2.3.	9.1.3.2.3.
<i>Key Role Type Enumeration</i>	9.1.3.2.16.	9.1.3.2.17.	9.1.3.2.17.
<i>Key Value Location Type Enumeration</i>	-	-	9.1.3.2.35.
<i>Link Type Enumeration</i>	9.1.3.2.19.	9.1.3.2.20.	9.1.3.2.20.
<i>Name Type Enumeration</i>	9.1.3.2.10.	9.1.3.2.11.	9.1.3.2.11.
<i>Object Group Member Enumeration</i>	-	9.1.3.2.33.	9.1.3.2.33.
<i>Object Type Enumeration</i>	9.1.3.2.11.	9.1.3.2.12.	9.1.3.2.12.
<i>Opaque Data Type Enumeration</i>	9.1.3.2.9.	9.1.3.2.10.	9.1.3.2.10.
<i>Operation Enumeration</i>	9.1.3.2.26.	9.1.3.2.27.	9.1.3.2.27.
<i>Padding Method Enumeration</i>	9.1.3.2.14.	9.1.3.2.15.	9.1.3.2.15.
<i>Put Function Enumeration</i>	9.1.3.2.25.	9.1.3.2.26.	9.1.3.2.26.
<i>Query Function Enumeration</i>	9.1.3.2.23.	9.1.3.2.24.	9.1.3.2.24.
<i>Recommended Curve Enumeration for ECDSA, ECDH, and ECMQV</i>	9.1.3.2.5.	9.1.3.2.5.	9.1.3.2.5.
<i>Result Reason Enumeration</i>	9.1.3.2.28.	9.1.3.2.29.	9.1.3.2.29.
<i>Result Status Enumeration</i>	9.1.3.2.27.	9.1.3.2.28.	9.1.3.2.28.
<i>Revocation Reason Code Enumeration</i>	9.1.3.2.18.	9.1.3.2.19.	9.1.3.2.19.
<i>Secret Data Type Enumeration</i>	9.1.3.2.8.	9.1.3.2.9.	9.1.3.2.9.
<i>Split Key Method Enumeration</i>	9.1.3.2.7.	9.1.3.2.8.	9.1.3.2.8.
<i>State Enumeration</i>	9.1.3.2.17.	9.1.3.2.18.	9.1.3.2.18.
<i>Storage Status Mask</i>	9.1.3.3.2.	9.1.3.3.2.	9.1.3.3.2.
<i>Tags</i>	9.1.3.1.	9.1.3.1.	9.1.3.1.
<i>TTLV Encoding</i>	9.1.	9.1.	9.1.
<i>TTLV Encoding Fields</i>	9.1.1.	9.1.1.	9.1.1.
<i>Usage Limits Unit Enumeration</i>	9.1.3.2.30.	9.1.3.2.31.	9.1.3.2.31.

<b>Reference Term</b>	<b>KMIP 1.0</b>	<b>KMIP 1.1</b>	<b>KMIP 1.2</b>
<i>Validity Indicator Enumeration</i>	9.1.3.2.22.	9.1.3.2.23.	9.1.3.2.23.
<i>Wrapping Method Enumeration</i>	9.1.3.2.4.	9.1.3.2.4.	9.1.3.2.4.
<i>XML Encoding</i>	9.2.	-	-
<b>10 Transport</b>			
<i>Transport</i>	10	10	10
<b>12 KMIP Server and Client Implementation Conformance</b>			
<i>Conformance clauses for a KMIP Server</i>	12.1.	-	-
<i>KMIP Client Implementation Conformance</i>	-	12.2.	12.2.
<i>KMIP Server Implementation Conformance</i>	-	12.1.	12.1.

521

---

## Appendix C. Revision History

Revision	Date	Editor	Changes Made
wd01	27-Jun-2013	Tim Hudson / Rod Wideman / Stan Feather	Converted from draft proposal to OASIS template incorporating updates from Stan Feather and inclusion of references to KMIP 1.2 documents. Editorial and formatting cleanup.
wd02	6-August-2013	Tim Hudson	Updated to include Permitted Test Case Variations and updated Test Cases based on July 2013 Interop
wd03	8-August-2013	Stan Feather / Rod Wideman	Editorial changes to section 3
wd04	10-August-2013	Tim Hudson	Updated Permitted Test Case Variations
wd04a	24-October-2013	Tim Hudson	Editorial update to include VendorIdentification in the list of allowed variations as per TC motion.
pr01update	11-June-2014	Tim Hudson	Updated following Public Review

522