

OData Version 4.0 Part 3: Common Schema Definition Language (CSDL)

Committee Specification Draft 03 / Public Review Draft 03

03 October 2013

Specification URIs

This version:

<http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part3-csdl/odata-v4.0-csprd03-part3-csdl.doc> (Authoritative)
<http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part3-csdl/odata-v4.0-csprd03-part3-csdl.html>
<http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part3-csdl/odata-v4.0-csprd03-part3-csdl.pdf>

Previous version:

<http://docs.oasis-open.org/odata/odata/v4.0/cs01/part3-csdl/odata-v4.0-cs01-part3-csdl.doc> (Authoritative)
<http://docs.oasis-open.org/odata/odata/v4.0/cs01/part3-csdl/odata-v4.0-cs01-part3-csdl.html>
<http://docs.oasis-open.org/odata/odata/v4.0/cs01/part3-csdl/odata-v4.0-cs01-part3-csdl.pdf>

Latest version:

<http://docs.oasis-open.org/odata/odata/v4.0/odata-v4.0-part3-csdl.doc> (Authoritative)
<http://docs.oasis-open.org/odata/odata/v4.0/odata-v4.0-part3-csdl.html>
<http://docs.oasis-open.org/odata/odata/v4.0/odata-v4.0-part3-csdl.pdf>

Technical Committee:

OASIS Open Data Protocol (OData) TC

Chairs:

Barbara Hartel (barbara.hartel@sap.com), SAP AG
Ram Jeyaraman (Ram.Jeyaraman@microsoft.com), Microsoft

Editors:

Mike Pizzo (mikep@microsoft.com), Microsoft
Ralf Handl (ralf.handl@sap.com), SAP AG
Martin Zurmuehl (martin.zurmuehl@sap.com), SAP AG

Additional artifacts:

This prose specification is one component of a Work Product that also includes:

- *OData Version 4.0 Part 1: Protocol*. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part1-protocol/odata-v4.0-csprd03-part1-protocol.html>
- *OData Version 4.0 Part 2: URL Conventions*. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part2-url-conventions/odata-v4.0-csprd03-part2-url-conventions.html>
- *OData Version 4.0 Part 3: Common Schema Definition Language (CSDL)* (this document). <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part3-csdl/odata-v4.0-csprd03-part3-csdl.html>
- ABNF components: *OData ABNF Construction Rules Version 4.0* and *OData ABNF Test Cases*. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/abnf/>

- Vocabulary components: *OData Core Vocabulary*, *OData Measures Vocabulary* and *OData Capabilities Vocabulary*. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/vocabularies/>
- XML schemas: OData EDMX XML Schema and OData EDM XML Schema. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/schemas/>
- OData Metadata Service Entity Model: <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/models/MetadataService.edmx>

Related work:

This specification is related to:

- *OData Atom Format Version 4.0*. Latest version. <http://docs.oasis-open.org/odata/odata-atom-format/v4.0/odata-atom-format-v4.0.html>.
- *OData JSON Format Version 4.0*. Latest version. <http://docs.oasis-open.org/odata/odata-json-format/v4.0/odata-json-format-v4.0.html>.

Declared XML namespaces:

- <http://docs.oasis-open.org/odata/ns/edmx>
- <http://docs.oasis-open.org/odata/ns/edm>

Abstract:

OData services are described by an Entity Data Model (EDM). The Common Schema Definition Language (CSDL) defines an XML representation of the entity data model exposed by an OData service.

Status:

This document was last revised or approved by the OASIS Open Data Protocol (OData) TC on the above date. The level of approval is also listed above. Check the “Latest version” location noted above for possible later revisions of this document.

Technical Committee members should send comments on this specification to the Technical Committee’s email list. Others should send comments to the Technical Committee by using the “[Send A Comment](#)” button on the Technical Committee’s web page at <http://www.oasis-open.org/committees/odata/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<http://www.oasis-open.org/committees/odata/ipr.php>).

Citation format:

When referencing this specification the following citation format should be used:

[OData-Part3]

OData Version 4.0 Part 3: Common Schema Definition Language (CSDL). 03 October 2013. OASIS Committee Specification Draft 03 / Public Review Draft 03. <http://docs.oasis-open.org/odata/odata/v4.0/csprd03/part3-csdl/odata-v4.0-csprd03-part3-csdl.html>.

Notices

Copyright © OASIS Open 2013. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <http://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

Table of Contents

1	Introduction	9
1.1	Terminology	9
1.2	Normative References	9
1.3	Typographical Conventions	10
2	CSDL Namespaces	11
2.1	Namespace EDMX	11
2.2	Namespace EDM	11
2.3	XML Schema Definitions	11
2.4	XML Document Order	12
3	Entity Model Wrapper	13
3.1	Element <code>edmx:Edmx</code>	13
3.1.1	Attribute <code>Version</code>	13
3.2	Element <code>edmx:DataServices</code>	13
3.3	Element <code>edmx:Reference</code>	13
3.3.1	Attribute <code>Uri</code>	14
3.4	Element <code>edmx:Include</code>	14
3.4.1	Attribute <code>Namespace</code>	14
3.4.2	Attribute <code>Alias</code>	14
3.5	Element <code>edmx:IncludeAnnotations</code>	15
3.5.1	Attribute <code>TermNamespace</code>	15
3.5.2	Attribute <code>Qualifier</code>	15
3.5.3	Attribute <code>TargetNamespace</code>	16
4	Common Characteristics of Entity Models	17
4.1	Nominal Types	17
4.2	Structured Types	17
4.3	Structural Properties	17
4.4	Primitive Types	17
4.5	Built-In Abstract Types	19
4.6	Annotations	19
5	Schema	20
5.1	Element <code>edm:Schema</code>	20
5.1.1	Attribute <code>Namespace</code>	20
5.1.2	Attribute <code>Alias</code>	20
6	Structural Property	21
6.1	Element <code>edm:Property</code>	21
6.1.1	Attribute <code>Name</code>	21
6.1.2	Attribute <code>Type</code>	21
6.2	Property Facets	21
6.2.1	Attribute <code>Nullable</code>	21
6.2.2	Attribute <code>MaxLength</code>	22
6.2.3	Attribute <code>Precision</code>	22
6.2.4	Attribute <code>Scale</code>	22

6.2.5	Attribute Unicode	22
6.2.6	Attribute SRID	22
6.2.7	Attribute DefaultValue	23
7	Navigation Property	24
7.1	Element edm:NavigationProperty	24
7.1.1	Attribute Name	24
7.1.2	Attribute Type	24
7.1.3	Attribute Nullable	24
7.1.4	Attribute Partner	25
7.1.5	Attribute ContainsTarget	25
7.2	Element edm:ReferentialConstraint	26
7.2.1	Attribute Property	26
7.2.2	Attribute ReferencedProperty	26
7.3	Element edm:OnDelete	26
7.3.1	Attribute Action	26
8	Entity Type	28
8.1	Element edm:EntityType	28
8.1.1	Attribute Name	28
8.1.2	Attribute BaseType	28
8.1.3	Attribute Abstract	29
8.1.4	Attribute OpenType	29
8.1.5	Attribute HasStream	29
8.2	Element edm:Key	29
8.3	Element edm:PropertyRef	30
8.3.1	Attribute Name	30
8.3.2	Attribute Alias	30
9	Complex Type	32
9.1	Element edm:ComplexType	32
9.1.1	Attribute Name	32
9.1.2	Attribute BaseType	32
9.1.3	Attribute Abstract	32
9.1.4	Attribute OpenType	33
10	Enumeration Type	34
10.1	Element edm:EnumType	34
10.1.1	Attribute Name	34
10.1.2	Attribute UnderlyingType	34
10.1.3	Attribute IsFlags	34
10.2	Element edm:Member	34
10.2.1	Attribute Name	34
10.2.2	Attribute Value	35
11	Type Definition	36
11.1	Element edm:TypeDefinition	36
11.1.1	Attribute Name	36

11.1.2 Attribute UnderlyingType.....	36
11.1.3 Type Definition Facets.....	36
12 Action and Function.....	37
12.1 Element edm:Action.....	37
12.1.1 Attribute Name	37
12.1.1.1 Action Overload Rules	37
12.1.2 Attribute IsBound.....	37
12.1.3 Attribute EntitySetPath.....	37
12.2 Element edm:Function.....	38
12.2.1 Attribute Name	38
12.2.1.1 Function Overload Rules	38
12.2.2 Attribute IsBound.....	38
12.2.3 Attribute IsComposable	38
12.2.4 Attribute EntitySetPath.....	39
12.3 Element edm:ReturnType	39
12.3.1 Attribute Type	39
12.3.2 Attribute Nullable.....	39
12.4 Element edm:Parameter	39
12.4.1 Attribute Name	39
12.4.2 Attribute Type	39
12.4.3 Attribute Nullable.....	40
12.4.4 Parameter Facets.....	40
13 Entity Container.....	41
13.1 Element edm:EntityContainer	42
13.1.1 Attribute Name	42
13.1.2 Attribute Extends	42
13.2 Element edm:EntitySet	42
13.2.1 Attribute Name	42
13.2.2 Attribute EntityType	42
13.2.3 Attribute IncludeInServiceDocument.....	42
13.3 Element edm:Singleton	43
13.3.1 Attribute Name	43
13.3.2 Attribute Type	43
13.4 Element edm:NavigationPropertyBinding.....	43
13.4.1 Attribute Path	43
13.4.2 Attribute Target	43
13.5 Element edm:ActionImport.....	44
13.5.1 Attribute Name	44
13.5.2 Attribute Action	44
13.5.3 Attribute EntitySet.....	44
13.6 Element edm:FunctionImport.....	44
13.6.1 Attribute Name	44
13.6.2 Attribute Function.....	44

13.6.3	Attribute EntitySet.....	44
13.6.4	Attribute IncludeInServiceDocument	45
14	Vocabulary and Annotation	46
14.1	Element edm:Term	47
14.1.1	Attribute Name	47
14.1.2	Attribute Type	47
14.1.3	Attribute BaseTerm.....	47
14.1.4	Attribute DefaultValue	47
14.1.5	Attribute AppliesTo.....	47
14.1.6	Term Facets	47
14.2	Element edm:Annotations	48
14.2.1	Attribute Target	48
14.2.2	Attribute Qualifier.....	48
14.3	Element edm:Annotation	48
14.3.1	Attribute Term	49
14.3.2	Attribute Qualifier.....	49
14.4	Constant Expressions	49
14.4.1	Expression edm:Binary.....	50
14.4.2	Expression edm:Bool	50
14.4.3	Expression edm:Date	50
14.4.4	Expression edm:DateTimeOffset.....	50
14.4.5	Expression edm:Decimal.....	51
14.4.6	Expression edm:Duration.....	51
14.4.7	Expression edm:EnumMember	51
14.4.8	Expression edm:Float	52
14.4.9	Expression edm:Guid	52
14.4.10	Expression edm:Int	52
14.4.11	Expression edm:String.....	52
14.4.12	Expression edm:TimeOfDay	53
14.5	Dynamic Expressions	53
14.5.1	Comparison and Logical Operators	53
14.5.2	Expression edm:AnnotationPath.....	54
14.5.3	Expression edm:Apply	54
14.5.3.1	Attribute Function	54
14.5.3.1.1	Function odata.concat.....	54
14.5.3.1.2	Function odata.fillUriTemplate	55
14.5.3.1.3	Function odata.uriEncode	55
14.5.4	Expression edm:Cast	56
14.5.4.1	Attribute Type.....	56
14.5.5	Expression edm:Collection	56
14.5.6	Expression edm:If.....	56
14.5.7	Expression edm:IsOf	57
14.5.7.1	Attribute Type.....	57

14.5.8 Expression edm:LabeledElement.....	57
14.5.8.1 Attribute Name.....	58
14.5.9 Expression edm:LabeledElementReference	58
14.5.10 Expression edm:Null	58
14.5.11 Expression edm:NavigationPropertyPath	58
14.5.12 Expression edm:Path	59
14.5.13 Expression edm:PropertyPath.....	60
14.5.14 Expression edm:Record.....	61
14.5.14.1 Attribute Type.....	61
14.5.14.2 Element edm:PropertyValue	61
14.5.14.2.1 Attribute Property.....	61
14.5.15 Expression edm:UrlRef	62
15 Metadata Service Schema	63
15.1 Entity Model Wrapper	64
15.2 Schema.....	65
15.3 Types	66
15.4 Properties.....	67
15.5 Actions and Functions	70
15.6 Entity Container	71
15.7 Terms and Annotations.....	73
16 CSDL Examples	76
16.1 Products and Categories Example	76
16.2 Annotations for Products and Categories Example.....	77
17 Attribute Values	79
17.1 Namespace.....	79
17.2 SimpleIdentifier	79
17.3 QualifiedName	79
17.4 TypeName	79
17.5 TargetPath	79
17.6 Boolean.....	80
18 Conformance.....	81
Appendix A. Acknowledgments.....	82
Appendix B. Revision History	83

1 Introduction

OData services are described in terms of an Entity Data Model (EDM). The Common Schema Definition Language (CSDL) defines an XML representation of the entity data model exposed by an OData service. CSDL is articulated in the Extensible Markup Language (XML) 1.1 (Second Edition) **[XML-1.1]** with further building blocks from the W3C XML Schema Definition Language (XSD) 1.1 as described in **[XML-Schema-1]** and **[XML-Schema-2]**.

1.1 Terminology

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in **[RFC2119]**.

1.2 Normative References

- | | |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [EPSG] | European Petroleum Survey Group (EPSG). http://www.epsg.org/Geodetic.html . |
| [OData-ABNF] | <i>OData ABNF Construction Rules Version 4.0</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-Atom] | <i>OData ATOM Format Version 4.0</i> .
See link in “Related work” section on cover page. |
| [OData-EDM] | <i>OData EDM XML Schema</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-EDMX] | <i>OData EDMX XML Schema</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-JSON] | <i>OData JSON Format Version 4.0</i> .
See link in “Related work” section on cover page. |
| [OData-Meta] | <i>OData Metadata Service Schema</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-Protocol] | <i>OData Version 4.0 Part 1: Protocol</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-URL] | <i>OData Version 4.0 Part 2: URL Conventions</i> .
See link in “Additional artifacts” section on cover page. |
| [OData-VocCore] | <i>OData Core Vocabulary</i> .
See link in “Additional artifacts” section on cover page. |
| [RFC2119] | Bradner, S., “Key words for use in RFCs to Indicate Requirement Levels”, BCP 14, RFC 2119, March 1997. http://www.ietf.org/rfc/rfc2119.txt . |
| [RFC6570] | Gregorio, J., Fielding, R., Hadley, M., Nottingham, M., and D. Orchard, “URI Template”, RFC 6570, March 2012. http://tools.ietf.org/html/rfc6570 . |
| [XML-1.1] | Extensible Markup Language (XML) 1.1 (Second Edition), F. Yergeau, E. Maler, J. Cowan, T. Bray, C. M. Sperberg-McQueen, J. Paoli, Editors, W3C Recommendation, 16 August 2006,
http://www.w3.org/TR/2006/REC-xml11-20060816 .
Latest version available at http://www.w3.org/TR/xml11/ . |
| [XML-Base] | XML Base (Second Edition) , J. Marsh, R. Tobin, Editors, W3C Recommendation, 28 January 2009,
http://www.w3.org/TR/2009/REC-xmlbase-20090128/ .
Latest version available at http://www.w3.org/TR/xmlbase/ . |
| [XML-Schema-1] | W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures, D. Beech, M. Maloney, C. M. Sperberg-McQueen, H. S. Thompson, S. Gao, N. Mendelsohn, Editors, W3C Recommendation, 5 April 2012, |

<http://www.w3.org/TR/2012/REC-xmlschema11-1-20120405/>.
Latest version available at <http://www.w3.org/TR/xmlschema11-1/>.

[XML-Schema-2] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes, D. Peterson, S. Gao, C. M. Sperberg-McQueen, H. S. Thompson, P. V. Biron, A. Malhotra, Editors, W3C Recommendation, 5 April 2012,
<http://www.w3.org/TR/2012/REC-xmlschema11-2-20120405/>.
Latest version available at <http://www.w3.org/TR/xmlschema11-2/>.

1.3 Typographical Conventions

Keywords defined by this specification use this monospaced font.

Normative source code uses this paragraph style.

Some sections of this specification are illustrated with non-normative examples.

Example 1: text describing an example uses this paragraph style

Non-normative examples use this paragraph style.

All examples in this document are non-normative and informative only.

All other text is normative unless otherwise labeled.

2 CSDL Namespaces

In addition to the default XML namespace, the elements and attributes used to describe the entity model of an OData service are defined in one of the following namespaces. An XML document using these namespaces and having an `edmx:Edmx` root element will be called a CSDL document.

2.1 Namespace EDMX

Elements and attributes associated with the top-level wrapper that contains the CSDL used to define the entity model for an OData Service are qualified with the Entity Data Model for Data Services Packaging namespace:

- `http://docs.oasis-open.org/odata/ns/edmx`

Prior versions of OData used the following namespace for EDMX:

- EDMX version 1.0: `http://schemas.microsoft.com/ado/2007/06/edmx`

They are non-normative for this specification.

In this specification the namespace prefix `edmx` is used to represent the Entity Data Model for Data Services Packaging namespace, however the prefix name is not prescriptive.

2.2 Namespace EDM

Elements and attributes that define the entity model exposed by the OData Service are qualified with the Entity Data Model namespace:

- `http://docs.oasis-open.org/odata/ns/edm`

Prior versions of CSDL used the following namespaces for EDM:

- CSDL version 1.0: `http://schemas.microsoft.com/ado/2006/04/edm`
- CSDL version 1.1: `http://schemas.microsoft.com/ado/2007/05/edm`
- CSDL version 1.2: `http://schemas.microsoft.com/ado/2008/01/edm`
- CSDL version 2.0: `http://schemas.microsoft.com/ado/2008/09/edm`
- CSDL version 3.0: `http://schemas.microsoft.com/ado/2009/11/edm`

They are non-normative for this specification.

In this specification the namespace prefix `edm` is used to represent the Entity Data Model namespace, however the prefix name is not prescriptive.

2.3 XML Schema Definitions

This specification contains normative XML schemas for the EDMX and EDM namespaces; see **[OData-EDMX]** and **[OData-EDM]**.

These XML schemas only define the shape of a well-formed CSDL document, but are not descriptive enough to define what a correct CSDL document **MUST** be in every imaginable use case. This specification document defines additional rules that correct CSDL documents **MUST** fulfill. In case of doubt on what makes a CSDL document correct the rules defined in this specification document take precedence.

2.4 XML Document Order

Client libraries MUST retain the document order of XML elements for CSDL documents because for some elements the order of child elements is significant. This includes, but is not limited to, [members of enumeration types](#) and items within a [collection-valued annotation](#).

OData does not impose any ordering constraints on XML attributes within XML elements.

3 Entity Model Wrapper

An OData service exposes a single entity model. This model may be distributed over several schemas, and these schemas may be distributed over several physical locations. The entity model wrapper provides a single point of access to these parts by including them directly or referencing their physical locations.

A service is defined by a single CSDL document which can be accessed by sending a `GET` request to `<serviceRoot>/$metadata`. This document is called the metadata document. It may reference other CSDL documents.

The metadata document contains a single `entity container` that defines the resources exposed by this service. This entity container MAY `extend` an entity container defined in `referenced documents`.

The *model* of the service consists of all CSDL constructs used in its entity containers.

3.1 Element `edmx:Edmx`

A CSDL document MUST contain a root `edmx:Edmx` element. This element MUST contain a single direct child `edmx:DataServices` element. In addition to the data services element, the `Edmx` element contains zero or more `edmx:Reference` elements.

Example 2:

```
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx"
  Version="4.0">
  <edmx:DataServices>
    ...
  </edmx:DataServices>
</edmx:Edmx>
```

3.1.1 Attribute `Version`

The `edmx:Edmx` element MUST provide the value `4.0` for the `Version` attribute. It specifies the version of the EDMX wrapper defined by this version of the specification.

3.2 Element `edmx:DataServices`

The `edmx:DataServices` element MUST contain at least one `edm:Schema` element which define the schema(s) exposed by the OData service.

3.3 Element `edmx:Reference`

The `edmx:Reference` element specifies external CSDL documents referenced by the referencing document. The child elements `edmx:Include` and `edmx:IncludeAnnotations` specify which parts of the referenced document are available for use in the referencing document. The `edmx:Reference` element MUST contain at least one `edmx:Include` or `edmx:IncludeAnnotations` child element.

The `edmx:Reference` element contains zero or more `edm:Annotation` elements.

The *scope* of a CSDL document is the document itself and all schemas included from directly referenced documents. All entity types, complex types and other named elements *in scope* (that is, defined in the document itself or a schema of a directly referenced document) can be accessed from a referencing document by their namespace-qualified names.

Referencing another document may alter the model defined by the referencing document. For instance, if a referenced document defines an entity type derived from an entity type in the referencing document, then an `entity set` of the service defined by the referencing document may return entities of the derived

type. This is identical to the behavior if the derived type had been defined directly in the referencing document.

Note: referencing documents is not recursive. Only named elements defined in directly referenced documents can be accessed; elements that are defined in documents that are only referenced by referenced documents cannot be accessed.

Example 3: to reference entity models containing definitions of vocabulary terms

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx"
  Version="4.0">
  <edmx:Reference Uri="http://vocab.odata.org/capabilities/v1">
    <edmx:Include Namespace="Org.OData.Capabilities.V1" />
  </edmx:Reference>
  <edmx:Reference Uri="http://vocab.odata.org/display/v1">
    <edmx:Include Alias="UI" Namespace="org.example.Display" />
  </edmx:Reference>
  <edmx:DataServices>...</edmx:DataServices>
</edmx:Edmx>
```

3.3.1 Attribute Uri

The `edmx:Reference` element MUST specify a `Uri` attribute. The `Uri` attribute uniquely identifies a model, so two references MUST NOT specify the same URI. The value of the `Uri` attribute SHOULD be URL that locates a CSDL document describing the referenced model. If the URI is not dereferencable it SHOULD identify a well-known schema. The value of the `Uri` attribute MAY be an absolute or relative URI; relative URIs are relative to the `xml:base` attribute, see [XML-Base].

3.4 Element `edmx:Include`

The `edmx:Reference` element contains zero or more `edmx:Include` elements that specify the schemas to include from the target document.

3.4.1 Attribute Namespace

The `edmx:Include` element MUST provide a `Namespace` value for the `Namespace` attribute. The value MUST match the namespace of a schema defined in the referenced CSDL document. The same namespace MUST NOT be included more than once, even if it is declared in more than one referenced document.

3.4.2 Attribute Alias

An `edmx:Include` element MAY define a `SimpleIdentifier` value for the `Alias` attribute. The `Alias` attribute defines an alias for the specified `Namespace` that can be used in qualified names instead of the namespace. It only provides a more convenient notation. Every model element that can be used via an alias-qualified name can alternatively also be used via its full namespace-qualified name. An alias allows a short string to be substituted for a long namespace. For instance, an alias of `display` might be assigned to the namespace `org.example.vocabularies.display`. An alias-qualified name is resolved to a fully qualified name by examining aliases on `edmx:Include` and `edm:Schema` elements within the same document.

Aliases are document-global, so `edmx:Include` and `edm:Schema` elements within a document MUST NOT assign the same alias to different namespaces.

The `Alias` attribute MUST NOT use the reserved values `Edm`, `odata`, `System`, or `Transient`.

An alias is only valid within the document in which it is declared; a referencing document has to define its own aliases with the `edmx:Include` element.

3.5 Element `edmx:IncludeAnnotations`

The `edmx:Reference` element contains zero or more `edmx:IncludeAnnotations` elements that specify the annotations to include from the target document. If no `edmx:IncludeAnnotations` element is specified, a client MAY ignore all annotations in the referenced document that are not explicitly used in an `edm:Path` expression of the referencing document.

Example 4: reference documents that contain annotations

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx"
  Version="4.0">
  <edmx:Reference Uri="http://odata.org/ann/b">
    <edmx:IncludeAnnotations TermNamespace="org.example.validation" />
    <edmx:IncludeAnnotations TermNamespace="org.example.display"
      Qualifier="Tablet" />
    <edmx:IncludeAnnotations TermNamespace="org.example.hcm"
      TargetNamespace="com.contoso.Sales" />
    <edmx:IncludeAnnotations TermNamespace="org.example.hcm"
      Qualifier="Tablet"
      TargetNamespace="com.contoso.Person" />
  </edmx:Reference>
  <edmx:DataServices>...</edmx:DataServices>
</edmx:Edmx>
```

The following annotations from `http://odata.org/ann/b` are included:

- Annotations that use a term from the `org.example.validation` namespace, and
- Annotations that use a term from the `org.example.display` namespace and specify a `Tablet` qualifier and
- Annotations that apply a term from the `org.example.hcm` namespace to an element of the `com.contoso.Sales` namespace and
- Annotations that apply a term from the `org.example.hcm` namespace to an element of the `com.contoso.Person` namespace and specify a `Tablet` qualifier.

3.5.1 Attribute `TermNamespace`

An `edmx:IncludeAnnotations` element MUST provide a `Namespace` value for the `TermNamespace` attribute.

The `edmx:IncludeAnnotations` element will import the set of annotations that apply `terms` defined in the schema identified by the `TermNamespace` value. The `TermNamespace` attribute also provides consumers insight about what namespaces are used in the annotations document. If there are no `edmx:IncludeAnnotations` elements that have a term namespace of interest to the consumer, the consumer can opt not to download the document.

3.5.2 Attribute `Qualifier`

An `edmx:IncludeAnnotations` element MAY specify a `SimpleIdentifier` for the `Qualifier` attribute. A qualifier is used to apply an annotation to a subset of consumers. For instance, a service author might want to supply a different set of annotations for various device form factors.

If `Qualifier` is specified, only those annotations applying terms from the specified `TermNamespace` with the specified `Qualifier` (applied to an element of the `TargetNamespace`, if present) SHOULD be imported. If `Qualifier` is not specified, all annotations within the referenced document from the specified `TermNamespace` (taking into account the `TargetNamespace`, if present) SHOULD be imported.

The `Qualifier` attribute also provides consumers insight about what qualifiers are used in the annotations document. If the consumer is not interested in that particular qualifier, the consumer can opt not to download the document.

3.5.3 Attribute `TargetNamespace`

An `edmx:IncludeAnnotations` element MAY specify a `Namespace` value for the `TargetNamespace` attribute.

If `TargetNamespace` is specified, only those annotations which apply a term from the specified `TermNamespace` to an element of the `TargetNamespace` (with the specified `Qualifier`, if present) SHOULD be imported. If `TargetNamespace` is not specified, all annotations within the referenced document from the specified `TermNamespace` (taking into account the `Qualifier`, if present) SHOULD be imported.

The `TargetNamespace` attribute also provides consumers insight about what namespaces are used in the annotations document. If there are no target elements that have a namespace of interest to the consumer, the consumer can opt not to download the document.

4 Common Characteristics of Entity Models

4.1 Nominal Types

A nominal type has a name that MUST be a [SimpleIdentifier](#). Nominal types are referenced using their [QualifiedName](#). The qualified type name MUST be unique within a model as it facilitates references to the element from other parts of the model.

When referring to nominal types, the reference MUST use one of the following:

- [Namespace](#)-qualified name
- [Alias](#)-qualified name

Example 5:

```
<Schema xmlns="http://docs.oasis-open.org/odata/ns/edm"
  Namespace="org.example"
  Alias="sales">
  <ComplexType Name="Address">...</ComplexType>
</Schema>
```

The two ways of referring to the nominal type *Address* are:

- the fully qualified name *org.example.Address* can be used in any namespace
- an alias could be specified in any namespace and used in an alias-qualified name, e.g. *sales.Address*

4.2 Structured Types

Structured types are composed of other model elements. Structured types are common in entity models as the means of representing entities and structured properties in an OData service. [Entity types](#) and [complex types](#) are both structured types.

4.3 Structural Properties

A [structural property](#) is a property (of a structural type) that has one of the following types:

- [Primitive type](#)
- [Complex type](#)
- [Enumeration type](#)
- A collection of one of the above

4.4 Primitive Types

Structured types are composed of other structured types and primitive types. OData defines the following primitive types:

Type	Meaning
Edm.Binary	Binary data
Edm.Boolean	Binary-valued logic
Edm.Byte	Unsigned 8-bit integer
Edm.Date	Date without a time-zone offset

Type	Meaning
Edm.DateTimeOffset	Date and time with a time-zone offset, no leap seconds
Edm.Decimal	Numeric values with fixed precision and scale
Edm.Double	IEEE 754 binary64 floating-point number (15-17 decimal digits)
Edm.Duration	Signed duration in days, hours, minutes, and (sub)seconds
Edm.Guid	16-byte (128-bit) unique identifier
Edm.Int16	Signed 16-bit integer
Edm.Int32	Signed 32-bit integer
Edm.Int64	Signed 64-bit integer
Edm.SByte	Signed 8-bit integer
Edm.Single	IEEE 754 binary32 floating-point number (6-9 decimal digits)
Edm.Stream	Binary data stream
Edm.String	Sequence of UTF-8 characters
Edm.TimeOfDay	Clock time 00:00-23:59:59.999999999999
Edm.Geography	Abstract base type for all Geography types
Edm.GeographyPoint	A point in a round-earth coordinate system
Edm.GeographyLineString	Line string in a round-earth coordinate system
Edm.GeographyPolygon	Polygon in a round-earth coordinate system
Edm.GeographyMultiPoint	Collection of points in a round-earth coordinate system
Edm.GeographyMultiLineString	Collection of line strings in a round-earth coordinate system
Edm.GeographyMultiPolygon	Collection of polygons in a round-earth coordinate system
Edm.GeographyCollection	Collection of arbitrary Geography values
Edm.Geometry	Abstract base type for all Geometry types
Edm.GeometryPoint	Point in a flat-earth coordinate system
Edm.GeometryLineString	Line string in a flat-earth coordinate system
Edm.GeometryPolygon	Polygon in a flat-earth coordinate system
Edm.GeometryMultiPoint	Collection of points in a flat-earth coordinate system
Edm.GeometryMultiLineString	Collection of line strings in a flat-earth coordinate system
Edm.GeometryMultiPolygon	Collection of polygons in a flat-earth coordinate system
Edm.GeometryCollection	Collection of arbitrary Geometry values

Edm.Date and Edm.DateTimeOffset follow **[XML-Schema-2]** and use the proleptic Gregorian calendar, allowing the year 0000 and negative years.

Some of these types allow [facet attributes](#), defined in section 6.2.

See rule `primitiveLiteral` in [OData-ABNF] for the representation of primitive type values in URLs, and [OData-Atom] and [OData-JSON] for the representation in requests and responses.

4.5 Built-In Abstract Types

The following built-in abstract types can be used within a model:

- `Edm.PrimitiveType`
- `Edm.ComplexType`
- `Edm.EntityType`

Conceptually, these are the abstract base types for primitive types (including type definitions and enumeration types), complex types, and entity types, respectively, and can be used anywhere a corresponding concrete type can be used, except:

- `Edm.EntityType`
 - cannot be used as the type of a singleton in an entity container because it doesn't define a structure, which defeats the purpose of a singleton.
 - cannot be used as the type of an entity set because all entities in an entity set must have the same key fields to uniquely identify them within the set.
 - cannot be the base type of an entity type or complex type.
- `Edm.ComplexType`
 - cannot be the base type of an entity type or complex type.
- `Edm.PrimitiveType`
 - cannot be used as the type of a key property of an entity type.
 - cannot be used as the underlying type of a type definition or enumeration type.
- `Collection(Edm.PrimitiveType)` and `Collection(Edm.ComplexType)`
 - cannot be used as the type of a property.
 - cannot be used as the return type of a function.

Vocabulary terms can, in addition, use

- `Edm.AnnotationPath`
- `Edm.PropertyPath`
- `Edm.NavigationPropertyPath`

as the type of a primitive term, or the type of a property of a complex type that is exclusively used as the type of a term.

4.6 Annotations

Many parts of the model can be annotated with additional information using the `edm:Annotation` element.

A model element MUST NOT specify more than one annotation for a given combination of `Term` and `Qualifier` attributes.

Vocabulary annotations can be specified as a child of the model element being annotated or as a child of an `edm:Annotations` element that targets the model element.

Refer to [Vocabulary Annotations](#) for details on which model elements support vocabulary annotations.

5 Schema

One or more schemas describe the entity model exposed by an OData service. The schema acts as a namespace for elements of the entity model such as entity types, complex types, enumerations and terms.

5.1 Element `edm:Schema`

The `edm:Schema` element contains one or more of the following elements:

- `edm:Action`
- `edm:Annotations`
- `edm:Annotation`
- `edm:ComplexType`
- `edm:EntityContainer`
- `edm:EntityType`
- `edm:EnumType`
- `edm:Function`
- `edm:Term`
- `edm:TypeDefinition`

Values of the `Name` attribute MUST be unique across all direct child elements of a schema, with the sole exception of overloads for an action and overloads for a function. The names are local to the schema; they need not be unique within a document.

5.1.1 Attribute `Namespace`

A schema is identified by a `Namespace`. All `edm:Schema` elements MUST have a `Namespace` defined through a `Namespace` attribute which MUST be unique within the document, and SHOULD be globally unique. A schema cannot span more than one document.

The schema's namespace is combined with the name of elements in the entity model to create unique [qualified names](#), so identifiers that are used to name types MUST be unique within a namespace to prevent ambiguity. See [Nominal Types](#) for more detail.

The `Namespace` attribute MUST NOT use the reserved values `Edm`, `odata`, `System`, or `Transient`.

5.1.2 Attribute `Alias`

A schema MAY define an alias by providing a [SimpleIdentifier](#) value for the `Alias` attribute. An alias allows nominal types to be qualified with a short string rather than a long namespace.

Aliases are document-global, so all `edmx:Include` and `edm:Schema` elements within a document MUST specify different values for the `Alias` attribute. Aliases defined by an `edm:Schema` element can be used throughout the containing document and are not restricted to the schema that defines them.

The `Alias` attribute MUST NOT use the reserved values `Edm`, `odata`, `System`, or `Transient`.

6 Structural Property

[Structured Types](#) are composed of zero or more structural properties (represented as `edm:Property` elements) and navigation properties (represented as `edm:NavigationProperty` elements).

Example 6: complex type with two properties

```
<ComplexType Name="Measurement">
  <Property Name="Dimension" Type="Edm.String" Nullable="false" MaxLength="50"
    DefaultValue="Unspecified" />
  <Property Name="Length" Type="Edm.Decimal" Nullable="false" Precision="18"
    Scale="2" />
</ComplexType>
```

[Open entity types](#) and [open complex types](#) allow properties to be added dynamically to instances of the open type.

6.1 Element `edm:Property`

The `edm:Property` element defines a structural property.

Example 7: property that can have zero or more strings as its value

```
<Property Name="Units" Type="Collection(Edm.String)" />
```

A property MUST specify a unique [name](#) as well as a type and zero or more facets. [Facets](#) are attributes that modify or constrain the acceptable values for a property value.

6.1.1 Attribute Name

The `edm:Property` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#) used when referencing, serializing or deserializing the property.

The name of the structural property MUST be unique within the set of structural and navigation properties of the containing [structured type](#) and any of its base types.

6.1.2 Attribute Type

The `edm:Property` element MUST include a `Type` attribute. The value of the `Type` attribute MUST be the [Qualified Name](#) of a [primitive type](#), [complex type](#), or [enumeration type](#) in scope, or a collection of one of these types.

6.2 Property Facets

Property facets allow a model to provide additional constraints or data about the value of structural properties. Facets are expressed as attributes on the property element.

Facets apply to the type referenced in the element where the facet is declared. If the type is a collection, the facets apply to the type of elements in the collection.

Example 8: [Precision](#) facet applied to the `DateTimeOffset` type

```
<Property Name="SuggestedTimes" Type="Collection(Edm.DateTimeOffset)"
  Precision="6" />
```

6.2.1 Attribute `Nullable`

The `edm:Property` element MAY contain the `Nullable` attribute whose Boolean value specifies whether a value is required for the property.

If no value is specified for a property whose `Type` attribute does not specify a collection, the `Nullable` attribute defaults to `true`.

If the `edm:Property` element contains a `Type` attribute that specifies a collection, the property **MUST** always exist, but the collection **MAY** be empty. In this case, the `Nullable` attribute applies to members of the collection and specifies whether the collection can contain null values.

6.2.2 Attribute `MaxLength`

A binary, stream or string property **MAY** define a positive integer value for the `MaxLength` facet attribute. The value of this attribute specifies the maximum length of the value of the property on a type instance. Instead of an integer value the constant `max` **MAY** be specified as a shorthand for the maximum length supported for the type by the service.

If no value is specified, the property has unspecified length.

6.2.3 Attribute `Precision`

A datetime-with-offset, decimal, duration, or time-of-day property **MAY** define a value for the `Precision` attribute.

For a decimal property the value of this attribute specifies the maximum number of digits allowed in the property's value; it **MUST** be a positive integer. If no value is specified, the decimal property has unspecified precision.

For a temporal property the value of this attribute specifies the number of decimal places allowed in the seconds portion of the property's value; it **MUST** be a non-negative integer between zero and twelve. If no value is specified, the temporal property has a precision of zero.

Note: service designers **SHOULD** be aware that some clients are unable to support a precision greater than 29 for decimal properties and 7 for temporal properties. Client developers **MUST** be aware of the potential for data loss when round-tripping values of greater precision. Updating via `PATCH` and exclusively specifying modified properties will reduce the risk for unintended data loss.

6.2.4 Attribute `Scale`

A decimal property **MAY** define a non-negative integer value or `variable` for the `Scale` attribute. This attribute specifies the maximum number of digits allowed to the right of the decimal point. The value `variable` means that the number of digits to the right of the decimal point may vary from zero to the value of the `Precision` attribute.

The value of the `Scale` attribute **MUST** be less than or equal to the value of the `Precision` attribute.

If no value is specified, the `Scale` facet defaults to zero.

6.2.5 Attribute `Unicode`

A string property **MAY** define a Boolean value for the `Unicode` attribute.

A `true` value assigned to this attribute indicates that the value of the property is encoded with Unicode. A `false` value assigned to this attribute indicates that the value of the property is encoded with ASCII.

If no value is specified, the `Unicode` facet defaults to `true`.

6.2.6 Attribute `SRID`

A geometry or geography property **MAY** define a value for the `SRID` attribute. The value of this attribute identifies which spatial reference system is applied to values of the property on type instances.

The value of the `SRID` attribute **MUST** be a non-negative integer or the special value `variable`. If no value is specified, the attribute defaults to 0 for `Geometry` types or 4326 for `Geography` types.

The valid values of the `SRID` attribute and their meanings are as defined by the European Petroleum Survey Group **[EPSG]**.

6.2.7 Attribute `DefaultValue`

A primitive or enumeration property MAY define a value for the `DefaultValue` attribute. The value of this attribute determines the value of the property if the property is not explicitly represented in an annotation or the body of a `POST` or `PUT` request.

Default values of type `Edm.String` MUST be represented according to the XML escaping rules for character data in attribute values. Values of other primitive types MUST be represented according to the appropriate alternative in the `primitiveValue` rule defined in **[OData-ABNF]**, i.e. `Edm.Binary` as `binaryValue`, `Edm.Boolean` as `booleanValue` etc..

If no value is specified, the `DefaultValue` attribute defaults to `null`.

7 Navigation Property

7.1 Element `edm:NavigationProperty`

A navigation property allows navigation to related entities.

Example 9: the Product entity type has a navigation property to a Category, which has a navigation link back to one or more products

```
<EntityType Name="Product">
  ...
  <NavigationProperty Name="Category" Type="Self.Category" Nullable="false"
    Partner="Products" />
  <NavigationProperty Name="Supplier" Type="Self.Supplier" />
</EntityType>

<EntityType Name="Category">
  ...
  <NavigationProperty Name="Products" Type="Collection(Self.Product)"
    Partner="Category" />
</EntityType>
```

7.1.1 Attribute Name

The `edm:NavigationProperty` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#) that is used when navigating from the [structured type](#) that declares the navigation property to the related entity type.

The name of the navigation property MUST be unique within the set of structural and navigation properties of the containing [structured type](#) and any of its base types.

7.1.2 Attribute Type

The `edm:NavigationProperty` element MUST include a `Type` attribute. The value of the type attribute MUST resolve to an [entity type](#) or a collection of an entity type declared in the same document or a document referenced with an `edmx:Reference` element, or the [abstract type](#) `Edm.EntityType`.

If the value is an entity type name, there can be at most one related entity. If it is a collection, an arbitrary number of entities can be related.

The related entities MUST be of the specified entity type or one of its subtypes.

7.1.3 Attribute Nullable

The `edm:NavigationProperty` element MAY contain the `Nullable` attribute whose Boolean value specifies whether a navigation target is required for the navigation property.

If no value is specified for a navigation property whose `Type` attribute does not specify a collection, the `Nullable` attribute defaults to `true`. The value `true` (or the absence of the `Nullable` attribute) indicates that no navigation target is required. The value `false` indicates that a navigation target is required for the navigation property on instances of the containing type.

A navigation property whose `Type` attribute specifies a collection MUST NOT specify a value for the `Nullable` attribute as the collection always exists, it may just be empty.

7.1.4 Attribute **Partner**

A navigation property of an **entity type** MAY specify a navigation property path value for the **Partner** attribute.

This attribute MUST NOT be specified for navigation properties of complex types.

If specified, the value of this attribute MUST be a path from the entity type specified in the **Type** attribute to a navigation property defined on that type or a derived type. The path may traverse complex types, including derived complex types, but MUST NOT traverse any navigation properties. The type of the partner navigation property MUST be the containing entity type of the current navigation property or one of its parent entity types.

If the **Partner** attribute identifies a single-valued navigation property, the partner navigation property MUST lead back to the source entity from all related entities. If the **Partner** attribute identifies a multi-valued navigation property, the source entity MUST be part of that collection.

If no partner navigation property is specified, no assumptions can be made as to whether one of the navigation properties on the target type will lead back to the source entity.

If a partner navigation property is specified, this partner navigation property MUST either specify the current navigation property as its partner to define a bi-directional relationship or it MUST NOT specify a partner attribute. The latter can occur if the partner navigation property is defined on a complex type or the current navigation property is defined on a type derived from the type of the partner navigation property.

7.1.5 Attribute **ContainsTarget**

A navigation property MAY assign a Boolean value to the **ContainsTarget** attribute. If no value is assigned to the **ContainsTarget** attribute, the attribute defaults to *false*. If the value of the **ContainsTarget** attribute is *true*, the navigation property is called a *containment navigation property*.

Containment navigation properties define an implicit entity set for each instance of its declaring entity type. This implicit entity set is identified by the read URL of the navigation property for that entity.

Entities of the entity type that declares the navigation property, either directly or indirectly via a property of complex type, contain the entities referenced by the containment navigation property. The canonical URL for contained entities is the canonical URL of the containing entity, followed by the path segment of the navigation property and the key of the contained entity, see **[OData-URL]**.

As items in a collection of complex type do not have a canonical URL, complex types declaring a containment navigation property, either directly or indirectly via a property of complex type, MUST NOT be used as the type of a collection-valued property.

An entity cannot be referenced by more than one containment relationship, and cannot both belong to an entity set declared within the entity container and be referenced by a containment relationship.

Containment navigation properties MUST NOT be specified as the last path segment in the **Path** attribute of a **navigation property binding**.

When a containment navigation property navigates between entity types in the same inheritance hierarchy, the containment it is called *recursive*.

Containment navigation properties MAY specify a **Partner** attribute. If the containment is recursive, the partner navigation property MUST be nullable and specify a single entity type (i.e. have a multiplicity of 0..1). If the containment is not recursive, the partner navigation property MUST NOT be nullable (i.e. have a multiplicity of 1).

An entity type hierarchy MUST NOT contain more than one navigation property with a **Partner** attribute referencing a containment relationship.

Note: without a partner attribute, there is no reliable way for a client to determine which entity contains a given contained entity. This may lead to problems for clients if the contained navigation property can also be reached via a non-containment navigation path.

7.2 Element `edm:ReferentialConstraint`

A navigation property whose `Type` attribute specifies a single entity type MAY define one or more referential constraints. A referential constraint asserts that the *dependent property* (the property defined on the *dependent entity* containing the navigation property) MUST have the same value as the *principal property* (the referenced property defined on the *principal entity* that is the target of the navigation).

The type of the dependent property MUST match the type of the principal property. If the navigation property on which the referential constraint is defined or the principal property is nullable, then the dependent property MUST be nullable. If both the navigation property and the principal property are not nullable, then the dependent property MUST be marked with the `Nullable="false"` attribute value.

Example 10: the category must exist for a product in that category to exist, and the `CategoryID` of the product is identical to the `ID` of the category

```
<EntityType Name="Product">
  ...
  <Property Name="CategoryID" Type="Edm.String" Nullable="false"/>
  <NavigationProperty Name="Category" Type="Self.Category" Nullable="false">
    <ReferentialConstraint Property="CategoryID" ReferencedProperty="ID" />
  </NavigationProperty>
</EntityType>
```

7.2.1 Attribute `Property`

A referential constraint MUST specify a value for the `Property` attribute. The `Property` attribute specifies the property that takes part in the referential constraint on the dependent entity type. Its value MUST be a path expression resolving to a primitive property of the dependent entity type itself or to a primitive property of a complex property (recursively) of the dependent entity type. The names of the properties in the path are joined together by forward slashes.

7.2.2 Attribute `ReferencedProperty`

A referential constraint MUST specify a value for the `ReferencedProperty` attribute. The `ReferencedProperty` attribute specifies the corresponding property of the principal entity type. Its value MUST be a path expression resolving to a primitive property of the principal entity type itself or to a primitive property of a complex property (recursively) of the principal entity type that MUST have the same data type as the property of the dependent entity type.

7.3 Element `edm:OnDelete`

A navigation property MAY define one `edm:OnDelete` element. It describes the action the service will take on related entities when the entity on which the navigation property is defined is deleted.

Example 11: deletion of a category implies deletion of the related products in that category

```
<EntityType Name="Category">
  ...
  <NavigationProperty Name="Products" Type="Collection(Self.Product)">
    <OnDelete Action="Cascade" />
  </NavigationProperty>
</EntityType>
```

7.3.1 Attribute `Action`

The `edm:OnDelete` element MUST include the `Action` attribute with one of the following values:

- `Cascade`, meaning the related entities will be deleted if the source entity is deleted,
- `None`, meaning a `DELETE` request on a source entity with related entities will fail,

- `SetNull`, meaning all properties of related entities that are tied to properties of the source entity via a referential constraint and that do not participate in other referential constraints will be set to null,
- `SetDefault`, meaning all properties of related entities that are tied to properties of the source entity via a referential constraint and that do not participate in other referential constraints will be set to their default value.

If no `edm:OnDelete` element is present, the action taken by the service is not predictable by the client and could vary per entity.

8 Entity Type

Entity types are [nominal structured types](#) with a key that consists of one or more references to [structural properties](#). An entity type is the template for an entity: any uniquely identifiable record such as a customer or order.

An [edm.Key](#) child element MAY be specified if the entity type does not specify a [base type](#) that already has a key declared. The key consists of one or more references to structural properties of the entity type.

An entity type can define two types of properties. A [structural property](#) is a named reference to a primitive, complex, or enumeration type, or a collection of primitive, complex, or enumeration types. A [navigation property](#) is a named reference to another entity type or collection of entity types.

All properties MUST have a unique name within an entity type. Properties MUST NOT have the same name as the declaring entity type. They MAY have the same name as one of the direct or indirect base types or derived types.

An [open entity type](#) allows properties to be dynamically added to instances of the type.

Example 12: a simple entity type

```
<EntityType Name="Employee">
  <Key>
    <PropertyRef Name="ID" />
  </Key>
  <Property Name="ID" Type="Edm.String" Nullable="false" />
  <Property Name="FirstName" Type="Edm.String" Nullable="false" />
  <Property Name="LastName" Type="Edm.String" Nullable="false" />
  <NavigationProperty Name="Manager" Type="Model.Manager" />
</EntityType>
```

Example 13: a derived entity type based on the previous example

```
<EntityType Name="Manager" BaseType="Model.Employee">
  <Property Name="AnnualBudget" Type="Edm.Decimal" />
  <NavigationProperty Name="Employees" Type="Collection (Model.Employee)" />
</EntityType>
```

Note: the derived type has the same name as one of the properties of its base type.

8.1 Element `edm:EntityType`

The `edm:EntityType` element represents an entity type in the entity model. It contains zero or more [edm:Property](#) and [edm:NavigationProperty](#) elements describing the properties of the entity type.

It MAY contain one [edm.Key](#) element.

8.1.1 Attribute Name

The `edm:EntityType` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). The name MUST be unique within its namespace.

8.1.2 Attribute BaseType

An entity type can inherit from another entity type by specifying the [QualifiedName](#) of the base entity type as the value for the `BaseType` attribute.

An entity type inherits the [key](#) as well as structural and navigation properties declared on the entity type's base type.

An entity type MUST NOT introduce an inheritance cycle via the base type attribute.

8.1.3 Attribute Abstract

An entity type MAY indicate that it cannot be instantiated by providing a Boolean value of `true` to the `Abstract` attribute. If not specified, the `Abstract` attribute defaults to `false`.

If `Abstract` is `false`, the entity type MUST define a [key](#) or derive from a [base type](#) with a defined key.

An abstract entity type MUST NOT inherit from a non-abstract entity type.

8.1.4 Attribute OpenType

An entity type MAY indicate that it is open by providing a value of `true` for the `OpenType` attribute. An open type allows clients to add properties dynamically to instances of the type by specifying uniquely named values in the payload used to insert or update an instance of the type.

If not specified, the value of the `OpenType` attribute defaults to `false`.

An entity type derived from an open entity type MUST NOT provide a value of `false` for the `OpenType` attribute.

Note: structural and navigation properties MAY be returned by the service on instances of any structured type, whether or not the type is marked as open. Clients MUST always be prepared to deal with additional properties on instances of any structured type, see [\[OData-Protocol\]](#).

8.1.5 Attribute HasStream

An entity type MAY specify a Boolean value for the `HasStream` attribute.

A value of `true` specifies that the entity type is a media entity. *Media entities* are entities that represent a media stream, such as a photo. For more information on media entities see [\[OData-Protocol\]](#).

If no value is provided for the `HasStream` attribute, the value of the `HasStream` attribute is set to `false`.

Entity types that specify `HasStream="true"` MAY specify a list of acceptable media types using an annotation with term `Core.AcceptableMediaTypes`, see [\[OData-VocCore\]](#).

8.2 Element `edm:Key`

An entity is uniquely identified within an entity set by its key. An entity type that is not [abstract](#) MUST either contain exactly one `edm:Key` element or inherit its key from its [base type](#). An abstract entity type MAY define a key if it doesn't inherit one.

An entity type's key refers to the set of properties that uniquely identify an instance of the entity type within an entity set.

The `edm:Key` element MUST contain at least one `edm:PropertyRef` element. An `edm:PropertyRef` element references an `edm:Property`. The properties that compose the key MUST be non-nullable and typed with an [enumeration type](#), one of the following [primitive types](#), or a [type definition](#) based on one of these primitive types:

- `Edm.Boolean`
- `Edm.Byte`
- `Edm.Date`
- `Edm.DateTimeOffset`
- `Edm.Decimal`
- `Edm.Duration`
- `Edm.Guid`
- `Edm.Int16`
- `Edm.Int32`

- Edm.Int64
- Edm.SByte
- Edm.String
- Edm.TimeOfDay

The properties that make up a primary key MAY be language-dependent, but their values MUST be unique across all languages and the entity ids (defined in [OData-Protocol]) MUST be language independent.

Example 14: entity type with a simple key

```
<EntityType Name="Category">
  <Key>
    <PropertyRef Name="ID" />
  </Key>
  <Property Name="ID" Type="Edm.Int32" Nullable="false" />
  <Property Name="Name" Type="Edm.String" />
</EntityType>
```

Example 15: entity type with a simple key referencing a property of a complex type

```
<EntityType Name="Category">
  <Key>
    <PropertyRef Name="Info/ID" Alias="EntityInfoID" />
  </Key>
  <Property Name="Info" Type="Sales.EntityInfo" Nullable="false" />
  <Property Name="Name" Type="Edm.String" />
</EntityType>

<ComplexType Name="EntityInfo">
  <Property Name="ID" Type="Edm.Int32" Nullable="false" />
  <Property Name="Created" Type="Edm.DateTimeOffset" />
</ComplexType>
```

Example 16: entity type with a composite key

```
<EntityType Name="OrderLine">
  <Key>
    <PropertyRef Name="OrderID" />
    <PropertyRef Name="LineNumber" />
  </Key>
  <Property Name="OrderID" Type="Edm.Int32" Nullable="false" />
  <Property Name="LineNumber" Type="Edm.Int32" Nullable="false" />
</EntityType>
```

8.3 Element **edm:PropertyRef**

The **edm:PropertyRef** element provides an **edm:Key** with a reference to a property.

8.3.1 Attribute **Name**

The **edm:PropertyRef** element MUST specify a value for the **Name** attribute which MUST be a path expression resolving to a primitive property of the entity type itself or to a primitive property of a complex property (recursively) of the entity type. The names of the properties in the path are joined together by forward slashes.

8.3.2 Attribute **Alias**

If the property identified by the **Name** attribute is a member of a complex type, the **edm:PropertyRef** element MUST specify the **Alias** attribute.

The value of the `Alias` attribute MUST be a [SimpleIdentifier](#) and MUST be unique within the set of aliases, structural and navigation properties of the containing entity type and any of its base types.

The `Alias` attribute MUST NOT be defined if the key property is not a member of a complex type.

For keys that are members of complex types, the alias MUST be used in the key predicate of URLs instead of the value assigned to the `Name` attribute. The alias MUST NOT be used in the query part.

Example 17 (based on example 15): requests to an entity set `Categories` of type `Category` must use the alias

```
http://host/service/Categories(EntityInfoID=1)
```

Example 18 (based on example 15): in a query part the value assigned to the name attribute must be used

```
http://example.org/OData.svc/Categories?$filter=Info/ID le 100
```

9 Complex Type

Complex types are keyless [nominal structured types](#). The lack of a key means that complex types cannot be referenced, created, updated or deleted independently of an entity type. Complex types allow entity models to group properties into common structures.

A complex type can define two types of properties. A [structural property](#) is a named reference to a primitive, complex, or enumeration type, or a collection of primitive, complex, or enumeration types. A [navigation property](#) is a named reference to an entity type or a collection of entity types.

All properties MUST have a unique name within a complex type. Properties MUST NOT have the same name as the declaring complex type. They MAY have the same name as one of the direct or indirect base types or derived types.

An [open complex type](#) allows properties to be dynamically added to instances of the type.

Example 19: a complex type used by two entity types

```
<ComplexType Name="Dimensions">
  <Property Name="Height" Nullable="false" Type="Edm.Decimal" />
  <Property Name="Weight" Nullable="false" Type="Edm.Decimal" />
  <Property Name="Length" Nullable="false" Type="Edm.Decimal" />
</ComplexType>

<EntityType Name="Product">
  ...
  <Property Name="ProductDimensions" Type="Self.Dimensions" />
  <Property Name="ShippingDimensions" Type="Self.Dimensions" />
</EntityType>

<EntityType Name="ShipmentBox">
  ...
  <Property Name="Dimensions" Type="Self.Dimensions" />
</EntityType>
```

9.1 Element `edm:ComplexType`

The `edm:ComplexType` element represents a complex type in an entity model. It contains zero or more [edm:Property](#) and [edm:NavigationProperty](#) elements describing properties of the complex type.

9.1.1 Attribute Name

The `edm:ComplexType` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). The value identifies the complex type and MUST be unique within its namespace.

9.1.2 Attribute BaseType

A complex type can inherit from another complex type by specifying the [QualifiedName](#) of the base complex type as the value for the `BaseType` attribute.

A complex type inherits the properties declared on the complex type's base type.

A complex type MUST NOT introduce an inheritance cycle via the base type attribute.

9.1.3 Attribute Abstract

A complex type MAY indicate that it cannot be instantiated by providing a Boolean value of `true` to the `Abstract` attribute.

If not specified, the `Abstract` attribute defaults to `false`.

9.1.4 Attribute `OpenType`

A complex type MAY indicate that it is open by providing a value of `true` for the `OpenType` attribute. An open type allows clients to add properties dynamically to instances of the type by specifying uniquely named values in the payload used to insert or update an instance of the type.

If not specified, the `OpenType` attribute defaults to `false`.

A complex type derived from an open complex type MUST NOT provide a value of `false` for the `OpenType` attribute.

Note: structural and navigation properties MAY be returned by the service on instances of any structured type, whether or not the type is marked as open. Clients MUST always be prepared to deal with additional properties on instances of any structured type, see **[OData-Protocol]**.

10 Enumeration Type

Enumeration types are [nominal](#) scalar types that represent a series of related values. Enumeration types expose these related values as members of the enumeration.

The `IsFlags` attribute indicates that more than one member may be selected at a time.

Example 20: a simple flags-enabled enumeration

```
<EnumType Name="FileAccess" UnderlyingType="Edm.Int32" IsFlags="true">
  <Member Name="Read" Value="1" />
  <Member Name="Write" Value="2" />
  <Member Name="Create" Value="4" />
  <Member Name="Delete" Value="8" />
</EnumType>
```

10.1 Element `edm:EnumType`

The `edm:EnumType` element represents an enumeration type in an entity model.

10.1.1 Attribute `Name`

The `edm:EnumType` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). The value identifies the enumeration type and MUST be unique within its namespace.

The enumeration type element contains one or more child `edm:Member` elements defining the members of the enumeration type.

10.1.2 Attribute `UnderlyingType`

An enumeration type MAY include an `UnderlyingType` attribute to specify an underlying type whose value MUST be one of `Edm.Byte`, `Edm.SByte`, `Edm.Int16`, `Edm.Int32`, or `Edm.Int64`. If the `UnderlyingType` attribute is not specified, `Edm.Int32` is used as the underlying type.

10.1.3 Attribute `IsFlags`

An enumeration type MAY specify a Boolean value for the `IsFlags` attribute. A value of `true` indicates that the enumeration type allows multiple members to be selected simultaneously.

If no value is specified for this attribute, its value defaults to `false`.

10.2 Element `edm:Member`

The `edm:Member` element defines the discrete options for the enumeration type .

Example 21: an enumeration type with three discrete members

```
<EnumType Name="ShippingMethod">
  <Member Name="FirstClass" />
  <Member Name="TwoDay" />
  <Member Name="Overnight" />
</EnumType>
```

10.2.1 Attribute `Name`

Each `edm:Member` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). The enumeration type MUST NOT declare two members with the same name.

10.2.2 Attribute value

The value of an enumeration member allows instances to be sorted by a property that has an enumeration member for its value.

If the `IsFlags` attribute has a value of `false`, either all members MUST specify an integer value for the `Value` attribute, or all members MUST NOT specify a value for the `Value` attribute. If no values are specified, the members are assigned consecutive integer values in the order of their appearance, starting with zero for the first member. Client libraries MUST preserve elements in document order.

If the `IsFlags` attribute has a value of `true`, a non-negative integer value MUST be specified for the `Value` attribute. A combined value is equivalent to the bitwise OR of the discrete values.

The value MUST be a valid value for the `UnderlyingType` of the enumeration type.

Example 22: `FirstClass` has a value of 0, `TwoDay` a value of 1, and `Overnight` a value of 2.

```
<EnumType Name="ShippingMethod">
  <Member Name="FirstClass" />
  <Member Name="TwoDay" />
  <Member Name="Overnight" />
</EnumType>
```

Example 23: pattern values can be combined, and some combined values have explicit names

```
<EnumType Name="Pattern" UnderlyingType="Edm.Int32" IsFlags="true">
  <Member Name="Plain" Value="0" />
  <Member Name="Red" Value="1" />
  <Member Name="Blue" Value="2" />
  <Member Name="Yellow" Value="4" />
  <Member Name="Solid" Value="8" />
  <Member Name="Striped" Value="16" />
  <Member Name="SolidRed" Value="9" />
  <Member Name="SolidBlue" Value="10" />
  <Member Name="SolidYellow" Value="12" />
  <Member Name="RedBlueStriped" Value="19" />
  <Member Name="RedYellowStriped" Value="21" />
  <Member Name="BlueYellowStriped" Value="22" />
</EnumType>
```

11 Type Definition

11.1 Element `edm:TypeDefinition`

A type definition defines a specialization of one of the [primitive types](#).

Type definitions can be used wherever a primitive type is used (other than as the underlying type in a new type definition), and are type-comparable with their underlying types and any type definitions defined using the same underlying type.

11.1.1 Attribute Name

The `edm:TypeDefinition` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). The name identifies the type definition and MUST be unique within its namespace.

11.1.2 Attribute `UnderlyingType`

The `edm:TypeDefinition` element MUST provide the [QualifiedName](#) of a [primitive type](#) as the value of the `UnderlyingType` attribute. This type MUST NOT be another type definition.

11.1.3 Type Definition Facets

The `edm:TypeDefinition` element MAY specify facets applicable to the underlying type: [MaxLength](#), [Unicode](#), [Precision](#), [Scale](#), or [SRID](#).

Additional facets appropriate for the underlying type MAY be specified when the type definition is used but the facets specified in the type definition MUST NOT be re-specified.

Annotations MAY be applied to a type definition, and are considered applied wherever the type definition is used. Applying the same annotation to a property whose type definition already defines that annotation is an error.

Where type definitions are used, the type definition is returned in place of the primitive type wherever the type is specified in a response.

Example 24:

```
<TypeDefinition Name="Length" UnderlyingType="Edm.Int32">
  <Annotation Term="Org.OData.Measurements.V1.Unit"
    String="Centimeters" />
</TypeDefinition>

<TypeDefinition Name="Weight" UnderlyingType="Edm.Int32">
  <Annotation Term="Org.OData.Measurements.V1.Unit"
    String="Kilograms" />
</TypeDefinition>

<ComplexType Name="Size">
  <Property Name="Height" Type="Self.Length" />
  <Property Name="Weight" Type="Self.Weight" />
</ComplexType>
```

12 Action and Function

12.1 Element `edm:Action`

The `edm:Action` element represents an action in an entity model.

Actions MAY have observable side effects and MAY return a single instance or a collection of instances of any type. Actions are not composable.

The action MAY specify a return type using the `edm:ReturnType` element. The return type must be a scalar, entity or complex type, or a collection of scalar, entity or complex types.

The action may also define zero or more `edm:Parameter` elements to be used during the execution of the action.

12.1.1 Attribute Name

The `edm:Action` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#).

12.1.1.1 Action Overload Rules

[Bound](#) actions support overloading (multiple actions having the same name within the same namespace) by binding parameter type. The combination of action name and the binding parameter type MUST be unique within a namespace.

[Unbound](#) actions do not support overloads. The names of all unbound actions MUST be unique within a namespace.

An unbound action MAY have the same name as a bound action.

12.1.2 Attribute `IsBound`

An action element MAY specify a Boolean value for the `IsBound` attribute.

Actions whose `IsBound` attribute is `false` or not specified are considered *unbound*. Unbound actions are invoked through an [action import](#).

Actions whose `IsBound` attribute is `true` are considered *bound*. Bound actions are invoked by appending a segment containing the qualified action name to a segment of the appropriate binding parameter type within the resource path. Bound actions MUST contain at least one `edm:Parameter` element, and the first parameter is the binding parameter. The binding parameter can be of any type, and it MAY be [nullable](#).

12.1.3 Attribute `EntitySetPath`

Bound actions that return an entity or a collection of entities MAY specify a value for the `EntitySetPath` attribute if determination of the entity set for the return type is contingent on the binding parameter.

The value for the `EntitySetPath` attribute consists of a series of segments joined together with forward slashes.

The first segment of the entity set path MUST be the name of the binding parameter. The remaining segments of the entity set path MUST represent navigation segments or type casts.

A navigation segment names the [SimpleIdentifier](#) of the [navigation property](#) to be traversed. A type cast segment names the [QualifiedName](#) of the entity type that should be returned from the type cast.

12.2 Element `edm:Function`

The `edm:Function` element represents a function in an entity model.

Functions **MUST NOT** have observable side effects and **MUST** return a single instance or a collection of instances of any type. Functions **MAY** be composable.

The function **MUST** specify a return type using the `edm:ReturnType` element. The return type must be a scalar, entity or complex type, or a collection of scalar, entity or complex types.

The function may also define zero or more `edm:Parameter` elements to be used during the execution of the function.

12.2.1 Attribute Name

The `edm:Function` element **MUST** include a `Name` attribute whose value is a [SimpleIdentifier](#).

12.2.1.1 Function Overload Rules

[Bound](#) functions support overloading (multiple functions having the same name within the same namespace) subject to the following rules:

- The combination of function name, binding parameter type, and unordered set of non-binding parameter names **MUST** be unique within a namespace.
- The combination of function name, binding parameter type, and ordered set of parameter types **MUST** be unique within a namespace.
- All bound functions with the same function name and binding parameter type within a namespace **MUST** specify the same return type.

[Unbound](#) functions support overloading subject to the following rules:

- The combination of function name and unordered set of parameter names **MUST** be unique within a namespace.
- The combination of function name and ordered set of parameter types **MUST** be unique within a namespace.
- All unbound functions with the same function name within a namespace **MUST** specify the same return type.

An unbound function **MAY** have the same name as a bound function.

Note that [type definitions](#) can be used to disambiguate overloads for both bound and unbound functions, even if they specify the same underlying type.

12.2.2 Attribute `IsBound`

A function element **MAY** specify a Boolean value for the `IsBound` attribute

Functions whose `IsBound` attribute is `false` or not specified are considered *unbound*. Unbound functions are invoked as static functions within a filter or orderby expression, or from the entity container through a [function import](#).

Functions whose `IsBound` attribute is `true` are considered *bound*. Bound functions are invoked by appending a segment containing the qualified function name to a segment of the appropriate binding parameter type within a resource path, filter, or orderby expression. Bound functions **MUST** contain at least one `edm:Parameter` element, and the first parameter is the binding parameter. The binding parameter can be of any type, and it **MAY** be [nullable](#).

12.2.3 Attribute `IsComposable`

A function element can specify a Boolean value for the `IsComposable` attribute. If no value is specified for the `IsComposable` attribute, the value defaults to `false`.

12.2.4 Attribute `EntitySetPath`

`Bound` functions that return an entity or a collection of entities MAY specify a value for the `EntitySetPath` attribute if determination of the entity set for the return type is contingent on the binding parameter.

The value for the `EntitySetPath` attribute consists of a series of segments joined together with forward slashes.

The first segment of the entity set path MUST be the name of the binding parameter. The remaining segments of the entity set path MUST represent navigation segments or type casts.

A navigation segment names the `SimpleIdentifier` of the `navigation property` to be traversed. A type cast segment names the `QualifiedName` of the entity type that should be returned from the type cast.

12.3 Element `edm:ReturnType`

The attributes `MaxLength`, `Precision`, `Scale`, and `SRID` can be used to specify the facets of the return type, as appropriate. If the facet attributes are not specified, their values are considered unspecified.

12.3.1 Attribute `Type`

The `Type` attribute specifies the type of the result returned by the function or action.

12.3.2 Attribute `Nullable`

A return type whose `Type` attribute does not specify a collection MAY specify a Boolean value for the `Nullable` attribute. If not specified, the `Nullable` attribute defaults to `true`.

The value of `true` means that the action or function may return a single `null` value. A value of `false` means that the action or function will never return a `null` value and instead fail with an error response if it cannot compute a result.

If the return type has a `Type` attribute that specifies a collection, the result will always exist, but the collection MAY be empty. In this case, the `Nullable` attribute applies to members of the collection and specifies whether the collection can contain null values.

12.4 Element `edm:Parameter`

The `edm:Parameter` element allows one or more parameters to be passed to a function or action.

Example 25: a function returning the top-selling products for a given year. In this case the year must be specified as a parameter of the function with the `edm:Parameter` element.

```
<Function Name="TopSellingProducts">
  <Parameter Name="Year" Type="Edm.Decimal" Precision="4" Scale="0" />
  <ReturnType Type="Collection(Model.Product)" />
</Function>
```

12.4.1 Attribute `Name`

The `edm:Parameter` element MUST include a `Name` attribute whose value is a `SimpleIdentifier`. The parameter name MUST be unique within its parent element.

12.4.2 Attribute `Type`

The `edm:Parameter` element MUST include the `Type` attribute whose value is a `TypeName` indicating the type of value that can be passed to the parameter.

12.4.3 Attribute `Nullable`

A parameter whose `Type` attribute does not specify a collection MAY specify a Boolean value for the `Nullable` attribute. If not specified, the `Nullable` attribute defaults to `true`.

The value of `true` means that the parameter accepts a `null` value.

12.4.4 Parameter Facets

An `edm:Parameter` element MAY specify values for the `MaxLength`, `Precision`, `Scale`, or `SRID` attributes. The descriptions of these facets and their implications are covered in section 6.2.

13 Entity Container

Each metadata document used to describe an OData service MUST define exactly one entity container. Entity containers define the entity sets, singletons, function and action imports exposed by the service.

An [entity set](#) allows access to entity type instances. Simple entity models frequently have one entity set per entity type.

Example 26: one entity set per entity type

```
<EntitySet Name="Products" EntityType="Self.Product" />
<EntitySet Name="Categories" EntityType="Self.Category" />
```

Other entity models may expose multiple entity sets per type.

Example 27: three entity sets referring to the two entity types

```
<EntitySet Name="StandardCustomers" EntityType="Self.Customer">
  <NavigationPropertyBinding Path="Orders" Target="Orders" />
</EntitySet>
<EntitySet Name="PreferredCustomers" EntityType="Self.Customer">
  <NavigationPropertyBinding Path="Orders" Target="Orders" />
</EntitySet>
<EntitySet Name="Orders" EntityType="Self.Order" />
```

There are separate entity sets for standard customers and preferred customers, but only one entity set for orders. The entity sets for standard customers and preferred customers both have [navigation property bindings](#) to the orders entity set, but the orders entity set does not have a navigation property binding for the Customer navigation property, since it could lead to either set of customers.

Note: although a model may expose multiple entity sets of the same type, an entity can be a member of at most one entity set, see **[OData-Protocol]**.

An entity set can expose instances of the specified entity type as well as any entity type inherited from the specified entity type.

A [singleton](#) allows addressing a single entity directly from the entity container without having to know its key, and without requiring an entity set.

A [function import](#) or an [action import](#) is used to expose a function or action defined in an entity model as a top level resource.

Example 28: function import returning the top ten revenue-generating products for a given fiscal year

```
<FunctionImport Name="TopSellingProducts"
  Function="Model.TopSellingProducts"
  EntitySet="Products" />
```

Example 29: An entity container aggregates entity sets, singletons, action imports, and function imports.

```
<EntityContainer Name="DemoService">
  <EntitySet Name="Products" EntityType="Self.Product">
    <NavigationPropertyBinding Path="Category"
      Target="Self.DemoService.Categories" />
    <NavigationPropertyBinding Path="Supplier"
      Target="Self.DemoService.Suppliers" />
  </EntitySet>
  <EntitySet Name="Categories" EntityType="Self.Category">
    <NavigationPropertyBinding Path="Products"
      Target="Self.DemoService.Products" />
  </EntitySet>
```

```

<EntitySet Name="Suppliers" EntityType="Self.Supplier">
  <NavigationPropertyBinding Path="Products"
    Target="Self.DemoService.Products" />
</EntitySet>
<Singleton Name="Contoso" Type="Self.Supplier" />
<ActionImport Name="LeaveRequestApproval" Action="Self.Approval" />
<FunctionImport Name="ProductsByRating" Function="Self.ProductsByRating"
  EntitySet="Products" />
</EntityContainer>

```

13.1 Element `edm:EntityContainer`

The `edm:EntityContainer` element represents an entity container in an entity model. It corresponds to a virtual or physical data store and contains one or more `edm:EntitySet`, `edm:Singleton`, `edm:ActionImport`, or `edm:FunctionImport` elements. Entity set, singleton, action import, and function import names MUST be unique within an entity container.

13.1.1 Attribute Name

The `edm:EntityContainer` element MUST provide a unique [SimpleIdentifier](#) value for the `Name` attribute.

13.1.2 Attribute Extends

The `edm:EntityContainer` element MAY include an `Extends` attribute whose value is the [QualifiedName](#) of an entity container in scope. All children of the “base” entity container specified in the `Extends` attribute are added to the “extending” entity container that has the `Extends` attribute.

Example 30: the entity container `Extending` will contain all child elements that it defines itself, plus all child elements of the `Base` entity container located in `SomeOtherSchema`

```

<EntityContainer Name="Extending" Extends="SomeOtherSchema.Base">
  ...
</EntityContainer>

```

13.2 Element `edm:EntitySet`

The `edm:EntitySet` element represents an entity set in an entity model.

13.2.1 Attribute Name

The `edm:EntitySet` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#).

13.2.2 Attribute `EntityType`

The `edm:EntitySet` element MUST include an `EntityType` attribute whose value is the [QualifiedName](#) of an [entity type](#) in scope. Each entity type in the model may have zero or more entity sets that reference the entity type.

An entity set MUST contain only instances of the entity type specified by the `EntityType` attribute or its subtypes. The entity type named by the `EntityType` attribute MAY be [abstract](#) but MUST have a [key](#) defined.

13.2.3 Attribute `IncludeInServiceDocument`

The `edm:EntitySet` element MAY include the `IncludeInServiceDocument` attribute whose Boolean value indicates whether the entity set is advertised in the service document.

If no value is specified for this attribute, its value defaults to `true`.

Entity sets that cannot be queried without specifying additional query options SHOULD specify the value `false` for this attribute.

13.3 Element `edm:Singleton`

The `edm:Singleton` element represents a single entity in an entity model, called a *singleton*.

13.3.1 Attribute Name

The `edm:Singleton` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#).

13.3.2 Attribute Type

The `edm:Singleton` element MUST include a `Type` attribute whose value is the [QualifiedName](#) of an entity type in scope. Each entity type in the model may be used in zero or more `edm:Singleton` elements.

A singleton MUST reference an instance of the entity type specified by the `Type` attribute.

13.4 Element `edm:NavigationPropertyBinding`

An [entity set](#) or a [singleton](#) SHOULD contain an `edm:NavigationPropertyBinding` element for each [navigation property](#) of its entity type, including navigation properties defined on complex typed properties.

If omitted, clients MUST assume that the target entity set or singleton can vary per related entity.

13.4.1 Attribute Path

A navigation property binding MUST name a navigation property of the entity set's or singleton's entity type or one of its subtypes in the `Path` attribute. If the navigation property is defined on a subtype, the path attribute MUST contain the [QualifiedName](#) of the entity type, followed by a forward slash, followed by the navigation property name. If the navigation property is defined on a complex type used in the definition of the entity set's entity type, the path attribute MUST contain a forward-slash separated list of complex property names and qualified type names that describe the path leading to the navigation property.

A navigation property MUST NOT be named in more than one navigation property binding; navigation property bindings are only used when all related entities are known to come from a single entity set.

13.4.2 Attribute Target

A navigation property binding MUST specify a [SimpleIdentifier](#) or [TargetPath](#) value for the `Target` attribute that names the entity set that contains the related instances targeted by the navigation property specified in the `Path` attribute, or the name of a singleton. If a [SimpleIdentifier](#) is specified, it MUST resolve to an entity set or singleton defined in the same entity container as the enclosing element. If a [TargetPath](#) is specified, it MUST resolve to an entity set or singleton in scope.

Example 31: for an entity set in the same container as the enclosing entity set `Categories`

```
<EntitySet Name="Categories" EntityType="Self.Category">
  <NavigationPropertyBinding Path="Products"
                             Target="SomeSet" />
</EntitySet>
```

Example 32: for an entity set in any container in scope

```
<EntitySet Name="Categories" EntityType="Self.Category">
  <NavigationPropertyBinding Path="Products"
                             Target="SomeModel.SomeContainer/SomeSet" />
</EntitySet>
```

13.5 Element `edm:ActionImport`

The `edm:ActionImport` element allows exposing an [unbound action](#) as a top-level element in an entity container. Action imports are never advertised in the service document.

13.5.1 Attribute `Name`

The `edm:ActionImport` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). It MAY be identical to the last segment of the [QualifiedName](#) used to specify the [Action](#) attribute value.

13.5.2 Attribute `Action`

The `edm:ActionImport` element MUST include a [QualifiedName](#) value for the `Action` attribute which MUST resolve to the name of an [unbound `edm:Action`](#) element in scope.

13.5.3 Attribute `EntitySet`

If the return type of the action specified in the [Action](#) attribute is an entity or a collection of entities, a [SimpleIdentifier](#) or [TargetPath](#) value MAY be specified for the `EntitySet` attribute that names the entity set to which the returned entities belong. If a [SimpleIdentifier](#) is specified, it MUST resolve to an entity set defined in the same entity container. If a [TargetPath](#) is specified, it MUST resolve to an entity set in scope.

If the return type is not an entity or a collection of entities, a value MUST NOT be defined for the `EntitySet` attribute.

13.6 Element `edm:FunctionImport`

The `edm:FunctionImport` element allows exposing an [unbound function](#) as a top-level element in an entity container.

13.6.1 Attribute `Name`

The `edm:FunctionImport` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#). It MAY be identical to the last segment of the [QualifiedName](#) used to specify the [Function](#) attribute value.

13.6.2 Attribute `Function`

The `edm:FunctionImport` element MUST include the `Function` attribute whose value MUST be a [QualifiedName](#) that resolves to the name of an [unbound `edm:Function`](#) element in scope.

13.6.3 Attribute `EntitySet`

If the return type of the function specified in the [Function](#) attribute is an entity or a collection of entities, a [SimpleIdentifier](#) or [TargetPath](#) value MAY be defined for the `EntitySet` attribute that names the entity set to which the returned entities belong. If a [SimpleIdentifier](#) is specified, it MUST resolve to an entity set defined in the same entity container. If a [TargetPath](#) is specified, it MUST resolve to an entity set in scope.

If the return type is not an entity or a collection of entities, a value MUST NOT be defined for the `EntitySet` attribute.

13.6.4 Attribute `IncludeInServiceDocument`

The `edm:FunctionImport` for a parameterless function MAY include the `IncludeInServiceDocument` attribute whose Boolean value indicates whether the function import is advertised in the service document.

If no value is specified for this attribute, its value defaults to `false`.

14 Vocabulary and Annotation

Vocabularies and annotations provide the ability to annotate metadata as well as instance data, and define a powerful extensibility point for OData. An *annotation* applies a *term* to a model element and defines how to calculate a value for the applied term.

Metadata annotations can be used to define additional characteristics or capabilities of a metadata element, such as a service, entity type, property, function, action or parameter. For example, a metadata annotation may define ranges of valid values for a particular property. Metadata annotations are applied in CSDL documents describing or referencing an entity model.

Instance annotations can be used to define additional information associated with a particular result, entity, property, or error; for example, whether a property is read-only for a particular instance. Where the same annotation is defined at both the metadata and instance level, the instance-level annotation overrides the annotation specified at the metadata level. Instance annotations appear in the actual payload as described in **[OData-Atom]** and **[OData-JSON]**. Annotations that apply across instances should be specified as metadata annotations.

A *vocabulary* is a namespace containing a set of terms where each *term* is a named metadata extension. Anyone can define a vocabulary (a set of terms) that is scenario-specific or company-specific; more commonly used terms can be published as shared vocabularies such as the OData Core vocabulary **[OData-VocCore]**.

A *term* can be used:

- To extend model elements and type instances with additional information.
- To map instances of annotated structured types to an interface defined by the term type; i.e. annotations allow viewing instances of a structured type as instances of a differently structured type specified by the applied term.

A service SHOULD NOT require a client to interpret annotations.

Example 33: the Product entity type is extended with a DisplayName by a metadata annotation that binds the term DisplayName to the value of the property Name. The Product entity type also includes an annotation that allows its instances to be viewed as instances of the type specified by the term SearchResult

```
<EntityType Name="Product">
  <Key>
    <PropertyRef Name="ID" />
  </Key>
  <Property Name="ID" Nullable="false" Type="Edm.Int32" />
  <Property Name="Name" Type="Edm.String" />
  <Property Name="Description" Type="Edm.String" />
  ...
  <Annotation Term="UI.DisplayName" Path="Name" />
  <Annotation Term="SearchVocabulary.SearchResult">
    <Record>
      <PropertyValue Property="Title" Path="Name" />
      <PropertyValue Property="Abstract" Path="Description" />
      <PropertyValue Property="Url">
        <Apply Function="odata.concat">
          <String>Products(</String>
            <Path>ID</Path>
            <String>)</String>
          </Apply>
        </PropertyValue>
      </Record>
    </Annotation>
  </EntityType>
```

14.1 Element `edm:Term`

The `edm:Term` element defines a term in a vocabulary.

A term allows annotating a CSDL element or OData resource representation with additional data.

14.1.1 Attribute `Name`

The `edm:Term` element MUST include a `Name` attribute whose value is a [SimpleIdentifier](#).

14.1.2 Attribute `Type`

The `edm:Term` element MUST include a `Type` attribute whose value is a [TypeName](#). It indicates what type of value must be returned by the expression contained in an annotation using the term.

14.1.3 Attribute `BaseTerm`

The `edm:Term` element MAY provide a [QualifiedName](#) value for the `BaseTerm` attribute. The value of the `BaseTerm` attribute MUST be the name of a term in scope. When applying a term with a base term, the base term MUST also be applied with the same qualifier, and so on until a term without a base term is reached.

14.1.4 Attribute `DefaultValue`

A `edm:Term` element of primitive or enumeration type MAY define a value for the `DefaultValue` attribute. The value of this attribute determines the value of the term when applied in an [edm:Annotation](#) without providing an expression.

Default values of type `Edm.String` MUST be represented according to the XML escaping rules for character data in attribute values. Values of other primitive types MUST be represented according to the appropriate alternative in the `primitiveValue` rule defined in **[OData-ABNF]**, i.e. `Edm.Binary` as `binaryValue`, `Edm.Boolean` as `booleanValue` etc.

If no value is specified, the `DefaultValue` attribute defaults to `null`.

14.1.5 Attribute `AppliesTo`

The `edm:Term` element MAY define a value for the `AppliesTo` attribute. The value of this attribute is a whitespace-separated list of CSDL element names that this term can be applied to. If no value is supplied, the term is not restricted in its application.

*Example 34: the `IsURI` term can be applied to properties and terms that are of type `Edm.String` (the `Core.Tag` type and the two `Core` terms are defined in **[OData-VocCore]**)*

```
<Term Name="IsURI" Type="Core.Tag" DefaultValue="true"
  AppliesTo="Property">
  <Annotation Term="Core.Description">
    <String>
      Properties and terms annotated with this term MUST contain a valid URI
    </String>
  </Annotation>
  <Annotation Term="Core.RequiresType" String="Edm.String" />
</Term>
```

14.1.6 Term Facets

The `edm:Term` element MAY specify values for the [Nullable](#), [DefaultValue](#), [MaxLength](#), [Precision](#), [Scale](#), or [SRID](#) attributes. These facets and their implications are described in section 6.2.

14.2 Element `edm:Annotations`

The `edm:Annotations` element is used to apply a group of annotations to a single model element. It MUST contain at least one `edm:Annotation` element.

14.2.1 Attribute `Target`

The `edm:Annotations` element MUST include a `Target` attribute whose value is a `TargetPath` that MUST resolve to a model element in the entity model.

External targeting is only possible for EDM elements that are uniquely identified within their parent, and all their ancestor elements are uniquely identified within their parent:

- `edm:ActionImport`
- `edm:ComplexType`
- `edm:EntityContainer`
- `edm:EntitySet`
- `edm:EntityType`
- `edm:EnumType`
- `edm:FunctionImport`
- `edm:Member`
- `edm:NavigationProperty`
- `edm:Property`
- `edm:Singleton`
- `edm:Term`
- `edm:TypeDefinition`

These are the direct children of a schema with a unique name (i.e. except actions and functions whose overloads do not possess a natural identifier), and all direct children of an entity container. Most of the not uniquely identifiable EDM elements can still be annotated using a nested `edm:Annotation` element.

The allowed path expressions are:

- `QualifiedName` of schema child
- `QualifiedName` of schema child followed by a forward slash and name of child element

Example 35: Target expressions

```
Schema.Type
Schema.EntityType/Property
Schema.ComplexType/NavigationProperty
Schema.EnumType/Member
Schema.EntityContainer
Schema.EntityContainer/EntitySet
```

14.2.2 Attribute `Qualifier`

An `edm:Annotations` element MAY provide a `SimpleIdentifier` value for the `Qualifier` attribute.

The `Qualifier` attribute allows annotation authors a means of conditionally applying an annotation.

Example 36: annotations should only be applied to tablet devices

```
<Annotations Target="Self.Person" Qualifier="Tablet">
  ...
</Annotations>
```

14.3 Element `edm:Annotation`

The `edm:Annotation` element represents a single annotation. An annotation applies a `term` to a model element and defines how to calculate a value for the term application. The following model elements MAY be annotated with a term:

- `edm:Action`
- `edm:ActionImport`

- [edm:Annotation](#)
- [edm:Apply](#)
- [edm:Cast](#)
- [edm:ComplexType](#)
- [edm:EntityContainer](#)
- [edm:EntitySet](#)
- [edm:EntityType](#)
- [edm:EnumType](#)
- [edm:Function](#)
- [edm:FunctionImport](#)
- [edm:If](#)
- [edm:IsOf](#)
- [edm:LabeledElement](#)
- [edm:Member](#)
- [edm:NavigationProperty](#)
- [edm:Null](#)
- [edm:OnDelete](#)
- [edm:Parameter](#)
- [edm:Property](#)
- [edm:PropertyValue](#)
- [edm:Record](#)
- [edm:ReferentialConstraint](#)
- [edm:Schema](#)
- [edm:Singleton](#)
- [edm:Term](#)
- [edm:TypeDefinition](#)
- [edm:UrlRef](#)
- [edmx:Reference](#)
- all [Comparison and Logical Operators](#)

An [edm:Annotation](#) element can be used as a child of the model element it annotates, or as the child of an [edm:Annotations](#) element that targets the model element to be annotated.

An [edm:Annotation](#) element MAY contain a [constant expression](#) or [dynamic expression](#) in either attribute or element notation. If no expression is specified for a term with a primitive type, the annotation evaluates to the [default value](#) of the term definition. If no expression is specified for a term with a complex type, the annotation evaluates to a complex instance with default values for all properties is used. If no expression is specified for a collection-valued term, the annotation evaluates to an empty collection.

If an entity type or complex type is annotated with a term that itself has a structured type, an instance of the annotated type may be viewed as an “instance” of the term, and the qualified term name may be used as a term-cast segment in [path expressions](#).

14.3.1 Attribute Term

An annotation element MUST provide a [QualifiedName](#) value for the `Term` attribute. The value of the `Term` attribute MUST be the name of a [term](#) in scope. The target of the annotation MUST comply with any [AppliesTo](#) constraint.

14.3.2 Attribute Qualifier

An annotation element MAY provide a [SimpleIdentifier](#) value for the `Qualifier` attribute.

The qualifier attribute allows annotation authors a means of conditionally applying an annotation.

Example 37: annotation should only be applied to tablet devices

```
<Annotation Term="org.example.display.DisplayName" Path="FirstName"
  Qualifier="Tablet" />
```

Annotation elements that are children of an [edm:Annotations](#) element MUST NOT provide a value for the qualifier attribute if the parent [edm:Annotations](#) element provides a value for the qualifier attribute.

14.4 Constant Expressions

Constant expressions allow assigning a constant value to an applied term. The constant expressions support element and attribute notation.

Example 38: two annotations intended as user interface hints

```
<EntitySet Name="Products" EntityType="Self.Product">
  <Annotation Term="org.example.display.DisplayName"
    String="Product Catalog" />
</EntitySet>

<EntitySet Name="Suppliers" EntityType="Self.Supplier">
  <Annotation Term="org.example.display.DisplayName">
    <String>Supplier Directory</String>
  </Annotation>
</EntitySet>
```

14.4.1 Expression **edm:Binary**

The **edm:Binary** expression evaluates to a primitive binary value. A binary expression **MUST** be assigned a value conforming to the rule **binaryValue** in **[OData-ABNF]**.

The binary expression **MAY** be provided using element notation or attribute notation.

Example 39: base64url-encoded binary value (OData)

```
<Annotation Term="org.example.display.Thumbnail" Binary="T0RhdGE" />

<Annotation Term="org.example.display.Thumbnail">
  <Binary>T0RhdGE</Binary>
</Annotation>
```

14.4.2 Expression **edm:Bool**

The **edm:Bool** expression evaluates to a primitive Boolean value. A Boolean expression **MUST** be assigned a Boolean value.

The Boolean expression **MAY** be provided using element notation or attribute notation.

Example 40:

```
<Annotation Term="org.example.display.ReadOnly" Bool="true" />

<Annotation Term="org.example.display.ReadOnly">
  <Bool>true</Bool>
</Annotation>
```

14.4.3 Expression **edm:Date**

The **edm:Date** expression evaluates to a primitive date value. A date expression **MUST** be assigned a value of type **xs:date**, see **[XML-Schema-2]**, [section 3.3.9](#). The value **MUST** also conform to rule **dateValue** in **[OData-ABNF]**, i.e. it **MUST NOT** contain a time-zone offset.

The date expression **MAY** be provided using element notation or attribute notation.

Example 41:

```
<Annotation Term="org.example.vCard.birthday" Date="2000-01-01" />

<Annotation Term="org.example.vCard.birthday">
  <Date>2000-01-01</Date>
</Annotation>
```

14.4.4 Expression **edm:DateTimeOffset**

The **edm:DateTimeOffset** expression evaluates to a primitive date/time value with a time-zone offset. A date/time expression **MUST** be assigned a value of type **xs:dateTimeStamp**, see **[XML-Schema-2]**,

[section 3.4.28](#). The value MUST also conform to rule `dateTimeOffsetValue` in **[OData-ABNF]**, i.e. it MUST NOT contain an end-of-day fragment (24:00:00).

The date/time expression MAY be provided using element notation or attribute notation.

Example 42:

```
<Annotation Term="org.example.display.LastUpdated"
  DateTimeOffset="2000-01-01T16:00:00.000Z" />

<Annotation Term="org.example.display.LastUpdated">
  <DateTimeOffset>2000-01-01T16:00:00.000-09:00</DateTimeOffset>
</Annotation>
```

14.4.5 Expression `edm:Decimal`

The `edm:Decimal` expression evaluates to a primitive decimal value. A decimal expression MUST be assigned a value conforming to the rule `decimalValue` in **[OData-ABNF]**.

The decimal expression MAY be provided using element notation or attribute notation.

Example 43:

```
<Annotation Term="org.example.display.Width" Decimal="3.14" />

<Annotation Term="org.example.display.Width">
  <Decimal>3.14</Decimal>
</Annotation>
```

14.4.6 Expression `edm:Duration`

The `edm:Duration` expression evaluates to a primitive duration value. A duration expression MUST be assigned a value of type `xs:dayTimeDuration`, see **[XML-Schema-2]**, [section 3.4.27](#).

The duration expression MAY be provided using element notation or attribute notation.

Example 44:

```
<Annotation Term="org.example.task.duration" Duration="P7D" />

<Annotation Term="org.example.task.duration">
  <Duration>P11D23H59M59.999999999999S</Duration>
</Annotation>
```

14.4.7 Expression `edm:EnumMember`

The `edm:EnumMember` expression references a [member](#) of an [enumeration type](#). An enumeration member expression MUST be assigned a value that consists of the qualified name of the enumeration type, followed by a forward slash and the name of the enumeration member. If the enumeration type specifies an `IsFlags` attribute with value `true`, the expression MAY also be assigned a whitespace-separated list of values. Each of these values MUST resolve to the name of a member of the enumeration type of the specified term.

The enumeration member expression MAY be provided using element notation or attribute notation.

Example 45: single value

```
<Annotation Term="org.example.HasPattern"
  EnumMember="org.example.Pattern/Red" />

<Annotation Term="org.example.HasPattern">
  <EnumMember>org.example.Pattern/Red</EnumMember>
</Annotation>
```

Example 46: combined value for IsFlags enumeration type

```
<Annotation Term="org.example.HasPattern"
  EnumMember="org.example.Pattern/Red org.example.Pattern/Striped" />

<Annotation Term="org.example.HasPattern">
  <EnumMember>org.example.Pattern/Red org.example.Pattern/Striped</EnumMember>
</Annotation>
```

14.4.8 Expression **edm:Float**

The **edm:Float** expression evaluates to a primitive floating point (or double) value. A float expression **MUST** be assigned a value conforming to the rule `doubleValue` in **[OData-ABNF]**.

The float expression **MAY** be provided using element notation or attribute notation.

Example 47:

```
<Annotation Term="org.example.display.Width" Float="3.14" />

<Annotation Term="org.example.display.Width">
  <Float>3.14</Float>
</Annotation>
```

14.4.9 Expression **edm:Guid**

The **edm:Guid** expression evaluates to a primitive 32-character string value. A guid expression **MUST** be assigned a value conforming to the rule `guidValue` in **[OData-ABNF]**.

The guid expression **MAY** be provided using element notation or attribute notation.

Example 48:

```
<Annotation Term="org.example.display.Id"
  Guid="21EC2020-3AEA-1069-A2DD-08002B30309D" />

<Annotation Term="org.example.display.Id">
  <Guid>21EC2020-3AEA-1069-A2DD-08002B30309D</Guid>
</Annotation>
```

14.4.10 Expression **edm:Int**

The **edm:Int** expression evaluates to a primitive integer value. An integer **MUST** be assigned a value conforming to the rule `int64Value` in **[OData-ABNF]**.

The integer expression **MAY** be provided using element notation or attribute notation.

Example 49:

```
<Annotation Term="org.example.display.Width" Int="42" />

<Annotation Term="org.example.display.Width">
  <Int>42</Int>
</Annotation>
```

14.4.11 Expression **edm:String**

The **edm:String** expression evaluates to a primitive string value. A string expression **MUST** be assigned a value of the type `xs:string`, see **[XML-Schema-2]**, [section 3.2.1](#).

The string expression **MAY** be provided using element notation or attribute notation.

Example 50:

```

<Annotation Term="org.example.display.DisplayName" String="Product Catalog" />

<Annotation Term="org.example.display.DisplayName">
  <String>Product Catalog</String>
</Annotation>

```

14.4.12 Expression `edm:TimeOfDay`

The `edm:TimeOfDay` expression evaluates to a primitive time value. A time-of-day expression **MUST** be assigned a value conforming to the rule `timeOfDayValue` in [OData-ABNF].

The time-of-day expression **MAY** be provided using element notation or attribute notation.

Example 51:

```

<Annotation Term="org.example.display.EndTime" TimeOfDay="21:45:00" />

<Annotation Term="org.example.display.EndTime">
  <TimeOfDay>21:45:00</TimeOfDay>
</Annotation>

```

14.5 Dynamic Expressions

Dynamic expressions allow assigning a calculated value to an applied term. The dynamic expressions `edm:AnnotationPath`, `edm:NavigationPropertyPath`, `edm:Path`, `edm:PropertyPath`, and `edm:UrlRef` expressions support element and attribute notation, all other dynamic expressions only support element notation.

14.5.1 Comparison and Logical Operators

The following EDM elements allow service authors to supply a dynamic conditional expression which evaluates to a value of type `Edm.Boolean`. They **MAY** be combined and they **MAY** be used anywhere instead of an `edm:Bool` expression.

Element	Description	Example
Logical Operators		
<code>edm:And</code>	Logical and	<code><And><Path>IsMale</Path><Path>IsMarried</Path></And></code>
<code>edm:Or</code>	Logical or	<code><Or><Path>IsMale</Path><Path>IsMarried</Path></Or></code>
<code>edm:Not</code>	Logical negation	<code><Not><Path>IsMale</Path></Not></code>
Comparison Operators		
<code>edm:Eq</code>	Equal	<code><Eq><Null/><Path>IsMale</Path></Eq></code>
<code>edm:Ne</code>	Not equal	<code><Ne><Null/><Path>IsMale</Path></Ne></code>
<code>edm:Gt</code>	Greater than	<code><Gt><Path>Price</Path><Int>20</Int></Gt></code>
<code>edm:Ge</code>	Greater than or equal	<code><Ge><Path>Price</Path><Int>10</Int></Ge></code>
<code>edm:Lt</code>	Less than	<code><Lt><Path>Price</Path><Int>20</Int></Lt></code>
<code>edm:Le</code>	Less than or equal	<code><Le><Path>Price</Path><Int>100</Int></Le></code>

The `edm:And` and `edm:Or` elements require two child expressions that evaluate to Boolean values. The `edm:Not` elements requires a single child expression that evaluates to a Boolean value.

The other elements representing the comparison operators require two child expressions that evaluate to comparable values.

14.5.2 Expression `edm:AnnotationPath`

The `edm:AnnotationPath` expression provides a value for terms or term properties that specify the [built-in abstract type](#) `Edm.AnnotationPath`. It uses the same syntax and rules as the `edm:Path` expression, with the added restriction that the last path segment **MUST** be a term cast with optional qualifier in the context of the preceding path part.

In contrast to the `edm:Path` expression the value of the `edm:AnnotationPath` expression is the path itself, not the value of the annotation identified by the path. This is useful for terms that reuse or refer to other terms.

The `edm:AnnotationPath` expression **MAY** be provided using element notation or attribute notation.

Example 52:

```
<Annotation Term="UI.ReferenceFacet"
  AnnotationPath="Product/Supplier/@UI.LineItem" />

<Annotation Term="UI.CollectionFacet" Qualifier="Contacts">
  <Collection>
    <AnnotationPath>Supplier/@Communication.Contact</AnnotationPath>
    <AnnotationPath>Customer/@Communication.Contact</AnnotationPath>
  </Collection>
</Annotation>
```

14.5.3 Expression `edm:Apply`

The `edm:Apply` expression enables a value to be obtained by applying a client-side function. The `Apply` expression **MUST** contain at least one expression. The expressions contained within the `Apply` expression are used as parameters to the function. The `edm:Apply` expression **MUST** be written with element notation.

14.5.3.1 Attribute Function

The `edm:Apply` expression **MUST** include a `Function` attribute whose value is a [Qualified Name](#) specifying the name of the client-side function to apply.

OData defines the following canonical functions. Services **MAY** support additional functions that **MUST** be qualified with a namespace or alias other than `odata`. Function names qualified with `odata` are reserved for this specification and its future versions.

14.5.3.1.1 Function `odata.concat`

The `odata.concat` standard client-side function takes two or more expressions as arguments. Each argument **MUST** evaluate to a primitive or enumeration type. It returns a value of type `Edm.String` that is the concatenation of the literal representations of the results of the argument expressions. Values of primitive types other than `Edm.String` are represented according to the appropriate alternative in the `primitiveValue` rule of **[OData-ABNF]**, i.e. `Edm.Binary` as `binaryValue`, `Edm.Boolean` as `booleanValue` etc.

Example 53:

```

<Annotation Term="org.example.display.DisplayName">
  <Apply Function="odata.concat">
    <String>Product: </String>
    <Path>ProductName</Path>
    <String> (</String>
    <Path>Available/Quantity</Path>
    <String> </String>
    <Path>Available/Unit</Path>
    <String> available)</String>
  </Apply>
</Annotation>

```

ProductName is of type String, Quantity in complex type Available is of type Decimal, and Unit in Available is of type enumeration, so the result of the Path expression is represented as the member name of the enumeration value.

14.5.3.1.2 Function `odata.fillUriTemplate`

The `odata.fillUriTemplate` standard client-side function takes two or more expressions as arguments and returns a value of type `Edm.String`.

The first argument MUST be of type `Edm.String` and specifies a URI template according to [RFC6570], the other arguments MUST be `edm:LabeledElement` expressions. Each `edm:LabeledElement` expression specifies the template parameter name in its `Name` attribute and evaluates to the template parameter value.

[RFC6570] defines three kinds of template parameters: simple values, lists of values, and key-value maps.

Simple values are represented as `edm:LabeledElement` expressions that evaluate to a single primitive value. The literal representation of this value according to [OData-ABNF] is used to fill the corresponding template parameter.

Lists of values are represented as `edm:LabeledElement` expressions that evaluate to a collection of primitive values.

Key-value maps are represented as `edm:LabeledElement` expressions that evaluate to a collection of complex types with two properties that are used in lexicographic order. The first property is used as key, the second property as value.

Example 54: assuming there are no special characters in values of the `NameOfMovieGenre` property

```

<Apply Function="odata.fillUriTemplate">
  <String>http://host/service/Genres('{genreName}')</String>
  <LabeledElement Name="genreName" Path="NameOfMovieGenre" />
</Apply>

```

14.5.3.1.3 Function `odata.uriEncode`

The `odata.uriEncode` standard client-side function takes one argument of primitive type and returns the URL-encoded OData literal that can be used as a key value in OData URLs or in the query part of OData URLs. Note: string literals are surrounded by single quotes.

Example 55:

```

<Apply Function="odata.fillUriTemplate">
  <String>http://host/service/Genres({genreName})</String>
  <LabeledElement Name="genreName">
    <Apply Function="odata.uriEncode" >
      <Path>NameOfMovieGenre</Path>
    </Apply>
  </LabeledElement>
</Apply>

```

14.5.4 Expression `edm:Cast`

The `edm:Cast` expression casts the value obtained from its single child expression to the specified type. The cast expression follows the same rules as the `cast` canonical function defined in [OData-URL].

The cast expression MUST specify a `Type` attribute and contain exactly one expression.

The cast expression MUST be written with element notation.

Example 56:

```
<Annotation Term="org.example.display.Threshold">
  <Cast Type="Edm.Decimal">
    <Path>Average</Path>
  </Cast>
</Annotation>
```

14.5.4.1 Attribute `Type`

The `edm:Cast` expression MUST specify a `Type` attribute whose value is a `TypeName` in scope.

If the specified type is a primitive type, the facet attributes `MaxLength`, `Precision`, `Scale`, and `SRID` MAY be specified if applicable to the specified primitive type. If the facet attributes are not specified, their values are considered unspecified.

14.5.5 Expression `edm:Collection`

The `edm:Collection` expression enables a value to be obtained from zero or more child expressions. The value calculated by the collection expression is the collection of the values calculated by each of the child expressions.

The collection expression contains zero or more child expressions. The values of the child expressions MUST all be type compatible.

The collection expression MUST be written with element notation.

Example 57:

```
<Annotation Term="org.example.seo.SeoTerms">
  <Collection>
    <String>Product</String>
    <String>Supplier</String>
    <String>Customer</String>
  </Collection>
</Annotation>
```

14.5.6 Expression `edm:If`

The `edm:If` expression enables a value to be obtained by evaluating a *conditional expression*. It MUST contain exactly three child elements with dynamic or static expressions. There is one exception to this rule: if and only if the `edm:If` expression is a direct child of `edm:Collection` element the third child element MAY be omitted (this can be used to conditionally add an element to a collection).

The first child element is the conditional expression and MUST evaluate to a Boolean result, e.g. the [comparison and logical operators](#) can be used.

The second and third child elements are the expressions, which are evaluated conditionally. They result MUST be type compatible with the type expected by the surrounding element or expression.

If the first expression evaluates to `true`, the second child element MUST be evaluated and its value MUST be returned as the result of the `edm:If` expression. If the conditional expression evaluates to `false` and a third child element is present, it MUST be evaluated and its value MUST be returned as the result of the `edm:If` expression. If no third child element is present, nothing is added to the collection.

The `edm:If` expression MUST be written with element notation, as shown in the following example.

Example 58:

```
<Annotation Term="org.example.person.Gender">
  <If>
    <Path>IsFemale</Path>
    <String>Female</String>
    <String>Male</String>
  </If>
</Annotation>
```

14.5.7 Expression `edm:IsOf`

The `edm:IsOf` expression evaluates a child expression and returns a Boolean value indicating whether the child expression returns the specified type.

An `edm:IsOf` expression MUST specify a [Type](#) attribute and contain exactly one child expression. The `edm:IsOf` expression MUST return `true` if the child expression returns a type that is compatible with the type named in the [Type](#) attribute. The `edm:IsOf` expression MUST return `false` if the child expression returns a type that is not compatible with the type named in the [Type](#) attribute.

The `edm:IsOf` expression MUST be written with element notation.

Example 59:

```
<Annotation Term="Self.IsPreferredCustomer">
  <IsOf Type="Self.PreferredCustomer">
    <Path>Customer</Path>
  </IsOf>
</Annotation>
```

14.5.7.1 Attribute `Type`

The `edm:IsOf` expression MUST specify a `Type` attribute whose value is a [TypeName](#) in scope.

If the specified type is a primitive type, the facet attributes [MaxLength](#), [Precision](#), [Scale](#), and [SRID](#) MAY be specified if applicable to the specified primitive type. If the facet attributes are not specified, their values are considered unspecified.

14.5.8 Expression `edm:LabeledElement`

The `edm:LabeledElement` expression assigns a name to a child expression. The value of the child expression can then be reused elsewhere with an [edm:LabeledElementReference](#) expression.

A labeled-element expression MUST contain exactly one child expression written either in attribute notation or element notation. The value of the child expression is passed through the labeled-element expression.

A labeled-element expression MUST be written with element notation.

Example 60:

```
<Annotation Term="org.example.display.DisplayName">
  <LabeledElement Name="CustomerFirstName" Path="FirstName" />
</Annotation>

<Annotation Term="org.example.display.DisplayName">
  <LabeledElement Name="CustomerFirstName">
    <Path>FirstName</Path>
  </LabeledElement>
</Annotation>
```

14.5.8.1 Attribute Name

An `edm:LabeledElement` expression MUST provide a `SimpleIdentifier` value for the `Name` attribute that is unique within the schema containing the expression.

14.5.9 Expression `edm:LabeledElementReference`

The `edm:LabeledElementReference` expression returns the value of an `edm:LabeledElement` expression.

The labeled-element reference expression MUST contain the `QualifiedName` name of a labeled element expression in scope.

The labeled-element reference expression MUST be written with element notation.

Example 61:

```
<Annotation Term="org.example.display.DisplayName">
  <LabeledElementReference>Model.CustomerFirstName</LabeledElementReference>
</Annotation>
```

14.5.10 Expression `edm:Null`

The `edm:Null` expression returns an untyped null value. The null expression MUST NOT contain any other elements or expressions.

The null expression MUST be written with element notation.

Example 62:

```
<Annotation Term="org.example.display.DisplayName">
  <Null/>
</Annotation>
```

14.5.11 Expression `edm:NavigationPropertyPath`

The `edm:NavigationPropertyPath` expression provides a value for terms or term properties that specify the `built-in abstract type` `Edm.NavigationPropertyPath`. It uses the same syntax and rules as the `edm:Path` expression with the following exceptions:

- The `NavigationPropertyPath` expression may traverse multiple collection-valued scalar or navigation properties
- The last path segment MUST resolve to a `navigation property` in the context of the preceding path part, or to a `term cast` where the term MUST be of type `Edm.EntityType`, a concrete entity type or a collection of `Edm.EntityType` or concrete entity type.

In contrast to the `edm:Path` expression, the value of the `edm:NavigationPropertyPath` expression is the path itself, not the target instance(s) of the navigation property identified by the path.

The `edm:NavigationPropertyPath` expression MAY be provided using element notation or attribute notation.

Example 63:

```

<Annotation Term="UI.HyperLink" NavigationPropertyPath="Supplier" />

<Annotation Term="Capabilities.UpdateRestrictions">
  <Record>
    <PropertyValue Property="NonUpdatableNavigationProperties">
      <Collection>
        <NavigationPropertyPath>Supplier</NavigationPropertyPath>
        <NavigationPropertyPath>Category</NavigationPropertyPath>
      </Collection>
    </PropertyValue>
  </Record>
</Annotation>

```

14.5.12 Expression `edm:Path`

The `edm:Path` expression enables a value to be obtained by traversing an object graph. It can be used in annotations that target entity containers, entity sets, entity types, complex types, navigation properties of structured types, and properties of structured types.

The value assigned to the path expression MUST be composed of zero or more path segments joined together by forward slashes (/).

If a path segment is a [QualifiedName](#), it represents a *type cast*, and the segment MUST be the name of a type in scope. If the instance identified by the preceding path part cannot be cast to the specified type, the path expression evaluates to the null value.

If a path segment starts with an at (@) character, it represents a *term cast*. The at (@) character MUST be followed by a [QualifiedName](#) that MAY be followed by a hash (#) character and a [SimpleIdentifier](#). The [QualifiedName](#) preceding the hash character MUST resolve to a term that is in scope, the [SimpleIdentifier](#) following the hash sign is interpreted as a [Qualifier](#) for the term. If the instance identified by the preceding path part has been annotated with that term (and if present, with that qualifier), the term cast evaluates to the value of that annotation, otherwise it evaluates to the null value. Three special terms are implicitly “annotated” for media entities and stream properties:

- `odata.mediaEditLink`
- `odata.mediaReadLink`
- `odata.mediaContentType`

If a path segment is a [SimpleIdentifier](#), it MUST be the name of a structural property or a navigation property of the instance identified by the preceding path part.

When used within an `edm:Path` expression, a path may contain at most one segment representing a multi-valued structural or navigation property. The result of the expression is the collection of instances resulting from applying the remaining path to each instance in the multi-valued property.

A path may terminate in a `$count` segment if the previous segment is multi-valued, in which case the path evaluates to the number of elements identified by the preceding segment.

If a path segment starts with a navigation property followed by an at (@) character, then the at (@) character MUST be followed by a [QualifiedName](#) that MAY be followed by a hash (#) character and a [SimpleIdentifier](#). The [QualifiedName](#) preceding the hash character MUST resolve to a term that is in scope, the [SimpleIdentifier](#) following the hash sign is interpreted as a [Qualifier](#) for the term. If the navigation property has been annotated with that term (and if present, with that qualifier), the path segment evaluates to the value of that annotation, otherwise it evaluates to the null value.

Annotations MAY be embedded within their target, or embedded within an `edm:Annotations` element that specifies the annotation target with a path expression in its `Target` attribute. The latter situation is referred to as *targeting* in the remainder of this section.

For annotations embedded within or targeting an entity container, the path expression is evaluated starting at the entity container, i.e. an empty path resolves to the entity container, and non-empty path values MUST start with the name of a container child (entity set, function import, action import, or

singleton). The subsequent segments follow the rules for path expressions targeting the corresponding child element.

For annotations embedded within or targeting an entity set or a singleton, the path expression is evaluated starting at the entity set, i.e. an empty path resolves to the entity set, and non-empty paths MUST follow the rules for annotations targeting the declared entity type of the entity set or singleton.

For annotations embedded within or targeting an entity type or complex type, the path expression is evaluated starting at the type, i.e. an empty path resolves to the type, and the first segment of a non-empty path MUST be a property or navigation property of the type, a type cast, or a term cast.

For annotations embedded within a property of an entity type or complex type, the path expression is evaluated starting at the directly enclosing type. This allows e.g. specifying the value of an annotation on one property to be calculated from values of other properties of the same type. An empty path resolves to the enclosing type, and non-empty paths MUST follow the rules for annotations targeting the directly enclosing type.

For annotations targeting a property of an entity type or complex type, the path expression is evaluated starting at the *outermost* entity type or complex type named in the [Target](#) of the enclosing [edm:Annotations](#) element, i.e. an empty path resolves to the outermost type, and the first segment of a non-empty path MUST be a property or navigation property of the outermost type, a type cast, or a term cast.

A path expression MAY be provided using element notation or attribute notation.

Example 64:

```
<Annotation Term="org.example.display.DisplayName" Path="FirstName" />

<Annotation Term="org.example.display.DisplayName">
  <Path>@vCard.Address#work/FullName</Path>
</Annotation>
```

14.5.13 Expression `edm:PropertyPath`

The `edm:PropertyPath` expression provides a value for terms or term properties that specify the [built-in abstract type](#) `Edm.PropertyPath`. It uses the same syntax and rules as the `edm:Path` expression, with the following exceptions:

- The `PropertyPath` expression may traverse multiple collection-valued scalar or navigation properties
- The last path segment MUST resolve either to a structural property in the context of the preceding path part, or to a [term cast](#) where the term MUST be of type `Edm.ComplexType`, `Edm.PrimitiveType`, a complex type, an enumeration type, a concrete primitive type, a type definition, or a collection of one of these types.

In contrast to the `edm:Path` expression, the value of the `edm:PropertyPath` expression is the path itself, not the value of the property identified by the path.

The `edm:PropertyPath` MAY be provided using either element notation or attribute notation.

Example 65:

```
<Annotation Term="UI.RefreshOnChangeOf" PropertyPath="ChangedAt" />

<Annotation Term="Capabilities.UpdateRestrictions">
  <Record>
    <PropertyValue Property="NonUpdatableProperties">
      <Collection>
        <PropertyPath>CreatedAt</PropertyPath>
        <PropertyPath>ChangedAt</PropertyPath>
      </Collection>
    </PropertyValue>
  </Record>
</Annotation>
```

```
</Record>
</Annotation>
```

14.5.14 Expression `edm:Record`

The `edm:Record` expression enables a new entity type or complex type instance to be constructed.

A record expression contains zero or more `edm:PropertyValue` elements. For each single-valued structural or navigation property of the record construct's type that is neither nullable nor specifies a default value an `edm:PropertyValue` child element **MUST** be provided. The only exception is if the record expression is the direct child of an `edm:Annotation` element for a term that has a **base term** whose type is structured and directly or indirectly inherits from the type of its base term. In this case, property values that already have been specified in the annotation for the base term or its base term etc. need not be specified again.

For collection-valued properties the absence of an `edm:PropertyValue` child element is equivalent to specifying a child element with an empty collection as its value.

A record expression **MUST** be written with element notation, as shown in the following example.

Example 66: record with two structural and two navigation properties

```
<Annotation Term="org.example.person.Employee">
  <Record>
    <PropertyValue Property="GivenName" Path="FirstName" />
    <PropertyValue Property="Surname" Path="LastName" />
    <PropertyValue Property="Manager" Path="DirectSupervisor" />
    <PropertyValue Property="CostCenter">
      <UrlRef>
        <Apply Function="odata.fillUriTemplate">
          <String>http://host/anotherservice/CostCenters('{ccid}')
```

14.5.14.1 Attribute Type

A record expression **MAY** specify a **QualifiedName** value for the `Type` attribute that **MUST** resolve to an entity type or complex type in scope. If no value is specified for the type attribute, the type is derived from the expression's context.

14.5.14.2 Element `edm:PropertyValue`

The `edm:PropertyValue` element supplies a value to a property on the type instantiated by an `edm:Record` expression. The value is obtained by evaluating an expression.

The `PropertyValue` element **MUST** contain exactly one expression. The `edm:PropertyValue` expression **MAY** be provided using element notation or attribute notation.

14.5.14.2.1 Attribute Property

The `PropertyValue` element **MUST** assign a **SimpleIdentifier** value to the `Property` attribute. The value of the property attribute **MUST** resolve to a property of the type of the enclosing `edm:Record` expression.

14.5.15 Expression `edm:UrlRef`

The `edm:UrlRef` expression enables a value to be obtained by sending a `GET` request to the value of the `UrlRef` expression.

The `edm:UrlRef` element **MUST** contain exactly one expression of type `Edm.String`. The `edm:UrlRef` expression **MAY** be provided using element notation or attribute notation.

The response body of the `GET` request **MUST** be returned as the result of the `edm:UrlRef` expression. The result of the `edm:UrlRef` expression **MUST** be type compatible with the type expected by the surrounding element or expression.

Example 67:

```
<Annotation Term="Vocab.Supplier">
  <UrlRef>
    <Apply Function="odata.fillUriTemplate">
      <String>http://host/service/Suppliers({suppID})</String>
      <LabeledElement Name="suppID">
        <Apply Function="odata.uriEncode">
          <Path>SupplierId</Path>
        </Apply>
      </LabeledElement>
    </Apply>
  </UrlRef>
</Annotation>

<Annotation Term="Core.LongDescription">
  <UrlRef><String>http://host/wiki/HowToUse</String></UrlRef>
</Annotation>
```

15 Metadata Service Schema

The Metadata Service is a representation of the entity model of an OData service as an OData service with a fixed (meta) data model. The Metadata Service provides convenient access to the entity model of a service, i.e. all CSDL constructs used in its entity containers.

With `~/` as an abbreviation for the service root URL, the Metadata Service root URL is `~/ $metadata/`, i.e. the canonical URL of the metadata document of the underlying service with a forward slash appended, and a GET request to `~/ $metadata/ $metadata` returns the CSDL document of the Metadata Service itself, defined in **[OData-Meta]**.

The following sections describe the schema of the Metadata Service.

Example 68: service document of Metadata Service

```
GET ~/ $metadata/
```

would return

```
{
  "@odata.context": "~/ $metadata/ $metadata",
  "value": [
    { "name": "References"           , "url": "References" },
    { "name": "Schemata"           , "url": "Schemata" },
    { "name": "Types"              , "url": "Types" },
    { "name": "Properties"          , "url": "Properties" },
    { "name": "NavigationProperties", "url": "NavigationProperties" },
    { "name": "EnumTypeMembers"    , "url": "EnumTypeMembers" },
    { "name": "Actions"            , "url": "Actions" },
    { "name": "Functions"          , "url": "Functions" },
    { "name": "Terms"              , "url": "Terms" },
    { "name": "Annotations"        , "url": "Annotations" },
    { "name": "EntityContainer"    , "url": "EntityContainer",
      "kind": "Singleton" },
    { "name": "EntitySets"         , "url": "EntitySets" },
    { "name": "Singletons"         , "url": "Singletons" },
    { "name": "NavigationPropertyBindings", "url": "NavigationPropertyBindings" },
    { "name": "ActionImports"      , "url": "ActionImports" },
    { "name": "FunctionImports"    , "url": "FunctionImports" }
  ]
}
```


Note: all examples in this chapter use `~/` as an abbreviation for the service root URL.

Note: `~/ $metadata/ $metadata` is not a typo, it is the metadata URL of the Metadata Service for the service with root URL `~/`.

15.1 Entity Model Wrapper

The Metadata Service provides convenient access to the entity model of a service, i.e. all CSDL constructs used in its entity containers. This model may be distributed over several schemas, and these schemas may be distributed over several physical locations, bound together via the [entity model wrapper](#).

This document structure is represented in the metadata service as an entity type `Reference` and two complex types `Include` and `IncludeAnnotations`.



Legend: boxes without a stereotype represent entity types; boxes with stereotype `<<complex>>` represent complex types. Compositions represent complex properties; associations represent navigation properties. Arrows indicate navigation properties without a partner; associations without arrows are bidirectional. No multiplicity means 1.

A reference is identified by its `Uri` property, which is the absolute value of the `Uri` attribute after resolving a relative value against the `xml:base` attribute.

Example 69: for the *Products and Categories* example the request


```
GET ~/ $metadata/References?$expand=Include/Schema($select=Namespace)
```

would return

```
{
  "@odata.context":
    "~/ $metadata/ $metadata#References (., Include/Schema (Namespace) ) ",
  "value": [
    {
      "Uri": "http://tinyurl.com/Org-OData-Core",
      "Include": [
        { "Alias": "Core", "Schema": { "Namespace": "Org.OData.Core.V1" } }
      ],
      "IncludeAnnotations": []
    }, {
      "Uri": "http://tinyurl.com/Org-OData-Measures-V1",
      "Include": [
        { "Alias": "UoM", "Schema": { "Namespace": "Org.OData.Measures.V1" } }
      ],
      "IncludeAnnotations": []
    }
  ]
}
```


15.2 Schema

The *model* of the service consists of all CSDL constructs used in its entity containers. Each model construct is defined in a schema:



A schema is identified by its `Namespace` property. If it defines an alias, direct key access using the alias instead of the namespace redirects to the schema with this alias.

Example 70: for the Products and Categories example the request

```
GET ~/ $metadata/Schemata
```

would return

```
{
  "@odata.context": "~/ $metadata#Schemata",
  "value": [
    {
      "Namespace": "ODataDemo", "Alias": null
    }, {
      "Namespace": "Org.OData.Core.V1", "Alias": "Core"
    }, {
      "Namespace": "Org.OData.Measures.V1", "Alias": "UoM"
    }, {
      "Namespace": "Edm", "Alias": null
    }
  ]
}
```

Example 71: redirecting from alias to schema

```
GET ~/ $metadata/Schemata('Core')
```


would return

```
{
  "@odata.context": "~/ $metadata#Schemata/@entity",
  "Namespace": "Org.OData.Core.V1",
  "Alias": "Core"
}
```

All schemata used in the model are listed in this entity set, independently of whether they are defined directly in the metadata document or included via a reference.

15.3 Types

Types form an inheritance hierarchy



A type is identified by its `QualifiedName` property, which is the `Namespace` of the defining schema, followed by a dot (.) and the `Name` of the type. There is only one entity set `Types` for all types. Type cast segments can be used to access specialized types.

Only those built-in primitive types that are actually used in the model appear in the `Types` entity set.

Example 72: single type by name, and all entity types

```
GET ~/ $metadata/Types('ODataDemo.Product')
GET ~/ $metadata/Types/Meta.EntityType
```

Example 73: all types

```
GET ~/ $metadata/Types
```

would return

```
{
  "@odata.context": "~/ $metadata/ $metadata#Types",
  "value": [ {
    "@odata.type": "Meta.EntityType",
    "QualifiedName": "ODataDemo.Product", "Name": "Product",
    "Key": [ { "PropertyPath": "ID", "Alias": null } ],
    "Abstract": false, "OpenType": false, "HasStream": true
  }, {
    "@odata.type": "Meta.EntityType",
    "QualifiedName": "ODataDemo.Category", "Name": "Category",
    "Key": [ { "PropertyPath": "ID", "Alias": null } ],
    "Abstract": false, "OpenType": false, "HasStream": false
  }, {
    "@odata.type": "Meta.EntityType",
    "QualifiedName": "ODataDemo.Supplier", "Name": "Supplier",
    "Key": [ { "PropertyPath": "ID", "Alias": null } ],
    "Abstract": false, "OpenType": false, "HasStream": false
  }, {
    "@odata.type": "Meta.EntityType",
    "QualifiedName": "ODataDemo.Country", "Name": "Country",
    "Key": [ { "PropertyPath": "Code", "Alias": null } ],
    "Abstract": false, "OpenType": false, "HasStream": false
  }, {
    "@odata.type": "Meta.ComplexType",
    "QualifiedName": "ODataDemo.Address", "Name": "Address",
    "Abstract": false, "OpenType": false
  }, {
    "@odata.type": "Meta.ComplexType",
    "QualifiedName": "Core.OptimisticConcurrencyControl",
    "Name": "OptimisticConcurrencyControl",
```


```

    "Abstract":false, "OpenType":false
  },{
    "@odata.type":"Meta.PrimitiveType",
    "QualifiedName":"Edm.Date", "Name":"Date"
  },{
    "@odata.type":"Meta.PrimitiveType",
    "QualifiedName":"Edm.Decimal", "Name":"Decimal"
  },{
    "@odata.type":"Meta.PrimitiveType",
    "QualifiedName":"Edm.Int32", "Name":"Int32"
  },{
    "@odata.type":"Meta.PrimitiveType",
    "QualifiedName":"Edm.String", "Name":"String"
  },{
    "@odata.type":"Meta.PrimitiveType",
    "QualifiedName":"Edm.PropertyPath", "Name":"PropertyPath"
  },{
    "@odata.type":"Meta.EntityType",
    "QualifiedName":"Edm.EntityType", "Name":"EntityType", "Key":[],
    "Abstract":true, "OpenType":false, "HasStream":false  }
  ]
}

```

15.4 Properties

Structural properties and navigation properties are represented as



This model is intentionally simplified. It closely resembles the XML schema and makes querying easy as it e.g. allows expanding the **Type** for all structural properties. A structured type is only related to properties it directly declares, not to properties it inherits from ancestor types. All inherited and directly declared properties or navigation properties can be requested with the bound functions `Meta.AllProperties` and `Meta.AllNavigationProperties`.

Structural properties and navigation properties are identified by their `Fullname` property, which is the `QualifiedName` of the containing entity type or complex type, followed by a forward slash (/) and the `Name` of the property or navigation property.

Example 74: single property or navigation property by name

```

GET ~/ $metadata/Properties (ODataDemo.Product%2FID')
GET ~/ $metadata/NavigationProperties (ODataDemo.Category%2FProducts)

```

Example 75: all properties with type

```

GET ~/ $metadata/Properties?$expand=Type($select=QualifiedName)

```

would return

```

{
  "@odata.context": "~/$metadata/$metadata#Properties(*,Type(QualifiedName))",
  "value": [
    {
      "Fullname": "ODataDemo.Product/ID", "Name": "ID",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Product/Description", "Name": "Description",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Product/ReleaseDate", "Name": "ReleaseDate",
      "Nullable": true, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.Date"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Product/DiscontinuedDate",
      "Name": "DiscontinuedDate",
      "Nullable": true, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.Date"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Product/Rating", "Name": "Rating",
      "Nullable": true, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.Int32"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Product/Currency", "Name": "Currency",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": [{"Name": "MaxLength", "Value": "3"}]
    }, {
      "Fullname": "ODataDemo.Category/ID", "Name": "ID",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.Int32"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Category/Name", "Name": "Name",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Supplier/ID", "Name": "ID",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Supplier/Name", "Name": "Name",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.String"},
      "Facets": []
    }, {
      "Fullname": "ODataDemo.Supplier/Address", "Name": "Address",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "ODataDemo.Address"},
      "Facets": []
    }, {
      "@odata.type": "Meta.PrimitiveProperty",
      "Fullname": "ODataDemo.Supplier/Concurrency", "Name": "Concurrency",
      "Nullable": false, "IsCollection": false,
      "Type": {"QualifiedName": "Edm.Int32"},

```

```

    "Facets":[]
  },{
    "Fullname":"ODataDemo.Country/Code", "Name":"Code",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[{"Name":"MaxLength","Value":"2"}]
  },{
    "Fullname":"ODataDemo.Country/Name", "Name":"Name",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"ODataDemo.Address/Street", "Name":"Street",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"ODataDemo.Address/City", "Name":"City",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"ODataDemo.Address/State", "Name":"State",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"ODataDemo.Address/ZipCode", "Name":"ZipCode",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"ODataDemo.Address/CountryName", "Name":"CountryName",
    "Nullable":false, "IsCollection":false,
    "Type":{"QualifiedName":"Edm.String"},
    "Facets":[]
  },{
    "Fullname":"Core.OptimisticConcurrencyControl/ETagDependsOn",
    "Name":"ETagDependsOn",
    "Nullable":false, "IsCollection":true,
    "Type":{"QualifiedName":"Edm.PropertyPath"},
    "Facets":[]
  }
]
}

```

Example 76: all navigation properties with type and partner

```

GET ~/ $metadata/NavigationProperties?
    $expand=Type($select=QualifiedName),Partner($select=Name)

```

would return

```

{
  "@odata.context":"~/ $metadata/$metadata#NavigationProperties(Type(QualifiedN
ame),Partner(Name))",
  {
    "Fullname":"ODataDemo.Product/Category", "Name":"Category",
    "Nullable":false, "ContainsTarget":false,
    "OnDelete":null,
    "ReferentialConstraints":[],
    "IsCollection":false,
    "Type":{"QualifiedName":"ODataDemo.Category" },
    "Partner":{"Name":"Product" }
  }
}

```


```

    }, {
      "Fullname": "ODataDemo.Product/Supplier", "Name": "Supplier",
      "Nullable": false, "ContainsTarget": false,
      "OnDelete": null,
      "ReferentialConstraints": [],
      "IsCollection": false,
      "Type": { "QualifiedName": "ODataDemo.Supplier" },
      "Partner": { "Name": "Products" }
    }, {
      "Fullname": "ODataDemo.Category/Products", "Name": "Products",
      "Nullable": false, "ContainsTarget": false,
      "OnDelete": { "Action": "Cascade", "Annotations": [] },
      "ReferentialConstraints": [],
      "IsCollection": true,
      "Type": { "QualifiedName": "ODataDemo.Product" },
      "Partner": { "Name": "Category" }
    }, {
      "Fullname": "ODataDemo.Supplier/Products", "Name": "Products",
      "Nullable": false, "ContainsTarget": false,
      "OnDelete": null,
      "ReferentialConstraints": [],
      "IsCollection": true,
      "Type": { "QualifiedName": "ODataDemo.Product" },
      "Partner": { "Name": "Supplier" }
    }, {
      "Fullname": "ODataDemo.Address/Country", "Name": "Country",
      "Nullable": false, "ContainsTarget": false,
      "OnDelete": null,
      "ReferentialConstraints": [
        {
          "Property": "CountryName", "ReferencedProperty": "Name",
          "Annotations": []
        }
      ],
      "IsCollection": false,
      "Type": { "QualifiedName": "ODataDemo.Product" },
      "Partner": { "Name": "Supplier" }
    }
  ]
}

```

15.5 Actions and Functions

Actions and functions are represented as



Actions and functions are identified by their `QualifiedName` property, which is the `Namespace` of the containing schema, followed by a dot (.) and the `Name` of the action or function.

Example 77:

```

GET ~/metadata/Actions('SampleModel.Approval')
GET ~/metadata/Functions('ODataDemo.ProductsByRating')

```

Example 78: all functions


```
GET ~/ $metadata/Functions?
    $expand=Overloads/Parameters/Type($select=QualifiedName)
```

would return

```
{
  "@odata.context":
  "~/ $metadata/ $metadata#Functions(*,Overloads/Parameters/Type(QualifiedName)) ",
  "value": [
    {
      "QualifiedName": "ODataDemo.ProductsByRating",
      "Name": "ProductsByRating",
      "Overloads": [
        {
          "IsBound": false, "IsComposable": false,
          "ReturnType": {
            "IsCollection": true, "Nullable": false, "Facets": [],
            "Type": { "QualifiedName": "ODataDemo.Product" }
          },
          "Parameters": [
            {
              "Name": "Rating", "IsBinding": false,
              "Nullable": true,
              "IsCollection": false, "Facets": [],
              "Type": { "QualifiedName": "Edm.Int32" }
            }
          ]
        }
      ]
    }
  ]
}
```

15.6 Entity Container

Entity container constructs are represented as



An entity container is identified by its `QualifiedName` property, which is the `Namespace` of the containing schema, followed by a dot (.) and the `Name` of the entity container. As there is exactly one entity container per service, it is a singleton.

Example 79:

```
GET ~/ $metadata/EntityContainer
```

Direct children of an entity container are identified by their `Fullname` property, which is the `QualifiedName` of the entity container, followed by a forward slash (/) and the `Name` of the child.

Example 80:

```
GET ~/ $metadata/EntitySets('ODataDemo.DemoService%2FCategories')
```

A navigation property binding is identified by its `Fullname` property, which is the `Fullname` of the source entity set or singleton, followed by a forward slash (/) and the `Path` of the navigation property binding.

Example 81:

```
GET ~/ $metadata/NavigationPropertyBindings (
    'ODataDemo.DemoService%2FCategories%2FProducts')
```

Example 82: all containers with direct children


```
GET ~/ $metadata/EntityContainer?$expand=*
```

would return

```
{
  "@odata.context": "~/ $metadata/$metadata#EntityContainer",
  "value": [
    {
      "QualifiedName": "ODataDemo.DemoService",
      "Name": "DemoService",
      "EntitySets": [
        {
          "Fullname": "ODataDemo.DemoService/Products",
          "Name": "Products"
        }, {
          "Fullname": "ODataDemo.DemoService/Suppliers",
          "Name": "Suppliers"
        }, {
          "Fullname": "ODataDemo.DemoService/Categories",
          "Name": "Categories"
        }, {
          "Fullname": "ODataDemo.DemoService/Countries",
          "Name": "Countries"
        }
      ],
      "Singletons": [
        {
          "QualifiedName": "ODataDemo.DemoService/Contoso",
          "Name": "Contoso"
        }
      ],
      "ActionImports": [],
      "FunctionImports": [
        {
          "QualifiedName": "ODataDemo.DemoService/ProductsByRating",
          "Name": "ProductsByRating",
          "IncludeInServiceDocument": false
        }
      ]
    }
  ]
}
```


15.7 Terms and Annotations

Terms and annotations based on these terms are represented as



A term is identified by its `QualifiedName` property, which is the `Namespace` of the containing schema, followed by a dot (.) and the `Name` of the term.

Example 83:

```
GET ~//$metadata/Terms?$expand=Type($select=QualifiedName)
```

would return

```
{
  "@odata.context": "~//$metadata/$metadata#Terms(Type(QualifiedName))",
  "value": [
    {
      "QualifiedName": "Core.Description", "Name": "Description",
      "DefaultValue": null, "IsCollection": false,
      "Type": { "QualifiedName": "Edm.String" }
    }, {
      "QualifiedName": "Core.OptimisticConcurrencyControl",
      "Name": "OptimisticConcurrencyControl",
      "DefaultValue": null, "IsCollection": false,
      "Type": { "QualifiedName": "Core.OptimisticConcurrencyControlType" }
    }
  ]
}
```

Annotations can be stated in CSDL in two ways: *inline* as child elements of the annotated element, or *externally* as children of an `edm:Annotations` element that targets the model element to be annotated. The external form is only possible for model elements that can be uniquely identified by a target path expression, and these model elements are represented in the Metadata Service as entity types, while all model elements that cannot be targeted are represented as complex types.

Consequently annotations that can only be stated with the inline form are represented with the complex type `Edm.Metadata.InlineAnnotation`, while annotations that can be stated externally are represented with the entity type `Edm.Metadata.Annotation`, whether they are stated inline or externally in the metadata document or referenced CSDL documents. If the example metadata document in Example 85 would reference the CSDL document in Example 86, all its annotations would also be members of the Annotations entity set of the Metadata Service for Example 85.

These annotations are identified by the combination of their target, term, and qualifier. The `Fullname` of an annotation is the `Fullname` of the target, followed by an at (@) sign and the `QualifiedName` of the term, and for non-empty qualifiers followed by a hash (#) sign and the qualifier.

Example 84:

```
GET ~//$metadata/Annotations
```

would return

```
{
  "@odata.context": "~//$metadata/$metadata#Annotations",
  "value": [
    {
      "Fullname": "ODataDemo.Product/Description@Core.IsLanguageDependent",
      "Qualifier": null,
      "Value": { "@odata.type": "Meta.ConstantExpression", "Value": true }
    },
    {
      "Fullname": "ODataDemo.Product/Price@UoM.ISOCurrency",
      "Qualifier": null,
      "Value": { "@odata.type": "Meta.Path", "Value": "Currency" }
    },
    {
      "Fullname": "ODataDemo.Category/Name@Core.IsLanguageDependent",
      "Qualifier": null,

```

```
{
  "Value": { "@odata.type": "Meta.Constant", "Value": true }
},
{
  "Fullname":
    "ODataDemo.DemoService/Suppliers@Core.OptimisticConcurrencyControl",
  "Qualifier": null,
  "Value": {
    "@odata.type": "Meta.Record",
    "Annotations": [],
    "PropertyValues": [
      {
        "Annotations": [],
        "Property": "ETagDependsOn",
        "Value": {
          "@odata.type": "Meta.Collection",
          "Annotations": [],
          "Items": [
            {
              "@odata.type": "Meta.PropertyPath",
              "Value": "Concurrency"
            }
          ]
        }
      }
    ]
  }
}
]
```

16 CSDL Examples

Following are two basic examples of valid EDM models as represented in CSDL. These examples demonstrate many of the topics covered above.

16.1 Products and Categories Example

Example 85:

```
<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx"
  Version="4.0">
  <edmx:Reference Uri="http://docs.oasis-
open.org/odata/odata/v4.0/cs01/vocabularies/Org.OData.Core.V1.xml">
    <edmx:Include Namespace="Org.OData.Core.V1" Alias="Core" />
  </edmx:Reference>
  <edmx:Reference Uri="http://docs.oasis-
open.org/odata/odata/v4.0/cs01/vocabularies/Org.OData.Measures.V1.xml">
    <edmx:Include Alias="UoM" Namespace="Org.OData.Measures.V1" />
  </edmx:Reference>
  <edmx:DataServices>
    <Schema xmlns="http://docs.oasis-open.org/odata/ns/edm"
      Namespace="ODataDemo">
      <EntityType Name="Product" HasStream="true">
        <Key>
          <PropertyRef Name="ID" />
        </Key>
        <Property Name="ID" Type="Edm.Int32" Nullable="false" />
        <Property Name="Description" Type="Edm.String" >
          <Annotation Term="Core.IsLanguageDependent" />
        </Property>
        <Property Name="ReleaseDate" Type="Edm.Date" />
        <Property Name="DiscontinuedDate" Type="Edm.Date" />
        <Property Name="Rating" Type="Edm.Int32" />
        <Property Name="Price" Type="Edm.Decimal">
          <Annotation Term="UoM.ISOCurrency" Path="Currency" />
        </Property>
        <Property Name="Currency" Type="Edm.String" MaxLength="3" />
        <NavigationProperty Name="Category" Type="ODataDemo.Category"
          Nullable="false" Partner="Products" />
        <NavigationProperty Name="Supplier" Type="ODataDemo.Supplier"
          Partner="Products" />
      </EntityType>
      <EntityType Name="Category">
        <Key>
          <PropertyRef Name="ID" />
        </Key>
        <Property Name="ID" Type="Edm.Int32" Nullable="false" />
        <Property Name="Name" Type="Edm.String">
          <Annotation Term="Core.IsLanguageDependent" />
        </Property>
        <NavigationProperty Name="Products" Partner="Category"
          Type="Collection(ODataDemo.Product)">
          <OnDelete Action="Cascade" />
        </NavigationProperty>
      </EntityType>
      <EntityType Name="Supplier">
        <Key>
          <PropertyRef Name="ID" />
        </Key>
        <Property Name="ID" Type="Edm.String" Nullable="false" />
```

```

    <Property Name="Name" Type="Edm.String" />
    <Property Name="Address" Type="ODataDemo.Address" Nullable="false" />
    <Property Name="Concurrency" Type="Edm.Int32" Nullable="false" />
    <NavigationProperty Name="Products" Partner="Supplier"
        Type="Collection(ODataDemo.Product)" />
</EntityType>
<EntityType Name="Country">
    <Key>
        <PropertyRef Name="Code" />
    </Key>
    <Property Name="Code" Type="Edm.String" MaxLength="2"
        Nullable="false" />
    <Property Name="Name" Type="Edm.String" />
</EntityType>
<ComplexType Name="Address">
    <Property Name="Street" Type="Edm.String" />
    <Property Name="City" Type="Edm.String" />
    <Property Name="State" Type="Edm.String" />
    <Property Name="ZipCode" Type="Edm.String" />
    <Property Name="CountryName" Type="Edm.String" />
    <NavigationProperty Name="Country" Type="ODataDemo.Country">
        <ReferentialConstraint Property="CountryName"
            ReferencedProperty="Name" />
    </NavigationProperty>
</ComplexType>
<Function Name="ProductsByRating">
    <Parameter Name="Rating" Type="Edm.Int32" />
    <ReturnType Type="Collection(ODataDemo.Product)" />
</Function>
<EntityContainer Name="DemoService">
    <EntitySet Name="Products" EntityType="ODataDemo.Product">
        <NavigationPropertyBinding Path="Category" Target="Categories" />
    </EntitySet>
    <EntitySet Name="Categories" EntityType="ODataDemo.Category">
        <NavigationPropertyBinding Path="Products" Target="Products" />
    </EntitySet>
    <EntitySet Name="Suppliers" EntityType="ODataDemo.Supplier">
        <NavigationPropertyBinding Path="Products" Target="Products" />
        <NavigationPropertyBinding Path="Address/Country"
            Target="Countries" />
    <Annotation Term="Core.OptimisticConcurrencyControl">
        <Collection>
            <PropertyPath>Concurrency</PropertyPath>
        </Collection>
    </Annotation>
</EntitySet>
    <Singleton Name="Contoso" Type="Self.Supplier">
        <NavigationPropertyBinding Path="Products" Target="Products" />
    </Singleton>
    <EntitySet Name="Countries" EntityType="ODataDemo.Country" />
    <FunctionImport Name="ProductsByRating" EntitySet="Products"
        Function="ODataDemo.ProductsByRating" />
</EntityContainer>
</Schema>
</edmx:DataServices>
</edmx:Edmx>

```

16.2 Annotations for Products and Categories Example

Example 86:

```

<edmx:Edmx xmlns:edmx="http://docs.oasis-open.org/odata/ns/edmx"
  Version="4.0">
  <edmx:Reference Uri="http://host/service/$metadata">
    <edmx:Include Namespace="ODataDemo" />
  </edmx:Reference>
  <edmx:Reference Uri="http://somewhere/Vocabulary/V1">
    <edmx:Include Alias="Vocabulary1" Namespace="Some.Vocabulary.V1" />
  </edmx:Reference>
  <edmx:DataServices>
    <Schema xmlns="http://docs.oasis-open.org/odata/ns/edm"
      Namespace="Annotations">
      <Annotations Target="ODataDemo.Supplier">
        <Annotation Term="Vocabulary1.Email">
          <Null />
        </Annotation>
        <Annotation Term="Vocabulary1.AccountID" Path="ID" />
        <Annotation Term="Vocabulary1.Title" String="Supplier Info" />
        <Annotation Term="Vocabulary1.DisplayName">
          <Apply Function="odata.concat">
            <Path>Name</Path>
            <String> in </String>
            <Path>Address/CountryName</Path>
          </Apply>
        </Annotation>
      </Annotations>
      <Annotations Target="ODataDemo.Product">
        <Annotation Term="Vocabulary1.Tags">
          <Collection>
            <String>MasterData</String>
          </Collection>
        </Annotation>
      </Annotations>
    </Schema>
  </edmx:DataServices>
</edmx:Edmx>

```

17 Attribute Values

17.1 Namespace

A Namespace is a character sequence of type `edm:TNamespaceName`, see [OData-EDM].

Non-normatively speaking it is a dot-separated sequence of [SimpleIdentifiers](#) with a maximum length of 511 Unicode characters.

17.2 SimpleIdentifier

A SimpleIdentifier is a character sequence of type `edm:TSimpleIdentifier`, see [OData-EDM]:

```
<xs:simpleType name="TSimpleIdentifier">
  <xs:restriction base="xs:NCName">
    <xs:maxLength value="128" />
    <xs:pattern
      value="[\p{L}\p{Nl}_][\p{L}\p{Nl}\p{Nd}\p{Mn}\p{Mc}\p{Pc}\p{Cf}]{0,}"
    />
  </xs:restriction>
</xs:simpleType>
```

Non-normatively speaking it starts with a letter or underscore, followed by at most 127 letters, underscores or digits.

17.3 QualifiedName

For model elements that are direct children of a schema: the namespace or alias of the schema that defines the model element, followed by a dot and the name of the model element, see rule `qualifiedTypeName` in [OData-ABNF].

For built-in [primitive types](#): the name of the type, prefixed with `Edm` followed by a dot.

17.4 TypeName

The [QualifiedName](#) of a built-in primitive or abstract type, a type definition, complex type, enumeration type, or entity type, or a collection of one of these types, see rule `qualifiedTypeName` in [OData-ABNF].

The type must be in scope, i.e. the type MUST be defined in the `Edm` namespace or it MUST be defined in the schema identified by the namespace or alias portion of the qualified name, and the identified schema MUST be defined in the same CSDL document or [included](#) from a directly [referenced](#) document.

17.5 TargetPath

Target paths are used in attributes of CSDL elements to refer to other CSDL elements or their nested child elements.

The allowed path expressions are:

- The [QualifiedName](#) of a schema child
- The [QualifiedName](#) of a schema child followed by a forward slash and name of a child element
- The TargetPath of a complex property of a structured type, followed by a forward slash and the name of a property of the complex property

Example 87: Target expressions

```
Schema.Type
```

```
Schema.EntityType/Property  
Schema.ComplexType/NavigationProperty  
Schema.EntityType/ComplexProperty/NestedComplexProperty/NestedProperty  
Schema.EnumType/Member  
Schema.EntityContainer  
Schema.EntityContainer/EntitySet  
Schema.EntityContainer/Singleton
```

17.6 Boolean

One of the literals `true` and `false`.

18 Conformance

Conforming services **MUST** follow all rules of this specification document for the types, sets, functions, actions, containers and annotations they expose.

Conforming clients **MUST** be prepared to consume a model that uses any or all of the constructs defined in this specification, including custom annotations, and **MUST** ignore any elements or attributes not defined in this version of the specification.

Appendix A. Acknowledgments

The contributions of the OASIS OData Technical Committee members, enumerated in **[OData-Protocol]**, are gratefully acknowledged.

Appendix B. Revision History

Revision	Date	Editor	Changes Made
Working Draft 01	2012-08-22	Michael Pizzo	Translated Contribution to OASIS format/template
Committee Specification Draft 01	2013-04-26	Michael Pizzo, Ralf Handl, Martin Zurmuehl	Simplified annotations, relationships, added containment, singletons Added Type Definitions, Edm.Date, Edm.TimeOfDay, Edm.Duration datatypes. Retired Edm.DateTime, Edm.Time. Enhanced ComplexType support Expanded Service Document Fleshed out descriptions and examples and addressed numerous editorial and technical issues processed through the TC Added Conformance section
Committee Specification Draft 02	2013-07-01	Michael Pizzo, Ralf Handl, Martin Zurmuehl	Restricted services to exactly one entity container Simplified function and action overloads Rounded off annotations Fleshed out containment Simplified rules for implicit enum member values Clarified intention of Partner and NavigationPropertyBinding Simplified and completed CSDL for Metadata Service, added description of behavior
Committee Specification 01	2013-07-30	Michael Pizzo, Ralf Handl, Martin Zurmuehl	Non-Material Changes
Committee Specification Draft 03	2013-10-xx	Michael Pizzo, Ralf Handl, Martin Zurmuehl	Changed function overload resolution rules Improved path expressions for annotations