



# Web Services Resource Properties 1.2 (WS-ResourceProperties)

## Committee Specification, 20 January 2006

### Document identifier:

wsrf-ws\_resource\_properties-1.2-spec-cs-01

### Location:

[http://docs.oasis-open.org/wsrf/wsrf-ws\\_resource\\_properties-1.2-spec-cs-01.pdf](http://docs.oasis-open.org/wsrf/wsrf-ws_resource_properties-1.2-spec-cs-01.pdf)

### Editors:

Steve Graham, IBM <[sgraham@us.ibm.com](mailto:sgraham@us.ibm.com)>

Jem Treadwell, Hewlett-Packard Company <[Jem.Treadwell@hp.com](mailto:Jem.Treadwell@hp.com)>

### Abstract:

The relationship between Web services and stateful resources is defined in [WS-Resource] in terms of a WS-Resource which represents the composition of a stateful resource and a Web service.

One characteristic of a WS-Resource is the set of properties associated with the resource. This document standardizes the means by which the definition of the properties of a WS-Resource may be declared as part of a Web service interface. The declaration of the WS-Resource's properties represents a projection of or a view on the WS-Resource's state. This projection is defined in terms of a resource properties document. This resource properties document serves to define a basis for access to the resource properties through Web service interfaces.

This specification also defines a standard set of message exchanges that allow a requestor to query or update the property values of the WS-Resource. The set of properties defined in the resource properties document associated with the service interface defines the constraints on the valid contents of these message exchanges.

### Status:

This document is published by this TC as a "Committee Specification". Committee members should send comments on this specification to the [wsrf@lists.oasis-open.org](mailto:wsrf@lists.oasis-open.org) list. Others may submit comments to the TC via the web form found on the TC's web page at <http://www.oasis-open.org/committees/wsrf>. Click the button for "Send A Comment" at the top of the page. Submitted comments (for this work as well as other

34 works of that TC) are publicly archived and can be viewed at <http://lists.oasis->  
35 [open.org/archives/wsrf-comment/](http://lists.oasis-open.org/archives/wsrf-comment/).

36 For information on whether any patents have been disclosed that may be essential to  
37 implementing this specification, and any offers of patent licensing terms, please refer to  
38 the Intellectual Property Rights section of the WSRF TC web page (<http://www.oasis->  
39 [open.org/committees/wsrf/](http://www.oasis-open.org/committees/wsrf/)).

## Table of Contents

41	1	Introduction .....	5
42	1.1	Goals and Requirements .....	5
43	1.1.1	Requirements.....	5
44	1.1.2	Non-Goals.....	6
45	1.2	Notational Conventions .....	6
46	1.3	Namespaces .....	7
47	1.4	Fault Definitions.....	7
48	2	Terminology and Concepts.....	8
49	3	Example .....	9
50	4	Declaring Resource Properties.....	11
51	4.1	Resource Properties Document.....	11
52	4.2	Resource Properties Document and Resource Properties.....	11
53	4.3	Declaring the Resource Properties Document Type in WSDL .....	12
54	5	Operations on Resource Properties .....	13
55	5.1	GetResourcePropertyDocument.....	13
56	5.1.1	Example SOAP Encoding of the GetResourcePropertyDocument Message	
57		Exchange .....	13
58	5.2	GetResourceProperty .....	15
59	5.2.1	Example SOAP Encoding of the GetResourceProperty Message Exchange .....	16
60	5.3	GetMultipleResourceProperties .....	17
61	5.3.1	Example SOAP Encoding of the GetMultipleResourceProperties Message	
62		Exchange .....	18
63	5.4	QueryResourceProperties.....	19
64	5.4.1	QueryExpressionDialect Resource Property .....	21
65	5.4.2	Example SOAP Encoding of the QueryResourceProperties Message Exchange ..	21
66	5.5	PutResourcePropertyDocument .....	22
67	5.5.1	Example SOAP Encoding of the PutResponsePropertyDocument Message	
68		Exchange .....	23
69	5.6	SetResourceProperties .....	24
70	5.6.1	Example SOAP Encoding of the SetResourceProperties Message Exchange.....	28
71	5.7	InsertResourceProperties .....	29
72	5.7.1	Example SOAP Encoding of the InsertResourceProperties Message Exchange...	30
73	5.8	UpdateResourceProperties.....	32
74	5.8.1	Example SOAP Encoding of the UpdateResourceProperties Message Exchange	33
75	5.9	DeleteResourceProperties .....	34
76	5.9.1	Example SOAP Encoding of the DeleteResourceProperties Message Exchange .	35

77	6	Subscription .....	37
78	6.1	Individual Resource Property Value Changes .....	37
79	6.2	Value Changes on Any Resource Property .....	39
80	7	ACID Properties of Operations on WS-Resources .....	40
81	8	Security Considerations .....	41
82	8.1	Securing the message exchanges .....	41
83	8.2	Securing Resource Properties .....	41
84	9	References.....	42
85	9.1	Normative .....	42
86	9.2	Non-Normative .....	42
87		Appendix A. Acknowledgments .....	43
88		Appendix B. XML Schema.....	44
89		Appendix C. WSDL 1.1.....	53
90		Appendix D. Revision History .....	62
91		Appendix E. Notices .....	64
92			

# 93 1 Introduction

94 The relationship between Web services and stateful resources is defined in [\[WS-Resource\]](#) in  
95 terms of a WS-Resource which represents the composition of a stateful resource and a Web  
96 service as a WS-Resource.

97 One characteristic of a WS-Resource is the set of properties associated with the resource. This  
98 specification standardizes the means by which the definition of the properties of a WS-Resource  
99 may be declared as part of the Web service interface. The declaration of the WS-Resource's  
100 properties represents a projection of or a *view* on the resource's state. The projection is defined in  
101 terms of a resource properties document. This resource properties document serves to define a  
102 basis for access to the resource properties through the Web service interface.

103 This specification also defines a standard set of message exchanges that allow a requestor to  
104 query or update the resource property values. The set of properties defined in the resource  
105 properties document, and associated with the service interface, defines the constraints on the  
106 valid contents of these message exchanges.

107 In this document, we outline the goals and requirements for resource properties. We define the  
108 means to declare resource properties as part of a Web service description. Following this, we  
109 define the message exchanges for querying and updating resource property values. We also  
110 define a standard means by which requestors can use WS-Notification to receive notification  
111 messages related to changes in resource property values. The document concludes with a  
112 discussion of security considerations associated with resource properties. As an appendix, we  
113 provide normative XML and WSDL descriptions of resource properties.

114 WS-ResourceProperties is inspired by a portion of the Global Grid Forum's "Open Grid  
115 Services Infrastructure (OGSI) Version 1.0" specification [\[OGSI\]](#).

## 116 1.1 Goals and Requirements

117 The goal of WS-ResourceProperties is to standardize the terminology, concepts, operations,  
118 WSDL and XML needed to express the resource properties projection, its association with the  
119 Web service interface, and the messages defining the query and update capability against the  
120 properties of a WS-Resource.

### 121 1.1.1 Requirements

122 In meeting this goal, the specification must address the following specific requirements:

#### 123 **This specification MUST:**

- 124 • Define the term "resource property" and its relationship to Web services and WS-Resources.
- 125 • Define the means by which a designer decorates a Web service description with the names  
126 and types of properties associated with a WS-Resource.
- 127 • Define the means by which a requestor can:
  - 128 • Retrieve the values of one or more properties of a WS-Resource
  - 129 • Update the values of one or more properties of a WS-Resource
  - 130 • Query across the values of one or more properties of a WS-Resource
  - 131 • Subscribe for notification [\[WS-BaseNotification\]](#) when the value of a WS-Resource  
132 property changes.

133 The means by which resource property values are retrieved and updated SHOULD reflect a  
134 document-oriented style and MUST provide the means to perform batched query and update  
135 operations against the WS-Resource in a single message exchange. This will facilitate improved

136 performance over approaches requiring a separate request message exchange for each  
137 individual resource property access.

138 Web services are often described using a collection of message exchange sets (e.g. WSDL 1.1  
139 portTypes). These message exchange sets may be aggregated (using manual cut-and-paste in  
140 WSDL 1.1) to form the “final” composed interface definition for the Web service. The requestor’s  
141 exposure to and interpretation of the Web service interface may be defined by a partial subset of  
142 the constituent message exchange sets in the overall interface composition. Therefore, a  
143 requestor will form resource property-related message requests based on this potentially partial  
144 understanding of the overall composed interface to the Web service. It MUST be possible for a  
145 requestor, having partial knowledge of the composed service interface, to form correct and  
146 consistent resource property access message requests that execute properly on a Web service  
147 that implements an extended message exchange set.

### 148 **1.1.2 Non-Goals**

149 The following topics are outside the scope of this specification:

150 General purpose XML document query and update: This specification is not meant to be used for  
151 querying and updating generic XML documents, or to be used outside the context of modeling  
152 stateful resources with Web services.

## 153 **1.2 Notational Conventions**

154 The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD",  
155 "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be  
156 interpreted as described in [\[RFC2119\]](#).

157 When describing abstract data models, this specification uses the notational convention used by  
158 the [\[XML Infoset\]](#). Specifically, abstract property names always appear in square brackets (e.g.,  
159 [some property]).

160 This specification uses a notational convention, referred to as “Pseudo-schemas” in a fashion  
161 similar to the WSDL 2.0 Part 1 specification [\[WSDL 2.0\]](#). A Pseudo-schema uses a BNF-style  
162 convention to describe attributes and elements:

- 163 • '?' denotes optionality (i.e. zero or one occurrences),
- 164 • '\*' denotes zero or more occurrences,
- 165 • '+' denotes one or more occurrences,
- 166 • '[' and ']' are used to form groups,
- 167 • '|' represents choice.

168 Attributes are conventionally assigned a value which corresponds to their type, as defined in the  
169 normative schema.

```
170 <!-- sample pseudo-schema -->  
171 <element  
172   required_attribute_of_type_QName="xs:QName"  
173   optional_attribute_of_type_string="xs:string"? >  
174   <required_element />  
175   <optional_element />?  
176   <one_or_more_of_these_elements />+  
177   [ <choice_1 /> | <choice_2 /> ]*  
178 </element>
```

179 Where there is disagreement between the separate XML schema and WSDL files describing the  
180 messages defined by this specification and the normative descriptive text (excluding any pseudo-

181 schema) in this document, the normative descriptive text will take precedence over the separate  
182 files. The separate files take precedence over any pseudo-schema and over any schema and  
183 WSDL included in the appendices.

## 184 **1.3 Namespaces**

185 The following namespaces are used in this document:

Prefix	Namespace
s11	<a href="http://schemas.xmlsoap.org/soap/envelope/">http://schemas.xmlsoap.org/soap/envelope/</a>
xsd	<a href="http://www.w3.org/2001/XMLSchema">http://www.w3.org/2001/XMLSchema</a>
wsa	<a href="http://www.w3.org/2005/08/addressing">http://www.w3.org/2005/08/addressing</a>
wsnt	<a href="http://docs.oasis-open.org/wsn/b-2">http://docs.oasis-open.org/wsn/b-2</a>
wsrf-rp	<a href="http://docs.oasis-open.org/wsrp/rp-2">http://docs.oasis-open.org/wsrp/rp-2</a>
wsrf-rpw	<a href="http://docs.oasis-open.org/wsrp/rpw-2">http://docs.oasis-open.org/wsrp/rpw-2</a>
wsrf-bf	<a href="http://docs.oasis-open.org/wsrp/bf-2">http://docs.oasis-open.org/wsrp/bf-2</a>
wsrf-rw	<a href="http://docs.oasis-open.org/wsrp/rw-2">http://docs.oasis-open.org/wsrp/rw-2</a>

## 186 **1.4 Fault Definitions**

187 All faults generated by a WS-Resource SHOULD be compliant with the WS-BaseFaults [[WS-](#)  
188 [BaseFaults](#)] specification.

189 All faults defined by this specification MUST use the following wsa:Action URI [[WS-Addressing](#)]:

190 <http://docs.oasis-open.org/wsrp/fault>.

## 191 **2 Terminology and Concepts**

192 The following definitions outline the terminology and usage in this specification. This section gives  
193 only brief description of these terms.

194 Resource Property:

- 195 • A resource property is a piece of information defined as part of the state model of a WS-  
196 Resource.
- 197 • A resource property may reflect a part of the resource's state, meta-data, manageability  
198 information, etc.

199 Resource Properties Document:

- 200 • The XML document representing a logical composition of resource property elements.  
201 The resource properties document defines a particular view or projection of the state data  
202 implemented by the WS-Resource.
- 203 • The type (e.g. the XML Schema definition of the root element) of a resource properties  
204 document is associated with the WSDL portType defining the Web service interface. This  
205 association is the basis of the WS-Resource definition. Each instance of a particular WS-  
206 Resource type MUST implement a logical resource properties document of the type  
207 declared in the WSDL portType.

208 Resource Property Element:

- 209 • The XML representation of a resource property.
- 210 • A resource property element must appear as the immediate child of the root element of a  
211 resource properties document.
- 212 • A resource property element must be an XML global element definition (GED), and is  
213 uniquely identified by QName.

214 Resource Property Value:

- 215 • The value(s) associated with a resource property.



216

### 3 Example

217 The simple example below defines the GenericDiskDrive portType and the resource properties  
218 document associated with GenericDiskDrive. The association of the resource properties  
219 document with the portType defines the type of the WS-Resource.

```
220 <wsdl:definitions ... xmlns:tns="http://example.com/diskDrive" ...>
221 ...
222 <wsdl:types>
223   <xsd:schema targetNamespace="http://example.com/diskDrive" ... >
224
225     <!-- Resource property element declarations -->
226     <xsd:element name="NumberOfBlocks" type="xsd:integer"/>
227     <xsd:element name="BlockSize" type="xsd:integer" />
228     <xsd:element name="Manufacturer" type="xsd:string" />
229     <xsd:element name="StorageCapability" type="xsd:string" />
230
231     <!-- Resource properties document declaration -->
232     <xsd:element name="GenericDiskDriveProperties">
233       <xsd:complexType>
234         <xsd:sequence>
235           <xsd:element ref="tns:NumberOfBlocks"/>
236           <xsd:element ref="tns:BlockSize" />
237           <xsd:element ref="tns:Manufacturer" />
238           <xsd:any minOccurs="0" maxOccurs="unbounded" />
239           <xsd:element ref="tns:StorageCapability"
240             minOccurs="0" maxOccurs="unbounded" />
241         </xsd:sequence>
242       </xsd:complexType>
243     </xsd:element>
244   ...
245 </xsd:schema>
246 </wsdl:types>
247 ...
248 <!-- Association of resource properties document to a portType -->
249 <wsdl:portType name="GenericDiskDrive"
250   wsrf-rp:ResourceProperties="tns:GenericDiskDriveProperties" >
251
252   <operation name="start" .../>
253   <operation name="stop" .../>
254 ...
255 </wsdl:portType>
256 ...
257 </wsdl:definitions>
```

258 The following represents the request message used to retrieve three resource property elements  
259 from the WS-Resource that implements the GenericDiskDrive portType:

```
260 ...
261 <wsrf-rp:GetMultipleResourceProperties
```

```
262 xmlns:tns="http://example.com/diskdrive" ...>
263 <wsrf-rp:ResourceProperty>
264     tns:NumberOfBlocks
265 </wsrf-rp:ResourceProperty>
266 <wsrf-rp:ResourceProperty>
267     tns:BlockSize
268 </wsrf-rp:ResourceProperty>
269 <wsrf-rp:ResourceProperty>
270     tns:StorageCapability
271 </wsrf-rp:ResourceProperty>
272 </wsrf-rp:GetMultipleResourceProperties>
273 ...
```

274 The following is a sample response to the simple get request:

```
275 ...
276 <wsrf-rp:GetMultipleResourcePropertiesResponse
277     xmlns:ns1="http://example.com/diskdrive"
278     xmlns:ns2="http://example.com/capabilities" ...>
279     <ns1:NumberOfBlocks>22</ns1:NumberOfBlocks>
280     <ns1:BlockSize>1024</ns1:BlockSize>
281     <ns1:StorageCapability>
282         <ns2:NoSinglePointOfFailure>true</ns2:NoSinglePointOfFailure>
283     </ns1:StorageCapability>
284     <ns1:StorageCapability>
285         <ns2:DataRedundancyMax>42</ns2:DataRedundancyMax>
286     </ns1:StorageCapability>
287
288 </wsrf-rp:GetMultipleResourcePropertiesResponse>
289 ...
```

## 290 **4 Declaring Resource Properties**

### 291 **4.1 Resource Properties Document**

292 The resource properties document type associated with a Web service's WSDL 1.1 portType  
293 definition provides the declaration of the exposed resource properties of the WS-Resource. It  
294 represents a particular composed structural view or projection of the resource properties of the  
295 WS-Resource, essentially exposing the stateful resource component within the WS-Resource  
296 composition. This may be used by a service requestor to form an XML-based query or update  
297 expression on the WS-Resource.

298 This specification does not dictate the means by which a service implements a resource  
299 properties document. A given service implementation may choose to realize its implementation of  
300 the resource properties document as an actual XML instance document, stored in memory, in the  
301 file system, in a database or in some XML Repository. Other service implementations may  
302 *dynamically* construct the resource property elements and their values, from data held in  
303 programming language objects (such as a J2EE EJB Entity Bean) or by executing a command on  
304 a private communications channel to a physical resource. Yet another implementation possibility  
305 is a mapping layer to a standard management interface (such as CIM or SNMP).

306 There is an explicit relationship between the resource properties document and the message  
307 exchanges defined in Section 5. Any Web service that implements an interface that includes a  
308 resource properties document type declaration is a WS-Resource and MUST comply with the  
309 definition of a WS-Resource in [WS-Resource]. A WS-Resource MUST accept message requests  
310 declared by the GetResourceProperty message exchange defined in Section 5. Similarly, such a  
311 Web service MAY accept message requests declared by the other message exchanges defined  
312 in Section 5.

313 However, there is no relationship, intended or implied by this specification, between the resource  
314 properties defined in the resource properties document and any other message exchanges that  
315 may be introduced as part of the Web service interface. Any relationships between the resource  
316 properties and messages that comprise an interface are entirely under the purview of the  
317 designer of that interface. For example, using the resource properties document described in  
318 Section 3, it would be legal for an interface designer to introduce a "ReformatSectorBlock"  
319 message exchange. However, with respect to this specification, there is no relationship either  
320 required or prohibited between such an operation and the properties declared in the resource  
321 properties document.

### 322 **4.2 Resource Properties Document and Resource Properties**

323 A *resource properties document* MUST be defined in XML Schema as a global element  
324 declaration (GED) in some XML namespace. This GED refers to the definition of the root element  
325 of a resource properties document.

326 A resource properties document MAY contain *resource property elements*, also referred to as  
327 simply *resource properties*. Resource properties appear as child elements of the root element of  
328 a resource properties document. If a resource properties document contains resource properties,  
329 its definition MUST be a complexType defining a collection of zero or more child elements, each  
330 of these child elements defining a resource property element. Each resource property element  
331 MUST be defined in XML Schema as a GED. The complexType defining the resource properties  
332 document MAY allow open element content (xsd:any). Resource properties are the atomic unit  
333 upon which many of the message exchanges defined in this document operate.

### 334 **4.3 Declaring the Resource Properties Document Type in WSDL**

335 The resource properties document definition is associated with a Web service WSDL 1.1  
336 portType in the following manner:

```
337 <wsdl:definitions ...>  
338 <wsdl:portType ...  
339   wsrf-rp:ResourceProperties="xsd:QName"? ... >  
340 ...  
341 </wsdl:portType>
```

342 This definition is further constrained as follows:

343 /wsdl:portType/@wsrf-rp:ResourceProperties

344 If this attribute appears on a WSDL 1.1 portType element (using attribute extensibility  
345 available in the WSDL 1.1 XML schema definition for the portType element) its value  
346 MUST be a QName referring to a resource properties document as defined in Section  
347 4.2.

348 Any service that implements a portType annotated with @wsrf-rp:ResourceProperties MUST be a  
349 component of a WS-Resource and MUST provide the interface to resource properties via a  
350 document whose root element is defined by the XML global element declaration associated with  
351 the portType.

## 5 Operations on Resource Properties

352

353 This section defines a collection of message exchanges that standardize the means by which a  
354 requestor can retrieve values of resource properties, update values of resource properties, and  
355 issue queries against resource properties.

356 Any interface that includes a resource properties document type declaration  
357 (/wsdl:portType/@ResourceProperties) MUST also include the GetResourceProperty message  
358 exchange (operation) defined in this section. Any Web service that implements an interface that  
359 includes a resource properties document type declaration MAY also support the other message  
360 exchanges defined in this section.

### 5.1 GetResourcePropertyDocument

361 A WS-Resource MAY support the message exchange defined in this section that allows a  
362 requestor to retrieve the values of all resource properties associated with the WS-Resource.

363 The format of this request message MUST be:

```
364 <wsrf-rp:GetResourcePropertyDocument />
```

365 The wsa:Action MUST contain the URI

```
366 http://docs.oasis-open.org/wsrf/rpw-  
367 2/GetResourcePropertyDocument/GetResourcePropertyDocumentRequest.
```

368 The response of the GetResourcePropertyDocument request message is a message of the  
369 following form:

```
370 <wsrf-rp:GetResourcePropertyDocumentResponse>  
371 {any}  
372 </wsrf-rp:GetResourcePropertyDocumentResponse>
```

373 The wsa:Action MUST contain the URI

```
374 http://docs.oasis-open.org/wsrf/rpw-  
375 2/GetResourcePropertyDocument/GetResourcePropertyDocumentResponse.
```

376 The contents of the GetResourcePropertyDocumentResponse message are further described as  
377 follows:

```
378 /wsrf-rp:GetResourcePropertyDocumentResponse/{any}
```

379 An XML element that MUST correspond to the resource properties document of the WS-  
380 Resource.

381 If the WS-Resource does not respond to the GetResourcePropertyDocument request message  
382 with the GetResourcePropertyDocumentResponse message, then it MUST send a fault. This  
383 specification does not define any additional faults for this operation other than those defined for  
384 all WS-Resources in [WS-Resource]. One of these faults, or a specialization thereof, SHOULD be  
385 sent upon failure although other fault messages MAY be returned instead.

#### 5.1.1 Example SOAP Encoding of the GetResourcePropertyDocument Message Exchange

386 Consider the following resource properties document defining resource properties for a WS-  
387 Resource defined by the GenericDiskDrive portType:

```
388 <tns:GenericDiskDriveProperties
```

```

392     xmlns:tns="http://example.com/diskDrive"
393     xmlns:cap="http://example.com/capabilities">
394     <tns:NumberOfBlocks>22</tns:NumberOfBlocks>
395     <tns:BlockSize>1024</tns:BlockSize>
396     <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
397     <tns:StorageCapability>
398       <cap:NoSinglePointOfFailure>true</cap:NoSinglePointOfFailure>
399     </tns:StorageCapability>
400     <tns:StorageCapability>
401       <cap:DataRedundancyMax>42</cap:DataRedundancyMax>
402     </tns:StorageCapability>
403   </tns:GenericDiskDriveProperties>

```

404 The following is a non-normative example of a GetResourcePropertyDocument request message  
405 using SOAP 1.1:

```

406 <s11:Envelope ...>
407   <s11:Header>
408     <wsa:Action>
409     http://docs.oasis-open.org/wsrf/rpw-
410     2/GetResourcePropertyDocument/GetResourcePropertyDocumentRequest
411     </wsa:Action>
412   ...
413   </s11:Header>
414   <s11:Body>
415     <wsrf-rp:GetResourcePropertyDocument/>
416   </s11:Body>
417 </s11:Envelope>

```

418 The following is an example GetResourcePropertyDocumentResponse message using SOAP  
419 1.1:

```

420 <s11:Envelope ...>
421   <s11:Header>
422     <wsa:Action>
423     http://docs.oasis-open.org/wsrf/rpw-
424     2/GetResourcePropertyDocument/GetResourcePropertyDocumentResponse
425     </wsa:Action>
426   ...
427   </s11:Header>
428   <s11:Body>
429     <wsrf-rp:GetResourcePropertyDocumentResponse
430       xmlns:tns="http://example.com/diskDrive"
431       xmlns:cap="http://example.com/capabilities">
432       <tns:GenericDiskDriveProperties>
433         <tns:NumberOfBlocks>22</tns:NumberOfBlocks>
434         <tns:BlockSize>1024</tns:BlockSize>
435         <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
436         <tns:StorageCapability>
437           <cap:NoSinglePointOfFailure>true</cap:NoSinglePointOfFailure>
438         </tns:StorageCapability>

```

```

439 <tns:StorageCapability>
440 <cap:DataRedundancyMax>42</cap:DataRedundancyMax>
441 </tns:StorageCapability>
442 </tns:GenericDiskDriveProperties>
443 </wsrf-rp:GetResourcePropertyDocumentResponse>
444 </s11:Body>
445 </s11:Envelope>

```

## 446 5.2 GetResourceProperty

447 A WS-Resource whose portType includes the resource properties document type declaration  
448 (/wsdl:portType/@ResourceProperties) MUST support the message exchange defined in this  
449 section that allows a requestor to retrieve the value of a single resource property of a WS-  
450 Resource.

451 The format of this request message MUST be:

```

452 <wsrf-rp:GetResourceProperty>
453   QName
454 </wsrf-rp:GetResourceProperty>
455
456

```

457 The wsa:Action MUST contain the URI

```

458   http://docs.oasis-open.org/wsrf/rpw-
459   2/GetResourceProperty/GetResourcePropertyRequest.

```

460 The components of the GetResourceProperty request message are further described as follows:

461 /wsrf-rp:GetResourceProperty/QName

462 This MUST correspond to the QName of a resource property element (child of the root of  
463 the WS-Resource's resource properties document).

464 The response of the GetResourceProperty request message is a message of the following form:

```

465 <wsrf-rp:GetResourcePropertyResponse>
466   {any}*
467 </wsrf-rp:GetResourcePropertyResponse>
468
469

```

470 The wsa:Action MUST contain the URI

```

471   http://docs.oasis-open.org/wsrf/rpw-
472   2/GetResourceProperty/GetResourcePropertyResponse.

```

473 The contents of the GetResourceProperty response message are further described as follows:

474 /wsrf-rp:GetResourcePropertyResponse/{any}

475 The resource property value, as XML element(s), that corresponds to the QName in the  
476 GetResourceProperty request. Note: in the case where the resource property element is  
477 defined with minOccurs="0" and the resource properties document does not contain any  
478 value for that resource property, the response MUST be an empty wsrf-  
479 rp:GetResourcePropertyResponse element. If an implementation cannot return all of the  
480 resource property values associated with the request, due to, for example, security  
481 considerations, then it MUST fault.

482 If the WS-Resource does not respond to the GetResourceProperty request message with the  
483 GetResourcePropertyResponse message, then it MUST send a fault. This specification defines  
484 the following faults associated with failure to process the GetResourceProperty request message,  
485 in addition to those faults defined for all WS-Resources in [WS-Resource]:

486 InvalidResourcePropertyQNameFault

- 487 • The QName in the request message did not correspond to a resource property element  
488 of the WS-Resource referred to in the request message.

489 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
490 fault messages MAY be returned instead.

## 491 **5.2.1 Example SOAP Encoding of the GetResourceProperty Message** 492 **Exchange**

493 Consider the resource properties document defining resource properties for a WS-Resource as  
494 shown in section 5.1.1. The following is a non-normative example of a GetResourceProperty  
495 request message using SOAP 1.1:

```
496 <s11:Envelope ...>  
497   <s11:Header>  
498     <wsa:Action>  
499     http://docs.oasis-open.org/wsrf/rpw-2/GetResourceProperty/GetResourcePropertyRequest  
500     </wsa:Action>  
501     ...  
502   </s11:Header>  
503   <s11:Body>  
504     <wsrf-rp:GetResourceProperty  
505       xmlns:tns="http://example.com/diskDrive">  
506       tns:NumberOfBlocks  
507     </wsrf-rp: GetResourceProperty>  
508   </s11:Body>  
509 </s11:Envelope>
```

510 The following is an example GetResourcePropertyResponse message using SOAP 1.1:

```
511 <s11:Envelope ...>  
512   <s11:Header>  
513     <wsa:Action>  
514     http://docs.oasis-open.org/wsrf/rpw-2/GetResourceProperty/GetResourcePropertyResponse  
515     </wsa:Action>  
516     ...  
517   </s11:Header>  
518   <s11:Body>  
519     <wsrf-rp:GetResourcePropertyResponse  
520       xmlns:ns1="http://example.com/diskDrive">  
521     <ns1:NumberOfBlocks>22</ns1:NumberOfBlocks>  
522     </wsrf-rp:GetResourcePropertyResponse>  
523   </s11:Body>  
524 </s11:Envelope>
```



### 525 5.3 GetMultipleResourceProperties

526 A WS-Resource MAY support the message exchange defined in this section that allows a  
527 requestor to retrieve the values of multiple resource properties of a WS-Resource.

528 The format of this request message MUST be:

```
529 <wsrf-rp:GetMultipleResourceProperties>  
530 <wsrf-rp:ResourceProperty> QName <wsrf-rp:ResourceProperty>+  
531 </wsrf-rp:GetMultipleResourceProperties>
```

532 The wsa:Action MUST contain the URI

```
533 http://docs.oasis-open.org/wsrf/rpw-  
534 2/GetMultipleResourceProperties/GetMultipleResourcePropertiesRequest.
```

535 The components of the GetMultipleResourceProperties request message are further described as  
536 follows:

537 /wsrf-rp:GetMultipleResourceProperties/wsrf-rp:ResourceProperty+

538 This component MAY appear one or more times. Each ResourceProperty element  
539 contains an xsd:QName which MUST correspond to the QName of a resource property  
540 element child of the root of the WS-Resource's resource properties document.

541 The response of the GetMultipleResourceProperties request message is a message of the  
542 following form:

```
543 <wsrf-rp:GetMultipleResourcePropertiesResponse>  
544 {any}*  
545 </wsrf-rp:GetMultipleResourcePropertiesResponse>
```

546 The wsa:Action MUST contain the URI

```
547 http://docs.oasis-open.org/wsrf/rpw-  
548 2/GetMultipleResourceProperties/GetMultipleResourcePropertiesResponse.
```

549 The contents of the GetMultipleResourcePropertiesResponse message are further described as  
550 follows:

551 /wsrf-rp:GetMultipleResourcePropertiesResponse/{any}

552 A collection of resource property values, as XML elements that correspond to the  
553 QNames given in the GetMultipleResourceProperties request message. This collection is  
554 formed in the following fashion. For each QName in the request message, the resource  
555 must add to the collection all child elements of the root of the resource properties  
556 document whose name corresponds to that QName. Note: in the case where the  
557 resource property element is defined with minOccurs="0" and the resource properties  
558 document does not contain any value for that resource property, no child element is  
559 added to the collection for that QName. If an implementation cannot return all of the  
560 resource property values associated with the request, due to, for example, security  
561 considerations, then it MUST fault.

562 If the XML schema definition of the resource properties document root element does not  
563 permit the root element to contain a child element with that QName the processing of the  
564 GetMultipleResourceProperties request message MUST terminate with an  
565 InvalidResourcePropertyQName fault message.

566 The collection of resource property values SHOULD be formed in the same order as the  
567 resource property element QNames were specified in the GetMultipleResourceProperties  
568 request message.

569 If the WS-Resource does not respond to the GetMultipleResourceProperties request message  
570 with the GetMultipleResourcePropertiesResponse message, then it MUST send a fault. This  
571 specification defines the following faults associated with failure to process the  
572 GetMultipleResourceProperties request message, in addition to those faults defined for all WS-  
573 Resources in [WS-Resource]:

574 InvalidResourcePropertyQNameFault

- 575 • One or more of the QNames in the request message did not correspond to a resource  
576 property element of the WS-Resource referred to in the request message.

577 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
578 fault messages MAY be returned instead.

579 Note: the functionality provided by the GetResourceProperty message exchange is a strict subset  
580 of that provided by GetMultipleResourceProperties. WS-ResourceProperties defines two  
581 message exchange sets to provide implementation flexibility. GetResourceProperty is a simple,  
582 required message exchange that allows simple Web service implementations to be compliant  
583 with WS-ResourceProperties. The optional GetMultipleResourceProperties, while more  
584 sophisticated, allows efficient retrieval of multiple resource property values using a single  
585 message exchange.

586 An example use of the GetMultipleResourceProperties operation is shown in Section 3. Note: it is  
587 the responsibility of the requestor to correlate the elements of the response message that  
588 correspond to the QNames contained in the request message.

### 589 **5.3.1 Example SOAP Encoding of the GetMultipleResourceProperties** 590 **Message Exchange**

591 Consider the resource properties document defining resource properties for a WS-Resource as  
592 shown in section 5.1.1. The following is a non-normative example of a  
593 GetMultipleResourceProperties request message using SOAP 1.1:

```
594 <s11:Envelope ...>  
595   <s11:Header>  
596     <wsa:Action>  
597       http://docs.oasis-open.org/wsrf/rpw-  
598       2/GetMultipleResourceProperties/GetMultipleResourcePropertiesRequest  
599     </wsa:Action>  
600     ...  
601   </s11:Header>  
602   <s11:Body>  
603     <wsrf-rp:GetMultipleResourceProperties  
604       xmlns:tns="http://example.com/diskdrive">  
605       <wsrf-rp:ResourceProperty>  
606         tns:NumberOfBlocks  
607       </wsrf-rp:ResourceProperty>  
608       <wsrf-rp:ResourceProperty>  
609         tns:BlockSize  
610       </wsrf-rp:ResourceProperty>  
611     </wsrf-rp:GetMultipleResourceProperties>  
612   </s11:Body>  
613 </s11:Envelope>
```

614 The following is an example GetMultipleResourcePropertiesResponse message using SOAP 1.1:

```

615 <s11:Envelope ...>
616   <s11:Header>
617     <wsa:Action>
618     http://docs.oasis-open.org/wsrf/rpw-
619     2/GetMultipleResourceProperties/GetMultipleResourcePropertiesResponse
620     </wsa:Action>
621     ...
622   </s11:Header>
623   <s11:Body>
624     <wsrf-rp:GetMultipleResourcePropertiesResponse
625       xmlns:ns1="http://example.com/diskdrive" ...>
626       <ns1:NumberOfBlocks>22</ns1:NumberOfBlocks>
627       <ns1:BlockSize>1024</ns1:BlockSize>
628     </wsrf-rp:GetMultipleResourcePropertiesResponse>
629   </s11:Body>
630 </s11:Envelope>

```

## 5.4 QueryResourceProperties

A WS-Resource MAY support the message exchange defined in this section that allows a requestor to query the resource properties document of a WS-Resource using a query expression such as XPath [XPATH].

The format of this request message MUST be:

```

636 <wsrf-rp:QueryResourceProperties>
637   <wsrf-rp:QueryExpression Dialect="xsd:anyURI">
638     xsd:any
639   </wsrf-rp:QueryExpression>
640 </wsrf-rp:QueryResourceProperties>

```

The wsa:Action MUST contain the URI

```

642 http://docs.oasis-open.org/wsrf/rpw-
643 2/QueryResourceProperties/QueryResourcePropertiesRequest.

```

The components of the QueryResourceProperties request message are further described as follows:

/wsrf-rp:QueryResourceProperties/wsrf-rp:QueryExpression

The context of the expression is to be evaluated against the resource properties document of the WS-Resource identified by the request. The results of evaluating the QueryExpression are returned in the response to this request message.

/wsrf-rp:QueryResourceProperties/wsrf-rp:QueryExpression/@Dialect

This attribute contains a URI specifying the type of expression contained by the element. If the implementation does not recognize the URI identified by @Dialect, it MUST fault. There is one well-known dialect identified by this specification, corresponding to the current stable version of the XPath [XPATH] language.

```

655 http://www.w3.org/TR/1999/REC-xpath-19991116

```

This URI identifies the XPath 1.0 language. The contents of the QueryExpression MUST be a string containing a valid XPath 1.0 expression. The namespace URI prefixes for the in-scope namespace

659 declarations of the QueryExpression element may be used in the XPath  
660 expression. The actual namespace declaration may be on any of the  
661 ancestors of the QueryResourceProperties element.

662 Note: It is RECOMMENDED that users avoid the use of previously-  
663 defined namespace prefixes when there is a chance the message could  
664 traverse intermediaries or when encryption is applied to the message, as  
665 there is a chance that an intermediary will modify the namespace  
666 prefixes. In such cases the expression will become incoherent with  
667 respect to the namespace-prefix to namespace-URI mapping intended  
668 by the requestor.

669 A WS-Resource that supports the QueryResourceProperties message exchange MUST  
670 support QueryExpressions that contain a Dialect with value  
671 "<http://www.w3.org/TR/1999/REC-xpath-19991116>". Such a WS-Resource MAY also  
672 support other dialects.

673 /wsrf-rp:QueryResourceProperties/QueryExpression/{any}

674 The QueryExpression MUST contain an expression in an expression language specified  
675 by the dialect attribute. Note: this element may contain mixed content.

676 The response of the QueryResourceProperties request message MUST be a message of the  
677 following form:

```
678 <wsrf-rp:QueryResourcePropertiesResponse>  
679 {any}  
680 </wsrf-rp:QueryResourcePropertiesResponse>
```

681 The wsa:Action MUST contain the URI

682 [http://docs.oasis-open.org/wsrf/rpw-  
683 2/QueryResourceProperties/QueryResourcePropertiesResponse](http://docs.oasis-open.org/wsrf/rpw-2/QueryResourceProperties/QueryResourcePropertiesResponse).

684 The contents of the QueryResourcePropertiesResponse message are further described as  
685 follows:

686 /wsrf-rp:QueryResourcePropertiesResponse/{any}

687 The response of the QueryResourceProperties request is variable, depending on the  
688 nature of the QueryExpression component of the QueryResourceProperties request. The  
689 response MUST contain an XML serialization of the results of evaluating the  
690 QueryExpression against the resource properties document. Note: this element has  
691 mixedContent, to allow for the case where the QueryExpression evaluates to a simple  
692 type (such as a Boolean, a string or an integer) as well as the case where a node-set of  
693 elements is returned.

694 If the WS-Resource does not respond to the QueryResourceProperties request message with the  
695 QueryResourcePropertiesResponse message, then it MUST send a fault. This specification  
696 defines the following faults associated with failure to process the QueryResourceProperties  
697 request message, in addition to those faults defined for all WS-Resources in [WS-Resource]:

698 UnknownQueryExpressionDialectFault

- 699 • The given QueryExpression has a dialect that is unknown to the Web service.

700 InvalidQueryExpressionFault

- 701 • The given QueryExpression is not valid within the QueryExpression language identified  
702 by the dialect attribute.

703 QueryEvaluationErrorFault

- 704 • The QueryExpression failed during evaluation.

705 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
706 fault messages MAY be returned instead.

### 707 5.4.1 QueryExpressionDialect Resource Property

708 If a WS-Resource supports the QueryResourceProperty operation and supports dialects in  
709 addition to the required XPath 1.0 dialect, then it MUST include a wsrf-rp:QueryExpressionDialect  
710 resource property within its resource property document definition. Such a WS-Resource MAY  
711 include this resource property if it supports only the XPath 1.0 dialect. The form of the wsrf-  
712 rp:QueryExpressionDialect resource property is:

```
713 <wsrf-rp:QueryExpressionDialect>  
714   xsd:anyURI  
715 </wsrf-rp:QueryExpressionDialect>
```

716 Furthermore, this reference MUST reflect the minOccurs and maxOccurs properties as follows:

```
717 <xsd:element ref="wsrf-rp:QueryExpressionDialect"  
718   minOccurs="0" maxOccurs="unbounded" />
```

719 This resource property element is further constrained as follows:

720 /wsrf-rp:QueryExpressionDialect

721 This resource property declares one or more QueryExpression dialects that are  
722 supported by the Web service.

723 /wsrf-rp:QueryExpressionDialect/{anyURI}

724 If a requestor sends a QueryResourceProperties request message using a  
725 QueryExpression with Dialect matching the URI contained in this resource property  
726 element, the WS-Resource MUST NOT issue an *UnknownQueryExpressionDialect* fault.  
727 The value of this element is a URI that MUST correspond to a QueryExpression dialect.

### 728 5.4.2 Example SOAP Encoding of the QueryResourceProperties 729 Message Exchange

730 Consider the resource properties document defining resource properties for a WS-Resource as  
731 shown in Section 5.1.1. The following is a non-normative example of a QueryResourceProperties  
732 request message using SOAP 1.1:

```
733 <s11:Envelope ...>  
734   <s11:Header>  
735     <wsa:Action>  
736       http://docs.oasis-open.org/wsrf/rpw-  
737       2/QueryResourceProperties/QueryResourcePropertiesRequest  
738     </wsa:Action>  
739     ...  
740   </s11:Header>  
741   <s11:Body>  
742     <wsrf-rp:QueryResourceProperties>  
743       <wsrf-rp:QueryExpression  
744         Dialect="http://www.w3.org/TR/1999/REC-xpath-19991116" >
```

```
745     boolean(/*/NumberOfBlocks > 20 and */BlockSize=1024)
746     </wsrf-rp:QueryExpression>
747     </wsrf-rp:QueryResourceProperties>
748     </s11:Body>
749 </s11:Envelope>
```

750 The following is an example QueryResourcePropertiesResponse message using SOAP 1.1,  
751 containing the results of evaluating that XPath [XPATH] expression against the root element of  
752 the resource's resource properties document:

```
753 <s11:Envelope ...>
754   <s11:Header>
755     <wsa:Action>
756       http://docs.oasis-open.org/wsrf/rpw-
757       2/QueryResourceProperties/QueryResourcePropertiesResponse
758     </wsa:Action>
759   </s11:Header>
760   <s11:Body>
761     <wsrf-rp:QueryResourcePropertiesResponse>
762       true
763     </wsrf-rp:QueryResourcePropertiesResponse>
764   </s11:Body>
765 </s11:Envelope>
```

## 766 5.5 PutResourcePropertyDocument

767 A WS-Resource MAY support the message exchange defined in this section that allows a  
768 requestor to completely replace the values of a WS-Resource's properties with an entirely new  
769 resource property document. This message exchange is symmetric to the  
770 GetResourcePropertyDocument message exchange defined in Section 5.1.

771 The format of the PutResourcePropertyDocument request message MUST be:

```
772 <wsrf-rp:PutResourcePropertyDocument>
773   {any}
774 </wsrf-rp:PutResourcePropertyDocument>
```

775 The wsa:Action MUST contain the URI

```
776     http://docs.oasis-open.org/wsrf/rpw-
777     2/PutResourcePropertyDocument/PutResourcePropertyDocumentRequest.
```

778 The contents of the PutResourcePropertyDocument request message are further described as  
779 follows:

```
780 /wsrf-rp:PutResourcePropertyDocument/{any}
```

781 An XML element that MUST correspond to the element declared in the value of the  
782 ResourceProperties attribute of the portType defining the PutResourcePropertyDocument  
783 operation. This is the value the requestor intends to be the new resource property  
784 document for the WS-Resource.

785 The response of the PutResourcePropertyDocument request message is a message of the  
786 following form:

```
787 <wsrf-rp:PutResourcePropertyDocumentResponse>
```

```
788 {any} ?
789 </wsrf-rp:PutResourcePropertyDocumentResponse>
```

790 The wsa:Action MUST contain the URI

```
791 http://docs.oasis-open.org/wsrf/rpw-
792 2/PutResourcePropertyDocument/PutResourcePropertyDocumentResponse.
```

793 The contents of the PutResourcePropertyDocumentResponse message are further described as  
794 follows:

```
795 /wsrf-rp:PutResourcePropertyDocumentResponse/{any}
```

796 If, after processing the PutResourcePropertyDocument request, the XML Infoset of the  
797 WS-Resource's resource properties document is identical to the XML Infoset of the  
798 contents of the PutResourcePropertyDocument request itself, then the contents of the  
799 PutResourcePropertyDocumentResponse MUST be empty.

800 If, after processing the PutResourcePropertyDocument request, the XML Infoset of the  
801 WS-Resource's resource properties document is **not** identical to the XML Infoset of the  
802 contents of the PutResourcePropertyDocument request itself, then the contents of the  
803 PutResourcePropertyDocumentResponse MUST contain the updated resource property  
804 document. If an implementation cannot return all of the resource property values  
805 associated with the request, due to, for example, security considerations, then it MUST  
806 fault.

807 If the WS-Resource does not respond to the PutResourcePropertyDocument request message  
808 with the PutResourcePropertyDocumentResponse message, then it MUST send a fault. If the  
809 request results in a fault for any reason, such as read-only property changed or some other  
810 update fault, none of the resource properties are modified. This specification defines the following  
811 faults associated with failure to process the PutResourcePropertyDocument request message, in  
812 addition to those faults defined for all WS-Resources in [WS-Resource]:

813 UnableToPutResourcePropertyDocumentFault

- 814 • The WS-Resource was unable to complete the processing of the  
815 PutResourcePropertyDocument for some reason.

816 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
817 fault messages MAY be returned instead.

## 818 5.5.1 Example SOAP Encoding of the 819 PutResponsePropertyDocument Message Exchange

820 Consider the resource properties document defining resource properties for a WS-Resource as  
821 shown in Section 5.1.1. The following is a non-normative example of a  
822 PutResourcePropertyDocument request message using SOAP 1.1:

```
823 <s11:Envelope ...>
824   <s11:Header>
825     <wsa:Action>
826       http://docs.oasis-open.org/wsrf/rpw-
827       2/PutResourcePropertyDocument/PutResourcePropertyDocumentRequest
828     </wsa:Action>
829     ...
830   </s11:Header>
831   <s11:Body>
```

```

832 <wsrf-rp:PutResourcePropertyDocument>
833   <tns:GenericDiskDriveProperties
834     xmlns:tns="http://example.com/diskDrive"
835     xmlns:cap="http://example.com/capabilities">
836     <tns:NumberOfBlocks>22</tns:NumberOfBlocks>
837     <tns:BlockSize>1024</tns:BlockSize>
838     <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
839     <tns:StorageCapability>
840       <cap:NoSinglePointOfFailure>true</cap:NoSinglePointOfFailure>
841     </tns:StorageCapability>
842     <tns:StorageCapability>
843       <cap:DataRedundancyMax>42</cap:DataRedundancyMax>
844     </tns:StorageCapability>
845   </tns:GenericDiskDriveProperties>
846 </wsrf-rp:PutResourcePropertyDocument>
847 </s11:Body>
848 </s11:Envelope>

```

849 The following is an example PutResourcePropertyDocumentResponse message using SOAP  
850 1.1:

```

851 <s11:Envelope ...>
852   <s11:Header>
853     <wsa:Action>
854     http://docs.oasis-open.org/wsrf/rpw-
855     2/PutResourcePropertyDocument/PutResourcePropertyDocumentResponse
856     </wsa:Action>
857     ...
858   </s11:Header>
859   <s11:Body>
860     <wsrf-rp:PutResourcePropertyDocumentResponse />
861   </s11:Body>
862 </s11:Envelope>

```

## 863 5.6 SetResourceProperties

864 A WS-Resource MAY support the message exchange defined in this section that allows a  
865 requestor to modify the values of multiple resource properties of a WS-Resource.

866 The SetResourceProperties message allows the processing of a single request message to make  
867 multiple changes to the resource properties document. There are three types of changes, each  
868 modeled as separate types of component (called SetRequestComponent) of a  
869 SetResourceProperties request message:

- 870 • Insert: wherein a new resource property element is inserted into the resource properties  
871 document;
- 872 • Update: wherein existing resource property element(s) are modified; and
- 873 • Delete: wherein existing resource property element(s) are removed.

874 The format of this request message MUST be:

```

875 <wsrf-rp:SetResourceProperties>
876 [

```



```

877 <wsrf-rp:Insert >
878   {any}*
879 </wsrf-rp:Insert> |
880
881 <wsrf-rp:Update >
882   {any}*
883 </wsrf-rp:Update> |
884
885 <wsrf-rp:Delete ResourceProperty="QName" />
886 ]+
887 </wsrf-rp:SetResourceProperties>

```

888 The wsa:Action MUST contain the URI

889 <http://docs.oasis-open.org/wsrf/rpw-2/SetResourceProperties/SetResourcePropertiesRequest>.

891 The contents of the SetResourceProperties request message are further described as follows:

892 /wsrf-rp:SetResourceProperties

893 This element contains a collection of one or more components called  
894 SetRequestComponents. Each of the SetRequestComponents must be processed  
895 against the WS-Resource's resource properties document. These  
896 SetRequestComponents MUST appear to be processed in the order in which they are  
897 listed in the request. Each request component MUST be processed to completion in this  
898 conceptual sequence before a subsequent SetRequestComponent is processed. The  
899 result of processing a given SetRequestComponent MUST be observable to the  
900 processing of a subsequent SetRequestComponent, and to subsequent message  
901 exchanges with the same WS-Resources.

902 If a service fails to process a SetRequestComponent, it MUST cease processing the  
903 SetResourceProperties request message. The values of the resource properties  
904 associated with this SetRequestComponent MAY reflect partial processing of this  
905 SetRequestComponent. An implementation MAY restore the contents of the resource  
906 properties document to a state as if no processing of the failed SetRequestComponent  
907 had occurred. The implementation MAY additionally choose to restore the resource  
908 properties document as if none of the SetRequestComponents had been processed.  
909 Refer to Section 7 for additional information of resource recovery.

910 /wsrf-rp:SetResourceProperties/wsrf-rp:Insert

911 The intent of this component is to insert the contents of the component into the resource  
912 properties document. The exact placement of the element insertion is implementation-  
913 dependent. If, as a result of processing the Insert component, the resource properties  
914 document is no longer able to validate, the processing of the component MUST fault. The  
915 implementation may be unable to accept the insertion of an element because it does not  
916 allow the requestor to insert a resource property (or its value) of that given name. In such  
917 circumstances, the resource MUST fault the processing of the component.

918 /wsrf-rp:SetResourceProperties/wsrf-rp:Insert/{any}

919 This component identifies the element(s) to be inserted into the resource properties  
920 document. If there are multiple child elements of the Insert component, each MUST have  
921 the same namespace and name (i.e. the same QName). The QName MUST correspond  
922 to the QName of a resource property element associated with the WS-Resource (i.e. an

923 element that is a valid child element of the root element of the resource properties  
924 document). Note, for those resource properties documents that allow open element  
925 content, the set of valid content types can be very large.

926 `/wsrf-rp:SetResourceProperties/wsrf-rp:Update`

927 The intent of this component is to change the value of the resource property by removing  
928 any and all resource property element(s) of the given QName and replacing them with  
929 the contents of this component. If, as a result of processing the Update component, the  
930 resource properties document is no longer able to validate, the processing of the  
931 component MUST fault. The resource may be unable to accept the update of an element  
932 because it does not allow the requestor to update a resource property (or its value) of  
933 that given name. In such circumstances, the resource MUST fault the processing of the  
934 component.

935 `/wsrf-rp:SetResourceProperties/wsrf-rp:Update/{any}`

936 This identifies the element(s) to be inserted into the resource properties document,  
937 replacing all element children of the root of the resource properties document with the  
938 same QName. If there are multiple child elements of the Insert component, each MUST  
939 have the same namespace and name (i.e. the same QName). The QName MUST  
940 correspond to the QName of a resource property element associated with the WS-  
941 Resource (i.e. an element that is a valid child element of the root element of the resource  
942 properties document). Note, for those resource properties documents that allow open  
943 element content, the set of valid content types can be very large.

944 `/wsrf-rp:SetResourceProperties/wsrf-rp>Delete`

945 The intent of this component is to remove all element children of the root of the resource  
946 properties document whose QNames correspond to the value of `@ResourceProperty`. If  
947 the resource is unable to remove all identified elements, the processing of the component  
948 MUST fault. If, as a result of processing the Delete component, the resource properties  
949 document is no longer able to validate, the processing of the component MUST fail. The  
950 resource may be unable to accept the delete of an element because it does not allow the  
951 requestor to delete a resource property (or its value) of the given name. In such  
952 circumstances, the resource MUST fault the processing of the component.

953 `/wsrf-rp:SetResourceProperties/wsrf-rp>Delete/@ResourceProperty`

954 This attribute contains the QName of a resource property to be deleted by this  
955 component.

956 The response of the SetResourceProperties request message, all of whose components were  
957 successfully processed, MUST be a message of the following form:

```
958 <wsrf-rp:SetResourcePropertiesResponse>  
959 </wsrf-rp:SetResourcePropertiesResponse>
```

960 The `wsa:Action` MUST contain the URI

961 `http://docs.oasis-open.org/wsrf/rpw-  
962 2/SetResourceProperties/SetResourcePropertiesResponse`.

963 If the WS-Resource does not respond to the SetResourceProperties request message with the  
964 SetResourcePropertiesResponse message, then it MUST send a fault message. This  
965 specification defines the following faults associated with failure to process the  
966 SetResourcePropertyDocument request message, in addition to those faults defined for all WS-  
967 Resources in [WS-Resource]:

968 InvalidModificationFault

969     • The contents of the SetResourceProperties request component cause the resource  
970       properties document to no longer be able to validate.

971 UnableToModifyResourcePropertyFault

972     • A resource property identified by one of the SetResourceProperties request components  
973       is read-only.

974 InvalidResourcePropertyQNameFault

975     • A resource property QName does not identify a resource property.

976 SetResourcePropertyRequestFailedFault

977     • One or more components of the SetResourceProperties request failed.

978 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
979 fault messages MAY be returned instead.

980 Any fault message indicating a failure during the update of the resource properties document  
981 MUST also indicate whether the document was restored or not by using the  
982 ResourcePropertyChangeFailure element of the fault. This fault element indicates the resource  
983 property element change associated with the fault and indicates if the resource property  
984 document as a whole was restored. The format of this element is indicated as follows:

```
985 <wsrf-rp:ResourcePropertyChangeFailure Restored=xsd:boolean?>  
986   <wsrf-rp:CurrentValue>{any}*</wsrf-rp:CurrentValue> ?  
987   <wsrf-rp:RequestedValue>{any}*</wsrf-rp:RequestedValue> ?  
988 </wsrf-rp:ResourcePropertyChangeFailure>
```

989 This element is further constrained as follows:

990 /wsrf-rp:ResourcePropertyChangeFailure

991       The contents of this element provide more information about the element associated with  
992       a failed modification to a resource property document.

993 /wsrf-rp:ResourcePropertyChangeFailure/@Restored

994       If the value of this optional attribute is “true”, then the resource property document was  
995       restored to its state prior to the attempt to process the request message. The absence of  
996       this attribute is identical to this attribute having the value “false”, indicating that no attempt  
997       was made to restore the resource property document.

998 /wsrf-rp:ResourcePropertyChangeFailure/wsrf-rp:CurrentValue

999       If present, this component contains the current value(s) of the resource property  
1000       elements associated with the fault.

1001 /wsrf-rp:ResourcePropertyChangeFailure/wsrf-rp:RequestedValue

1002       If present, this component contains the value(s) of the resource property elements  
1003       associated with the fault as found within the request message.

1004 Note: There is no isolation policy implied, for either modifications to the resource properties  
1005 document resulting from the processing of the request or the modifications implemented by the  
1006 restore. See Section 7 for more discussion.

## 1007 5.6.1 Example SOAP Encoding of the SetResourceProperties 1008 Message Exchange

1009 Consider the resource properties document defining resource properties for a WS-Resource as  
1010 shown in Section 5.1.1.: The following is a non-normative example of a SetResourceProperties  
1011 request message using SOAP 1.1:

```
1012 <s11:Envelope ...>  
1013   <s11:Header>  
1014     <wsa:Action>  
1015       http://docs.oasis-open.org/wsrf/rpw-2/SetResourceProperties/SetResourcePropertiesRequest  
1016     </wsa:Action>  
1017     ...  
1018   </s11:Header>  
1019   <s11:Body>  
1020     <wsrf-rp:SetResourceProperties  
1021       xmlns:tns="http://example.com/diskdrive">  
1022       <wsrf-rp:Update>  
1023         <tns:NumberOfBlocks>143</tns:NumberOfBlocks>  
1024       </wsrf-rp:Update>  
1025  
1026       <wsrf-rp>Delete ResourceProperty="tns:StorageCapability" />  
1027  
1028       <wsrf-rp:Insert>  
1029         <tns:someElement>42</tns:someElement>  
1030       </wsrf-rp:Insert>  
1031  
1032     </wsrf-rp:SetResourceProperties>  
1033   </s11:Body>  
1034 </s11:Envelope>
```

1035 The following is an example SetResourcePropertiesResponse message using SOAP 1.1:

```
1036 <s11:Envelope ...>  
1037   <s11:Header>  
1038     <wsa:Action>  
1039       http://docs.oasis-open.org/wsrf/rpw-2/SetResourceProperties/SetResourcePropertiesResponse  
1040     </wsa:Action>  
1041     ...  
1042   </s11:Header>  
1043   <s11:Body>  
1044     <wsrf-rp:SetResourcePropertiesResponse>  
1045   </wsrf-rp:SetResourcePropertiesResponse>  
1046 </s11:Body>  
1047 </s11:Envelope>
```

1048 The new contents of the resource properties document after successful processing of the request  
1049 message will be:

```
1050 <tns:xmlns:tns="http://example.com/diskDrive" >  
1051   <tns:NumberOfBlocks>143</tns:NumberOfBlocks>
```

```
1052 <tns:BlockSize>1024</tns:BlockSize>
1053 <tns:someElement>42</tns:someElement>
1054 <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
1055 </tns:GenericDiskDriveProperties>
```

1056 Now consider the situation wherein it is illegal to change the value of the resource property  
1057 tns:Manufacturer, for example because the resource property is not modifiable. If a  
1058 SetResourceProperties operation contained a component that attempted to modify this resource  
1059 property value, then a fault message would be returned in response to the  
1060 SetResourceProperties request, and that fault message would contain the following XML  
1061 fragment:

```
1062 ...
1063 <wsrf-rp:ResourcePropertyChangeFailure Restored="true">
1064   <wsrf-rp:CurrentValue>
1065     <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
1066   </wsrf-rp:CurrentValue>
1067   <wsrf-rp:RequestedValue>
1068     <tns:Manufacturer>BogusName</tns:Manufacturer>
1069   </wsrf-rp:RequestedValue>
1070 </wsrf-rp:ResourcePropertyChangeFailure>
```

## 1071 **5.7 InsertResourceProperties**

1072 A WS-Resource MAY support the message exchange defined in this section that allows a  
1073 requestor to insert new values of a resource property of a WS-Resource.

1074 The InsertResourceProperties message is used to request the insertion of one or more element  
1075 values of a single resource property into the resource properties document of a WS-Resource.

1076 The format of this request message MUST be:

```
1077 <wsrf-rp:InsertResourceProperties>
1078   <wsrf-rp:Insert>
1079     {any}*
1080   </wsrf-rp:Insert>
1081 </wsrf-rp:InsertResourceProperties>
```

1082 The wsa:Action MUST contain the URI

```
1083 http://docs.oasis-open.org/wsrf/rpw-
1084 2/InsertResourceProperties/InsertResourcePropertiesRequest.
```

1085 The contents of the InsertResourceProperties request message are further described as follows:

1086 /wsrf-rp:InsertResourceProperties/wsrf-rp:Insert

1087 The intent of this component is to insert the contents of the component into the resource  
1088 properties document. The exact placement of the element insertion is implementation-  
1089 dependent. If, as a result of processing the InsertResourceProperties request, the  
1090 resource properties document is no longer able to validate, the processing of the request  
1091 MUST fault. The implementation may be unable to accept the insertion of an element  
1092 because it does not allow the requestor to insert a resource property (or its value) of that  
1093 given name. In such circumstances, the resource MUST fault the processing of the  
1094 request message.

1095 /wsrf-rp:InsertResourceProperties/wsrf-rp:Insert/{any}

1096 This component identifies the element(s) to be inserted into the resource properties  
1097 document. If there are multiple child elements of the wsrf-rp:Insert element, each MUST  
1098 have the same namespace and name (i.e. the same QName). The QName MUST  
1099 correspond to the QName of a resource property element associated with the WS-  
1100 Resource (i.e. an element that is a valid child element of the root element of the resource  
1101 properties document). Note, for those resource properties documents that allow open  
1102 element content, the set of valid content types can be very large.

1103 When an InsertResourceProperties request message has been successfully processed, the  
1104 response message MUST have the following form:

```
1105 <wsrf-rp:InsertResourcePropertiesResponse>  
1106 </wsrf-rp:InsertResourcePropertiesResponse>
```

1107 The wsa:Action MUST contain the URI

1108 `http://docs.oasis-open.org/wsrf/rpw-`  
1109 `2/InsertResourceProperties/InsertResourcePropertiesResponse.`

1110 If the WS-Resource does not respond to the InsertResourceProperties request message with the  
1111 InsertResourcePropertiesResponse message, then it MUST send a fault. This specification  
1112 defines the following faults associated with failure to process the InsertResourceProperties  
1113 request message, in addition to those faults defined for all WS-Resources in [WS-Resource]:

1114 InvalidModificationFault

- 1115 • The contents of the InsertResourceProperties request component cause the resource  
1116 properties document to no longer be able to validate.

1117 UnableToModifyResourcePropertyFault

- 1118 • A resource property identified by the InsertResourceProperties request is not modifiable.

1119 InvalidResourcePropertyQNameFault

- 1120 • A resource property QName does not identify a resource property.

1121 InsertResourcePropertiesRequestFailedFault

- 1122 • The InsertResourceProperties request failed for some reason.

1123 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
1124 fault messages MAY be returned instead.

1125 Any fault message indicating a failure during the update of the resource properties document  
1126 MUST also indicate whether the document was restored by using the  
1127 ResourcePropertyChangeFailure element of the fault. This fault element indicates the resource  
1128 property element change associated with the fault and indicates if the resource property  
1129 document as a whole was restored. The format of this element is described in Section 5.6.

## 1130 **5.7.1 Example SOAP Encoding of the InsertResourceProperties** 1131 **Message Exchange**

1132 Consider the following resource properties document defining resource properties for a WS-  
1133 Resource defined by the GenericDiskDrive portType:

```
1134 <tns:GenericDiskDriveProperties xmlns:tns="http://example.com/diskDrive" >  
1135 <tns:NumberOfBlocks>22</tns:NumberOfBlocks>  
1136 <tns:BlockSize>1024</tns:BlockSize>  
1137 <tns:Manufacturer>DrivesRUs</tns:Manufacturer>  
1138 </tns:GenericDiskDriveProperties>
```

1139 The following is a non-normative example of an InsertResourceProperties request message using  
1140 SOAP 1.1:

```
1141 <s11:Envelope ...>
1142   <s11:Header>
1143     <wsa:Action>
1144     http://docs.oasis-open.org/wsrf/rpw-
1145     2/InsertResourceProperties/InsertResourcePropertiesRequest
1146     </wsa:Action>
1147     ...
1148   </s11:Header>
1149   <s11:Body>
1150     <wsrf-rp:InsertResourceProperties
1151       xmlns:tns="http://example.com/diskdrive">
1152       <wsrf-rp:Insert>
1153         <tns:StorageCapability>
1154           <tns:NoSinglePointOfFailure>true</tns:NoSinglePointOfFailure>
1155         </tns:StorageCapability>
1156         <tns:StorageCapability>
1157           <tns:DataRedundancyMax>42</tns:DataRedundancyMax>
1158         </tns:StorageCapability>
1159       </wsrf-rp:Insert>
1160     </wsrf-rp:InsertResourceProperties>
1161   </s11:Body>
1162 </s11:Envelope>
```

1164 The following is an example InsertResourcePropertiesResponse message using SOAP 1.1:

```
1165 <s11:Envelope ...>
1166   <s11:Header>
1167     <wsa:Action>
1168     http://docs.oasis-open.org/wsrf/rpw-
1169     2/InsertResourceProperties/InsertResourcePropertiesResponse
1170     </wsa:Action>
1171     ...
1172   </s11:Header>
1173   <s11:Body>
1174     <wsrf-rp:InsertResourcePropertiesResponse>
1175     </wsrf-rp:InsertResourcePropertiesResponse>
1176   </s11:Body>
1177 </s11:Envelope>
```

1178 The new contents of the resource properties document after successful processing of the request  
1179 message will be:

```
1180 <tns:GenericDiskDriveProperties xmlns:tns="http://example.com/diskDrive" >
1181   <tns:NumberOfBlocks>22</tns:NumberOfBlocks>
1182   <tns:BlockSize>1024</tns:BlockSize>
1183   <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
1184   <tns:StorageCapability>
1185     <tns:NoSinglePointOfFailure>true</tns:NoSinglePointOfFailure>
```

```
1186 </tns:StorageCapability>
1187 <tns:StorageCapability>
1188 <tns:DataRedundancyMax>42</tns:DataRedundancyMax>
1189 </tns:StorageCapability>
1190 </tns:GenericDiskDriveProperties>
```

## 1191 **5.8 UpdateResourceProperties**

1192 A WS-Resource MAY support the message exchange defined in this section that allows a  
1193 requestor to replace the existing values of a resource property with new values.

1194 The UpdateResourceProperties message is used to request the replacement of all the element  
1195 values of a single resource property in the resource properties document of a WS-Resource with  
1196 a new set of values.

1197 The format of this request message MUST be:

```
1198 <wsrf-rp:UpdateResourceProperties>
1199 <wsrf-rp:Update>
1200 {any}*
1201 </wsrf-rp:Update>
1202 </wsrf-rp:UpdateResourceProperties>
```

1203 The wsa:Action MUST contain the URI

1204 [http://docs.oasis-open.org/wsrf/rpw-](http://docs.oasis-open.org/wsrf/rpw-2/UpdateResourceProperties/UpdateResourcePropertiesRequest)  
1205 [2/UpdateResourceProperties/UpdateResourcePropertiesRequest](http://docs.oasis-open.org/wsrf/rpw-2/UpdateResourceProperties/UpdateResourcePropertiesRequest).

1206 The contents of the UpdateResourceProperties request message are further described as  
1207 follows:

1208 /wsrf-rp:UpdateResourceProperties/wsrf-rp:Update

1209 The intent of this request is to change the value of the elements of a resource property by  
1210 removing any and all resource property element(s) of the given QName and replacing  
1211 them with the contents of this component. If, as a result of processing the entire  
1212 UpdateResourceProperties request, the resource properties document is no longer able  
1213 to validate, the processing of the request MUST fault. The resource may be unable to  
1214 accept the update of an element because it does not allow the requestor to update a  
1215 resource property (or its value) of that given name. In such circumstances, the resource  
1216 MUST fault the processing of the request message.

1217 /wsrf-rp:UpdateResourceProperties/wsrf-rp:Update/{any}

1218 This identifies the element(s) to be inserted into the resource properties document,  
1219 replacing all element children of the root of the resource properties document with the  
1220 same QName. If there are multiple child elements of the wsrf-rp:Update component, each  
1221 MUST have the same namespace and name (i.e. the same QName). The QName MUST  
1222 correspond to the QName of a resource property element associated with the WS-  
1223 Resource (i.e. an element that is a valid child element of the root element of the resource  
1224 properties document). Note: for those resource properties documents that allow open  
1225 element content, the set of valid content types can be very large.

1226 When an UpdateResourceProperties request message has been successfully processed, the  
1227 response message MUST have the following form:

```
1228 <wsrf-rp:UpdateResourcePropertiesResponse>
```



1229 </wsrf-rp:UpdateResourcePropertiesResponse>

1230 The wsa:Action MUST contain the URI

1231 http://docs.oasis-open.org/wsrf/rpw-

1232 2/UpdateResourceProperties/UpdateResourcePropertiesResponse.

1233 If the WS-Resource does not respond to the UpdateResourceProperties request message with  
1234 the UpdateResourcePropertiesResponse message, then it MUST send a fault. This specification  
1235 defines the following faults associated with failure to process the UpdateResourceProperties  
1236 request message, in addition to those faults defined for all WS-Resources in [WS-Resource]:

1237 InvalidModificationFault

- 1238 • The contents of the UpdateResourceProperties request component cause the resource  
1239 properties document to no longer be able to validate.

1240 UnableToModifyResourcePropertyFault

- 1241 • A resource property identified by the UpdateResourceProperties request is not  
1242 modifiable.

1243 InvalidResourcePropertyQNameFault

- 1244 • A resource property QName does not identify a resource property.

1245 UpdateResourcePropertiesRequestFailedFault

- 1246 • The UpdateResourceProperties request failed for some reason.

1247 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
1248 fault messages MAY be returned instead.

1249 Any fault message indicating a failure during the update of the resource properties document  
1250 MUST also indicate whether the document was restored by using the  
1251 ResourcePropertyChangeFailure element of the fault. This fault element indicates the resource  
1252 property element change associated with the fault and indicates if the resource property  
1253 document as a whole was restored. The format of this element is described in Section 5.6.

## 1254 5.8.1 Example SOAP Encoding of the UpdateResourceProperties 1255 Message Exchange

1256 Consider the resource properties document defining resource properties for a WS-Resource as  
1257 shown in Section 5.7.1. The following is a non-normative example of an  
1258 UpdateResourceProperties request message using SOAP 1.1:

```
1259 <s11:Envelope ...>  
1260   <s11:Header>  
1261     <wsa:Action>  
1262       http://docs.oasis-open.org/wsrf/rpw-  
1263       2/UpdateResourceProperties/UpdateResourcePropertiesRequest  
1264     </wsa:Action>  
1265     ...  
1266   </s11:Header>  
1267   <s11:Body>  
1268     <wsrf-rp:UpdateResourceProperties  
1269       xmlns:tns="http://example.com/diskdrive">  
1270       <wsrf-rp:Update>  
1271         <tns:NumberOfBlocks>143</tns:NumberOfBlocks>  
1272       </wsrf-rp:Update>
```

```
1273 </wsrf-rp:UpdateResourceProperties>
1274 </s11:Body>
1275 </s11:Envelope>
```

1276 The following is an example UpdateResourcePropertiesResponse message using SOAP 1.1:

```
1277 <s11:Envelope ...>
1278 <s11:Header>
1279 <wsa:Action>
1280 http://docs.oasis-open.org/wsrf/rpw-
1281 2/UpdateResourceProperties/UpdateResourcePropertiesResponse
1282 </wsa:Action>
1283 ...
1284 </s11:Header>
1285 <s11:Body>
1286 <wsrf-rp:UpdateResourcePropertiesResponse>
1287 </wsrf-rp:UpdateResourcePropertiesResponse>
1288 </s11:Body>
1289 </s11:Envelope>
```

1290 The new contents of the resource properties document after successful processing of the request  
1291 message will be:

```
1292 <tns:GenericDiskDriveProperties xmlns:tns="http://example.com/diskDrive" >
1293 <tns:NumberOfBlocks>143</tns:NumberOfBlocks>
1294 <tns:BlockSize>1024</tns:BlockSize>
1295 <tns:Manufacturer>DrivesRUs</tns:Manufacturer>
1296 </tns:GenericDiskDriveProperties>
```

## 1297 **5.9 DeleteResourceProperties**

1298 A WS-Resource MAY support the message exchange defined in this section that allows a  
1299 requestor to remove all values of a resource property of a WS-Resource.

1300 The DeleteResourceProperties message is used to request the removal of all values of a single  
1301 resource property from the resource properties document of a WS-Resource.

1302 The format of this request message MUST be:

```
1303 <wsrf-rp>DeleteResourceProperties>
1304 <wsrf-rp>Delete ResourceProperty="QName" />
1305 </wsrf-rp>DeleteResourceProperties>
```

1306 The wsa:Action MUST contain the URI

```
1307 http://docs.oasis-open.org/wsrf/rpw-
1308 2/DeleteResourceProperties/DeleteResourcePropertiesRequest.
```

1309 The contents of the DeleteResourceProperties request message are further described as follows:

1310 /wsrf-rp>DeleteResourceProperties/wsrf-rp>Delete

1311 The intent of this message is to remove all element children of the root of the resource  
1312 properties document whose QNames correspond to the value of @ResourceProperty. If  
1313 the resource is unable to remove all identified elements, the processing of the message  
1314 MUST fault. If, as a result of processing the DeleteResourceProperty request, the resource  
1315 properties document is no longer able to validate, the processing of the request MUST

1316 fault. The resource may be unable to accept the deletion of an element because it does  
1317 not allow the requestor to delete a resource property (or its value) of the given name. In  
1318 such circumstances, the resource MUST fault the processing of the request message.

1319 /wsrf-rp>DeleteResourceProperties/wsrf-rp>Delete/@ResourceProperty

1320 This attribute contains the QName of a resource property to be deleted by this request.

1321 When a DeleteResourceProperties request message has been successfully processed, the  
1322 response message MUST have the following form:

```
1323 <wsrf-rp>DeleteResourcePropertiesResponse>  
1324 </wsrf-rp>DeleteResourcePropertiesResponse>
```

1325 The wsa:Action MUST contain the URI

1326 http://docs.oasis-open.org/wsrf/rpw-  
1327 2/DeleteResourceProperties/DeleteResourcePropertiesResponse.

1328 If the WS-Resource does not respond to the DeleteResourceProperties request message with the  
1329 DeleteResourcePropertiesResponse message, then it MUST send a fault. This specification  
1330 defines the following faults associated with failure to process the DeleteResourceProperties  
1331 request message, in addition to those faults defined for all WS-Resources in [WS-Resource]:

1332 InvalidModificationFault

1333 • The contents of the DeleteResourceProperties request component cause the resource  
1334 properties document to no longer be able to validate.

1335 UnableToModifyResourcePropertyFault

1336 • A resource property identified by the DeleteResourceProperties request is not modifiable.

1337 InvalidResourcePropertyQNameFault

1338 • A resource property QName does not identify a resource property.

1339 DeleteResourcePropertiesRequestFailedFault

1340 • One or more components of the DeleteResourceProperties request failed.

1341 One of these faults, or a specialization thereof, SHOULD be sent upon failure, although other  
1342 fault messages MAY be returned instead.

1343 Any fault message indicating a failure during the update of the resource properties document  
1344 MUST also indicate whether the document was restored by using the  
1345 ResourcePropertyChangeFailure element of the fault. This fault element indicates the resource  
1346 property element change associated with the fault and indicates if the resource property  
1347 document as a whole was restored. The format of this element is described in Section 5.6.

## 1348 **5.9.1 Example SOAP Encoding of the DeleteResourceProperties** 1349 **Message Exchange**

1350 Consider the resource properties document defining resource properties for a WS-Resource as  
1351 shown in Section 5.7.1. The following is a non-normative example of a DeleteResourceProperties  
1352 request message using SOAP 1.1:

```
1353 <s11:Envelope ...>  
1354 <s11:Header>  
1355 <wsa:Action>  
1356 http://docs.oasis-open.org/wsrf/rpw-  
1357 2/DeleteResourceProperties/DeleteResourcePropertiesRequest
```

```
1358 </wsa:Action>
1359 ...
1360 </s11:Header>
1361 <s11:Body>
1362 <wsrf-rp:DeleteResourceProperties
1363   xmlns:tns="http://example.com/diskdrive">
1364   <wsrf-rp:Delete ResourceProperty="tns:Manufacturer" />
1365 </wsrf-rp:DeleteResourceProperties>
1366 </s11:Body>
1367 </s11:Envelope>
```

1368 The following is an example DeleteResourcePropertiesResponse message using SOAP 1.1:

```
1369 <s11:Envelope ...>
1370 <s11:Header>
1371 <wsa:Action>
1372 http://docs.oasis-open.org/wsrf/rpw-
1373 2/DeleteResourceProperties/DeleteResourcePropertiesResponse
1374 </wsa:Action>
1375 ...
1376 </s11:Header>
1377 <s11:Body>
1378 <wsrf-rp:DeleteResourcePropertiesResponse>
1379 </wsrf-rp:DeleteResourcePropertiesResponse>
1380 </s11:Body>
1381 </s11:Envelope>
```

1382 The new contents of the resource properties document after successful processing of the request  
1383 message will be:

```
1384 <tns:GenericDiskDriveProperties xmlns:tns="http://example.com/diskDrive" >
1385 <tns:NumberOfBlocks>22</tns:NumberOfBlocks>
1386 <tns:BlockSize>1024</tns:BlockSize>
1387 </tns:GenericDiskDriveProperties>
```

## 1388 **6 Subscription**

1389 The WS-Notification [[WS-BaseNotification](#)] [[WS-Topics](#)] family of specifications describes the  
1390 patterns, concepts, standard message exchanges, and protocols of a topic-based, publish-  
1391 subscribe messaging pattern in Web services. In the notification model, a service creates  
1392 messages that are delivered to other services that had previously registered interest in the  
1393 situation associated with that message.

1394 With WS-ResourceProperties, it is a common pattern for Web service requestors to request  
1395 notification of inserts, updates and deletions made to the values of one or more resource property  
1396 elements of a given WS-Resource. This suggests the need for the WS-Resource to encapsulate  
1397 the stateful resource to ensure all changes made to the stateful resource (those made by Web  
1398 services invocations, or those that happen to the resource by other means) are *observed* by the  
1399 WS-Resource implementation. To the extent that encapsulation is not provided, and changes to  
1400 the stateful resource are made outside of the knowledge of the associated WS-Resource  
1401 implementation, the WS-Resource may not be able to provide notifications reflecting those  
1402 changes.

1403 If a WS-Resource supports the resource property value-change notification pattern, and if it uses  
1404 WS-Notification to implement this feature, then it **MUST** implement the message exchanges for  
1405 the NotificationProducer role, as specified in [[WS-BaseNotification](#)]. The WS-Resource **MAY**  
1406 accept subscriptions to only a subset of the resource properties defined for a WS-Resource. If an  
1407 implementation does not use WS-Notification, then it **MAY** ignore the requirements outlined in this  
1408 section.

### 1409 **6.1 Individual Resource Property Value Changes**

1410 One notification message artifact is created for each change to each resource property observed  
1411 by the WS-Resource implementation. For example, a SetResourceProperties request message  
1412 might contain five SetRequestComponents. Each of these components would result in the  
1413 creation of a separate message artifact. A PutResourcePropertyDocument request might result in  
1414 the change of most of the WS-Resource's resource properties, in which case each resource  
1415 property changed by the PutResourcePropertyDocument request would result in a separate  
1416 message artifact.

1417 WS-ResourceProperties defines the Notification TopicExpressions and TopicNamespace  
1418 elements [[WS-Topics](#)] that **MUST** be used to express the organization of the WS-Resource  
1419 property element value change notifications. By understanding the relationship between  
1420 TopicExpressions and resource properties, and examining the set of TopicExpressions supported  
1421 by the NotificationProducer Web service, the service requestor can determine which of the  
1422 resource properties are able to participate in the value-change notification pattern. The  
1423 TopicExpression and TopicNamespace elements associated with resource property value-  
1424 change notification are described as follows:

- 1425 1. The WS-Resource's resource properties document **MAY** be defined using resource  
1426 properties declared in multiple XML namespaces. For each of these XML namespaces, an  
1427 associated TopicNamespace element **MUST** be defined. The TopicNamespace element  
1428 defines a namespace intended to contain topics related to value changes of resource  
1429 properties declared in that XML namespace.
  - 1430 ○ The value of the TopicNamespace element's targetNamespace attribute **MUST** be  
1431 the same as the URI of the namespace in which the resource property element is

- 1432 defined. The name attribute of the TopicNamespace element SHOULD have the  
 1433 value "ResourcePropertiesTopicNamespace".
- 1434 2. For each resource property participating in the value-change notification pattern, a  
 1435 TopicExpression element MUST be defined as a child of the TopicNamespace element  
 1436 defined in 1.
- 1437 ○ Notification messages reflecting changes to the resource property are associated  
 1438 with this TopicExpression.
  - 1439 ○ The value of the TopicExpression element's name attribute MUST be the same as  
 1440 the NCName of the resource property element.
  - 1441 ○ The value of the TopicExpression element's messageTypes attribute MUST include  
 1442 wsrf-rp:ResourcePropertyValueChangeNotification (defined later in this section). In  
 1443 addition, it MAY include QNames of other message elements.
  - 1444 ○ A designer MAY introduce additional child sub-topic elements to the TopicExpression  
 1445 element that represent application-specific needs.
- 1446 3. The WS-Resource acting as the NotificationProducer MUST include TopicExpressions as  
 1447 defined in 2 above, as part of the value of its "wsnt:TopicExpression" resource property  
 1448 element. One such TopicExpression MUST be included for each resource property element  
 1449 offered as a target for a value-change subscription.
- 1450 4. When a WS-Resource observes a resource property value change, it SHOULD create a  
 1451 notification message that expresses the situation, and associate the notification message  
 1452 with the TopicExpression associated with that resource property. Note: there are many  
 1453 circumstances in which a change to a resource property might not result in the generation of  
 1454 a notification message. For example, a resource property value may change frequently,  
 1455 making generation of notification messages too expensive for the service. In this situation, a  
 1456 WS-Resource may choose to never generate notification message artifacts to record value  
 1457 change, or it may choose to generate notification message artifacts for a subset of the  
 1458 value-change situations.

1459 The wsrf-rp:ResourcePropertyValueChangeNotification element MUST appear as a component  
 1460 of the notification message associated with resource property value change topics. This element  
 1461 is defined as follows:

```

1462 <wsrf-rp:ResourcePropertyValueChangeNotification>
1463 <wsrf-rp:OldValues> xsd:any *</wsrf-rp:OldValues>?
1464 <wsrf-rp:NewValues> xsd:any *</wsrf-rp:NewValues>
1465 </wsrf-rp:ResourcePropertyValueChangeNotification>
  
```

1466 This element may appear as the root element of the notification message, or it may appear as a  
 1467 descendent of the root, accommodating patterns where the notification message itself is  
 1468 contained in an enveloping mechanism. The form of the  
 1469 ResourcePropertyValueChangeNotification is further constrained as follows:

1470 /wsrf-rp:ResourcePropertyValueChangeNotification

1471 One ResourcePropertyValueChangeNotification element is created for each resource  
 1472 property value-change situation detected and acted upon by the WS-Resource. This  
 1473 component records the value change of the affected resource property.

1474 /wsrf-rp:ResourcePropertyValueChangeNotification/OldValues

1475 This element, if it appears, MUST contain the resource property elements of the affected  
 1476 WS-Resource property immediately prior to when the value change was applied. If the

1477 resource property did not have any value prior to the value change (for example, this  
1478 notification represents an insertion of a new resource property element) then this element  
1479 is empty and will contain the attribute xsi:nil with value "true". If this component does not  
1480 appear in the message, then the WS-Resource was unable or unwilling to record the  
1481 resource property elements prior to the value change.

1482 /wsrf-rp:ResourcePropertyValueChangeNotification/NewValues

1483 This element MUST contain the resource property elements of the affected WS-Resource  
1484 property after the value-change condition was detected. If the WS-Resource property  
1485 does not have any value after the value change (for example, this notification represents  
1486 a deletion of the resource property element) then this element is empty and will contain  
1487 the attribute xsi:nil with value "true".

## 1488 **6.2 Value Changes on Any Resource Property**

1489 In addition to the TopicExpressions defined for value-change notification to individual resource  
1490 properties (described in the previous section), the WS-Resource MAY also support subscription  
1491 for changes to *any* resource property. This specification defines a distinguished topic, named  
1492 "AnyResourcePropertyValueChange" in a distinguished Topic Namespace corresponding to the  
1493 WS-ResourceProperties specification namespace.

1494 If the WS-Resource supports the NotificationProducer interface (as defined by WS-  
1495 BaseNotification) and it supports subscriptions on the wsrf-rp:AnyResourcePropertyValueChange  
1496 topic, then it MUST include this TopicExpression's QName in the value of its  
1497 wsnt:TopicExpression resource property. Furthermore, for any ResourcePropertyValueChange  
1498 notification message published on any Topic, the WS-Resource MUST also publish the  
1499 notification message on the wsrf-rp:AnyResourcePropertyValueChange Topic.

## 1500 **7 ACID Properties of Operations on WS-** 1501 **Resources**

1502 The ability to associate a transactional recovery policy to the execution of a Web service  
1503 message exchange is a quality of service the designer would compose into the definition of a  
1504 WS-Resource. In the presence of a transactional unit of work, a Web service capable of  
1505 participating in the transactional protocol must abide by the rules of two-phase-commit  
1506 transaction management. However, in the absence of a transaction management policy, the Web  
1507 service is under no obligation to recover the state of the WS-Resource in the event of a failure  
1508 during message processing.

1509 This specification is not prescriptive with respect to policy that governs concurrent read or write  
1510 access to a WS-Resource. The definition of specific policy governing concurrent updates,  
1511 whether or not separate message executions targeting the same WS-Resource may be  
1512 interleaved, and whether partially-completed WS-Resource updates within a given message  
1513 execution may be observed by other concurrent requests is beyond the scope of this definition.  
1514 The scope and extent of the isolation of changes made to the WS-Resource is an implementation  
1515 dependent responsibility of the WS-Resource itself. The WS-Resource must also take on the  
1516 responsibility for the scope and extent to which notifications of changes to the WS-Resource are  
1517 isolated and made observable. If WS-Resource update isolation is needed, we suggest the use of  
1518 a transaction to provide a context within which isolation of WS-Resource updates can be  
1519 provided. In the absence of a transactional unit of work, the level of WS-Resource update  
1520 atomicity, recovery, isolation, and durability provided is implementation-dependent.

1521 The ability to declare and attach isolation-level policy to the definition of a Web service message  
1522 exchange, whether or not a transactional unit of work is present, represents a general  
1523 requirement not met by the current Web service architecture. In the future, isolation-level policy  
1524 declarations may be introduced as a formal part of the WS-Resource definition.



## 1525 **8 Security Considerations**

1526 This specification defines the resource properties document and also the set of message  
1527 exchanges that **MUST** be supported by a WS-Resource. In this context, there are two categories  
1528 of security aspects that need to be considered: (a) securing the message exchanges and (b)  
1529 securing the resource properties.

### 1530 **8.1 Securing the message exchanges**

1531 When messages are exchanged between a requestor and a WS-Resource in order to access or  
1532 act upon one or more resource properties, it is **RECOMMENDED** that the communication  
1533 between the services be secured using the mechanisms described in WS-Security [[WS-Security](#)].

### 1534 **8.2 Securing Resource Properties**

1535 Since WS-ResourceProperties defines a mechanism to expose properties of a WS-Resource,  
1536 security policies should be established that ensure that only authorized requestors can access  
1537 the value of a resource property. In order to secure access to the resource properties, the  
1538 message exchanges that provide the access should be appropriately controlled. Authorization  
1539 policies should be put in place so that the implications of providing the state information (through  
1540 GetResourceProperty, GetMultipleResourceProperties, GetResourcePropertyDocument, or  
1541 QueryResourceProperties messages or through notification of value change and modification of  
1542 the resource properties), are taken into account. These policies should also take into account the  
1543 semantic difference between components of the SetResourceProperties message – i.e. that an  
1544 Update component updates a *value* of a resource property, whereas Insert and Delete  
1545 components modify whether the WS-Resource actually *contains* the resource property values.

1546 The authorization policies may also reflect the sensitivity of the resource property(ies) that are  
1547 accessible from a WS-Resource. Policies can be set at the coarse granularity of the message  
1548 exchange (e.g., Get(Multiple)ResourceProperty(ies) vs SetResourceProperty), but finer-grained  
1549 control at the level of individual resource properties may be desired in some scenarios (e.g. user  
1550 Bob can access value of “Manufacturer” but not “NumberOfBlocks”).

1551 Given that a requestor will be able to access a resource property value by subscribing to state  
1552 changes, care should be taken to set up security policies so that a consistent policy is in effect  
1553 irrespective of whether the resource property value is accessed through direct message  
1554 exchanges (e.g., GetResourceProperty) or indirectly through subscription for state changes (i.e.,  
1555 subscription to “ResourcePropertyValueChangeNotification” topic). It should also be noted that a  
1556 requestor will be able to query the value of a property through the QueryResourceProperties  
1557 operation, or by using a domain-specific operation corresponding to a resource property (e.g.,  
1558 getNumberOfBlocks) if one exists. Therefore, the authorization policy on  
1559 QueryResourceProperties operation (and the getXXX operation, if one is declared on the Web  
1560 service for resource property named XXX) should be set so that a requestor who is not  
1561 authorized to get a value of a resource property through a GetResourceProperty request is not  
1562 able to deduce the value indirectly through the QueryResourceProperties request (or the getXXX  
1563 operation on the Web service).

1564 Even if the requestor is authorized to access the requested resource properties, it is  
1565 **RECOMMENDED** that the resource properties that are exchanged between a requestor and a  
1566 Web service are secured to ensure integrity and/or confidentiality of the resource property values.  
1567 This will prevent unauthorized alteration of and/or access to the property values while in transit.  
1568 This would mean that the specific resource property elements are signed and/or encrypted within  
1569 the message by leveraging WS-Security as discussed in the previous section.

## 1570 9 References

### 1571 9.1 Normative

- 1572 [RFC2119] S. Bradner, *Key words for use in RFCs to Indicate Requirement Levels*, <http://www.ietf.org/rfc/rfc2119.txt>, IETF RFC 2119, March 1997.
- 1573
- 1574
- 1575 [WS-Addressing] <http://www.w3.org/TR/ws-addr-core>
- 1576 [WS-BaseFaults] [http://docs.oasis-open.org/wsrf/wsrf-ws\\_base\\_faults-1.2-spec-cs-01.pdf](http://docs.oasis-open.org/wsrf/wsrf-ws_base_faults-1.2-spec-cs-01.pdf)
- 1577
- 1578 [WS-BaseNotification] [http://docs.oasis-open.org/wsn/wsn-ws\\_base\\_notification-1.3-spec-pr-02.pdf](http://docs.oasis-open.org/wsn/wsn-ws_base_notification-1.3-spec-pr-02.pdf)
- 1579
- 1580 [WS-Resource] [http://docs.oasis-open.org/wsrf/wsrf-ws\\_resource-1.2-spec-cs-01.pdf](http://docs.oasis-open.org/wsrf/wsrf-ws_resource-1.2-spec-cs-01.pdf)
- 1581
- 1582 [WS-Topics] [http://docs.oasis-open.org/wsn/wsn-ws\\_topics-1.3-spec-pr-01.pdf](http://docs.oasis-open.org/wsn/wsn-ws_topics-1.3-spec-pr-01.pdf)
- 1583
- 1584 [XML-Infoset] <http://www.w3.org/TR/xml-infoset/>
- 1585 [XPath] <http://www.w3.org/TR/xpath>

### 1586 9.2 Non-Normative

- 1587 [OGSI 1.0] Open Grid Services Infrastructure (OGSI) V1.0  
<http://forge.gridforum.org/projects/ggf-editor/document/draft-ogsi-service-1/en/1>
- 1588
- 1589
- 1590 [WS-Security] <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>
- 1591
- 1592 [WSDL 2.0] <http://www.w3.org/TR/wsdl20/>
- 1593 [WS-I] <http://www.ws-i.org/Profiles/BasicProfile-1.1.html>

## 1594 **Appendix A. Acknowledgments**

1595 Special thanks to the Global Grid Forum's Open Grid Services Infrastructure working group,  
1596 which defined the OGSi v1.0 [OGSI] specification which was a large inspiration for the ideas  
1597 expressed in this specification.

1598 The following individuals were members of the committee during the development of this  
1599 specification:

1600 Mario Antonioletti (EPCC, The University of Edinburgh), Akhil Arora (Sun Microsystems), Tim  
1601 Banks (IBM), Jeff Bohren (OpenNetwork), Fred Carter (AmberPoint), Martin Chapman (Oracle),  
1602 Glen Daniels (Sonic Software), David De Roure (University of Southampton), Thomas Freund  
1603 (IBM), John Fuller (Individual), Stephen Graham (IBM), Anish Karmarkar (Oracle), Hideharu Kato  
1604 (Hitachi), David Levine (IBM), Paul Lipton (Computer Associates), Mark Little (Arjuna  
1605 Technologies Limited), Lily Liu (WebMethods, Inc.), Tom Maguire (IBM), Susan Malaika (IBM),  
1606 Mark Mc Keown (University of Manchester), David Martin (IBM), Samuel Meder (Argonne  
1607 National Laboratory), Jeff Mischkin (Oracle), Roger Menday (Forschungszentrum Jlich  
1608 GmbH), Bryan Murray (Hewlett-Packard), Mark Peel (Novell), Alain Regnier (Ricoh Company,  
1609 Ltd.), Ian Robinson (IBM), Tom Rutt (Fujitsu), Mitsunori Satomi (Hitachi), Igor Sedukhin  
1610 (Computer Associates), Hitoshi Sekine (Ricoh Company, Ltd.), Frank Siebenlist (Argonne  
1611 National Laboratory), Alex Sim (Lawrence Berkeley National Laboratory), David Snelling (Fujitsu),  
1612 Latha Srinivasan (Hewlett-Packard), Rich Thompson (IBM), Jem Treadwell (Hewlett-Packard),  
1613 Steve Tuecke (Argonne National Laboratory), William Vambenepe (Hewlett-Packard), Katy Warr  
1614 (IBM), Alan Weissberger (NEC Corporation), Pete Wenzel (SeeBeyond Technology Corporation),  
1615 Kirk Wilson (Computer Associates) and Umit Yalcinalp (SAP).

1616 In addition, the following people made contributions to this specification:

1617 Nick Butler (IBM), Karl Czajkowski (Globus / USC/ISI), Andrew Eisenberg (IBM), Donald F  
1618 Ferguson (IBM), Ian Foster (Globus / Argonne), Jeffrey Frey (IBM), Diane Jordan (IBM), Frank  
1619 Leymann (IBM), Andreas Meier (IBM), Nataraj Nagaratnam (IBM), Martin Nally (IBM), John  
1620 Rofrano (IBM), Ellen Stokes (IBM), Tony Storey (IBM), Jay Unger (IBM), Sanjiva Weerawarana  
1621 (IBM).

## 1622 Appendix B. XML Schema

1623 The XML types and elements used in this specification are included here for convenience. The  
1624 authoritative version of this schema document is available at

1625 <http://docs.oasis-open.org/wsrf/rp-2.xsd>

```
1626 <?xml version="1.0" encoding="UTF-8"?>
```

```
1627 <!--
```

```
1628
```

```
1629 OASIS takes no position regarding the validity or scope of any intellectual property or other rights  
1630 that might be claimed to pertain to the implementation or use of the technology described in this  
1631 document or the extent to which any license under such rights might or might not be available;  
1632 neither does it represent that it has made any effort to identify any such rights. Information on  
1633 OASIS's procedures with respect to rights in OASIS specifications can be found at the OASIS  
1634 website. Copies of claims of rights made available for publication and any assurances of licenses  
1635 to be made available, or the result of an attempt made to obtain a general license or permission  
1636 for the use of such proprietary rights by implementors or users of this specification, can be  
1637 obtained from the OASIS Executive Director.
```

```
1638
```

```
1639 OASIS invites any interested party to bring to its attention any copyrights, patents or patent  
1640 applications, or other proprietary rights which may cover technology that may be required to  
1641 implement this specification. Please address the information to the OASIS Executive Director.
```

```
1642
```

```
1643 Copyright (C) OASIS Open (2005). All Rights Reserved.
```

```
1644
```

```
1645 This document and translations of it may be copied and furnished to others, and derivative works  
1646 that comment on or otherwise explain it or assist in its implementation may be prepared, copied,  
1647 published and distributed, in whole or in part, without restriction of any kind, provided that the  
1648 above copyright notice and this paragraph are included on all such copies and derivative works.  
1649 However, this document itself may not be modified in any way, such as by removing the copyright  
1650 notice or references to OASIS, except as needed for the purpose of developing OASIS  
1651 specifications, in which case the procedures for copyrights defined in the OASIS Intellectual  
1652 Property Rights document must be followed, or as required to translate it into languages other  
1653 than English.
```

```
1654
```

```
1655 The limited permissions granted above are perpetual and will not be revoked by OASIS or its  
1656 successors or assigns.
```

```
1657
```

```
1658 This document and the information contained herein is provided on an "AS IS" basis and OASIS  
1659 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO  
1660 ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE  
1661 ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A  
1662 PARTICULAR PURPOSE.
```

```
1663
```

```
1664 -->
```

```
1665 <xsd:schema
```

```
1666   xmlns:xsd="http://www.w3.org/2001/XMLSchema"
```

```
1667   xmlns:wsrf-rp="http://docs.oasis-open.org/wsrf/rp-2"
```

```

1668 xmlns:wsrf-bf="http://docs.oasis-open.org/wsrf/bf-2"
1669 elementFormDefault="qualified" attributeFormDefault="unqualified"
1670 targetNamespace="http://docs.oasis-open.org/wsrf/rp-2"
1671 >
1672 <xsd:import
1673     namespace="http://docs.oasis-open.org/wsrf/bf-2"
1674     schemaLocation="http://docs.oasis-open.org/wsrf/bf-2.xsd"
1675 />
1676 <!-- ===== Resource Property Related ===== -->
1677 <!-- ===== Resource Properties for QueryResourceProperties ===== -->
1678 <xsd:element name="QueryExpressionDialect" type="xsd:anyURI"/>
1679
1680 <xsd:element name="QueryExpressionRPDocument">
1681     <xsd:complexType>
1682         <xsd:sequence>
1683             <xsd:element ref="wsrf-rp:QueryExpressionDialect"
1684                 minOccurs="0" maxOccurs="unbounded" />
1685         </xsd:sequence>
1686     </xsd:complexType>
1687 </xsd:element>
1688
1689 <!-- ===== Global Attribute Declaration for WSDL 1.1 portType===== -->
1690 <xsd:attribute name="ResourceProperties" type="xsd:QName" />
1691
1692 <!-- = Notification Message for ResourceProperties value change === -->
1693 <xsd:complexType name="ResourcePropertyValueChangeNotificationType">
1694     <xsd:sequence>
1695         <xsd:element name="OldValues" nillable="true"
1696             minOccurs="0" maxOccurs="1" >
1697             <xsd:complexType>
1698                 <xsd:sequence>
1699                     <xsd:any minOccurs="1" maxOccurs="unbounded" />
1700                 </xsd:sequence>
1701             </xsd:complexType>
1702         </xsd:element>
1703         <xsd:element name="NewValues" nillable="true"
1704             minOccurs="1" maxOccurs="1" >
1705             <xsd:complexType>
1706                 <xsd:sequence>
1707                     <xsd:any minOccurs="1" maxOccurs="unbounded" />
1708                 </xsd:sequence>
1709             </xsd:complexType>
1710         </xsd:element>
1711     </xsd:sequence>
1712 </xsd:complexType>
1713
1714 <xsd:element name="ResourcePropertyValueChangeNotification"
1715     type="wsrf-rp:ResourcePropertyValueChangeNotificationType" />
1716

```

```

1717 <xsd:complexType name="QueryExpressionType" mixed="true">
1718   <xsd:sequence>
1719     <xsd:any minOccurs="0" maxOccurs="1" processContents="lax" />
1720   </xsd:sequence>
1721   <xsd:attribute name="Dialect" type="xsd:anyURI" />
1722 </xsd:complexType>
1723
1724 <xsd:element name="QueryExpression" type="wsrf-rp:QueryExpressionType" />
1725
1726 <!-- ===== Message Types for GetResourcePropertyDocument ===== -->
1727
1728 <xsd:element name="GetResourcePropertyDocument">
1729   <xsd:complexType/>
1730 </xsd:element>
1731
1732 <xsd:element name="GetResourcePropertyDocumentResponse">
1733   <xsd:complexType>
1734     <xsd:sequence>
1735       <xsd:any minOccurs="1" maxOccurs="1"/>
1736     </xsd:sequence>
1737   </xsd:complexType>
1738 </xsd:element>
1739
1740 <!-- ===== Message Types for GetResourceProperty ===== -->
1741
1742 <xsd:element name="GetResourceProperty"
1743   type="xsd:QName" />
1744
1745 <xsd:element name="GetResourcePropertyResponse" >
1746   <xsd:complexType>
1747     <xsd:sequence>
1748       <xsd:any minOccurs="0" maxOccurs="unbounded" />
1749     </xsd:sequence>
1750   </xsd:complexType>
1751 </xsd:element>
1752
1753 <xsd:complexType name="InvalidResourcePropertyQNameFaultType">
1754   <xsd:complexContent>
1755     <xsd:extension base="wsrf-bf:BaseFaultType"/>
1756   </xsd:complexContent>
1757 </xsd:complexType>
1758 <xsd:element name="InvalidResourcePropertyQNameFault"
1759   type="wsrf-rp:InvalidResourcePropertyQNameFaultType"/>
1760
1761 <!-- ===== Message Types for GetMultipleResourceProperties ===== -->
1762 <xsd:element name="GetMultipleResourceProperties">
1763   <xsd:complexType>
1764     <xsd:sequence>
1765       <xsd:element name="ResourceProperty" type="xsd:QName"

```

```

1766         minOccurs="1" maxOccurs="unbounded" />
1767     </xsd:sequence>
1768 </xsd:complexType>
1769 </xsd:element>
1770
1771 <xsd:element name="GetMultipleResourcePropertiesResponse">
1772 <xsd:complexType>
1773 <xsd:sequence>
1774     <xsd:any minOccurs="0" maxOccurs="unbounded" />
1775 </xsd:sequence>
1776 </xsd:complexType>
1777 </xsd:element>
1778
1779 <!-- ===== Message Types for PutResourceProperty ===== -->
1780
1781 <xsd:element name="PutResourcePropertyDocument">
1782 <xsd:complexType>
1783 <xsd:sequence>
1784     <xsd:any minOccurs="1" maxOccurs="1"/>
1785 </xsd:sequence>
1786 </xsd:complexType>
1787 </xsd:element>
1788
1789 <xsd:element name="PutResourcePropertyDocumentResponse">
1790 <xsd:complexType>
1791 <xsd:sequence>
1792     <xsd:any minOccurs="0" maxOccurs="1"/>
1793 </xsd:sequence>
1794 </xsd:complexType>
1795 </xsd:element>
1796
1797 <xsd:complexType name="ResourcePropertyChangeFailureType">
1798 <xsd:sequence>
1799 <xsd:element name="CurrentValue" minOccurs="0" maxOccurs="1">
1800 <xsd:complexType>
1801 <xsd:sequence>
1802     <xsd:any minOccurs="1" maxOccurs="unbounded" />
1803 </xsd:sequence>
1804 </xsd:complexType>
1805 </xsd:element>
1806 <xsd:element name="RequestedValue" minOccurs="0" maxOccurs="1">
1807 <xsd:complexType>
1808 <xsd:sequence>
1809     <xsd:any minOccurs="1" maxOccurs="unbounded" />
1810 </xsd:sequence>
1811 </xsd:complexType>
1812 </xsd:element>
1813 </xsd:sequence>
1814 <xsd:attribute name="Restored" type="xsd:boolean"/>

```

```

1815 </xsd:complexType>
1816
1817 <xsd:complexType
1818   name="UnableToPutResourcePropertyDocumentFaultType">
1819 <xsd:complexContent>
1820 <xsd:extension base="wsrf-bf:BaseFaultType">
1821 <xsd:sequence>
1822 <xsd:element name="ResourcePropertyChangeFailure" type=
1823   "wsrf-rp:ResourcePropertyChangeFailureType"/>
1824 </xsd:sequence>
1825 </xsd:extension>
1826 </xsd:complexContent>
1827 </xsd:complexType>
1828 <xsd:element name="UnableToPutResourcePropertyDocumentFault"
1829   type=
1830   "wsrf-rp:UnableToPutResourcePropertyDocumentFaultType"/>
1831
1832 <!-- ===== Message Types for SetResourceProperties ===== -->
1833
1834 <xsd:complexType name="InsertType">
1835 <xsd:sequence>
1836 <xsd:any processContents="lax"
1837   minOccurs="1" maxOccurs="unbounded" />
1838 </xsd:sequence>
1839 </xsd:complexType>
1840 <xsd:element name="Insert" type="wsrf-rp:InsertType"/>
1841
1842 <xsd:complexType name="UpdateType">
1843 <xsd:sequence>
1844 <xsd:any processContents="lax"
1845   minOccurs="1" maxOccurs="unbounded" />
1846 </xsd:sequence>
1847 </xsd:complexType>
1848 <xsd:element name="Update" type="wsrf-rp:UpdateType"/>
1849
1850 <xsd:complexType name="DeleteType">
1851 <xsd:attribute name="ResourceProperty"
1852   type="xsd:QName" use="required" />
1853 </xsd:complexType>
1854 <xsd:element name="Delete" type="wsrf-rp:DeleteType"/>
1855
1856 <xsd:element name="SetResourceProperties">
1857 <xsd:complexType>
1858 <xsd:choice minOccurs="1" maxOccurs="unbounded">
1859 <xsd:element ref="wsrf-rp:Insert"/>
1860 <xsd:element ref="wsrf-rp:Update"/>
1861 <xsd:element ref="wsrf-rp:Delete"/>
1862 </xsd:choice>
1863 </xsd:complexType>

```



```

1864 </xsd:element>
1865
1866 <xsd:element name="SetResourcePropertiesResponse" >
1867   <xsd:complexType />
1868 </xsd:element>
1869
1870 <xsd:complexType
1871   name="InvalidModificationFaultType">
1872   <xsd:complexContent>
1873     <xsd:extension base="wsrf-bf:BaseFaultType">
1874       <xsd:sequence>
1875         <xsd:element name="ResourcePropertyChangeFailure" type=
1876           "wsrf-rp:ResourcePropertyChangeFailureType"/>
1877       </xsd:sequence>
1878     </xsd:extension>
1879   </xsd:complexContent>
1880 </xsd:complexType>
1881 <xsd:element name=
1882   "InvalidModificationFault"
1883   type=
1884   "wsrf-rp:InvalidModificationFaultType"/>
1885
1886 <xsd:complexType name="UnableToModifyResourcePropertyFaultType">
1887   <xsd:complexContent>
1888     <xsd:extension base="wsrf-bf:BaseFaultType">
1889       <xsd:sequence>
1890         <xsd:element name="ResourcePropertyChangeFailure" type=
1891           "wsrf-rp:ResourcePropertyChangeFailureType"/>
1892       </xsd:sequence>
1893     </xsd:extension>
1894   </xsd:complexContent>
1895 </xsd:complexType>
1896 <xsd:element name="UnableToModifyResourcePropertyFault"
1897   type="wsrf-rp:UnableToModifyResourcePropertyFaultType"/>
1898
1899 <xsd:complexType name="SetResourcePropertyRequestFailedFaultType">
1900   <xsd:complexContent>
1901     <xsd:extension base="wsrf-bf:BaseFaultType">
1902       <xsd:sequence>
1903         <xsd:element name="ResourcePropertyChangeFailure" type=
1904           "wsrf-rp:ResourcePropertyChangeFailureType"/>
1905       </xsd:sequence>
1906     </xsd:extension>
1907   </xsd:complexContent>
1908 </xsd:complexType>
1909 <xsd:element name="SetResourcePropertyRequestFailedFault"
1910   type=
1911   "wsrf-rp:SetResourcePropertyRequestFailedFaultType"/>
1912

```

```

1913 <xsd:complexType name="InsertResourcePropertiesRequestFailedFaultType">
1914 <xsd:complexContent>
1915 <xsd:extension base="wsrf-bf:BaseFaultType">
1916 <xsd:sequence>
1917 <xsd:element name="ResourcePropertyChangeFailure" type=
1918 "wsrf-rp:ResourcePropertyChangeFailureType"/>
1919 </xsd:sequence>
1920 </xsd:extension>
1921 </xsd:complexContent>
1922 </xsd:complexType>
1923 <xsd:element name="InsertResourcePropertiesRequestFailedFault"
1924 type=
1925 "wsrf-rp:InsertResourcePropertiesRequestFailedFaultType"/>
1926
1927 <xsd:complexType name="UpdateResourcePropertiesRequestFailedFaultType">
1928 <xsd:complexContent>
1929 <xsd:extension base="wsrf-bf:BaseFaultType">
1930 <xsd:sequence>
1931 <xsd:element name="ResourcePropertyChangeFailure" type=
1932 "wsrf-rp:ResourcePropertyChangeFailureType"/>
1933 </xsd:sequence>
1934 </xsd:extension>
1935 </xsd:complexContent>
1936 </xsd:complexType>
1937 <xsd:element
1938 name="UpdateResourcePropertiesRequestFailedFault"
1939 type="wsrf-rp:UpdateResourcePropertiesRequestFailedFaultType"/>
1940
1941 <xsd:complexType name="DeleteResourcePropertiesRequestFailedFaultType">
1942 <xsd:complexContent>
1943 <xsd:extension base="wsrf-bf:BaseFaultType">
1944 <xsd:sequence>
1945 <xsd:element name="ResourcePropertyChangeFailure" type=
1946 "wsrf-rp:ResourcePropertyChangeFailureType"/>
1947 </xsd:sequence>
1948 </xsd:extension>
1949 </xsd:complexContent>
1950 </xsd:complexType>
1951 <xsd:element
1952 name="DeleteResourcePropertiesRequestFailedFault"
1953 type="wsrf-rp:DeleteResourcePropertiesRequestFailedFaultType"/>
1954
1955 <!-- ===== Message Types for InsertResourceProperties ===== -->
1956 <xsd:element name="InsertResourceProperties">
1957 <xsd:complexType>
1958 <xsd:sequence>
1959 <xsd:element ref="wsrf-rp:Insert"/>
1960 </xsd:sequence>
1961 </xsd:complexType>

```

```

1962 </xsd:element>
1963
1964 <xsd:element name="InsertResourcePropertiesResponse" >
1965 <xsd:complexType />
1966 </xsd:element>
1967
1968 <!-- ===== Message Types for UpdateResourceProperties ===== -->
1969 <xsd:element name="UpdateResourceProperties">
1970 <xsd:complexType>
1971 <xsd:sequence>
1972 <xsd:element ref="wsrf-rp:Update"/>
1973 </xsd:sequence>
1974 </xsd:complexType>
1975 </xsd:element>
1976
1977 <xsd:element name="UpdateResourcePropertiesResponse" >
1978 <xsd:complexType />
1979 </xsd:element>
1980
1981 <!-- ===== Message Types for DeleteResourceProperties ===== -->
1982 <xsd:element name="DeleteResourceProperties">
1983 <xsd:complexType>
1984 <xsd:sequence>
1985 <xsd:element ref="wsrf-rp:Delete"/>
1986 </xsd:sequence>
1987 </xsd:complexType>
1988 </xsd:element>
1989
1990 <xsd:element name="DeleteResourcePropertiesResponse" >
1991 <xsd:complexType />
1992 </xsd:element>
1993
1994 <!-- ===== Message Types for QueryResourceProperties ===== -->
1995
1996 <xsd:element name="QueryResourceProperties" >
1997 <xsd:complexType>
1998 <xsd:sequence>
1999 <xsd:element ref="wsrf-rp:QueryExpression"
2000 minOccurs="1" maxOccurs="1"/>
2001 </xsd:sequence>
2002 </xsd:complexType>
2003 </xsd:element>
2004
2005 <xsd:element name="QueryResourcePropertiesResponse" >
2006 <xsd:complexType>
2007 <xsd:complexContent mixed="true">
2008 <xsd:restriction base="xsd:anyType">
2009 <xsd:sequence>
2010 <xsd:any processContents="lax"

```

```

2011         minOccurs="1" maxOccurs="unbounded"/>
2012     </xsd:sequence>
2013 </xsd:restriction>
2014 </xsd:complexContent>
2015 </xsd:complexType>
2016 </xsd:element>
2017
2018 <xsd:complexType name="UnknownQueryExpressionDialectFaultType">
2019 <xsd:complexContent>
2020 <xsd:extension base="wsrf-bf:BaseFaultType"/>
2021 </xsd:complexContent>
2022 </xsd:complexType>
2023 <xsd:element name="UnknownQueryExpressionDialectFault"
2024     type="wsrf-rp:UnknownQueryExpressionDialectFaultType"/>
2025
2026 <xsd:complexType name="InvalidQueryExpressionFaultType">
2027 <xsd:complexContent>
2028 <xsd:extension base="wsrf-bf:BaseFaultType"/>
2029 </xsd:complexContent>
2030 </xsd:complexType>
2031 <xsd:element name="InvalidQueryExpressionFault"
2032     type="wsrf-rp:InvalidQueryExpressionFaultType"/>
2033
2034 <xsd:complexType name="QueryEvaluationErrorFaultType">
2035 <xsd:complexContent>
2036 <xsd:extension base="wsrf-bf:BaseFaultType"/>
2037 </xsd:complexContent>
2038 </xsd:complexType>
2039 <xsd:element name="QueryEvaluationErrorFault"
2040     type="wsrf-rp:QueryEvaluationErrorFaultType"/>
2041
2042 </xsd:schema>

```

2043

## Appendix C. WSDL 1.1

2044

The WSDL 1.1 for the Web service methods described in this specification is compliant with WS-I

2045

Basic Profile 1.1 [WS-I] and is included here for convenience. The authoritative version of this

2046

WSDL is available at:

2047

<http://docs.oasis-open.org/wsrf/rpw-2.wsdl>

2048

```
<?xml version="1.0" encoding="utf-8"?>
```

2049

```
<!--
```

2050

2051

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS's procedures with respect to rights in OASIS specifications can be found at the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification, can be obtained from the OASIS Executive Director.

2052

2053

2054

2055

2056

2057

2058

2059

2060

2061

OASIS invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to implement this specification. Please address the information to the OASIS Executive Director.

2062

2063

2064

2065

Copyright (C) OASIS Open (2005). All Rights Reserved.

2066

2067

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works.

2068

2069

2070

2071

However, this document itself may not be modified in any way, such as by removing the copyright notice or references to OASIS, except as needed for the purpose of developing OASIS specifications, in which case the procedures for copyrights defined in the OASIS Intellectual Property Rights document must be followed, or as required to translate it into languages other than English.

2072

2073

2074

2075

2076

2077

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

2078

2079

2080

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

2081

2082

2083

2084

2085

2086

```
-->
```

2087

2088

```
<wsdl:definitions name="WS-ResourceProperties"
```

```

2089 xmlns="http://schemas.xmlsoap.org/wsdl/"
2090 xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
2091 xmlns:xsd="http://www.w3.org/2001/XMLSchema"
2092 xmlns:wsa="http://www.w3.org/2005/08/addressing"
2093 xmlns:wsrf-bf="http://docs.oasis-open.org/wsrf/bf-2"
2094 xmlns:wsrf-rp="http://docs.oasis-open.org/wsrf/rp-2"
2095 xmlns:wsrf-rpw="http://docs.oasis-open.org/wsrf/rpw-2"
2096 xmlns:wsrf-rw="http://docs.oasis-open.org/wsrf/rw-2"
2097 targetNamespace="http://docs.oasis-open.org/wsrf/rpw-2"
2098 >
2099
2100 <!-- ===== Imports ===== -->
2101
2102 <wsdl:import
2103     namespace="http://docs.oasis-open.org/wsrf/rw-2"
2104     location="http://docs.oasis-open.org/wsrf/rw-2.wsdl" />
2105
2106 <!-- ===== Types Definitions ===== -->
2107 <wsdl:types>
2108     <xsd:schema>
2109         <xsd:import
2110             namespace="http://docs.oasis-open.org/wsrf/rp-2"
2111             schemaLocation="http://docs.oasis-open.org/wsrf/rp-2.xsd" />
2112         </xsd:schema>
2113     </wsdl:types>
2114
2115 <!-- ===== GetResourcePropertyDocument =====
2116     GetResourcePropertyDocument()
2117     returns: any
2118 -->
2119 <wsdl:message name="GetResourcePropertyDocumentRequest">
2120     <wsdl:part name="GetResourcePropertyDocumentRequest"
2121         element="wsrf-rp:GetResourcePropertyDocument"/>
2122 </wsdl:message>
2123
2124 <wsdl:message name="GetResourcePropertyDocumentResponse">
2125     <wsdl:part name="GetResourcePropertyDocumentResponse"
2126         element="wsrf-rp:GetResourcePropertyDocumentResponse"/>
2127 </wsdl:message>
2128
2129 <!-- ===== GetResourceProperty =====
2130     GetResourceProperty(QName)
2131     returns: any
2132 -->
2133 <wsdl:message name="GetResourcePropertyRequest">
2134     <wsdl:part name="GetResourcePropertyRequest"
2135         element="wsrf-rp:GetResourceProperty" />
2136 </wsdl:message>
2137

```

```

2138 <wsdl:message name="GetResourcePropertyResponse">
2139   <wsdl:part name="GetResourcePropertyResponse"
2140     element="wsrf-rp:GetResourcePropertyResponse" />
2141 </wsdl:message>
2142
2143 <wsdl:message name="InvalidResourcePropertyQNameFault">
2144   <part name="InvalidResourcePropertyQNameFault"
2145     element="wsrf-rp:InvalidResourcePropertyQNameFault" />
2146 </wsdl:message>
2147
2148 <!-- =====GetMultipleResourceProperties =====
2149 GetMultipleResourceProperties(list of QName)
2150 returns: sequence of any
2151 -->
2152 <wsdl:message name="GetMultipleResourcePropertiesRequest">
2153   <wsdl:part name="GetMultipleResourcePropertiesRequest"
2154     element="wsrf-rp:GetMultipleResourceProperties" />
2155 </wsdl:message>
2156
2157 <wsdl:message name="GetMultipleResourcePropertiesResponse">
2158   <wsdl:part name="GetMultipleResourcePropertiesResponse"
2159     element="wsrf-rp:GetMultipleResourcePropertiesResponse" />
2160 </wsdl:message>
2161 <!-- ===== PutResourcePropertyDocument =====
2162 PutResourcePropertyDocument(any)
2163 returns: any?
2164 -->
2165 <wsdl:message name="PutResourcePropertyDocumentRequest">
2166   <wsdl:part name="PutResourcePropertyDocumentRequest"
2167     element="wsrf-rp:PutResourcePropertyDocument"/>
2168 </wsdl:message>
2169
2170 <wsdl:message name="PutResourcePropertyDocumentResponse">
2171   <wsdl:part name="PutResourcePropertyDocumentResponse"
2172     element="wsrf-rp:PutResourcePropertyDocumentResponse"/>
2173 </wsdl:message>
2174
2175 <wsdl:message name="UnableToPutResourcePropertyDocumentFault">
2176   <part name="UnableToPutResourcePropertyDocumentFault"
2177     element="wsrf-rp:UnableToPutResourcePropertyDocumentFault" />
2178 </wsdl:message>
2179
2180 <!-- ===== SetResourceProperties =====
2181 SetResourceProperties(
2182 { insert (any)* |
2183 update (any)* |
2184 delete@QName } +
2185 )
2186 returns: empty

```

```

2187 -->
2188 <wsdl:message name="SetResourcePropertiesRequest">
2189   <wsdl:part name="SetResourcePropertiesRequest"
2190     element="wsrf-rp:SetResourceProperties" />
2191 </wsdl:message>
2192
2193 <wsdl:message name="SetResourcePropertiesResponse">
2194   <wsdl:part name="SetResourcePropertiesResponse"
2195     element="wsrf-rp:SetResourcePropertiesResponse" />
2196 </wsdl:message>
2197
2198 <wsdl:message name="InvalidModificationFault">
2199   <part name="InvalidModificationFault"
2200     element="wsrf-rp:InvalidModificationFault" />
2201 </wsdl:message>
2202
2203 <wsdl:message name="UnableToModifyResourcePropertyFault">
2204   <part name="UnableToModifyResourcePropertyFault"
2205     element="wsrf-rp:UnableToModifyResourcePropertyFault" />
2206 </wsdl:message>
2207
2208 <wsdl:message name="SetResourcePropertyRequestFailedFault">
2209   <part name="SetResourcePropertyRequestFailedFault"
2210     element="wsrf-rp:SetResourcePropertyRequestFailedFault" />
2211 </wsdl:message>
2212
2213 <!-- ===== InsertResourceProperties =====>
2214 InsertResourceProperties((any)* )
2215 returns: empty
2216 -->
2217 <wsdl:message name="InsertResourcePropertiesRequest">
2218   <wsdl:part name="InsertResourcePropertiesRequest"
2219     element="wsrf-rp:InsertResourceProperties" />
2220 </wsdl:message>
2221
2222 <wsdl:message name="InsertResourcePropertiesResponse">
2223   <wsdl:part name="InsertResourcePropertiesResponse"
2224     element="wsrf-rp:InsertResourcePropertiesResponse" />
2225 </wsdl:message>
2226
2227 <wsdl:message name="InsertResourcePropertiesRequestFailedFault">
2228   <part name="InsertResourcePropertiesRequestFailedFault"
2229     element="wsrf-rp:InsertResourcePropertiesRequestFailedFault" />
2230 </wsdl:message>
2231
2232 <!-- ===== UpdateResourceProperties =====>
2233 UpdateResourceProperties((any)* )
2234 returns: empty
2235 -->

```



```

2236 <wsdl:message name="UpdateResourcePropertiesRequest">
2237   <wsdl:part name="UpdateResourcePropertiesRequest"
2238     element="wsrf-rp:UpdateResourceProperties" />
2239 </wsdl:message>
2240
2241 <wsdl:message name="UpdateResourcePropertiesResponse">
2242   <wsdl:part name="UpdateResourcePropertiesResponse"
2243     element="wsrf-rp:UpdateResourcePropertiesResponse" />
2244 </wsdl:message>
2245
2246 <wsdl:message name="UpdateResourcePropertiesRequestFailedFault">
2247   <part name="UpdateResourcePropertiesRequestFailedFault"
2248     element="wsrf-rp:UpdateResourcePropertiesRequestFailedFault" />
2249 </wsdl:message>
2250
2251 <!-- ===== DeleteResourceProperties =====
2252 DeleteResourceProperties( ResourceProperty )
2253 returns: empty
2254 -->
2255 <wsdl:message name="DeleteResourcePropertiesRequest">
2256   <wsdl:part name="DeleteResourcePropertiesRequest"
2257     element="wsrf-rp:DeleteResourceProperties" />
2258 </wsdl:message>
2259
2260 <wsdl:message name="DeleteResourcePropertiesResponse">
2261   <wsdl:part name="DeleteResourcePropertiesResponse"
2262     element="wsrf-rp:DeleteResourcePropertiesResponse" />
2263 </wsdl:message>
2264
2265 <wsdl:message name="DeleteResourcePropertiesRequestFailedFault">
2266   <part name="DeleteResourcePropertiesRequestFailedFault"
2267     element="wsrf-rp:DeleteResourcePropertiesRequestFailedFault" />
2268 </wsdl:message>
2269
2270 <!-- ===== QueryResourceProperties =====
2271 QueryResourceProperties(QueryExpression)
2272 returns: any
2273 -->
2274 <wsdl:message name="QueryResourcePropertiesRequest">
2275   <wsdl:part name="QueryResourcePropertiesRequest"
2276     element="wsrf-rp:QueryResourceProperties" />
2277 </wsdl:message>
2278
2279 <wsdl:message name="QueryResourcePropertiesResponse">
2280   <wsdl:part name="QueryResourcePropertiesResponse"
2281     element="wsrf-rp:QueryResourcePropertiesResponse" />
2282 </wsdl:message>
2283
2284 <wsdl:message name="UnknownQueryExpressionDialectFault">

```

```

2285     <part name="UnknownQueryExpressionDialectFault"
2286         element="wsrf-rp:UnknownQueryExpressionDialectFault" />
2287 </wsdl:message>
2288
2289 <wsdl:message name="InvalidQueryExpressionFault">
2290     <part name="InvalidQueryExpressionFault"
2291         element="wsrf-rp:InvalidQueryExpressionFault" />
2292 </wsdl:message>
2293
2294 <wsdl:message name="QueryEvaluationErrorFault">
2295     <part name="QueryEvaluationErrorFault"
2296         element="wsrf-rp:QueryEvaluationErrorFault" />
2297 </wsdl:message>
2298
2299 <!-- ===== PortType Definitions ===== -->
2300 <wsdl:portType name="GetResourcePropertyDocument">
2301     <wsdl:operation name="GetResourcePropertyDocument">
2302         <wsdl:input name="GetResourcePropertyDocumentRequest"
2303             message="wsrf-rpw:GetResourcePropertyDocumentRequest"/>
2304         <wsdl:output name="GetResourcePropertyDocumentResponse"
2305             message="wsrf-rpw:GetResourcePropertyDocumentResponse"/>
2306         <wsdl:fault name="ResourceUnknownFault"
2307             message="wsrf-rw:ResourceUnknownFault"/>
2308         <wsdl:fault name="ResourceUnavailableFault"
2309             message="wsrf-rw:ResourceUnavailableFault"/>
2310     </wsdl:operation>
2311 </wsdl:portType>
2312
2313 <wsdl:portType name="GetResourceProperty">
2314     <wsdl:operation name="GetResourceProperty">
2315         <wsdl:input name="GetResourcePropertyRequest"
2316             message="wsrf-rpw:GetResourcePropertyRequest" />
2317         <wsdl:output name="GetResourcePropertyResponse"
2318             message="wsrf-rpw:GetResourcePropertyResponse" />
2319         <wsdl:fault name="ResourceUnknownFault"
2320             message="wsrf-rw:ResourceUnknownFault"/>
2321         <wsdl:fault name="ResourceUnavailableFault"
2322             message="wsrf-rw:ResourceUnavailableFault"/>
2323         <wsdl:fault name="InvalidResourcePropertyQNameFault"
2324             message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2325     </wsdl:operation>
2326 </wsdl:portType>
2327
2328 <wsdl:portType name="GetMultipleResourceProperties">
2329     <wsdl:operation name="GetMultipleResourceProperties">
2330         <wsdl:input name="GetMultipleResourcePropertiesRequest"
2331             message="wsrf-rpw:GetMultipleResourcePropertiesRequest" />
2332         <wsdl:output name="GetMultipleResourcePropertiesResponse"
2333             message="wsrf-rpw:GetMultipleResourcePropertiesResponse" />

```

```

2334 <wsdl:fault name="ResourceUnknownFault"
2335     message="wsrf-rw:ResourceUnknownFault"/>
2336 <wsdl:fault name="ResourceUnavailableFault"
2337     message="wsrf-rw:ResourceUnavailableFault"/>
2338 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2339     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2340 </wsdl:operation>
2341 </wsdl:portType>
2342
2343 <wsdl:portType name="PutResourcePropertyDocument">
2344 <wsdl:operation name="PutResourcePropertyDocument">
2345 <wsdl:input name="PutResourcePropertyDocumentRequest"
2346     message="wsrf-rpw:PutResourcePropertyDocumentRequest" />
2347 <wsdl:output name="PutResourcePropertyDocumentResponse"
2348     message="wsrf-rpw:PutResourcePropertyDocumentResponse" />
2349 <wsdl:fault name="ResourceUnknownFault"
2350     message="wsrf-rw:ResourceUnknownFault"/>
2351 <wsdl:fault name="ResourceUnavailableFault"
2352     message="wsrf-rw:ResourceUnavailableFault"/>
2353 <wsdl:fault name="UnableToPutResourcePropertyDocumentFault"
2354     message="wsrf-rpw:UnableToPutResourcePropertyDocumentFault" />
2355 </wsdl:operation>
2356 </wsdl:portType>
2357
2358 <wsdl:portType name="SetResourceProperties">
2359 <wsdl:operation name="SetResourceProperties">
2360 <wsdl:input name="SetResourcePropertiesRequest"
2361     message="wsrf-rpw:SetResourcePropertiesRequest" />
2362 <wsdl:output name="SetResourcePropertiesResponse"
2363     message="wsrf-rpw:SetResourcePropertiesResponse" />
2364 <wsdl:fault name="ResourceUnknownFault"
2365     message="wsrf-rw:ResourceUnknownFault"/>
2366 <wsdl:fault name="ResourceUnavailableFault"
2367     message="wsrf-rw:ResourceUnavailableFault"/>
2368 <wsdl:fault name="InvalidModificationFault"
2369     message="wsrf-rpw:InvalidModificationFault" />
2370 <wsdl:fault name="UnableToModifyResourcePropertyFault"
2371     message="wsrf-rpw:UnableToModifyResourcePropertyFault" />
2372 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2373     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2374 <wsdl:fault name="SetResourcePropertyRequestFailedFault"
2375     message="wsrf-rpw:SetResourcePropertyRequestFailedFault" />
2376 </wsdl:operation>
2377 </wsdl:portType>
2378
2379 <wsdl:portType name="InsertResourceProperties">
2380 <wsdl:operation name="InsertResourceProperties">
2381 <wsdl:input name="InsertResourcePropertiesRequest"
2382     message="wsrf-rpw:InsertResourcePropertiesRequest" />

```

```

2383 <wsdl:output name="InsertResourcePropertiesResponse"
2384     message="wsrf-rpw:InsertResourcePropertiesResponse" />
2385 <wsdl:fault name="ResourceUnknownFault"
2386     message="wsrf-rw:ResourceUnknownFault"/>
2387 <wsdl:fault name="ResourceUnavailableFault"
2388     message="wsrf-rw:ResourceUnavailableFault"/>
2389 <wsdl:fault name="InvalidModificationFault"
2390     message="wsrf-rpw:InvalidModificationFault" />
2391 <wsdl:fault name="UnableToModifyResourcePropertyFault"
2392     message="wsrf-rpw:UnableToModifyResourcePropertyFault" />
2393 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2394     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2395 <wsdl:fault name="InsertResourcePropertiesRequestFailedFault"
2396     message="wsrf-rpw:InsertResourcePropertiesRequestFailedFault" />
2397 </wsdl:operation>
2398 </wsdl:portType>
2399
2400 <wsdl:portType name="UpdateResourceProperties">
2401 <wsdl:operation name="UpdateResourceProperties">
2402 <wsdl:input name="UpdateResourcePropertiesRequest"
2403     message="wsrf-rpw:UpdateResourcePropertiesRequest" />
2404 <wsdl:output name="UpdateResourcePropertiesResponse"
2405     message="wsrf-rpw:UpdateResourcePropertiesResponse" />
2406 <wsdl:fault name="ResourceUnknownFault"
2407     message="wsrf-rw:ResourceUnknownFault"/>
2408 <wsdl:fault name="ResourceUnavailableFault"
2409     message="wsrf-rw:ResourceUnavailableFault"/>
2410 <wsdl:fault name="InvalidModificationFault"
2411     message="wsrf-rpw:InvalidModificationFault" />
2412 <wsdl:fault name="UnableToModifyResourcePropertyFault"
2413     message="wsrf-rpw:UnableToModifyResourcePropertyFault" />
2414 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2415     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2416 <wsdl:fault name="UpdateResourcePropertiesRequestFailedFault"
2417     message="wsrf-rpw:UpdateResourcePropertiesRequestFailedFault" />
2418 </wsdl:operation>
2419 </wsdl:portType>
2420
2421 <wsdl:portType name="DeleteResourceProperties">
2422 <wsdl:operation name="DeleteResourceProperties">
2423 <wsdl:input name="DeleteResourcePropertiesRequest"
2424     message="wsrf-rpw:DeleteResourcePropertiesRequest" />
2425 <wsdl:output name="DeleteResourcePropertiesResponse"
2426     message="wsrf-rpw:DeleteResourcePropertiesResponse" />
2427 <wsdl:fault name="ResourceUnknownFault"
2428     message="wsrf-rw:ResourceUnknownFault"/>
2429 <wsdl:fault name="ResourceUnavailableFault"
2430     message="wsrf-rw:ResourceUnavailableFault"/>
2431 <wsdl:fault name="InvalidModificationFault"

```

```

2432     message="wsrf-rpw:InvalidModificationFault" />
2433 <wsdl:fault name="UnableToModifyResourcePropertyFault"
2434     message="wsrf-rpw:UnableToModifyResourcePropertyFault" />
2435 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2436     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2437 <wsdl:fault name="DeleteResourcePropertiesRequestFailedFault"
2438     message="wsrf-rpw:DeleteResourcePropertiesRequestFailedFault" />
2439 </wsdl:operation>
2440 </wsdl:portType>
2441
2442 <wsdl:portType name="QueryResourceProperties"
2443     wsrf-rp:ResourceProperties="wsrf-rp:QueryExpressionRPDocument">
2444 <wsdl:operation name="QueryResourceProperties">
2445 <wsdl:input name="QueryResourcePropertiesRequest"
2446     message="wsrf-rpw:QueryResourcePropertiesRequest" />
2447 <wsdl:output name="QueryResourcePropertiesResponse"
2448     message="wsrf-rpw:QueryResourcePropertiesResponse" />
2449 <wsdl:fault name="ResourceUnknownFault"
2450     message="wsrf-rw:ResourceUnknownFault"/>
2451 <wsdl:fault name="ResourceUnavailableFault"
2452     message="wsrf-rw:ResourceUnavailableFault"/>
2453 <wsdl:fault name="InvalidResourcePropertyQNameFault"
2454     message="wsrf-rpw:InvalidResourcePropertyQNameFault" />
2455 <wsdl:fault name="UnknownQueryExpressionDialectFault"
2456     message="wsrf-rpw:UnknownQueryExpressionDialectFault" />
2457 <wsdl:fault name="InvalidQueryExpressionFault"
2458     message="wsrf-rpw:InvalidQueryExpressionFault" />
2459 <wsdl:fault name="QueryEvaluationErrorFault"
2460     message="wsrf-rpw:QueryEvaluationErrorFault" />
2461 </wsdl:operation>
2462
2463 </wsdl:portType>
2464
2465 </wsdl:definitions>

```

## Appendix D. Revision History

Rev	Date	By Whom	What
wd-01	2004-05-18	Steve Graham	Initial version created from submission by contributing companies. Minor modifications made to reflect OASIS formatting and the following issues: WSRF2, WSRF3, WSRF14, WSRF33.
wd-02	2004-05-31	Steve Graham, Jem Treadwell	Mods to draft 01, including hyphenation, clarification of acknowledgements section
wd-03	2004-06-04	Steve Graham	Reformat rogue Veranda text with Arial.
wd-04	2004-06-07	Steve Graham	Base faults comment on faults (align with ResourceLifetime), update date URIs to 2004/06, update URLs in references to point to .pdfs, update Acknowledgements
wd-05	2004-07-19	Jem Treadwell	Changed [State Paper] & [WS-Notification] references to public URLs.
wd-06 (wd-05.b)	2004-09-17	Steve Graham	WSRF15, WSRF16, WSRF21
wd-05.c	2004-11-22	Jem Treadwell Steve Graham	Confirm WSRF15. WSRF16, WSRF21, fix up some small typos (Jem), verify typos fixes are correct and reversion to 05.c (sgg)
wd-05.d	2004-11-22	Steve Graham	Incorporate Chairman's editorial modifications (from Ian Robinson) on Title page, namespace URIs and References section.  Incorporate changes due to adoption of WS-Resource specification.  Addresses: WSRF4, WSRF24, WSRF27, WSRF30, WSRF43, WSRF49, WSRF53, WSRF56
wd-05.e	2004-11-26	Ian Robinson	Handful of typos corrected.
wd-05	2004-11-30	Steve Graham	Final typos accepted, PDF generated.
wd-06.a	2005-02-18	Steve Graham	WSRF25, WSRF51, WSRF55, WSRF62, WSRF63, WSRF68, WSRF72, WSRF79, WSRF81, WSRF83, WSRF86, WSRF93, WSRF95, WSRF96

Rev	Date	By Whom	What
wd-06.b	2005-02-25	Jem Treadwell	Few minor typos etc. corrected.
wd-06.c	2005-03-07	Jem Treadwell	Updated wsa namespace reference.
wd-06.d	2005-03-24	Ian Robinson	Added ResourcePropertyChangeFailure type to schema
wd-07.a	2005-05-16	Steve Graham	91, 92 (no changes required), 97, 98, 99, 101, 102, 103
wd-07.c	2005-05-17	Steve Graham	100, 109
wd-07.d	2005-05-17	Steve Graham	113
wd-07.e	2005-05-18	Steve Graham	Updates to 114, per Ian Robinson and F2F discussion.
wd-07.f	2005-05-18	Steve Graham	WSRF 91,97,99,100,101,102, 103
wd-07.g	2005-06-10	Steve Graham	Minor typos as reported by Hideharu Kato, a few additional related typos, update references to WS-Notification, update Acknowledgements.
pr-01	2005-06-10	Steve Graham	Change status to PR
wd-08	2005-09-06	Ian Robinson	127. TopicSpace->Topic Namespace
wd-09	2005-09-15	Steve Graham	Remove unused references and use hyperlinks for references, namespace URIs from -1 to -2, namespace locations now include .xsd and .wsdl WSRF 141, 152, 125, 126 (no action due to WSRF 140), 132, 133, 134, 135, 136, 138, 140, 143, 144, 146, 147
pr-02.a	2005-11-18	Jem Treadwell	158: Added wsnt prefix and fixed a few nits.
pr-02.b	2005-11-28	Jem Treadwell	Fixed minor typos.
pr-02.c	2006-01-11	Ian Robinson	Fixed wsnt namespace reference

2467

## Appendix E. Notices

2468 OASIS takes no position regarding the validity or scope of any intellectual property or other rights  
2469 that might be claimed to pertain to the implementation or use of the technology described in this  
2470 document or the extent to which any license under such rights might or might not be available;  
2471 neither does it represent that it has made any effort to identify any such rights. Information on  
2472 OASIS's procedures with respect to rights in OASIS specifications can be found at the OASIS  
2473 website. Copies of claims of rights made available for publication and any assurances of licenses  
2474 to be made available, or the result of an attempt made to obtain a general license or permission  
2475 for the use of such proprietary rights by implementors or users of this specification, can be  
2476 obtained from the OASIS Executive Director.

2477

2478 OASIS invites any interested party to bring to its attention any copyrights, patents or patent  
2479 applications, or other proprietary rights which may cover technology that may be required to  
2480 implement this specification. Please address the information to the OASIS Executive Director.

2481

2482 Copyright (C) OASIS Open (2005). All Rights Reserved.

2483

2484 This document and translations of it may be copied and furnished to others, and derivative works  
2485 that comment on or otherwise explain it or assist in its implementation may be prepared, copied,  
2486 published and distributed, in whole or in part, without restriction of any kind, provided that the  
2487 above copyright notice and this paragraph are included on all such copies and derivative works.  
2488 However, this document itself may not be modified in any way, such as by removing the copyright  
2489 notice or references to OASIS, except as needed for the purpose of developing OASIS  
2490 specifications, in which case the procedures for copyrights defined in the OASIS Intellectual  
2491 Property Rights document must be followed, or as required to translate it into languages other  
2492 than English.

2493

2494 The limited permissions granted above are perpetual and will not be revoked by OASIS or its  
2495 successors or assigns.

2496

2497 This document and the information contained herein is provided on an "AS IS" basis and OASIS  
2498 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO  
2499 ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE  
2500 ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A  
2501 PARTICULAR PURPOSE.