



# Cloud Application Management for Platforms (CAMP) Test Assertions Version 1.1

## Committee Specification Draft 02 / Public Review Draft 02

27 August 2014

### Specification URIs

#### This version:

<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd02/camp-ta-v1.1-csprd02.pdf> (Authoritative)  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd02/camp-ta-v1.1-csprd02.html>  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd02/camp-ta-v1.1-csprd02.doc>

#### Previous version:

<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd01/camp-ta-v1.1-csprd01.pdf> (Authoritative)  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd01/camp-ta-v1.1-csprd01.html>  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd01/camp-ta-v1.1-csprd01.doc>

#### Latest version:

<http://docs.oasis-open.org/camp/camp-ta/v1.1/camp-ta-v1.1.pdf> (Authoritative)  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/camp-ta-v1.1.html>  
<http://docs.oasis-open.org/camp/camp-ta/v1.1/camp-ta-v1.1.doc>

#### Technical Committee:

OASIS Cloud Application Management for Platforms (CAMP) TC

#### Chair:

Martin Chapman ([martin.chapman@oracle.com](mailto:martin.chapman@oracle.com)), Oracle

#### Editors:

Jacques Durand ([jdurand@us.fujitsu.com](mailto:jdurand@us.fujitsu.com)), Fujitsu Limited  
Gilbert Pilz ([gilbert.pilz@oracle.com](mailto:gilbert.pilz@oracle.com)), Oracle  
Adrian Otto ([adrian.otto@rackspace.com](mailto:adrian.otto@rackspace.com)), Rackspace Hosting, Inc.  
Tom Rutt ([trutt@us.fujitsu.com](mailto:trutt@us.fujitsu.com)), Fujitsu Limited

#### Related work:

This specification is related to:

- *Cloud Application Management for Platforms Version 1.1*. Edited by Jacques Durand, Adrian Otto, Gilbert Pilz, and Tom Rutt. Latest version: <http://docs.oasis-open.org/camp/camp-spec/v1.1/camp-spec-v1.1.html>.

#### Abstract:

This document defines the Test Assertions for version 1.1 of the OASIS Cloud Application Management for Platforms (CAMP) specification. Test Assertions are testable or measurable expressions related to normative statements in a specification for evaluating if an implementation (or part of it) conforms to this specification. These Test Assertions are intended to be used for defining precisely the conditions required by a CAMP implementation in order to conform. They

support the testing activity by acting as a bridge between the normative statements in the specification and the executable test cases that are parts of a conformance test suite.

**Status:**

This document was last revised or approved by the OASIS Cloud Application Management for Platforms (CAMP) TC on the above date. The level of approval is also listed above. Check the “Latest version” location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at [https://www.oasis-open.org/committees/tc\\_home.php?wg\\_abbrev=camp#technical](https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=camp#technical).

TC members should send comments on this specification to the TC’s email list. Others should send comments to the TC by using the “[Send A Comment](#)” button on the Technical Committee’s web page at <https://www.oasis-open.org/committees/camp/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<https://www.oasis-open.org/committees/camp/ipr.php>).

**Citation format:**

When referencing this specification the following citation format should be used:

**[CAMP-Test-Assertions-v1.1]**

*Cloud Application Management for Platforms (CAMP) Test Assertions Version 1.1*. Edited by Jacques Durand, Gilbert Pilz, Adrian Otto, and Tom Rutt. 27 August 2014. OASIS Committee Specification Draft 02 / Public Review Draft 02. <http://docs.oasis-open.org/camp/camp-ta/v1.1/csprd02/camp-ta-v1.1-csprd02.html>. Latest version: <http://docs.oasis-open.org/camp/camp-ta/v1.1/camp-ta-v1.1.html>.

---

# Notices

Copyright © OASIS Open 2014. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

---

# Table of Contents

1	Introduction.....	9
1.1	Normative References .....	9
1.2	Non-Normative References .....	9
2	Test Assertions Design and Objectives.....	10
2.1	Testing Objectives .....	10
2.2	Design Principles .....	10
2.3	Anatomy of a Test Assertion.....	11
2.3.1	Core Elements.....	11
	<b>Target</b> .....	11
	<b>Predicate</b> .....	12
2.3.2	Optional Elements .....	12
	<b>Description</b> .....	12
	<b>Prescription Level</b> .....	12
	<b>Prerequisite</b> .....	12
	<b>Tags</b> .....	12
2.3.3	Example Test Assertion .....	12
2.3.4	CAMP Profile .....	13
2.4	Categories of Test Assertions.....	13
2.5	Notational Conventions.....	14
2.5.1	Identification scheme for Test Assertions .....	14
2.5.2	Identifying a message inside a Test Assertion.....	14
2.5.3	Identifying an attribute of a resource in a message .....	14
(m2)	platform.assemblies_uri.....	15
2.6	Coverage of the Specification.....	15
3	Test Assertions.....	16
3.1	Provider Test Assertions.....	16
3.1.1	Basic Schema Compliance for Platform Resources, Provider Side.....	16
3.1.1.1	platform_endpoints Serialization (CAMP11-101) .....	16
3.1.1.2	platform_endpoint Serialization (CAMP11-102) .....	16
3.1.1.3	platform Serialization (CAMP11-103).....	17
3.1.1.4	service Serialization (CAMP11-104).....	17
3.1.2	Basic Schema Compliance for Application Resources .....	17
3.1.2.1	assembly Serialization (CAMP11-111).....	17
3.1.2.2	component Serialization (CAMP11-112) .....	18
3.1.2.3	plan Serialization (CAMP11-113) .....	18
3.1.3	Consistency of Serialization with Metadata.....	19
3.1.3.1	Consistent Use of Formats (CAMP11-114).....	19
3.1.3.2	Consistent Use of type_definition Names (CAMP11-150).....	19
3.1.3.3	Inheritance from camp_resource (CAMP11-151).....	20
3.1.3.4	Non-Mutability Enforcement (Provider) (CAMP11-115).....	20
3.1.4	Metadata Integrity and Serialization .....	21
3.1.4.1	parameters_definitions Serialization and Integrity (CAMP11-117) .....	21
3.1.4.2	parameters_definition Serialization and Integrity (CAMP11-118) .....	21

3.1.4.3	formats	Serialization (CAMP11-119)	22
3.1.4.4	format	Serialization (CAMP11-120)	22
3.1.4.5	Presence of JSON Format	(CAMP11-121)	22
3.1.4.6	Position of JSON Format	(CAMP11-122)	23
3.1.4.7	type_definitions	Serialization (CAMP11-123)	23
3.1.4.8	type_definition	Serialization (CAMP11-124)	23
3.1.4.9	attribute_definition	Serialization (CAMP11-125)	24
<b>TA_Id:</b>	CAMP11-125		24
3.1.5	Various Model Referential and Semantic Constraints		24
3.1.5.1	type_definitions	Reference in platform Resource (CAMP11-126)	24
3.1.5.2	platform_endpoint	and specification_version (CAMP11-127)	24
3.1.5.3	Platform	specification_version (CAMP11-128)	25
3.1.5.4	platform_endpoint	and platform matching specification_version (CAMP11-129)	25
3.1.5.5	platform_endpoint	and platform matching implementation_version (CAMP11-130)	25
3.1.5.6	Cross-References	platform_endpoints and platform (CAMP11-131)	26
<b>TA_Id:</b>	CAMP11-131		26
3.1.5.7	Parameter Definition for pdp_uri or plan_uri in assemblies	(CAMP11-132)	26
3.1.5.8	Parameter Definition for pdp_uri or plan_uri in plans	(CAMP11-152)	27
3.1.5.9	Required Parameter Definitions in service	(CAMP11-134)	27
<b>TA_Id:</b>	CAMP11-134		27
3.1.5.10	UTC Timestamps, Provider side	(CAMP11-136)	28
3.1.5.11	representation_skew	Content (CAMP11-137)	28
3.1.5.12	References to format	Resources associated with a platform (CAMP11-140)	28
3.1.5.13	Presence of format	Resources for every Supported Format (CAMP11-149)	29
3.1.5.14	Presence of type_definition	Resources associated with a Platform (CAMP11-141)	29
3.1.5.15	Inheritance of type_definition	Resources (CAMP11-148)	29
<b>TA_Id:</b>	CAMP11-148		30
3.1.5.16	Presence of attribute_definition	Resources associated with a Platform (CAMP11-142)	30
3.1.5.17	Presence of extension	Resources associated with a Platform (1) (CAMP11-143)	30
3.1.5.18	Presence of extension	Resources associated with a Platform (2) (CAMP11-144)	31
3.1.5.19	Presence of extensions	Resource associated with a platform (CAMP11-145)	31
3.1.5.20	Unique Name of extension	Resources associated with a Platform (CAMP11-146)	32
3.1.5.21	Presence of an extension	Resource advertising Support for Plans (CAMP11-147)	32
3.1.6	Support for HTTP Methods		32
3.1.6.1	GET method	(CAMP11-201)	32
3.1.6.2	PDP Registration by reference, Provider side	(CAMP11-410)	33
3.1.6.3	Supported HTTP Post for PDP or Plan Registration by Reference: Provider side	(CAMP11-435)	33
3.1.6.4	Supported HTTP Post for PDP or Plan Registration by value: Provider side	(CAMP11-436)	33
3.1.6.5	Supported HTTP Post for Application Deployment by value: Provider side	(CAMP11-434)	34
3.1.6.6	HTTP POST support for operation	Resource (1) (CAMP11-311)	34
<b>Predicate:</b>	the HTTP code in target (m2) is NOT 405 "Method Not Allowed"		34
3.1.7	Support for JSON		35
3.1.7.1	JSON media-type for Resources (1)	(CAMP11-202)	35
3.1.7.2	JSON media-type for Deployments of Applications (1)	(CAMP11-220)	35
3.1.7.3	JSON media-type for Plan Registration (1)	(CAMP11-221)	35
3.1.7.4	Duplicate Keys in JSON, Provider side	(CAMP11-204)	35

3.1.7.5 Duplicate Keys in JSON, Provider side, Error generation (CAMP11-205).....	36
3.1.8 Resource Queries and HTTP .....	36
3.1.8.1 select_attr Positive Case Provider side (CAMP11-206).....	36
3.1.8.2 select_attr Negative Case, GET (CAMP11-208).....	36
3.1.8.3 select_attr Positive Case, PUT (CAMP11-222a).....	37
3.1.8.4 select_attr Positive Case, PUT (CAMP11-222b).....	37
3.1.8.5 select_attr Positive Case, PUT (CAMP11-222c).....	38
3.1.8.6 select_attr Negative Case, PUT (CAMP11-209) .....	38
3.1.9 Resource Updates.....	38
3.1.9.1 ETag HTTP Header in Responses (CAMP11-211) .....	38
3.1.9.2 If-Match semantics (CAMP11-212) .....	39
3.1.9.3 PUT semantics, regular, Provider (1)( CAMP11-213).....	39
3.1.9.4 PUT semantics, regular, Provider (2) (CAMP11-214).....	40
3.1.9.5 PUT semantics, Immutable attributes, Provider (CAMP11-216).....	40
3.1.9.6 PATCH support, Provider (CAMP11-218) .....	41
3.1.9.7 PATCH semantics, Provider (CAMP11-219).....	41
3.1.10 Resource Creation and Consistency of Representations .....	42
3.1.10.1 Creation of a plan by Reference (1) (CAMP11-301).....	42
3.1.10.2 Creation of a plan by Reference (2) (CAMP11-321).....	42
3.1.10.3 Consistency of assemblies Links after Deployment of a PDP by Reference (CAMP11-302) .....	42
3.1.10.4 Consistency of assemblies Links after Deployment of a PDP or Plan by Value (CAMP11-303)....	43
3.1.10.5 Effective Creation of an assembly (2), setting Links (CAMP11-306).....	43
3.1.10.6 Direct Creation of a component (1) (CAMP11-310).....	44
3.1.11 Use of Parameters .....	44
3.1.11.1 Consistent Use of Parameters in POST (CAMP11-312) .....	44
3.1.11.2 Acceptable Value of Parameters in POST (CAMP11-313).....	44
3.1.12 Resource Deletion.....	45
3.1.12.1 HTTP-level Deletion of an assembly Resource (CAMP11-317) .....	45
3.1.12.2 Effective Deletion of an assembly resource (CAMP11-318).....	45
3.1.12.3 Effective Deletion of component Resources of an assembly Resource (CAMP11-340) .....	46
3.1.12.4 Effective Deletion of a component Resource (CAMP11-320).....	46
3.1.12.5 HTTP Deletion of a component Resource (CAMP11-323) .....	47
<b>Predicate:</b> the target message has NOT an HTTP code 405 “Method Not Allowed” .....	47
3.1.13 Representation Skew Semantics .....	47
3.1.13.1 representation_skew Semantics (1) (CAMP11-329).....	47
3.1.13.2 representation_skew Semantics (2) (CAMP11-330).....	48
3.1.13.3 representation_skew Semantics (3) (CAMP11-331).....	48
3.1.13.4 representation_skew Semantics (4) (CAMP11-332).....	49
3.1.13.5 representation_skew Semantics (5) (CAMP11-333).....	49
3.1.14 PDP and Plan Registration.....	50
3.1.14.1 PDP Registration by Reference: Provider side (1) (CAMP11-412).....	50
3.1.14.2 PDP Registration by Reference: Provider side (2) (CAMP11-414).....	50
3.1.14.3 PDP Registration by Reference: Provider side (CAMP11-425).....	50
3.1.14.4 PDP Registration by Value: Provider side (1) (CAMP11-418) .....	51
3.1.14.5 PDP Registration by Value: Provider side (2) (CAMP11-413).....	51
3.1.14.6 PDP Registration by Value: Provider side (2) (CAMP11-419).....	52

3.1.14.7 Plan Registration by Value using MIME Provider side (CAMP11-433).....	52
3.1.14.8 PDP Registration by Value using MIME Provider side (CAMP11-437) .....	52
3.1.14.9 PDP Registration: URI scheme for Artifact Content Reference (1) (CAMP11-415).....	53
3.1.14.10 PDP Registration: PDP scheme for Artifact Content Reference (Provider) (CAMP11-417) .....	53
3.1.14.11 Registering PDP by Value with .zip format (CAMP11-422) .....	53
3.1.14.12 Registering a PDP by Value with .tar format (CAMP11-423).....	54
3.1.14.13 Registering a PDP by Value with .tar.gz format (CAMP11-424).....	54
3.1.15 Application Deployment.....	55
3.1.15.1 Application Deployment by Reference: Provider side (1) (CAMP11-439) .....	55
3.1.15.2 Application Deployment by Reference: Provider side (2) (CAMP11-440) .....	55
3.1.15.3 Application Deployment by Value: Provider side (1) (CAMP11-441).....	55
3.1.15.4 Application Deployment by Value: Provider side (2) (CAMP11-442).....	56
3.1.15.5 Application Deployment by Value using MIME: Provider side (CAMP11-443) .....	56
3.1.15.6 Creation of <code>plan</code> Resource when Deploying an Application (1) (CAMP11-444).....	56
<b>NormativeSource: RMR-11</b> .....	57
3.2 Consumer Test Assertions .....	57
3.2.1 Basic Schema Compliance for Platform Resources, Consumer Side .....	57
3.2.1.1 Resource Serialization with PUT (CAMP11-105) .....	57
3.2.2 Consistency of Serialization with Metadata.....	57
3.2.2.1 Non-Mutability Enforcement (Consumer) (CAMP11-116) .....	57
3.2.3 Various Model Referential and Semantic Constraints .....	58
3.2.3.1 UTC Timestamps, Consumer side (CAMP11-135).....	58
3.2.4 Support for JSON .....	58
3.2.4.1 Duplicate Keys in JSON, Consumer side (CAMP11-203) .....	58
3.2.5 Resource Queries and HTTP .....	59
3.2.5.1 <code>select_attr</code> Positive Case Consumer side (CAMP11-207) .....	59
3.2.6 Resource Updates.....	59
3.2.6.1 If-Match HTTP Header in PUT Requests (CAMP11-210).....	59
3.2.6.2 PUT Semantics, Immutable Attributes, Consumer (CAMP11-215) .....	59
3.2.6.3 PATCH syntax, Consumer (CAMP11-217).....	60
3.2.7 PDP and Plan Contents .....	60
3.2.7.1 PDP Content by Reference, Consumer side (1) (CAMP11-401).....	60
3.2.7.2 PDP Content, by Reference, Consumer side (2) (CAMP11-402) .....	61
3.2.7.3 PDP Content by Value, Consumer side (1) (CAMP11-403) .....	61
3.2.7.4 PDP Content by Value, Consumer side (2) (CAMP11-404) .....	61
3.2.7.5 Plan Content, Consumer side (1) (CAMP11-405) .....	62
3.2.7.6 Plan Content, Consumer side (2) (CAMP11-406) .....	62
3.2.7.7 Plan Content, Consumer side (3) (CAMP11-430) .....	62
3.2.7.8 Plan Content, Consumer side (4) (CAMP11-431) .....	62
3.2.7.9 Plan Artifact Type Content Specification, Consumer side (CAMP11-407) .....	63
3.2.7.10 PDP Manifest, Consumer side (CAMP11-408).....	63
3.2.7.11 PDP Certificate, Consumer side (CAMP11-409).....	63
3.2.8 PDP and Plan Registration.....	64
3.2.8.1 PDP Registration: <code>pdp</code> scheme for Artifact Content reference (Consumer) (CAMP11-416).....	64
3.3 PDP and Plan Test Assertions .....	64
3.3.1 PDP Test Assertions .....	64
3.3.1.1 PDP and YAML Plan (CAMP11-401b) .....	64

3.3.1.2 PDP and Plan file (CAMP11-402b).....	64
3.3.1.3 PDP Manifest (CAMP11-408b).....	65
3.3.1.4 PDP Certificate (CAMP11-409b).....	65
3.3.2 Plan Test Assertions .....	65
3.3.2.1 Plan File Content (1) (CAMP11-405b).....	65
3.3.2.2 Plan CAMP version (CAMP11-406b).....	66
3.3.2.3 Plan and Unique Service IDs (CAMP11-430b).....	66
3.3.2.4 Plan References (CAMP11-431b).....	66
3.3.2.5 Plan Artifact integrity (CAMP11-407b).....	66
4 Conformance .....	68
4.1 Implementations .....	68
<b>Identification of test restrictions:</b> .....	68
4.2 CAMP Provider Test Suite Conformance Profile.....	68
4.3 CAMP Consumer Test Suite Conformance Profile .....	69
4.4 CAMP PDP Test Suite Conformance Profile .....	69
4.5 CAMP Plan Test Suite Conformance Profile .....	69
Appendix A. Acknowledgments.....	70
Appendix B. Revision History .....	71



---

# 1 Introduction

This document defines the Test Assertions for version 1.1 of the OASIS Cloud Application Management for Platforms (CAMP) specification **[CAMP]**. Test Assertions are testable or measurable expressions related to normative statements in a specification for evaluating if an implementation (or part of it) conforms to this specification. These Test Assertions are intended to be used for defining precisely the conditions required by a CAMP implementation in order to conform. They support the testing activity by acting as a bridge between the normative statements in the specification and the executable test cases that are parts of a conformance test suite.

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in **[RFC2119]**.

## 1.1 Normative References

- |                   |   |
|-------------------|---|
| <b>[RFC2119]</b>  | Bradner, S., “Key words for use in RFCs to Indicate Requirement Levels”, BCP 14, RFC 2119, March 1997. <a href="http://www.ietf.org/rfc/rfc2119.txt">http://www.ietf.org/rfc/rfc2119.txt</a> .  |
| <b>[TA-Model]</b> | <i>Test Assertions Model Version 1.0</i> . 15 October 2012. OASIS Standard. <a href="http://docs.oasis-open.org/tag/model/v1.0/os/testassertionsmodel-1.0-os.html">http://docs.oasis-open.org/tag/model/v1.0/os/testassertionsmodel-1.0-os.html</a> .   |
| <b>[CAMP]</b>     | <i>Cloud Application Management for Platforms Version 1.1</i> , February 2014, OASIS Committee Specification Draft 04,. <a href="http://docs.oasis-open.org/camp/camp-spec/v1.1/csd04/camp-spec-v1.1-csd04.pdf">http://docs.oasis-open.org/camp/camp-spec/v1.1/csd04/camp-spec-v1.1-csd04.pdf</a> |

## 1.2 Non-Normative References

- |                        |  |
|------------------------|--|
| <b>[TA-guidelines]</b> | <i>Test Assertions Guidelines Version 1.0</i> . June 2013. OASIS Committee Note. <a href="http://docs.oasis-open.org/tag/guidelines/v1.0/cn02/guidelines-v1.0-cn02.pdf">http://docs.oasis-open.org/tag/guidelines/v1.0/cn02/guidelines-v1.0-cn02.pdf</a> |
|------------------------|--|

---

## 2 Test Assertions Design and Objectives

### 2.1 Testing Objectives

A Test Assertion is a testable or measurable expression for evaluating the adherence of an implementation (or part of it) to a normative statement(s) in a specification.

The Test Assertions presented here are intended to help a precise understanding of what is expected from implementations of the CAMP specification.

They are also intended as a starting point for actual test suites. Testing for conformance to the CAMP specification occurs typically in two major contexts:

1. **Product Conformance assessment.** In this set-up the primary goal is to assess if an implementation behaves in conformance to CAMP. A test driver simulates a Consumer, when the implementation being tested is a CAMP Provider. Conversely, a Consumer may also be tested for conformance, in which case there is no test driver but merely some scenarios that the Consumer is expected to execute along with a Provider. The objective of testing is not always to establish conformance or interoperability. Conformance testing may also include an assessment of which options are or are not supported by an end-point, even if all the mandatory requirements are met.
2. **Product Interoperability test rounds.** In this set-up the ability of several implementations to interoperate with each-other is evaluated. A set of implementations is tested pair-wise based on test scenarios between a Consumer and Provider. Even if the exchanges are successful, they must be validated as conforming to CAMP (successful interoperability does not imply successful conformance to CAMP, and vice-versa.)

In both cases, some Consumer-Provider exchanges are executed according to some pre-defined scenarios. In both cases, these exchanges must be verified for conformance to CAMP.

There is also a 3<sup>rd</sup> context where testing for CAMP conformance is likely to occur: routine regression testing on systems in production. In this context, real business exchanges between a Consumer and a Provider are being monitored and tested for conformance. The rationale is that Cloud end-points may often be upgraded (patches, revisions) or their operational context be modified (configuration change, recovery, etc.), which might cause a deterioration of their conformance to CAMP. Since it is impractical to stop operations and undergo a full round of testing each time some end-point is upgrading, it is often sufficient to detect as early as possible a regression, whenever it occurs.

### 2.2 Design Principles

CAMP test assertions are intended to be usable by test suites designed for the various testing contexts and objectives described in the previous section. To achieve this versatility, the following design principles are used:


- The test assertions intended to verify conformance of Provider and Consumer are focusing on messages or artifacts exchanged between these roles. They are designed so that they could – ideally – be evaluated with a log of messages as sole input.
- Each test assertion is designed to apply to a particular pattern of messages (except for those directly targeting the PDP or Plan artifacts). The test assertion does not make any assumption about how to produce this pattern of message: it only describes it. A concrete test suite written from such test assertions could enforce (script) the test scenarios that will produce the expected message pattern, or could just discover and analyze such patterns in a message log.
- Each test assertion references the normative statement(s) in the original specification that it is addressing. The test assertion “interprets” the normative requirement in a testable way – i.e. translates the normative requirements in terms of what is a “correct (or incorrect) message exchange pattern” to be observed between a Consumer and a Provider. Clearly an important aspect of designing test assertions is to derive correct and testable interpretations of the original specification requirements.

- A test assertion may address more than one normative statement, as it is often difficult to design test assertions with the level of granularity fine enough to address, or verify, just one normative statement. When such a test assertion “fails” (i.e. related test case(s) fail), it means that at least one of the referred normative statements has been violated.
- Conversely, in order to address the same normative statement in a well-rounded way, several test assertions may be needed that focus on different aspects or sub-cases of the normative statement. In order to have confidence that a normative statement is satisfied by an implementation, all of the test assertions referring to a normative statement should be exercised successfully (i.e. test case(s) pass).

## 2.3 Anatomy of a Test Assertion

The structure of test assertions follows the recommendation from OASIS TAG [\[TA-guidelines\]](#).

The general structure used for Test Assertions is as follows:



### 2.3.1 Core Elements

The core elements of a Test Assertion are:

#### **Test Assertion ID** (or Identifier, or TA\_Id)

The unique identifier of the test assertion. It facilitates the mapping of assertions to specification statements. It is recommended that the identifier be made universally unique.

#### **Normative Source(s)**

These refer to the precise specification requirement(s) or normative statement(s) that the test assertion addresses.

#### **Target**

The target – or test target - categorizes an implementation or a part of an implementation of the referred specification that is the main object of the test assertion and of its Normative Sources. In CAMP, the target will typically be a message exchanged between Consumer and Provider (e.g. a response to an HTTP GET), or the PDP or Plan artifact.

NOTE: the “*test [assertion] target*” should not be confused with the “*conformance target*”. The test target is the artifact or component actually subject to the particular testing described in the test assertion (e.g. a message), while the conformance target is the entity ultimately evaluated for conformance, (e.g. a CAMP Provider implementation). Of course, the test target can be traced to a conformance target.

### Predicate

It contains the actual conformance logic. It is worded as a fact (not as a rule or requirement – i.e. no MUST/SHOULD). A predicate asserts, in the form of an expression that evaluates to either “true” or “false”, the feature (a behavior or a property) described in the specification statement(s) referred by the Normative Sources, concerning an instance of Target. If the predicate evaluates to “true” over the test assertion Target, this means that the Target exhibits this feature. “False” means the Target does not exhibit this feature.

## 2.3.2 Optional Elements

The following parts of a test assertion are optional:

### Description

An informal definition of the role of the test assertion, with some optional details on some of its parts. This description must not alter the general meaning of the test assertion and its parts. This description may be used to annotate the test assertion with any information useful to its understanding. It does not need to be an exhaustive description of the test assertion.

### Prescription Level

A keyword that indicates how imperative it is that the Normative Statement referred to in the Normative Source, be satisfied. Three prescription levels are used:

- **Mandatory:** this value applies to test assertions which address normative statements that include strongly imperative keywords such as “MUST”, “REQUIRED”, and “SHALL”, but also their negative counterparts (“MUST NOT”, “SHALL NOT”, etc.) as the Predicate is where the negative aspect is expressed.
- **Preferred:** applies to test assertions which address normative statements that can be interpreted as recommendations, using such keywords as “SHOULD” and “RECOMMENDED” as well as their negative counterparts.
- **Permitted:** applies to test assertions about normative statements that concern optional features about which the specification remains neutral (no recommendation) using such keywords as “MAY” or “OPTIONAL”. Note that the negative counterparts of these keywords (e.g. “NEED NOT” or “CAN NOT”) often have a **mandatory** character.

### Prerequisite

A test assertion Prerequisite is a logical expression (similar to a Predicate) which further qualifies the Target for undergoing the core test (expressed by the Predicate) that addresses the Normative Statement. It may include references to the outcome of other test assertions. If the Prerequisite evaluates to “false” then the Target instance is not qualified for evaluation by the Predicate. Prerequisites have also been called “preconditions”.

### Tags

Test assertions may be assigned ‘tags’ or ‘keywords’, which may in turn be given values. These tags allow for categorizing the test assertions.

The above test assertion model is formally described in the OASIS test assertions standard [\[TA-model\]](#).

## 2.3.3 Example Test Assertion

**TA\_Id:** CAMP11-NNN

**NormativeSource:** <a normative TAG, and optionally a section name>

**Target:** A response message to a GET assembly URI message.

**Predicate:** the target message content satisfies the JSON “schema” for assembly resources.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 2.3.4 CAMP Profile

The above test assertion model is profiled for CAMP in the following way:

1. The “**NormativeSource**” element refers to the section(s) in the specification that contain(s) the normative statements addressed by the test assertion. As CAMP has tagged its normative statements, there will be one or more “normative tags” in this field. (Sometimes it does more than make a reference, i.e. makes some “interpretation” of the original statement(s) that can be narrower, and that reflects more concretely the actual test expression). There may be some additional normative tags in parenthesis: this indicates that such normative statements are assumed to be satisfied before using this test assertion – i.e. some kind of prerequisite, or indicating a precedence order for using test assertions.
2. The “**Target**” may be the PDP or the Plan (for PDP and Plan conformance). For conformance of the Provider or Consumer (indicated by the “conformance” tag) , the target will be a particular message pattern (e.g. as expected to be captured in a log) that would “trigger” the verification.
3. The “**Predicate**” -should be evaluated each time a sequence of message appears in the log that satisfies the message pattern described in the Target, and in case the Prerequisite is also satisfied (if any). The Predicate is expressed using any content of the Target message and also contents from the Prerequisite messages if any (see below). Predicate=false means the implementation failed the normative requirement.
4. The “**Prerequisite**” in most cases is a contextual exchange of additional messages between Provider and Consumer that must have occurred along with the target message. These contextual messages must occur often prior to the target message (by default), but sometimes after the target message (this is indicated).
5. Test assertions “**Tags**” (not to be confused with CAMP normative tags in the “normativeSource” field), as accessory information. Only one tag named *conformance* is used in this document. In the above example, the *conformance* tag has value “Provider”. This means that the actual entity under evaluation for conformance by this assertion is the Provider (as opposed to the Consumer): the failure of the verification (i.e. predicate value=”false”) means a failure of the Provider to conform. Note that the conformance target is not always same as the test assertion target: in the above example, the conformance target is “Provider” while the test target is a message.
6. When the same test assertion logic applies to several resource types, a variable will be defined to represent any item over the set of resource types. This amounts to parameterizing the test assertions, so that it does not need to be repeated for each resource. This parameterizing may also apply for other elements when under the same logic.

In the example below, a *resource* variable is defined that can take either one among four resource names (sensor, plan, assembly, or component), thus avoiding to write four different test assertions that would only differ by the name of the resource.

```
Var: (resource) in {  
    sensor,  
    plan,  
    assembly,  
    component  
}
```

**Target:** A message (m1) of the form PUT *resource* URI (with no *select\_attr* query parameter)

## 2.4 Categories of Test Assertions

Four general categories of test assertions can be distinguished, depending on their conformance target (value of the *conformance* tag):

- **Provider TAs:** addressing normative statements concerning behavior of, and messages generated by the Provider, such as serialization of resources.
- **Consumer TAs:** addressing normative statements concerning behavior of, and messages generated by the Consumer, such as queries, operations on resources.
- **PDP TAs:** addressing normative statements concerning the structure and content of PDP artifacts as well as of their archive format.
- **Plan TAs:** addressing normative statements concerning the structure and content of Plan files.

NOTE: Provider TAs and Consumer TAs may also contain their own tests similar to those found in PDP and Plan TAs. The difference is that these tests will target the messages containing PDPs and Plans (or referring to these) instead of directly the PDP and Plan artifacts. In such cases, the Test Assertions will have an ID that indicates their close relationship. For example:

- **CAMP11-405**, is the ID of a Test Assertions about the Consumer's ability to send a Plan artifact that is correctly formed. Its target is a message referring to such a Plan.
- **CAMP11-405b**, is the ID of a similar Test Assertions about the Plan artifact itself. It describes the same test concerning the Plan as CAMP11-405 (addressing the same normative statement, using the same predicate). Its target is however the Plan itself, instead of a message containing or referring to the Plan.

## 2.5 Notational Conventions

### 2.5.1 Identification scheme for Test Assertions

Test Assertions are identified according to the scheme:

`<specificationID> "-" <number>`

Where `specificationID` is here "CAMP11", and `number` takes the following ranges:

- For **Model Serialization and Integrity** Test Assertions: `100 < number < 200`
- For **Protocol** Test Assertions: `200 < number < 300`
- For **Resource State Changes and Lifecycle** Test Assertions: `300 < number < 400`
- For **PDP** Test Assertions: `400 < number < 500`

### 2.5.2 Identifying a message inside a Test Assertion

When referring to an HTTP message, either request or response, the following notation is used:

`"(" messageID ")"`

where `messageID` is a symbolic identifier typically of the form. "m1", "m2" etc. Such an identifier is only relative to the test assertion; they are used to distinguish messages from each other in the same test assertion (i.e. this identifier does not appear in the message itself).

### 2.5.3 Identifying an attribute of a resource in a message

When referring to an attribute of a resource serialized in a message, the `Courier New` font is used to indicate a name proper to the CAMP model. The following notation is used:

`"(" messageID ")" <resource_type> "." <attribute_name>`

Where:

- `messageID` is a symbolic message identifier.
- `resource_type` is a reminder of the resource type expected to be found for the top-level serialized resource in this message.
- `attribute_name` is the attribute name of interest for the resource (defined for this `resource_type` and expected to be found on the serialized resource).

For example:

(m2)platform.assemblies\_uri

## 2.6 Coverage of the Specification

In this document, only “mandatory” normative statements (SHALL / SHALL NOT) have been addressed.



---

## 3 Test Assertions

### 3.1 Provider Test Assertions

These Test Assertions concern the Provider as conformance target.

#### 3.1.1 Basic Schema Compliance for Platform Resources, Provider Side

##### 3.1.1.1 `platform_endpoints` Serialization (CAMP11-101)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [RE-70]

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [RE-06]

---

**TA\_Id:** CAMP11-101

**NormativeSource:** RE-70, RE-06 (section: `platform_endpoints`)

**Target:** A successful response message (HTTP code 200) to a GET `platform_endpoints` message.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON) for `platform_endpoints`, AND has a `type` attribute of value = "`platform_endpoints`".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

##### 3.1.1.2 `platform_endpoint` Serialization (CAMP11-102)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [RE-70]

Each *platform\_endpoint resource* SHALL refer to exactly one *platform resource*, and indicate the versions supported by the Platform. [RE-20]

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [RE-06]

---

**TA\_Id:** CAMP11-102

**NormativeSource:** RE-70, RE-20, RE-06 (section: `platform_endpoint`)

**Target:** A successful response message (HTTP code 200) to a GET `platform_endpoint` message (m1).

**Prerequisite:** the URI used in message (m1) exists as a link in `platform_endpoints.platform_endpoint_links[]` as result to a previous GET `platform_endpoints` URI.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON) for `platform_endpoint`, AND has a `type` attribute of value = "`platform_endpoint`" AND non-empty `platform_uri`, `implementation_version`, `specification_version` attribute values.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider



### 3.1.1.3 platform Serialization (CAMP11-103)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-103

**NormativeSource:** RE-70, RE-06, (RE-53) (Section: `platform` Resource definition)

**Target:** A successful response message (HTTP code 200) to a GET `platform` message.

**Predicate:** the target message content satisfies the serialization schema (JSON ) for `platform`, AND has a `type` attribute of value = "platform".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.1.4 service Serialization (CAMP11-104)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-104

**NormativeSource:** RE-70, (RE-06, RE-53) (Section: `service` Resource definition)

**Target:** A successful response message (HTTP code 200) to a GET `service` message (m1).

**Prerequisite:** the URI used in message (m1) exists as a link in `services.service_links` where `services` is obtained from `platform.services_uri` as shown in the result to a previous GET `platform` URI message.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON ) for `service` , AND has a `type` attribute of value = "service".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.2 Basic Schema Compliance for Application Resources

### 3.1.2.1 assembly Serialization (CAMP11-111)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-111

**NormativeSource:** RE-70, RE-06, (RE-53) (Section: `assembly` Resource definition)

**Target:** A successful response message (HTTP code 200) to a GET `assembly` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as a link in `assemblies.assembly_links`, as shown in the result to a previous GET `assemblies` message (obtained from `platform.assemblies_uri`), OR there is a POST to an `assemblies` that returns this URI.

**Predicate:** the target message content satisfies the serialization schema (JSON ) for `assembly`, AND has a `type` attribute of value = "assembly".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.2.2 component Serialization (CAMP11-112)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-112

**NormativeSource:** RE-70, RE-06, (RE-53,) (Section: `component` Resource definition)

**Target:** A successful response message (HTTP code 200) to a GET `component` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as a link in `assembly.components[]` as shown in the result to a previous GET `assembly` message.

**Predicate:** the target message content satisfies the serialization schema (JSON ) for `component` AND has a link `assembly` to the parent `assembly` URI , AND has a `type` attribute of value = "component".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.2.3 plan Serialization (CAMP11-113)

Addressing normative statements:

The schema of the *plan resource* returned from a CAMP Provider SHALL conform to the schema for Plans described in Section **Error! Reference source not found.**, "[Plan Schema](#)", with the following additional requirements: [\[RMR-07\]](#)

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-113

**NormativeSource:** RMR-07, RE-70, RE-06, (RE-53) (Section: `plan` Resource definition)

**Target:** A successful response message (HTTP code 200) to a GET `plan` message (m1).

**Prerequisite:** the URI used in the message (m1) exists in a link in `plans.plan_links` as shown in the result to a previous GET `plans` message (obtained from `platform.plans_uri`), OR there is a POST to an `plans` Resource that returns this URI.

**Predicate:** the target message content satisfies the serialization schema (JSON ) for `plan`, AND has a `type` attribute of value = "plan".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.3 Consistency of Serialization with Metadata

### 3.1.3.1 Consistent Use of Formats (CAMP11-114)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

Providers SHALL respond in the requested Supported Format. [\[PR-05\]](#)

---

**TA\_Id:** CAMP11-114

**NormativeSource:** RE-70, PR-05, (section: Media Types / Supported Formats)

**Var:** (*resource*) in {  
    assembly,  
    component,  
    platform,  
    service  
}

**Target:** A response message (m4) to a GET *resource* message (m3).

**Prerequisite:**

- A successful response message (m2) to a previous GET `platform.supported_formats_uri` message (m1).
- The negotiated format (using the HTTP Accept request header) in the GET *resource* message (m3), is defined in (m2).

**Predicate:** in the target message (m4), the resource data in case of a successful response message (HTTP code 200), or the error data in case of an error code (4xx or 5xx), is serialized consistently with the requested format.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.3.2 Consistent Use of `type_definition` Names (CAMP11-150)

Addressing normative statement:

The value of the `name` attribute in a *type\_definition resource* SHALL match the value of the `type` attribute for the resource type that it describes. [\[RE-75\]](#)

---

**TA\_Id:** CAMP11-150

**NormativeSource:** RE-75, (section: `type_definition` resources)

**Var:** (*resource*) in {  
    assembly,  
    component,  
    platform,  
    service  
}

**Target:** A response message (m4) to a GET *resource* message (m3).

**Prerequisite:**

A successful response message (m2) to a previous GET `type_definitions` (m1) where `type_definitions` is obtained from `platform.type_definitions_uri`.

**Predicate:** in the target message (m4), the resource data in case of a successful response message (HTTP code 200) shows a `type` attribute with a value that is same as the `name` attribute in one of the `type_definition` items in (m1), AND each attribute of the *resource* in (m4) is also described by an

`attribute_definition` resource referred in the `type_definition.attribute_definition_links`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.3.3 Inheritance from `camp_resource` (CAMP11-151)

Addressing normative statement:

All CAMP resources SHALL inherit directly or indirectly from this resource. [\[MO-05\]](#)

---

**TA\_Id:** CAMP11-151

**NormativeSource:** MO-05, (section: `camp_resource` resource)

**Target:** A successful response message (m2) to a previous GET `type_definitions` (m1) where `type_definitions` is obtained from `platform.type_definitions_uri`.

**Prerequisite:**

- A successful response message (m4) to a previous GET `type_definition` (m3) where the `name` attribute value shown in (m4) is `camp_resource`.

**Predicate:** Every link in `type_definitions.type_definition_links` uses an URI that refers to a `type_definition` resource that satisfies either condition: (the `name` attribute has value `camp_resource` OR the `inherits_from` attribute has a link showing same URI as the URI used in (m3)).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.3.4 Non-Mutability Enforcement (Provider) (CAMP11-115)

Addressing normative statement:

This boolean indicates the mutability of the attribute's value(s). "false" indicates that the value of the attribute, once set, SHALL NOT change for the lifetime of the resource. [\[RE-07\]](#)

---

**TA\_Id:** CAMP11-115

**NormativeSource:** RE-07, (RE-53) (section: Mutable)

**Var:** (resource) in {  
    `assembly`,  
    `component`,  
    `plan`  
}

**Target:** A response message (m4) to a PUT request (m3) to a *resource*.

**Prerequisite:** The following message sequence occurred:

- A previous message (m1) of the form GET *resource* was sent with a successful response message (m2). (and assuming no "delete *resource*" message after m1).
- The PUT request (m3) is providing different value than shown in (m2) for a `consumer-mutable=false` attribute.

**Predicate:** the target message (m4) has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.4 Metadata Integrity and Serialization

### 3.1.4.1 `parameters_definitions` Serialization and Integrity (CAMP11-117)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-117

**NormativeSource:** RE-70, RE-06, (RE-53) (section: `parameter_definitions`)

**Target:** A successful response message (HTTP code 200)(m4) to a GET `parameter_definitions` message (m3).

**Prerequisite:** The following message sequence occurred:

- A successful response (HTTP 200) message (m2) to a GET `assemblies` message (m1)
- The GET `parameter_definitions` (m3) is on the URI returned as (m2)`assemblies.parameter_definitions_uri`.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON) for `parameter_definitions`, and has a `type` attribute of value = "parameter\_definitions"

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.2 `parameters_definition` Serialization and Integrity (CAMP11-118)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

If the Required boolean constraint for an attribute of a resource type has a value of "true", then a resource of this type SHALL have the attribute present. [\[RE-06\]](#)

---

**TA\_Id:** CAMP11-118

**NormativeSource:** RE-70, RE-06, (RE-53,) (section: `parameter_definition`)

**Target:** A successful response message (HTTP 200) (m6) to a GET `parameter_definition` message (m5).

**Prerequisite:** The following message sequence occurred:

- A successful response (HTTP 200) message (m2) to a GET `assemblies` message (m1)
- A successful response (HTTP 200) message (m4) to a GET `parameter_definitions` (m3) on the URI returned by (m2) as `assemblies.parameter_definitions_uri`.
- The GET `parameter_definition` (m5) is against on one of the URIs returned in (m4) `parameter_definitions.parameter_definition_links`

**Predicate:** the target message (m6) content satisfies the serialization schema (JSON) for `parameter_definition`, AND has a `type` attribute of value = "parameter\_definition"

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.3 formats Serialization (CAMP11-119)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-119

**NormativeSource:** RE-70 (section: `formats`)

**Target:** A successful response message (HTTP code 200) to a GET `formats` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as value of a `platform.supported_formats_uri` attribute as result to a previous GET `platform` message.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON) for `formats`, and has a `type` attribute of value = "formats".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.4 format Serialization (CAMP11-120)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-120

**NormativeSource:** RE-70 (section: `format`)

**Target:** A successful response message (HTTP code 200)(m4) to a GET `format` message (m3).

**Prerequisite:** the URI used in the message (m3) exists as an item in `formats.format_links` as shown in a result to a previous GET `formats` message (m2), itself obtained from a previous GET `platform` message (m1) as `platform.supported_formats_uri`.

**Predicate:** the target message (m4) content satisfies the serialization schema (JSON) for `format`, and has a `type` attribute of value = "format".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.5 Presence of JSON Format (CAMP11-121)

Addressing normative statement:

The *name*, *mime\_type*, *version*, and *documentation* attribute values for the JSON Format Resource SHALL reflect the above values. [\[RE-42\]](#)

---

**TA\_Id:** CAMP11-121

**NormativeSource:** RE-42 (section: Required JSON Format Resource)

**Target:** A successful response message (HTTP code 200)(m4) to a GET `format` message (m3) with query for "name"="JSON".

**Prerequisite:** the URI used in the message (m3) exists as an item in `formats.format_links` as a result to a previous GET `Formats` message (m2), itself obtained from a previous GET `platform` message (m1) as `platform.supported_formats_uri`.

**Predicate:** the target message (m4) has: "mime\_type", "version", "documentation" set respectively to the expected values ("application/json", "RFC4627", "http://www.ietf.org/rfc/rfc4627.txt") .

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.6 Position of JSON Format (CAMP11-122)

Addressing normative statement:

The Required JSON Format Resource SHALL be listed first in the `format_links` array. [\[RE-41\]](#)

---

**TA\_Id:** CAMP11-122

**NormativeSource:** RE-41 (section: `format_links`)

**Target:** A successful response message (HTTP code 200)(m2) to a GET `formats` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as `platform.supported_formats_uri` value, as a result to a previous GET `platform` message.

**Predicate:** the target message (m2) has its first link item with “`target_name`” set to “JSON”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.7 `type_definitions` Serialization (CAMP11-123)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-123

**NormativeSource:** RE-70, (RE-43) (section: `type_definitions` Resource)

**Target:** A successful response message (HTTP code 200)(m2) to a GET `type_definitions` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as `platform.type_definitions_uri` in a result to a previous GET `platform` message.

**Predicate:** the target message (m2) content satisfies the serialization schema (JSON ) for `type_definitions`, AND has a `type` attribute of value = “`type_definitions`”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.4.8 `type_definition` Serialization (CAMP11-124)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-124

**NormativeSource:** RE-70 (section: Resources)

**Target:** A successful response message (HTTP code 200) to a GET `type_definition` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as an item in `type_definitions.type_definitions_links` as a result to a previous GET `type_definitions` message, itself obtained from `platform.type_definitions_uri` in a previous GET Platform message.

**Predicate:** the target (response) message content satisfies the serialization schema (JSON ) for `type_definition`, AND has a `type` attribute of value = “`type_definition`”.

**PrescriptionLevel:** mandatory



**Tag:** conformance=Provider

### 3.1.4.9 attribute\_definition Serialization (CAMP11-125)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-125

**NormativeSource:** RE-70 (section: Resources)

**Target:** A successful response message (HTTP code 200)(m2) to a GET `Attribute_definition` message (m1).

**Prerequisite:** the URI used in the message (m1) exists as an item in `Type_definition . attribute_definition s_links` as a result to a previous GET `Type_definition`.

**Predicate:** the target message (m2) content satisfies the serialization schema (JSON ) for `Attribute_definition` , AND has a `type` attribute of value = "attribute\_definition".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.5 Various Model Referential and Semantic Constraints

### 3.1.5.1 type\_definitions Reference in platform Resource (CAMP11-126)

Addressing normative statement:

The *platform resource* SHALL provide a Link to the *type\_definitions resource* in the required attribute named `type_definitions_uri`. [\[RE-43\]](#)

---

**TA\_Id:** CAMP11-126

**NormativeSource:** RE-43, (section: `type_definitions` Resource)

**Target:** A successful response message (HTTP code 200)(m2) to a GET `platform` message (m1).

**Predicate:** the target message (m2) content has :

- an attribute `platform.type_definitions_uri`, that contains a valid URI referring to a `type_definitions` Resource.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.2 platform\_endpoint and specification\_version (CAMP11-127)

Addressing normative statements:

For Platforms that implement this version of the CAMP specification, the value of this attribute SHALL be "CAMP 1.1" as defined in Section **Error! Reference source not found.**, ["Specification Version"](#). [\[RE-22\]](#)

`platform_endpoint` resources that reference Specification Version "CAMP 1.1" Platform Resources SHALL NOT include this attribute because no previous versions are compatible. [\[RE-24\]](#)

---

**TA\_Id:** CAMP11-127

**NormativeSource:** RE-22, RE-24 (sections: `platform_endpoint` Resource / `specification_version`, `/backward_compatible_specification_versions`)

**Target:** A successful response message (HTTP code 200)(m2) to a GET `platform_endpoint` message (m1).



**Prerequisite:** the URI used in the message (m1) exists as a link in `platform_endpoints.platform_endpoint_links[]` as shown in the result to a previous GET `platform_endpoints` URI.

**Predicate:** the target message (m2) content has a `specification_version` attribute = "CAMP 1.1" AND does not contain an `backward_compatible_specification_versions` attribute.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.3 Platform specification\_version (CAMP11-128)

Addressing normative statement:

For Platforms that implement this version of the CAMP specification, the value of this attribute SHALL be as defined in Section **Error! Reference source not found.**, "Specification Version". [\[RE-26\]](#)

---

**TA\_Id:** CAMP11-128

**NormativeSource:** RE-26 (section: Platform / specification\_version )

**Target:** A successful response message (HTTP code 200)(m2) to a GET platform message (m1).

**Predicate:** the target message (m2) content has a `specification_version` attribute = "CAMP 1.1".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.4 platform\_endpoint and platform matching specification\_version (CAMP11-129)

Addressing normative statement:

The value of this attribute SHALL exactly match the value of the `specification_version` attribute of any *platform\_endpoint* resource that references this *platform* resource. [\[RE-27\]](#)

---

**TA\_Id:** CAMP11-129

**NormativeSource:** RE-27 (section: Platform / specification\_version ),

**Target:** A successful response message (HTTP code 200) (m4) to a GET platform message (m3).

**Prerequisite:** The sequence of messages occurred:

- A successful response message (HTTP code 200) (m2) to a GET `platform_endpoint` message.
- The URI in GET platform message (m3), is same as the `platform_endpoint.platform_uri` value in (m2)

**Predicate:** the target (response) message (m4) content has a `platform.specification_version` attribute = (m2)`platform_endpoint.specification_version`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.5 platform\_endpoint and platform matching implementation\_version (CAMP11-130)

Addressing normative statement:

The value of this attribute SHALL exactly match the value of the `implementation_version` attribute of any *platform\_endpoint* resource that references this *platform* resource. [\[RE-29\]](#)

---

**TA\_Id:** CAMP11-130

**NormativeSource:** RE-29 (section: `Platform / implementation_version` ),

**Target:** A successful response message (HTTP code 200) (m4) to a GET `platform` message (m3).

**Prerequisite:** The sequence of messages occurred:

- A successful response message (HTTP code 200) (m2) to a GET `platform_endpoint` message,
- The URI in GET `platform` message (m3), is same as the `platform_endpoint.platform_uri` value in (m2)

**Predicate:** the target message (m4) content has a `platform.implementation_version` attribute = (m2)`platform_endpoint.implementation_version`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.6 Cross-References `platform_endpoints` and `platform` (CAMP11-131)

Addressing normative statements:

This attribute is an array of Links to *platform\_endpoint* resources. This array SHALL contain at least one Link. [\[RE-18\]](#)

References between the resources (*platform\_endpoints*, *platform\_endpoint*, and *platform*) SHALL be self-consistent. [\[RE-19\]](#)

---

**TA\_Id:** CAMP11-131

**NormativeSource:** RE-19, RE-18 (section: `platform_endpoint_links`),

**Target:** A successful response (HTTP 200) message (m2) to a GET `platform` message (m1)

**Prerequisite:** The following message sequence occurred:

- A successful response message (HTTP code 200)(m4) to a GET `platform_endpoints` message (m3).

**Predicate:** there is at least one link in `platform_endpoints.platform_endpoint_links` that refers to a `platform_endpoint` resource with `platform_endpoint.platform_uri` attribute value same as the URI used in (m1).AND the (m2) `platform.platform_endpoints_uri` value is same URI as the URI used in (m3).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.7 Parameter Definition for `pdp_uri` or `plan_uri` in *assemblies* (CAMP11-132)

Addressing normative statement:

The *assemblies* resource SHALL indirectly reference *parameter\_definition* resources that describes the `pdp_uri`, `plan_uri`, `pdp_file`, and `plan_file` parameters. [\[RMR-03\]](#)

---

**TA\_Id:** CAMP11-132

**NormativeSource:** RMR-03 (section: `Assemblies / parameter_definitions_uri`),

**Target:** A successful response message (HTTP code 200) (m2) to a GET `assemblies` message (m1), with a `representation_skew`=NONE.

**Prerequisite:** The following message sequence occurred after (m2):

- A successful response (HTTP 200) message (m4) to a GET `parameter_definitions` message (m3) using the (m2) `assemblies.parameter_definitions_uri` URI.

**Predicate:** There exists at least four link items in

(m4)`parameter_definitions.parameter_definitions_links`, that describe the “`pdp_uri`”, “`plan_uri`”, “`pdp_file`” and “`plan_file`” parameters, i.e. for which respectively a GET `parameter_definition` message (m5) returns a successful response (m6) with `parameter_definition.name` = “`pdp_uri`”, “`plan_uri`”, “`pdp_file`” and “`plan_file`”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.8 Parameter Definition for `pdp_uri` or `plan_uri` in plans (CAMP11-152)

Addressing normative statement:

The *plans* resource SHALL indirectly reference *parameter\_definition* resources that describe the `pdp_uri`, `plan_uri`, `pdp_file`, and `plan_file` parameters. [\[RMR-06\]](#)

---

**TA\_Id:** CAMP11-152

**NormativeSource:** RMR-06 (section: `plans` Resource),

**Target:** A successful response message (HTTP code 200) (m2) to a GET `plans` message (m1), with a `representation_skew`=NONE.

**Prerequisite:** The following message sequence occurred after (m2):

- A successful response (HTTP 200) message (m4) to a GET `parameter_definitions` message (m3) using the (m2) `plans.parameter_definitions_uri` URI.

**Predicate:** There exists at least four link items in

(m4)`parameter_definitions.parameter_definitions_links`, that describe the “`pdp_uri`”, “`plan_uri`”, “`pdp_file`” and “`plan_file`” parameters, i.e. for which respectively a GET `parameter_definition` message (m5) returns a successful response (m6) with `Parameter_definition.name` = “`pdp_uri`”, “`plan_uri`”, “`pdp_file`” and “`plan_file`”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.9 Required Parameter Definitions in service (CAMP11-134)

Addressing normative statement:

The *parameter\_definitions* resource referenced by this attribute SHALL define parameters to allow setting the ‘name’, ‘description’, and ‘tags’ attributes of any new resource created in the course of interacting with this resource. [\[RE-37\]](#)

---

**TA\_Id:** CAMP11-134

**NormativeSource:** RE-37 (section: `Service / parameter_definitions_uri`),

**Target:** A successful response message (HTTP code 200) (m2) to a GET `service` message (m1), with a `representation_skew`=NONE.

**Prerequisite:** The following message sequence occurred after (m2):

- A successful response (HTTP 200) message (m4) to a GET `parameter_definitions` message (m3) using the (m2) `service.parameter_definitions_uri` URI.

**Predicate:** There exists link items in

(m4)`parameter_definitions.parameter_definitions_links`, for which a GET

`parameter_definition` message (m5) returns a successful response (m6) with `parameter_definition.name` = "name", AND another (m5') returns `parameter_definition.name` = "description", AND another (m5'') returns `parameter_definition.name` = "tags".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.10 UTC Timestamps, Provider side (CAMP11-136)

Addressing normative statement:

Consumers and Providers SHALL express Timestamps in UTC (Coordinated Universal Time), with the special UTC designator ("Z"). [\[RE-65\]](#)

---

**TA\_Id:** CAMP11-136

**NormativeSource:** RE-65 (section: Timestamp)

**Target:** A successful response message (HTTP code 200)(m2) that has a resource serialization showing the "timestamp" attribute, in response to a GET message (m1).

**Predicate:** the Timestamp value conforms to the UTC (Universal Time Coordinated) with a "zero" timezone offset, i.e. with format terminated with the designator "Z", of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss 'Z' (Example: 1994-11-05T13:15:30Z)

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.11 representation\_skew Content (CAMP11-137)

Addressing normative statement:

If present, `representation_skew` SHALL have one of the following values: [\[RE-11\]](#)

---

**TA\_Id:** CAMP11-137

**NormativeSource:** RE-11, (section: `representation_skew`)

**Target:** A successful response message (HTTP code 200) message to a GET resource message.

**Prerequisite:** The `representation_skew` attribute is present.

**Predicate:** the value of `representation_skew` is among { CREATING, NONE, UNKNOWN, DESTROYING }

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.12 References to format Resources associated with a platform (CAMP11-140)

Addressing normative statement:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [\[RE-70\]](#)

---

**TA\_Id:** CAMP11-140

**NormativeSource:** RE-70

**Target:** A successful response message (HTTP code 200) (m4) to a GET `formats` message (m3) with URI same as in (m2) `platform.supported_formats_uri`

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1)

**Predicate:** For each link in (m4) `formats.format_links`, a GET `format` on the URI referenced in the link, returns an HTTP code 2xx AND a `type` attribute = "format".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.13 Presence of `format` Resources for every Supported Format (CAMP11-149)

Addressing normative statement:

For every format that the Platform supports, there SHALL be a Format resource Link that represents such a format. [RE-40]

---

**TA\_Id:** CAMP11-149

**NormativeSource:** RE-40 (section: `Formats Resource / format_links`)

**Target:** A successful response message (HTTP code 200) (m4) to a GET message (m3) with HTTP Content-type in (m4) other than "application/json"

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1) where this resource (m4) is defined.

**Predicate:** There exists a link in `formats.format_links`, where `formats` is referred to by (m2) `platform.supported_formats_uri`, that refers to a `format` resource with `mime_type` attribute value same as Content-type in (m4).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.14 Presence of `type_definition` Resources associated with a Platform (CAMP11-141)

Addressing normative statement:

If the array is non-empty, for every resource type that the Platform supports, there SHALL be a `type_definition` resource Link that represents such a resource type. [RE-44]

---

**TA\_Id:** CAMP11-141

**NormativeSource:** RE-44 (section: `type_definitions Resource / type_definitions_links`)

**Target:** A successful response message (HTTP code 200) (m4) to a GET `resource` message (m3) of any kind.

**Prerequisite:**

A successful response message (HTTP code 200) (m2) to a GET `type_definitions` message (m1) with URI same as in `platform.type_definitions_uri`, showing a `type_definition_links` array with at least one link.

**Predicate:** There exists a link in (m2) `type_definitions.type_definition_links`, that references a `type_definition` resource with a `name` attribute value same as the `type` value in the resource returned in (m4).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.15 Inheritance of `type_definition` Resources (CAMP11-148)

Addressing normative statement:

Links in this array SHALL NOT either directly or transitively point to the described resource. [MO-06]

---

**TA\_Id:** CAMP11-148

**NormativeSource:** MO-06 (section: `type_definition Resource / inherits_from`)

**Target:** A successful response message (HTTP code 200) (m4) to a GET `type_definition` message (m3).

**Prerequisite:** The `type_definition` URI belongs to `type_definitions.type_definition_links` as obtained from `platform.type_definitions_uri` in previous message exchanges.

**Predicate:** If the `inherits_from` link is set in (m4) then every link present in it satisfies: the link refers to a Resource of type `type_definition` that has an attribute "type" of value "typeDefinition" AND an attribute "name" value different from the "name" value in (m4) AND an attribute "uri" value different from the URI used in (m3).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.16 Presence of `attribute_definition` Resources associated with a Platform (CAMP11-142)

Addressing normative statement:

For every attribute of the type not inherited from its super-types, there SHALL be an `AttributeLink` that references the *attribute\_definition resource* that defines that attribute. [RE-45]

---

**TA\_Id:** CAMP11-142

**NormativeSource:** RE-45 (section: `type_definition Resource / attribute_definitions_links`)

**Target:** A successful response message (HTTP code 200) (m6) to a GET `type_definition` message (m5), on a URI present in (m4) `type_definitions.type_definitions_links`

**Prerequisite:** A sequence of messages:

- A successful response (m2) to a previous GET `platform` message (m1)
- A successful response (m4) to a previous GET `type_definitions` message (m3) on the URI `platform.type_definitions_uri`.

**Predicate:** For each attribute of the `type_definition` in (m6) , there exists a link in `type_definition.attribute_definitions_links`, for which a GET `attribute_definition` on the URI referenced in the link, returns an HTTP code 2xx AND a `type` attribute = "attribute\_definition" AND a `name` attribute = the attribute name

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.17 Presence of `extension` Resources associated with a Platform (1) (CAMP11-143)

Addressing normative statement:

For every extension available, there SHALL be an *extension resource* Link that represents the extension. [EX-08]

---

**TA\_Id:** CAMP11-143

**NormativeSource:** EX-08 (section: `formats Resource / format_links`)

**Target:** A successful response message (HTTP code 200) (m6) to a GET `extension` message (m5) i.e. where (m6) shows an `type` attribute of value `"extension"`.

**Prerequisite:** A previous sequence of messages such as:

- A successful response (m2) to a previous GET `platform` message (m1)
- A successful response (m4) to a previous GET `extensions` message (m3) where the URI is same as (m2)`platform.extensions_uri`.

**Predicate:** There exists a link in (m4) `Extensions.extension_links`, with a reference URI same as the URI used in (m5).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.18 Presence of `extension` Resources associated with a Platform (2) (CAMP11-144)

Addressing normative statements:

For every `extension` available, there SHALL be an *extension resource* Link that represents the extension. [EX-08]

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [RE-70]

---

**TA\_Id:** CAMP11-144

**NormativeSource:** EX-08, RE-70 (section: `Formats Resource / format_links`)

**Target:** A successful response message (HTTP code 200) (m4) to a GET `extensions` message (m3) with URI same as in (m2) `platform.extensions_uri`

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1)

**Predicate:** For each link in (m4) `extensions.extension_links`, a GET `extension` message on the URI referenced in the link returns an HTTP code 2xx AND shows an `type` attribute of value `"extension"`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.19 Presence of `extensions` Resource associated with a platform (CAMP11-145)

Addressing normative statement:

The *platform resource* SHALL provide a Link to the *extensions resource* in the required attribute named `extensions_uri`. [EX-09]

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [RE-70]

---

**TA\_Id:** CAMP11-145

**NormativeSource:** EX-09, RE-70 (section: `Formats Resource / format_links`)

**Target:** a successful response message (HTTP code 200) (m4) to a GET `extensions` message (m3) with URI same as in (m2) `platform.extensions_uri`.

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1)

**Predicate:** The message (m4) has HTTP code 2xx, AND the returned serialization shows a `type` attribute of value `"extensions"` AND the serialization is conforming to the `extensions` schema.



**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.20 Unique Name of extension Resources associated with a Platform (CAMP11-146)

Addressing normative statement:

Entities added by an extension SHALL NOT interfere with names of existing entities, including any added by another extension. [EX-06]

---

**TA\_Id:** CAMP11-146

**NormativeSource:** EX-06, (EX-08) (section: Unique Name Requirement)

**Target:** A successful response message (m4) to a GET `extensions` message (m3) with URI same as in (m2) `platform.extensions_uri`

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1)

**Predicate:** For any pair of links in (m4) `extensions.extension_links`, the `target_name` values in these links are different AND different from any predefined resource or attribute name in the CAMP specification.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.5.21 Presence of an extension Resource advertising Support for Plans (CAMP11-147)

Addressing normative statement:

Providers that support the *plans* and *plan resources* SHALL advertise such support using the following *extension resource*: [RMR-12]

---

**TA\_Id:** CAMP11-147

**NormativeSource:** RMR-12 (section: Advertising Support for the Plan Resource)

**Target:** A successful response message (HTTP code 200) (m4) to a GET `extensions` message (m3) with URI same as in (m2) `platform.extensions_uri`

**Prerequisite:** A successful result (m2) to a previous GET `platform` message (m1), shows an `plans_uri` attribute set to a valid URI.

**Predicate:** There exists a link in (m4) `extensions.extension_links`, for which a GET `extension` message on the URI referenced in the link returns an `extension` that shows a `name` attribute of value "CAMP Plans Extension" .

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.6 Support for HTTP Methods

### 3.1.6.1 GET method (CAMP11-201)

Addressing normative statements:

When supporting such a Resource, a Provider SHALL implement it and serialize it as described in the corresponding sub-section. [RE-70]

Providers SHALL support the HTTP GET, PUT, and PATCH methods on all of the resources defined in this section. [RE-53]



---

**TA\_Id:** CAMP11-201

**NormativeSource:** RE-70, RE-53, (section: `platform_endpoints` resource)

**Target:** A response message to a GET `platform_endpoints` message.

**Predicate:** the target message has HTTP code 200 AND its content is valid for `platform_endpoints` serialization schema (JSON ).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.6.2 PDP Registration by reference, Provider side (CAMP11-410)

Addressing normative statement:

Providers SHALL support the deployment of applications via HTTP POST requests on the *assemblies resource* as described in this section. [\[PR-49\]](#)

---

**TA\_Id:** CAMP11-410

**NormativeSource:** PR-49 (section: [Registering an Application by Reference](#))

**Target:** A response (m2) to a POST message (m1) to an `assemblies` URL, with a "pdp\_uri" or a "plan\_uri" attribute.

**Predicate:** the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the new `assembly` resource, OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 "OK")

**Predicate:** the HTTP code in target (m2) is NOT 405 "Method Not Allowed"

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.6.3 Supported HTTP Post for PDP or Plan Registration by Reference: Provider side (CAMP11-435)

Addressing normative statements:

Providers that support the *plans resource* and *plan resources* SHALL support the registration of Plans via an HTTP POST request on the *plans resource* as described in this section. [\[PR-56\]](#)

In addition to the methods defined in Section **Error! Reference source not found.**, "[HTTP Method Support](#)", Providers SHALL support the HTTP POST method on the *plans resource* as described in Section **Error! Reference source not found.**, "[Registering a Plan](#)". [\[RMR-05\]](#)

---

**TA\_Id:** CAMP11-435

**NormativeSource:** PR-56, RMR-05

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) contains a "pdp\_uri" or a "plan\_uri" attribute.

**Predicate:** the HTTP code in target (m2) is NOT 405 "Method Not Allowed"

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.6.4 Supported HTTP Post for PDP or Plan Registration by value: Provider side (CAMP11-436)

Addressing normative statement:

In addition to the methods defined in Section **Error! Reference source not found.**, “[HTTP Method Support](#)”, Providers SHALL support the HTTP POST method on the *plans resource* as described in Section **Error! Reference source not found.**, “[Registering a Plan](#)”. [\[RMR-05\]](#)

Providers that support the *plans resource* and *plan resources* SHALL support the registration of Plans via HTTP POST requests on the *plans resource* in which the entity body of the request contains the PDP or the Plan file that is being registered. [\[PR-61\]](#)

---

**TA\_Id:** CAMP11-436

**Var:** *archtype* in { application/x-zip, application/x-tar, application/x-tgz, application/x-yaml }

**NormativeSource:** PR-61, RMR-05

**Target:** A response message (m2) to a POST *Plans* message (m1) where (m1) does not contain a “pdp\_uri” nor a “plan\_uri” attribute, and contains a Content-Type = *archtype*.

**Predicate:** the HTTP code in target (m2) is NOT 405 “Method Not Allowed”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.6.5 Supported HTTP Post for Application Deployment by value: Provider side (CAMP11-434)

Addressing normative statement:

Providers SHALL support the deployment of applications via HTTP POST requests on the *assemblies resource* in which the entity body of the request contains the PDP or the Plan file that is being deployed. [\[PR-60\]](#)

In addition to the methods defined in Section **Error! Reference source not found.**, “[HTTP Method Support](#)”, Providers SHALL support the HTTP POST method on the *assemblies resource* as described in Section **Error! Reference source not found.**, “[Deploying an Application](#)”. [\[RMR-02\]](#)

---

**TA\_Id:** CAMP11-434

**Var:** *archtype* in { application/x-zip, application/x-tar, application/x-tgz, application/x-yaml }

**NormativeSource:** PR-60, RMR-02

**Target:** A response message (m2) to a POST *assemblies* message (m1) where (m1) does not contain a “pdp\_uri” nor a “plan\_uri” attribute, and contains a Content-Type = *archtype*.

**Prerequisite:** enough time elapsed to allow for the creation to complete.

**Predicate:** the HTTP code in target (m2) is NOT 405 “Method Not Allowed”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.6.6 HTTP POST support for operation Resource (1) (CAMP11-311)

Addressing normative statement:

The Provider SHALL update the *plan\_links* attribute of the *plans resource* to include a reference to the newly created *plan resource*. [\[PR-64\]](#)

---

**TA\_Id:** CAMP11-311

**NormativeSource:** RE-64 (section: *operation Resource*)

**Target:** A response message to a POST *operation* message.

**Prerequisite:** the Operation URI exists as an item in *operations.operation\_links[]* as shown in the result to a previous GET *operations* URI, itself obtained from a GET *assembly.operations\_uri*.

**Predicate:** the HTTP code in target (m2) is NOT 405 “Method Not Allowed”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.7 Support for JSON

### 3.1.7.1 JSON media-type for Resources (1) (CAMP11-202)

Addressing normative statement:

Providers SHALL provide representations of all available resources in JSON. [PR-01]

---

**TA\_Id:** CAMP11-202

**NormativeSource:** PR-01 (section: Required Formats)

**Target:** A successful response message (HTTP code 200)(m2) to a GET resource message (m1) that has no HTTP “Accept” header or has one set to “application/json”.

**Predicate:** In the target (m2) the HTTP Content-Type value is “application/json”, AND the content if any is valid JSON.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.7.2 JSON media-type for Deployments of Applications (1) (CAMP11-220)

Addressing normative statement:

To support the deployment of applications via a reference to either a PDP, Plan file, or *plan resource*, Providers SHALL accept the “application/json” media type. [PR-68]

---

**TA\_Id:** CAMP11-220

**NormativeSource:** PR-68 (section: Deploying an Application by Reference)

**Target:** A response message (m2) to a POST *assemblies* message (m1) that has no HTTP “Accept” header or has one set to “application/json” and contains a “pdp\_uri” or a “plan\_uri” attribute.

**Predicate:** The HTTP code of (m2) is NOT code 415, “Unsupported Media Type”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.7.3 JSON media-type for Plan Registration (1) (CAMP11-221)

Addressing normative statement:

To support the registration of Plans via a reference to either a PDP or a Plan file, Providers SHALL accept the “application/json” media type. [PR-69]

---

**TA\_Id:** CAMP11-221

**NormativeSource:** PR-69 (section: Registering a Plan by Reference)

**Target:** A response message (m2) to a POST *plans* message (m1) where (m1) has no HTTP “Accept” header or has one set to “application/json” and contains a “pdp\_uri” or a “plan\_uri” attribute.

**Predicate:** The HTTP code of (m2) is NOT code 415, “Unsupported Media Type”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.7.4 Duplicate Keys in JSON, Provider side (CAMP11-204)

Addressing normative statement:

Consumers and Providers SHALL NOT transmit JSON objects that contain duplicate keys. [\[PR-02\]](#)

---

**TA\_Id:** CAMP11-204

**NormativeSource:** PR-02 (section: Required Formats / Duplicate Keys in JSON Objects)

**Target:** A successful response message (m2) with JSON content (Content-Type = "application/json") to a GET resource request (m1).

**Predicate:** there is no duplicate JSON keys at same level in the JSON content of the target message (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.7.5 Duplicate Keys in JSON, Provider side, Error generation (CAMP11-205)

Addressing normative statement:

If a Consumer sends a Provider a request containing duplicate keys in a JSON object, the Provider SHOULD reject the request by sending back a '400 Bad Request' status code. [\[PR-03\]](#)

---

**TA\_Id:** CAMP11-205

**NormativeSource:** PR-03 (section: Required Formats / Duplicate Keys in JSON Objects)

**Target:** A response message (m2) to a request message (m1) with JSON content that has duplicate keys at same level.

**Predicate:** The HTTP code in the target (m2) is '400 Bad Request'.

**PrescriptionLevel:** preferred

**Tag:** conformance=Provider

## 3.1.8 Resource Queries and HTTP

### 3.1.8.1 select\_attr Positive Case Provider side (CAMP11-206)

Addressing normative statement:

A Provider SHALL return only those attributes of the queried resource whose name occurs in the list specified by the value of 'select\_attr'. [\[PR-47\]](#)

---

**TA\_Id:** CAMP11-206

**NormativeSource:** PR-47 (*"If a GET message is sent with a select\_attr request parameter in the URI, then only the attributes of the queried resource that match these parameters must be returned."*) (derived from Section: Request parameters)

**Target:** A successful response message (HTTP code 200) (m4) to a GET resource query message (m3) that uses "select\_attr" query parameter.

**Prerequisite:** A previous message (m1) of the form GET resource URI (with no select\_attr query parameter) was sent with a successful response message (m2). (and assuming no "delete resource" message after m1).

**Predicate:** the body of the target message (m4) contains only the attributes of the resource within those returned in (m2), that match those attributes in the "select\_attr" query parameter.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.8.2 *select\_attr* Negative Case, GET (CAMP11-208)

Addressing normative statement:

If an attribute is not part of the resource, an HTTP 400 Bad Request status code SHALL be returned. [\[PR-09\]](#)

---

**TA\_Id:** CAMP11-208

**NormativeSource:** PR-09 (section: Request Parameters)

**Target:** A response message (m4) to a GET *resource* query message (m3) that uses “select\_attr” query parameter.

**Prerequisite:**

- A previous message (m1) of the form GET *resource* URI (with no *select\_attr* query parameter) was sent with a successful response message (m2). (and assuming no “delete *resource*” message after m1).
- In the request message (m3), there are attribute names (in *select\_attr* query parameter) that do not appear in the response (m2).

**Predicate:** the HTTP code in the target message (m4) is 400.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.8.3 *select\_attr* Positive Case, PUT (CAMP11-222a)

Addressing normative statement: (regular case with explicit value update)

To allow an update of a subset of a resource’s attributes, Providers SHALL support the use of the ‘select\_attr’ query parameter in conjunction with the HTTP PUT method. [\[PR-76\]](#)

---

**TA\_Id:** CAMP11-222a

**NormativeSource:** PR-76 (section: Partial Updates with PUT)

**Target:** A response message (m4) to a GET *resource* URI query message (m3).

**Prerequisite:**

- A previous message (m1) of the form PUT *resource* URI with *select\_attr* query parameter showing attribute names that also appear in (m1) body with actual values was sent, with a successful response message (m2). (and assuming no “delete *resource*” message after m1).

**Predicate:** The target message (m4) is a successful response and the attributes in (m4) that also appear in the *select\_attr* query parameter of (m1) as well as in (m1) body, show the same values as in the body of (m1).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.8.4 *select\_attr* Positive Case, PUT (CAMP11-222b)

Addressing normative statement: (case with implicit value deletion)

To allow an update of a subset of a resource’s attributes, Providers SHALL support the use of the ‘select\_attr’ query parameter in conjunction with the HTTP PUT method. [\[PR-76\]](#)

---

**TA\_Id:** CAMP11-222b

**NormativeSource:** PR-76 (section: Partial Updates with PUT)

**Target:** A response message (m4) to a GET *resource URI* query message (m3).

**Prerequisite:**

- A previous message (m1) of the form PUT *resource URI* with `select_attr` query parameter showing attribute names that do not appear in (m1) body was sent, with a successful response message (m2). (and assuming no “delete *resource*” message after m1).

**Predicate:** The target message (m4) is a successful response and the attributes that appear in the `select_attr` query parameter of (m1) but not in (m1) body, are absent (i.e. empty-valued) from (m4).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.8.5 `select_attr` Positive Case, PUT (CAMP11-222c)

Addressing normative statement: (case showing that attributes NOT present in `select_attr` are not affected )

To allow an update of a subset of a resource’s attributes, Providers SHALL support the use of the ‘`select_attr`’ query parameter in conjunction with the HTTP PUT method. [\[PR-76\]](#)

---

**TA\_Id:** CAMP11-222c

**NormativeSource:** PR-76 (section: Partial Updates with PUT)

**Target:** A response message (m6) to a GET *resource URI* query message (m5).

**Prerequisite:**

- A previous message (m1) of the form GET *resource URI* has a successful response message (m2) showing some attribute values.
- A previous message (m3) of the form PUT *resource URI* with `select_attr` query parameter showing attribute names that are a subset of those in (m2) was sent, with a successful response message (m4).

**Predicate:** The target message (m6) is a successful response and shows same attribute values as in (m2) for those attributes that do not appear in the `select_attr` query parameter of (m3).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.8.6 `select_attr` Negative Case, PUT (CAMP11-209)

Addressing normative statement:

Upon receiving such a malformed request (see PR-12 case) the Provider SHALL respond with a 400 status code. [\[PR-13\]](#)

---

**TA\_Id:** CAMP11-209

**NormativeSource:** PR-13 (section: Request Parameters )

**Target:** A response message (m4) to a PUT *resource* query message (m3) that uses “`select_attr`” query parameter, where (m3) includes attributes in its request body that are not listed in `select_attr` values.

- 

**Predicate:** the HTTP code in the target message (m4) is 400.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.9 Resource Updates

### 3.1.9.1 ETag HTTP Header in Responses (CAMP11-211)

Addressing normative statement:

All HTTP responses that return representation of a resource SHOULD use strong Etag response header field indicating the current value of the entity tag for the resource. [\[PR-20\]](#)

---

**TA\_Id:** CAMP11-211

**NormativeSource:** PR-20 (section: Response Headers)

**Target:** A successful response message (HTTP code 200) (m2) to a GET *resource* message (m1).

**Predicate:** the target (m2) has an *ETag* HTTP header, with a valid entity tag value.

**PrescriptionLevel:** preferred

**Tag:** conformance=Provider

### 3.1.9.2 If-Match semantics (CAMP11-212)

Addressing normative statement:

If the If-Match header field value in the request does not match the one on the server-side, the Provider SHALL send back a '412 Precondition Failed' status code. [\[PR-07\]](#)

---

**TA\_Id:** CAMP11-212

**NormativeSource:** PR-07 (section: Request Headers)

**Target:** A response message (m2) to a PUT request message (m1) that has an empty *If-Match* HTTP header value.

**Prerequisite:** Some previous responses to GET *resource* messages show the use of *ETag* by the provider.

**Predicate:** the target message (m2) has HTTP code '412 Precondition Failed'.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.9.3 PUT semantics, regular, Provider (1)( CAMP11-213)

Addressing normative statement:

On successfully processing an HTTP PUT request a Provider SHALL update all the Consumer-mutable attributes of the target resource, and only these, with the values of the matching attributes in the request. [\[PR-48\]](#)

On successfully processing the request the Provider SHALL create an *assembly resource* and return a 201 *Created* status code in the HTTP response. [\[PR-53\]](#)

---

**TA\_Id:** CAMP11-213

**NormativeSource:** PR-48, RE-53 (section: Updating Resources)

**Var:** (resource) in {  
    sensor,  
    plan,  
    assembly,  
    component  
}

**Target:** A successful response message (HTTP code 200)(m4) to a GET *resource* message (m3).

**Prerequisite:**



- A previous message (m1) of the form PUT *resource* URI (with no `select_attr` query parameter) was sent with a successful response message (m2). (and assuming no “delete *resource*” message after m1).

**Predicate:** the target message (m4) shows for consumer-mutable attributes (e.g. `name`, `description`) the same attribute values as their counterpart in the message (m1).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.9.4 PUT semantics, regular, Provider (2) (CAMP11-214)

Addressing normative statement:

If a resource attribute is present on a resource and if an HTTP PUT request omits that attribute, it SHOULD be treated by the Provider as a request to delete the attribute. [\[PR-25\]](#)

---

**TA\_Id:** CAMP11-214

**NormativeSource:** PR-25, (section: Updating Resources)

**Var:** (resource) in {  
     sensor,  
     plan,  
     assembly,  
     component  
 }

**Target:** A successful response message (HTTP code 200)(m4) to a GET *resource* message (m3).

**Prerequisite:**

A previous message (m1) of the form PUT *resource* URI (with no `select_attr` query parameter) and with some consumer-mutable attribute missing (e.g. `description`) was sent with a successful response message (m2). (and assuming no “delete *resource*” message after m1).

**Predicate:** the target message (m4) does not show any (consumer-mutable) attribute name or value, for attribute names that were missing in (m1).

**PrescriptionLevel:** preferred

**Tag:** conformance=Provider

### 3.1.9.5 PUT semantics, Immutable attributes, Provider (CAMP11-216)

Addressing normative statement:

On receiving such a request the Provider SHALL generate an HTTP response with 403 HTTP status code. [\[PR-22\]](#)

---

**TA\_Id:** CAMP11-216

**NormativeSource:** PR-22 (section: Mutability of Resources Attributes)

**Var:** (resource) in {  
     assembly,  
     component,  
     plan  
 }

**Target:** A response message (m4) to a PUT *resource* request (m3).

**Prerequisite:**

- A successful previous response message (m2) to a GET *resource* message (m1) (same resource URI as target) (and assuming no “delete *resource*” message after m1).



- The message (m3) is either missing some consumer-immutable attributes for this resource type (compared with those present in the message m2), or is providing some values different from those in (m2).

**Predicate:** The response (m4) has HTTP code 203

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.9.6 PATCH support, Provider (CAMP11-218)

Addressing normative statement:

Providers SHALL support the 'add', 'remove', and 'replace' operations. [\[PR-27\]](#)

Providers SHALL support the HTTP GET, PUT, and PATCH methods on all of the resources defined in this section. [\[RE-53\]](#)

**TA\_Id:** CAMP11-218

**NormativeSource:** PR-27, RE-53 (section: Updating with JSON Patch)

**Var:** (resource) in {  
     assembly,  
     component,  
     plan  
 }

**Target:** A response message (m4) to a PATCH *resource* request (m3) that contains no other operations than 'add', 'remove', and 'replace'.

**Prerequisite:**

- A previous GET *resource* message (m1) was sent on same resource URI as (m3) with a successful response message (m2). (and assuming no "delete *resource*" message after m1).
- The PATCH message (m3) only attempts to update consumer-mutable attributes.

**Predicate:** Target message (m4) has HTTP code 2xx .

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.9.7 PATCH semantics, Provider (CAMP11-219)

Addressing normative statement:

Providers SHALL support the 'add', 'remove', and 'replace' operations. [\[PR-27\]](#)

**TA\_Id:** CAMP11-219

**NormativeSource:** PR-27, (RE-53) (section: Updating with JSON Patch)

**Var:** (resource) in {  
     assembly,  
     component,  
     plan,  
     service  
 }

**Target:** A successful response message (HTTP code 200)(m4) to a GET *resource* request message (m3).

**Prerequisite:**

A previous message (m1) of the form PATCH *resource* on same URI as (m3) was sent with a successful response message (m2). (and assuming no "delete *resource*" message after m1).

**Predicate:** the target message (m4) shows for consumer-mutable attributes the same attribute values as the message (m1) for “replace” and “add” ops, and it does not show any (consumer-mutable) attribute that was in an “remove” op in (m1).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.10 Resource Creation and Consistency of Representations

#### 3.1.10.1 Creation of a *plan* by Reference (1) (CAMP11-301)

Addressing normative statements:

On successfully processing the request the Provider SHALL create a *plan resource* and return a 201 Created status code in the HTTP response. [\[PR-57\]](#)

---

**TA\_Id:** CAMP11-301

**NormativeSource:** PR-57 (section: Registering a Plan by Reference)

**Target:** A response message (m2) to a POST *plans* message (m1).

**Prerequisite:** the target message (m2) has not an HTTP code 202 “accepted”

**Predicate:** the target message (m2) has HTTP code 201 “created”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

#### 3.1.10.2 Creation of a *plan* by Reference (2) (CAMP11-321)

Addressing normative statements:

On successfully processing the request the Provider SHALL create a *plan resource* and return a 201 Created status code in the HTTP response. [\[PR-57\]](#)

---

**TA\_Id:** CAMP11-321

**NormativeSource:** PR-57 (section: Registering a Plan by Reference)

**Target:** A response message (m4) to a GET *plan* message (m3), with a *representation\_skew*=NONE.

**Prerequisite:** A sequence of messages occurred as follows:

- A POST *plans* message (m1) with a *pdp\_uri* has been sent, and a response message (m2) received with HTTP code 201 “Created” and with a location header with a URI.
- The GET message (m3) is sent to the location URI returned by (m2)

**Predicate:** the target message (m4) has HTTP code 200 AND its content satisfies the serialization schema (JSON ) for *Plan*, AND has a *type* attribute of value = “plan”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

#### 3.1.10.3 Consistency of *assemblies* Links after Deployment of a PDP by Reference (CAMP11-302)

Addressing normative statement:

The Provider SHALL update the *assembly\_links* attribute of the *assemblies resource* to include a reference to the newly created *assembly resource*. [\[PR-52\]](#)

---

**TA\_Id:** CAMP11-302

**NormativeSource:** PR-52 (section: Deploying an Application by Reference)

**Target:** A response message (m4) to a GET `assemblies` message (m3), with a `representation_skew=NONE`.

**Prerequisite:** A sequence of messages previously occurred as follows:

- A POST `assemblies` message (m1) with either a `pdp_uri` or a `plan_uri` has been sent,
- A successful (HTTP code 201 “Created” ) response message (m2) received with a location header with a URI.
- The GET `assemblies` message (m3) is sent on same platform as (m1).

**Predicate:** the target message (m4) has HTTP code 200 AND its `assemblies.assembly_links` resource contains the location URI returned by (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.10.4 Consistency of `assemblies` Links after Deployment of a PDP or Plan by Value (CAMP11-303)

Addressing normative statement:

The Provider SHALL update the `assembly_links` attribute of the `assemblies` resource to include a reference to the newly created `assembly` resource. [\[PR-55\]](#)

---

**TA\_Id:** CAMP11-303

**NormativeSource:** PR-55 (PR-53, PR-54), (section: Deploying an Application by Value)

**Target:** A response message (m4) to a GET `assemblies` message (m3), with a `representation_skew=NONE`.

**Prerequisite:** A sequence of messages occurred as follows:

- A POST `assemblies` message (m1) with either an embedded PDP or a Plan has been sent,
- A successful (HTTP code 201 “Created” ) response message (m2) received with a location header with a URI.
- The GET `assemblies` message (m3) is on same platform URI as (m1).

**Predicate:** the target message (m4) has HTTP code 200 AND its `assemblies.assembly_links` resource contains the location URI returned by (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.10.5 Effective Creation of an `assembly` (2), setting Links (CAMP11-306)

Addressing normative statement:

An `assembly` resource SHALL have at least one reference to a `component` resource. [\[RE-39\]](#)

Providers that support Plans SHALL include this attribute (`plan_uri`) in all `assembly` resources. [\[RMR-04\]](#)

---

**TA\_Id:** CAMP11-306

**NormativeSource:** RE-39, RMR-04

**Target:** A response message (m4) to a GET `assembly` message (m3), with a `representation_skew=NONE`.

**Prerequisite:** A sequence of messages occurred as follows:

- A POST `plan` message (m1) has been sent (the `plan` URI exists in the `plans.plan_links` obtained from `platform.plan_uris`), with a successful (HTTP code 201 “Created”) response message (m2) received with a location header with a URI.
- The GET `assembly` message (m3) is sent on the URI returned by (m2).

**Predicate:** the target message (m4) has HTTP code 200 AND its `assembly.components[]` has at least one link to a Component resource, AND its `assembly.plan_uri` link is set to the URI used in (m1).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.10.6 Direct Creation of a component (1) (CAMP11-310)

Addressing normative statement:

If this attribute is present in the resource, Providers SHALL support the POST method on that resource in addition to the methods defined in Section **Error! Reference source not found.**, “HTTP Method Support”. [RE-38]

---

**TA\_Id:** CAMP11-310

**NormativeSource:** RE-38 (section: `Service Resource / parameter_definitions_uri`)

**Target:** A response message (m2) to a POST `service` message (m1) that has the `parameter_definitions_uri` defined.

**Predicate:** the target message has HTTP code 201 “Created” and a location header with a URI.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.11 Use of Parameters

### 3.1.11.1 Consistent Use of Parameters in POST (CAMP11-312)

Addressing normative statement:

If a POST request body does not contain a value for a required parameter, a “400 Bad Request” response SHALL be returned. [PR-18]

---

**TA\_Id:** CAMP11-312

**NormativeSource:** PR-18, (section: POST Body Parameters / Parameter Handling)

**Var:** (resource) in {  
     `assembly`,  
     `plan`,  
     `service`  
 }

**Target:** A response message (m6) to a POST `resource` message (m5), where (m5) is not setting a required parameter as defined in (m4).

**Prerequisite:**

- A successful response message (m2) to a previous GET `resource` message (m1).
- A successful response message (m4) to a GET `resource.parameter_definitions_uri` message (m3). In the array (m4)`parameter_definitions.parameter_definitions_links` some link(s) refer to a `parameter_definition` resource with a required attribute set to “true”.

**Predicate:** the target message (m6) has an HTTP error code 400 “Bad request”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.11.2 Acceptable Value of Parameters in POST (CAMP11-313)

Addressing normative statement:

If a POST request body does not contain an acceptable value for a parameter, a “400 Bad Request” response SHALL be returned. [\[PR-19\]](#)

---

**TA\_Id:** CAMP11-313

**NormativeSource:** PR-19, (section: POST Body Parameters / Parameter Handling)

**Var:** (resource) in {  
    assemblies,  
    plans,  
    service  
}

**Target:** A response message (m6) to a POST *resource* message (m5), where (m5) is setting a parameter with a value incompatible with its *parameter\_type* as defined in (m4).

**Prerequisite:**

- A successful response message (m2) to a previous GET *resource* message (m1).
- A successful response message (m4) to a GET *resource.parameter\_definitions\_uri* message (m3).
- Successful response messages to access enough *parameter\_definition* resources referred in the links (m4)*parameter\_definitions.parameter\_definitions\_links*, in order to show incompatibility of a parameter value used in (m5)

**Predicate:** the target message (m6) has an HTTP error code 400 “Bad request”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.12 Resource Deletion

#### 3.1.12.1 HTTP-level Deletion of an *assembly* Resource (CAMP11-317)

Addressing normative statement:

In addition to the methods defined in Section **Error! Reference source not found.**, “HTTP Method Support”, Providers SHALL support the HTTP DELETE method on the *assembly resource*. [\[RE-61\]](#)

---

**TA\_Id:** CAMP11-317

**NormativeSource:** RE-61 (section: Deleting an Application Instance and a Deployed Application)

**Target:** A response message to a DELETE *assembly* message.

**Prerequisite:** The *assembly* URI exists as a link in *assemblies.assembly\_links* obtained from *platform.assemblies\_uri* from prior successful (HTTP code 200 “OK”) response message to a GET *platform* message.

**Predicate:** the target message has NOT an HTTP code 405 “Method Not Allowed”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.12.2 Effective Deletion of an `assembly` resource (CAMP11-318)

Addressing normative statement:

On reception of a DELETE request a Provider SHALL remove the reference to the *assembly resource* from the *assemblies resource*'s `assembly_links` array. [RE-74]

---

**TA\_Id:** CAMP11-318

**NormativeSource:** RE-74 (RE-61)(section: Deleting an Application Instance and a Deployed Application)

**Target:** A response message (m4) to a GET `assembly` URI message (m3).

**Prerequisite:** The following sequence of messages occurred:

- Prior to the target message:
- Prior to the target message: A successful (HTTP code 2xx) response (m2) to a DELETE `assembly` message (m1). The `assembly` URI is same as in (m3) and exists in a link in `assemblies.assembly_links` obtained from `platform.assemblies_uri` as shown in a previous GET `platform` message.
- After the target message: A successful (HTTP code 2xx) response (m6) to a GET `assemblies` message (m5).

**Predicate:** the target message (m4) has HTTP code 5xx, AND the URI does not exist anymore in a link in (m6) `assemblies.assembly_links`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.12.3 Effective Deletion of `component` Resources of an `assembly` Resource (CAMP11-340)

Addressing normative statement:

On reception of a DELETE request a Provider SHALL remove the *assembly resource* from the system along with any *component resources* referenced by that *assembly resource*. (i.e. the tree of resources that was created when the application was instantiated). [RE-73]

---

**TA\_Id:** CAMP11-340

**NormativeSource:** RE-73, (RE-61)(section: `assembly` Resource)

**Target:** A response message (m6) to a GET `component` URI message (m5), where the `component` URI belongs to `m2:assembly.components[]` (see prerequisite).

**Prerequisite:** The following sequence of messages occurred prior to the target message:

- A successful (HTTP code 2xx) response (m2) to a GET `assembly` message (m1).
- A successful (HTTP code 2xx) response (m4) to a DELETE `assembly` message (m3).

**Predicate:** the target message (m6) has HTTP code 5xx.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.12.4 Effective Deletion of a `component` Resource (CAMP11-320)

Addressing normative statement:

In addition to the methods defined in Section **Error! Reference source not found.**, "HTTP Method Support", Providers SHALL support the HTTP DELETE method on the *component resource*. [RE-62]

---

**TA\_Id:** CAMP11-320

**NormativeSource:** RE-62 (section: Component Resource)

**Target:** A response message (m4) to a GET `component` URI message (m3).

**Prerequisite:** The following sequence of messages occurred:

- Prior to the target message: A successful (HTTP code 2xx) response (m2) message to a DELETE `component` message (m1). The URI is same as in (m3), and exists in a link in an `assembly.components[]` as shown in a previous GET `assembly` message (m0).
- After the target message occurred: a successful (HTTP code 200 “OK”) response message (m6) to a GET `assembly` message (m5) on same URI as in (m0).

**Predicate:** the target message (m4) has HTTP code 5xx, AND the URI does not exist anymore as a link in (m6)`assembly.components[]`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.12.5 HTTP Deletion of a `component` Resource (CAMP11-323)

Addressing normative statement:

In addition to the methods defined in Section **Error! Reference source not found.**, “HTTP Method Support”, Providers SHALL support the HTTP DELETE method on the *component resource*. [RE-62]

**TA\_Id:** CAMP11-323

**NormativeSource:** RE-62 (section: Component Resource)

**Target:** A response message to a DELETE `component` message.

**Prerequisite:** The `component` URI exists as a link in an `assembly.components[]` as shown in a previous GET `assembly` message.

**Predicate:** the target message has NOT an HTTP code 405 “Method Not Allowed”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.13 Representation Skew Semantics

### 3.1.13.1 `representation_skew` Semantics (1) (CAMP11-329)

Addressing normative statement:

The following table lists the methods that SHALL be supported for each `representation_skew` value. [RE-12]

<code>representation_skew</code> value	Methods Available
CREATING	GET, DELETE
NONE	All supported methods for that resource.
UNKNOWN	All supported methods for that resource.
DESTROYING	GET

**TA\_Id:** CAMP11-329

**NormativeSource:** RE-12, (RE-53) (section: `representation_skew`)

**Var:** (resource) in {  
    plan,  
    component,



```
    assembly
}
```

**Target:** A response message (m4) to a PUT request (m3) to a *resource*.

**Prerequisite:** The following message sequence occurred:

- Prior to the target: A message (m1) of the form GET *resource* URI was sent with a successful response message (m2), showing `representation_skew=CREATING`.
- After the target: An message (m5) similar to (m1) with a successful response message (m6), still showing `representation_skew=CREATING`.

**Predicate:** the target message has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.13.2 `representation_skew` Semantics (2) (CAMP11-330)

Addressing normative statement:

(see CAMP11-329)

The following table lists the methods that SHALL be supported for each `representation_skew` value. [\[RE-12\]](#)

---

**TA\_Id:** CAMP11-330

**NormativeSource:** RE-12, (RE-53) (section: `representation_skew`)

**Var:** (resource) in {  
    plan,  
    component,  
    assembly  
}

**Target:** A response message (m4) to a PATCH *resource* message (m3).

**Prerequisite:** The following message sequence occurred:

- Prior to the target: A message (m1) of the form GET *resource* URI was sent with a successful response message (m2), showing `representation_skew=CREATING`.
- After the target: An message (m5) similar to (m1) with a successful response message (m6), still showing `representation_skew=CREATING`.

**Predicate:** the target message has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.13.3 `representation_skew` Semantics (3) (CAMP11-331)

Addressing normative statement:

(see CAMP11-329)

The following table lists the methods that SHALL be supported for each `representation_skew` value. [\[RE-12\]](#)

---

**TA\_Id:** CAMP11-331

**NormativeSource:** RE-12, (RE-53) (section: `representation_skew`)

**Var:** (resource) in {  
    plan,  
    assembly  
}



**Target:** A response message (m4) to a PUT *resource* message (m3).

**Prerequisite:** The following message sequence occurred:

- Prior to the target: A message (m1) of the form GET *resource* URI was sent with a successful response message (m2), showing `representation_skew=DESTROYING`.
- After the target: An message (m5) similar to (m1) with a successful response message (m6), still showing `representation_skew=DESTROYING`.

**Predicate:** the target message has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.13.4 `representation_skew` Semantics (4) (CAMP11-332)

Addressing normative statement:

(see CAMP11-329)

The following table lists the methods that SHALL be supported for each `representation_skew` value. [\[RE-12\]](#)

---

**TA\_Id:** CAMP11-332

**NormativeSource:** RE-12, (RE-53) (section: `representation_skew`)

**Var:** (resource) in {  
    plan,  
    assembly  
}

**Target:** A response message (m4) to a PATCH *resource* message (m3).

**Prerequisite:** The following message sequence occurred:

- Prior to the target: A message (m1) of the form GET *resource* URI was sent with a successful response message (m2), showing `representation_skew=DESTROYING`.
- After the target: An message (m5) similar to (m1) with a successful response message (m6), still showing `representation_skew=DESTROYING`.

**Predicate:** the target message has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.13.5 `representation_skew` Semantics (5) (CAMP11-333)

Addressing normative statement:

(see CAMP11-329)

The following table lists the methods that SHALL be supported for each `representation_skew` value. [\[RE-12\]](#)

---

**TA\_Id:** CAMP11-333

**NormativeSource:** RE-12, (RE-53) (section: `representation_skew`)

**Var:** (resource) in {  
    plan,  
    assembly  
}

**Target:** A response message (m4) to a DELETE *resource* message (m3).

**Prerequisite:** The following message sequence occurred:

- Prior to the target: A previous message (m1) of the form GET *resource* URI was sent with a successful response message (m2), showing *representation\_skew*=DESTROYING.
- After the target: An message (m5) similar to (m1) with a successful response message (m6), still showing *representation\_skew*=DESTROYING.

**Predicate:** the target message has an 4xx HTTP code.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14 PDP and Plan Registration

#### 3.1.14.1 PDP Registration by Reference: Provider side (1) (CAMP11-412)

Addressing normative statement:

On successfully processing the request the Provider SHALL create a *plan resource* and return a 201 Created status code in the HTTP response. [\[PR-57\]](#)

---

**TA\_Id:** CAMP11-412

**NormativeSource:** PR-57 (RMR-05)

**Target:** A response message (m2) to a POST *plans* message (m1) where (m1) has a “*pdp\_uri*” attribute.

**Prerequisite:** the HTTP code in target (m2) is NOT 202 “accepted”.

**Predicate:** the HTTP code in target (m2) is 201 “Created”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

#### 3.1.14.2 PDP Registration by Reference: Provider side (2) (CAMP11-414)

Addressing normative statement:

On successfully processing the request the Provider SHALL create a *plan resource* and return a 201 Created status code in the HTTP response. [\[PR-57\]](#)

The Provider SHALL include the *Location* header in the HTTP response and the value of this header SHALL reference the newly created *plan resource*. [\[PR-58\]](#)

---

**TA\_Id:** CAMP11-414

**NormativeSource:** PR-57, PR-58 (RMR-05)

**Target:** A response message (m2) to a POST *plans* message (m1) where (m1) has a “*pdp\_uri*” attribute.

**Prerequisite:** the HTTP code in target (m2) is 201 “Created”.

**Predicate:** the target message contains a location header with the URI for the new *plan* resource AND this URI resolves (GET *plan*) to a *plan* resource with *type* attribute = “plan”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

#### 3.1.14.3 PDP Registration by Reference: Provider side (CAMP11-425)

Addressing normative statement:

The Provider SHALL update the *plan\_links* attribute of the *plans resource* to include a reference to the newly created *plan resource*. [\[PR-59\]](#)

---

**TA\_Id:** CAMP11-425

**NormativeSource:** PR-59

**Target:** A response message (m4) to a GET `plans` message (m3), with a `representation_skew=NONE`.

**Prerequisite:** A sequence of messages previously occurred as follows:

- A POST `plans` message (m1) with either a `pdp_uri` or a `plan_uri` has been sent,
- A successful (HTTP code 201 "Created" ) response message (m2) received with a location header with a URI.
- The GET `plans` message (m3) is sent on same `platform` as (m1).

**Predicate:** the target message (m4) has HTTP code 200 AND its `plans.plan_links` attribute contains the location URI of the new `plan` resource returned by (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.4 PDP Registration by Value: Provider side (1) (CAMP11-418)

Addressing normative statement:

On successfully processing the request the Provider SHALL create a *plan resource* and return a 201 Created status code in the HTTP response. [\[PR-62\]](#)

The Provider SHALL include the *Location* header in the HTTP response and the value of this header SHALL reference the newly created *plan resource*. [\[PR-63\]](#)

---

**TA\_Id:** CAMP11-418

**NormativeSource:** PR-62, PR-63 (RMR-05)

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) does not contain a "`pdp_uri`" nor a "`plan_uri`" attribute, and contains a Content-Type: `application/x-zip` or `application/x-tar` or `application/x-tgz`, or `application/x-yaml`.

**Prerequisite:** the HTTP code in target (m2) is 201 "Created".

**Predicate:** the target message contains a location header with the URI for the new `plan` resource AND this URI resolves (GET `plan`) to a `plan` resource with `type` attribute = "plan".

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.5 PDP Registration by Value: Provider side (2) (CAMP11-413)

Addressing normative statement:

To support the registration of Plans using a PDP, Providers SHALL accept the media types associated with the various formats as follows:

- ZIP: "`application/x-zip`" [\[PR-70\]](#)
- TAR: "`application/x-tar`" [\[PR-71\]](#)
- GZIP compressed TAR: "`application/x-tgz`" [\[PR-72\]](#)

---

**TA\_Id:** CAMP11-413

**NormativeSource:** PR-70, PR-71, PR-72, (RMR-05)

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) does not contain a "`pdp_uri`" nor a "`plan_uri`" attribute, and contains a Content-Type: `application/x-zip` or `application/x-tar` or `application/x-tgz`.

**Predicate:** the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the new `plan` resource, OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 "OK").

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.6 PDP Registration by Value: Provider side (2) (CAMP11-419)

Addressing normative statement:

To support the registration of Plans using a Plan file, Providers SHALL accept the use of the "application/x-yaml" media type. [\[PR-73\]](#)

---

**TA\_Id:** CAMP11-419

**NormativeSource:** PR-73 (RMR-05)

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) does not contain a "pdp\_uri" nor a "plan\_uri" attribute, and contains a Content-Type: `application/x-yaml`.

**Predicate:** the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the new `plan` resource, OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 "OK").

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.7 Plan Registration by Value using MIME Provider side (CAMP11-433)

Addressing normative statement:

Providers that support the plans resource and plan resources SHALL support the registration of Plans via HTTP POST requests on the plans resource as described in this section. [\[PR-75\]](#)

---

**TA\_Id:** CAMP11-433

**NormativeSource:** PR-75, (RMR-05)

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) does not contain a "pdp\_uri" nor a "plan\_uri" attribute, and contains a Content-Type = `multipart/form-data`, and the Content-Disposition header has name set to "plan\_file"

**Predicate:** (the HTTP code in target (m2) is 201 "Created" AND the target message m2 contains a location header with the URI for the new `plan` resource), OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 "OK").

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.8 PDP Registration by Value using MIME Provider side (CAMP11-437)

Addressing normative statement:

Providers that support the plans resource and plan resources SHALL support the registration of Plans via HTTP POST requests on the plans resource as described in this section. [\[PR-75\]](#)

---

**TA\_Id:** CAMP11-437

**NormativeSource:** PR-75, (RMR-05)

**Target:** A response message (m2) to a POST `plans` message (m1) where (m1) does not contain a “`pdp_uri`” nor a “`plan_uri`” attribute, and contains a `Content-Type = multipart/form-data`, and the `Content-Disposition` header has name set to “`pdp_file`”

**Predicate:** (the HTTP code in target (m2) is 201 “Created” AND the target message m2 contains a location header with the URI for the new `plan` resource), OR ( code = 202 “accepted” AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 “OK”) .

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.9 PDP Registration: URI scheme for Artifact Content Reference (1) (CAMP11-415)

Addressing normative statement:

Providers SHALL support the “https” URI scheme as defined in RFC 2818 [RFC2818]. [PDP-27]

NOTE: partial test.

---

**TA\_Id:** CAMP11-415

**NormativeSource:** PDP-27 (section: ContentSpecification)

**Target:** A response message (m2) to a POST `platform` message (m1) that uses “https” scheme, and refers to a PDP or passes a PDP or a Plan by value, where some `ArtifactSpecification` element has a content element with an “href” attribute.

**Prerequisite:** the PDP and contained Plan are well-formed.

**Predicate:** the HTTP code in target message is 2xx.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.10 PDP Registration: PDP scheme for Artifact Content Reference (Provider) (CAMP11-417)

Addressing normative statement:

Providers SHALL understand this delimiter and SHALL NOT resolve any content if the archive format is unsupported. [PDP-29]

---

**TA\_Id:** CAMP11-417

**NormativeSource:** PDP-29 (section: ContentSpecification)

**Target:** A response to a POST `platform` message that refers to a PDP or passes a PDP or a Plan by value, where some `ArtifactSpecification` element has a content element with an “href” attribute, that uses the URI scheme “pdp”.

**Prerequisite:** the PDP and contained Plan are well-formed AND the archive format used in the first part of the URI path (before “!”) is known to be supported .

**Predicate:** the HTTP code in target is 2xx.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.11 Registering PDP by Value with .zip format (CAMP11-422)

Addressing normative statement:

A Provider SHALL support the following archive formats for a PDP:

- A PDP as a ZIP archive [ZIP] [PDP-02]

To support the registration of Plans using a PDP, Providers SHALL accept the media types associated with the various formats as follows:

- ZIP: "application/x-zip" [PR-70]
- 

**TA\_Id:** CAMP11-422

**NormativeSource:** PDP-02, PR-70, (RMR-02, PR-63)(section: Supported Archive Formats)

**Target:** A response message (m2) to a A POST `platform` message (m1) with no "pdp\_uri" nor a "plan\_uri" attribute, and with an embedded PDP of type .zip ( Content-Type: application/x-zip).

**Predicate:** the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the deployed `plan`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.12 Registering a PDP by Value with .tar format (CAMP11-423)

Addressing normative statement:

A Provider SHALL support the following archive formats for a PDP:

- A PDP as a TAR archive [TAR] [PDP-03]

To support the registration of Plans using a PDP, Providers SHALL accept the media types associated with the various formats as follows:

- TAR: "application/x-tar" [PR-71]
- 

**TA\_Id:** CAMP11-423

**NormativeSource:** PDP-03, PR-71 (PR-63) (section: Supported Archive Formats)

**Target:** A response message (m2) to a A POST `platform` message (m1) with no "pdp\_uri" nor a "plan\_uri" attribute, and with an embedded PDP of type .tar ( Content-Type: application/x-tar).

**Predicate:** the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the deployed `plan`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.14.13 Registering a PDP by Value with .tar.gz format (CAMP11-424)

Addressing normative statement:

A Provider SHALL support the following archive formats for a PDP:

- A PDP as a GZIP [RFC1952] compressed TAR archive [PDP-04]

To support the registration of Plans using a PDP, Providers SHALL accept the media types associated with the various formats as follows:

- GZIP compressed TAR: "application/x-tgz" [PR-72]
- 

**TA\_Id:** CAMP11-424

**NormativeSource:** PDP-04, PR-72 (PR-63) (section: Supported Archive Formats)

**Target:** A response message (m2) to a A POST `platform` message (m1) with no "pdp\_uri" nor a "plan\_uri" attribute, and with an embedded PDP of type .tar.gz ( Content-Type: application/x-tgz).

**Predicate:** the HTTP code in target (m2) is 201 “Created” AND the target message contains a location header with the URI for the deployed `plan`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.1.15 Application Deployment

### 3.1.15.1 Application Deployment by Reference: Provider side (1) (CAMP11-439)

Addressing normative statement:

On successfully processing the request the Provider SHALL create an *assembly resource* and return a 201 Created status code in the HTTP response. [\[PR-50\]](#)

---

**TA\_Id:** CAMP11-439

**NormativeSource:** PR-50 (section: Deploying an Application by Reference)

**Target:** A response message (m2) to a POST `assemblies` message (m1) where (m1) has a either a “`pdp_uri`” or a “`plan_uri`” attribute.

**Prerequisite:** the target message (m2) has not an HTTP code 202 “accepted”

**Predicate:** the target message (m2) has HTTP code 201 “created”

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.15.2 Application Deployment by Reference: Provider side (2) (CAMP11-440)

Addressing normative statement:

On successfully processing the request the Provider SHALL create an *assembly resource* and return a 201 Created status code in the HTTP response. [\[PR-50\]](#)

The Provider SHALL include the *Location* header in the HTTP response and the value of this header SHALL reference the newly created *assembly resource*. [\[PR-51\]](#)

---

**TA\_Id:** CAMP11-440

**NormativeSource:** PR-50, PR-51

**Target:** A response message (m2) to a POST `assemblies` message (m1) where (m1) has a either a “`pdp_uri`” or a “`plan_uri`” attribute.

**Predicate:** the target message contains a location header with the URI for the new *assembly resource*, OR ( code = 202 “accepted” AND a subsequent GET on the returned Location header URI shows either `representation_skew=CREATING` or HTTP code 200 “OK”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.15.3 Application Deployment by Value: Provider side (1) (CAMP11-441)

Addressing normative statement:

On successfully processing the request the Provider SHALL create an *assembly resource* and return a 201 *Created* status code in the HTTP response. [\[PR-53\]](#)

---

**TA\_Id:** CAMP11-441

**Var:** *archtype* in { `application/x-zip`, `application/x-tar`, `application/x-tgz`, `application/x-yaml` }

**NormativeSource:** PR-53, (PR-60), {PR-29, PR-30, PR-31, PR-32}



**Target:** A response message (m2) to a POST *assemblies* message (m1) where (m1) does not contain a "pdp\_uri" nor a "plan\_uri" attribute, and contains a Content-Type = *archtype*.

**Prerequisite:** HTTP code in (m2) is NOT 202 "accepted" i.e. enough time elapsed to allow for the creation to complete.

**Predicate:** the HTTP code in target (m2) is 201 "Created"

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.15.4 Application Deployment by Value: Provider side (2) (CAMP11-442)

Addressing normative statement:

On successfully processing the request the Provider SHALL create an *assembly resource* and return a 201 *Created* status code in the HTTP response. [PR-53]

The Provider SHALL include the *Location* header in the HTTP response and the value of this header SHALL reference the newly created *assembly resource*. [PR-54]

---

**TA\_Id:** CAMP11-442

**Var:** *archtype* in {application/x-zip, application/x-tar, application/x-tgz, application/x-yaml }

**NormativeSource:** PR-53, PR-54, (PR-60), {PR-29, PR-30, PR-31, PR-32}

**Target:** A response message (m2) to a POST *assemblies* message (m1) where (m1) does not contain a "pdp\_uri" nor a "plan\_uri" attribute, and contains a Content-Type = *archtype*.

**Predicate:** (the HTTP code in target (m2) is 201 "Created" AND the target message contains a location header with the URI for the new *assembly resource*), OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either *representation\_skew*=CREATING or HTTP code 200 "OK")

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

### 3.1.15.5 Application Deployment by Value using MIME: Provider side (CAMP11-443)

Addressing normative statement:

Providers SHALL support the deployment of applications via HTTP POST requests on the *assemblies resource* as described in this section. [PR-74]

---

**TA\_Id:** CAMP11-443

**NormativeSource:** PR-74, { PR-29, PR-30, PR-31, PR-32 }

**Target:** A response message (m2) to a POST *assemblies* message (m1) where (m1) does not contain a "pdp\_uri" nor a "plan\_uri" attribute, and contains a Content-Type = *multipart/form-data*.

**Prerequisite:** The name parameter of (m1) Content-Disposition header is set to "pdp\_file".

**Predicate:** (the HTTP code in target (m2) is 201 "Created" AND the target message m2 contains a location header with the URI for the new *assembly resource*), OR ( code = 202 "accepted" AND a subsequent GET on the returned Location header URI shows either *representation\_skew*=CREATING or HTTP code 200 "OK")

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider



### 3.1.15.6 Creation of `plan` Resource when Deploying an Application (1) (CAMP11-444)

Addressing normative statement:

Regardless of whether a Consumer attempts to create an *assembly resource* by POSTing to the *assemblies resource* or creates a *plan resource* by POSTing to the *plans resource*, a Provider that supports *plans* and *plan resources* SHALL create a *plan resource* for every deployed application. [RMR-11]

Providers that support Plans SHALL include this attribute (`plan_uri`) in all *assembly resources*. [RMR-04]

---

**TA\_Id:** CAMP11-444

**NormativeSource:** RMR-11

**Target:** A response message (m4) to a GET `assembly` message (m3), with HTTP code 200 and with a `representation_skew=NONE`.

**Prerequisite:** A set of messages previously occurred as follows:

- A successful POST `assemblies` message (m1) has been sent (response HTTP code 201 "Created"), that returns a Location header URI (m2) used in (m3) (GET `assembly`)
- A successful response message (m2) received from a GET `platform` message (m1) shows a `plan_uris` attribute set to a valid `plans` Resource.

**Predicate:** the target message (m4) has its `assembly.plan_uri` link set to a `plan` Resource (a GET on that URI returns HTTP code 200 "OK") AND the `plan` URI also exists in the `plans.plan_links` obtained from `platform.plan_uris`, (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Provider

## 3.2 Consumer Test Assertions

These Test Assertions concern the Consumer as conformance target.

### 3.2.1 Basic Schema Compliance for Platform Resources, Consumer Side

#### 3.2.1.1 Resource Serialization with PUT (CAMP11-105)

A Consumer SHALL serialize Resource data in its requests based on the definition of this Resource as described in the corresponding sub-section. [RE-71]

---

**TA\_Id:** CAMP11-105

**NormativeSource:** RE-71 (section: Resources)

**Var:** (`resource`) in {  
    `sensor`,  
    `plan`,  
    `assembly`,  
    `component`  
}

**Target:** A message (m1) of the form PUT *resource* URI (with no `select_attr` query parameter)

**Predicate:** the target message (m1) content satisfies the serialization schema (JSON ) for *resource*, AND has a `type` attribute of value = `<resource name>`.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.2 Consistency of Serialization with Metadata

### 3.2.2.1 Non-Mutability Enforcement (Consumer) (CAMP11-116)

Addressing normative statement:

“false” indicates that the value(s) of the attribute SHALL NOT be changed by Consumers. [\[RE-09\]](#)

---

**TA\_Id:** CAMP11-116

**NormativeSource:** RE-09, (RE-53) (section: Consumer-mutable)

**Var:** (resource) in {  
    assembly,  
    component,  
    platform  
}

**Target:** A PUT request (m3) to a *resource*.

**Prerequisite:** The following message sequence occurred:

A previous message (m1) of the form GET *resource* URI was sent with a successful response message (m2). (and assuming no “delete *resource*” message after m1).

**Predicate:** The PUT request (m3) is providing same values as shown in (m2) for `consumer-mutable=false` attributes.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.3 Various Model Referential and Semantic Constraints

### 3.2.3.1 UTC Timestamps, Consumer side (CAMP11-135)

Addressing normative statement:

Consumers and Providers SHALL express Timestamps in UTC (Coordinated Universal Time), with the special UTC designator ("Z"). [\[RE-65\]](#)

---

**TA\_Id:** CAMP11-135

**NormativeSource:** RE-65 (section: Timestamp)

**Target:** A POST or PUT message that has a resource serialization showing the “timestamp” attribute.

**Predicate:** the Timestamp value conforms to the UTC (Universal Time Coordinated) with a “zero” timezone offset, i.e. with format terminated with the designator “Z”, of the form: yyyy '-' mm '-' dd 'T' hh ':' mm ':' ss 'Z' (Example: 1994-11-05T13:15:30Z)

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.4 Support for JSON

### 3.2.4.1 Duplicate Keys in JSON, Consumer side (CAMP11-203)

Addressing normative statement:

Consumers and Providers SHALL NOT transmit JSON objects that contain duplicate keys. [\[PR-02\]](#)

---

**TA\_Id:** CAMP11-203

**NormativeSource:** PR-02 (sections: Required Formats / Duplicate Keys in JSON Objects)

**Target:** A POST or a PUT request with JSON content to any platform resource.

**Predicate:** there is no duplicate JSON keys at same level in the JSON content of the target message.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

NOTE: the corresponding error handling TA (Provider side) is addressing PR-03.

## 3.2.5 Resource Queries and HTTP

### 3.2.5.1 `select_attr` Positive Case Consumer side (CAMP11-207)

Addressing normative statement:

A Consumer SHALL NOT include attributes, whose name does not occur in the list specified by the value of the 'select\_attr' query parameter, in the entity body of a PUT request. [\[PR-12\]](#)

Note: Requirement about request parameters (6.5): "*In order to address a subset of attributes in a resource, the client can use request parameters in PUT ... When one or more request parameters are specified for a PUT request, a client shall not include attributes in the request entity body that are not specified in the request parameter.*"

---

**TA\_Id:** CAMP11-207

**NormativeSource:** PR-12 ("If a PUT message is sent with a `select_attr` request parameter in the URI, then only the attributes that appear in the `select_attr` request parameter must be used in the body of the update message.") (derived from section: Request parameters)

**Target:** A PUT request message to a *resource*, that uses "`select_attr`" query parameter.

**Predicate:** every attribute present in the body of the target message also appears in the "`select_attr`" query parameter.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.6 Resource Updates

### 3.2.6.1 If-Match HTTP Header in PUT Requests (CAMP11-210)

Addressing normative statement:

All PUT requests that update a resource SHOULD contain the If-Match header field with a single entity tag value. [\[PR-06\]](#)

---

**TA\_Id:** CAMP11-210

**NormativeSource:** PR-06 (section: Request Headers)

**Target:** A PUT request message to any resource existing in the platform.

**Predicate:** the target has an *If-Match* HTTP header.

**PrescriptionLevel:** preferred

**Tag:** conformance=Consumer

### 3.2.6.2 PUT Semantics, Immutable Attributes, Consumer (CAMP11-215)

Addressing normative statement:

Consumers SHALL NOT send a request that changes the value of a resource attribute that is declared with a constraint of 'Mutable=false' or 'Consumer-mutable=false'. [\[PR-21\]](#)

---

**TA\_Id:** CAMP11-215

**NormativeSource:** PR-21 (section: Mutability of Resources Attributes)

**Var:** (resource) in {  
    plan,  
    assembly,  
    component  
}

**Target:** A PUT *resource* request message.

**Prerequisite:**

A successful previous response message (m2) to a GET *resource* message (m1) (same resource URI as target) (and assuming no “delete *resource*” message after m1).

**Predicate:** the target message has all the consumer-immutable attributes for this resource type, as already present in the message (m2), and with same values as in (m2).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.6.3 PATCH syntax, Consumer (CAMP11-217)

Addressing normative statement:

Providers SHALL support the HTTP PATCH method in conjunction with the “application/json-patch+json” media type with the following, additional provisions with respect to the operations defined in Section 4 of the JSON Patch specification: [\[PR-26\]](#)

---

**TA\_Id:** CAMP11-217

**NormativeSource:** PR-26 (section: Updating with JSON Patch)

**Var:** (resource) in {  
    assembly,  
    component,  
    plan,  
    service  
}

**Target:** A PATCH *resource* request.

**Predicate:** the media-type (Content-Type header) application/json-patch

is used in HTTP headers, AND the JSON content complies with JSON patch syntax (at least: an array of triples with keys “op”, “path” and “value”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.7 PDP and Plan Contents

### 3.2.7.1 PDP Content by Reference, Consumer side (1) (CAMP11-401)

Addressing normative statements:

The Plan file SHALL be located at the root of the PDP archive. [\[PLAN-01\]](#)

The Plan file SHALL be named “camp.yaml”. [\[PLAN-02\]](#)

---

**TA\_Id:** CAMP11-401

**NormativeSource:** PLAN-01, PLAN-02 (section: [Plan Schema](#))

**Target:** A POST message with a “pdp\_uri” attribute to a `plans` resource (obtained from `platform.plan_uris`), or an `assemblies` resource (obtained from `platform.assemblies_uri`).

**Predicate:** the PDP identified by `pdp_uri` is an archive that contains at its root a file named “`camp.yaml`”, with a YAML structure recognizable as a Plan (same top-level attributes, and “tags”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.2 PDP Content, by Reference, Consumer side (2) (CAMP11-402)

Addressing normative statement:

A Platform Deployment Package (PDP) SHALL contain a single Plan file. [PDP-11]

---

**TA\_Id:** CAMP11-402

**NormativeSource:** PDP-11 (section: [Plan Schema](#))

**Target:** A POST message with a “`pdp_uri`” attribute to a `plans` resource (obtained from `platform.plan_uris`, or to an `assemblies` resource (obtained from `platform.assemblies_uri`).

**Predicate:** the PDP identified by `pdp_uri` is an archive that contains at its root a file named “`camp.yaml`”, and does not contain any other `yaml` file of this name or of a structure recognizable as a `plan` (same top-level attributes, and “tags”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.3 PDP Content by Value, Consumer side (1) (CAMP11-403)

Addressing normative statements:

The Plan file SHALL be located at the root of the PDP archive. [PLAN-01]

The Plan file SHALL be named “`camp.yaml`”. [PLAN-02]

---

**TA\_Id:** CAMP11-403

**NormativeSource:** PLAN-01, PLAN-02, (section: [Plan Schema](#))

**Target:** A POST message without a “`pdp_uri`” or “`plan_uri`” attribute, to a `plans` resource (obtained from `platform.plan_uris`, or to an `assemblies` resource (obtained from `platform.assemblies_uri`).

**Predicate:** the PDP in the embedded archive contains at its root a file named “`camp.yaml`”, with a structure recognizable as a `plan` (same top-level attributes, and “tags”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.4 PDP Content by Value, Consumer side (2) (CAMP11-404)

Addressing normative statement:

A Platform Deployment Package (PDP) SHALL contain a single Plan file. [PDP-11]

---

**TA\_Id:** CAMP11-404

**NormativeSource:** PDP-11 (section: [Plan Schema](#))

**Target:** A POST message without a “`pdp_uri`” or “`plan_uri`” attribute, to a `plans` resource (obtained from `platform.plan_uris`, or to an `assemblies` resource (obtained from `platform.assemblies_uri`)).

**Predicate:** the PDP in the embedded archive contains at its root a file named “camp.yaml”, and does not contain any other yaml file of this name or of a structure recognizable as a plan (same top-level attributes, and “tags”).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.5 Plan Content, Consumer side (1) (CAMP11-405)

Addressing normative statement:

A Plan file SHALL contain a single instance of a Plan. [PLAN-03]

---

**TA\_Id:** CAMP11-405

**NormativeSource:** PLAN-03 (PDP-11) (section: Plan)

**Target:** A POST message to a plans URL, containing or referring to a Plan file.

**Predicate:** the Plan file identified in this POST contains a single yaml plan node (satisfies the yaml schema for this node).

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.6 Plan Content, Consumer side (2) (CAMP11-406)

Addressing normative statement:

For Plans that conform to this document, the value of this node (camp\_version) SHALL be as defined in Section Error! Reference source not found. “Specification Version”. [PLAN-05]

---

**TA\_Id:** CAMP11-406

**NormativeSource:** PLAN-05 (PLAN-03) (section: campVersion)

**Target:** A POST message to a plans URL, containing or referring to a Plan file.

**Predicate:** the Plan file identified in this POST has a yaml node that has a camp\_version tag with value “CAMP 1.1”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.7 Plan Content, Consumer side (3) (CAMP11-430)

Addressing normative statement:

Plans SHALL use id values that are unique within the scope of the Plan. [PLAN-06]

---

**TA\_Id:** CAMP11-430

**NormativeSource:** PLAN-06 (section: serviceSpecification)

**Target:** A POST message to a plans URL, containing or referring to a Plan file.

**Predicate:** the services array (ServiceSpecification[]) contained in the Plan file identified in this POST does NOT have two ServiceSpecification items with same id node value.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.8 Plan Content, Consumer side (4) (CAMP11-431)

Addressing normative statement:

If a Consumer includes this node in a Plan, the value of this node SHALL reference a Consumer-visible resource within the target Platform. [\[RMR-01\]](#)

---

**TA\_Id:** CAMP11-431

**NormativeSource:** RMR-01 (section: [ServiceSpecification](#))

**Target:** A POST message to a `Plans` URL, containing or referring to a Plan file.

**Predicate:** Any `ServiceSpecification` items that has an `href` node in the `services` array (`ServiceSpecification[]`) contained in the Plan file identified in this POST, has the `href` value resolve to an existing resource on the target platform.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.9 Plan Artifact Type Content Specification, Consumer side (CAMP11-407)

Addressing normative statement:

The Plan file SHALL conform to the description provided in this section. [\[PLAN-09\]](#)

---

**TA\_Id:** CAMP11-407

**NormativeSource:** PLAN-09 (section: [ContentSpecification](#))

**Target:** A POST message to a `plans` URL, containing or referring to a Plan file.

**Predicate:** in the Plan file identified in this POST, every `ArtifactSpecification` item (`artifacts` array) has a `content` node that has either an `href` node, or a `data` node but not both.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.10 PDP Manifest, Consumer side (CAMP11-408)

Addressing normative statement:

The format of the manifest file and the certificate file SHALL be as defined by the OVF specification [\[OVF\]](#). [\[PDP-10\]](#)

---

**TA\_Id:** CAMP11-408

**NormativeSource:** PDP-10 (PDP-06) (section: [Validating Integrity](#))

**Target:** A POST message to a `plans` URL, with either (a) a `"pdp_uri"`, or (b) a `Content-Type`: `application/x-zip` or `application/x-tar` or `application/x-tgz`.

**Prerequisite:** the PDP referenced in the target message contains a manifest (`"camp.mf"`) at its root.

**Predicate:** the manifest (`"camp.mf"`) at the root of the PDP conforms to the structure defined in OVF [\[DSP0243\]](#) for OVF manifest files.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

### 3.2.7.11 PDP Certificate, Consumer side (CAMP11-409)

Addressing normative statement:

The format of the manifest file and the certificate file SHALL be as defined by the OVF specification [\[OVF\]](#). [\[PDP-10\]](#)

---

**TA\_Id:** CAMP11-409

**NormativeSource:** PDP-10 (section: [Validating Integrity](#))



**Target:** A POST message to a `plans` URL, with either (a) a `"pdp_uri"`, or (b) a `Content-Type: application/x-zip` or `application/x-tar` or `application/x-tgz`.

**Prerequisite:** the PDP referenced in the target message contains a certificate (named `"camp.cert"`) at its root.

**Predicate:** the certificate (named `"camp.cert"`) at the root of the PDP conforms to the structure defined in OVF [DSP0243] for OVF certificate files.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.2.8 PDP and Plan Registration

### 3.2.8.1 PDP Registration: pdp scheme for Artifact Content reference (Consumer) (CAMP11-416)

Addressing normative statement:

Consumers SHALL follow the syntax and semantics described here when using URIs with a `"pdp"` scheme. [PLAN-07]

---

**TA\_Id:** CAMP11-416

**NormativeSource:** PLAN-07 (section: ContentSpecification)

**Target:** A POST `platform` message that refers to a PDP or passes a PDP or a Plan by value, where some `ArtifactSpecification` element has a content element with an `"href"` attribute, that uses the URI scheme `"pdp"` and contains the `"!"` character.

**Predicate:** the URI either shows `"!"` just after the scheme, or just after an archive name AND the right part after `"!"` is a path for a file that is resolvable from the root of the archive.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Consumer

## 3.3 PDP and Plan Test Assertions

### 3.3.1 PDP Test Assertions

#### 3.3.1.1 PDP and YAML Plan (CAMP11-401b)

Addressing normative statements:

The Plan file SHALL be located at the root of the PDP archive. [PLAN-01]

The Plan file SHALL be named `"camp.yaml"`. [PLAN-02]

---

**TA\_Id:** CAMP11-401b

**NormativeSource:** PLAN-01, PLAN-02 (section: Plan Schema)

**Target:** A PDP artifact.

**Prerequisite:** the PDP is in archive format (ZIP, TAR or GZIP).

**Predicate:** the PDP archive contains at its root a file named `"camp.yaml"`, with the YAML structure of a Plan.

**PrescriptionLevel:** mandatory

**Tag:** conformance=PDP



### 3.3.1.2 PDP and Plan file (CAMP11-402b)

Addressing normative statement:

A Platform Deployment Package (PDP) SHALL contain a single Plan file. [PDP-11]

---

**TA\_Id:** CAMP11-402b

**NormativeSource:** PDP-11 (section: [Plan Schema](#))

**Target:** A PDP artifact.

**Predicate:** the PDP contains (at its root if an archive) a file named “camp.yaml”, and does not contain any other yaml file of this name or of a structure recognizable as a plan.

**PrescriptionLevel:** mandatory

**Tag:** conformance=PDP

### 3.3.1.3 PDP Manifest (CAMP11-408b)

Addressing normative statement:

The format of the manifest file and the certificate file SHALL be as defined by the OVF specification [OVF]. [PDP-10]

---

**TA\_Id:** CAMP11-408b

**NormativeSource:** PDP-10 (PDP-06) (section: [Validating Integrity](#))

**Target:** A PDP artifact.

**Prerequisite:** the PDP contains a manifest (“camp.mf”) at its root.

**Predicate:** the manifest (“camp.mf”) at the root of the PDP conforms to the structure defined in OVF [DSP0243] for OVF manifest files.

**PrescriptionLevel:** mandatory

**Tag:** conformance=PDP

### 3.3.1.4 PDP Certificate (CAMP11-409b)

Addressing normative statement:

The format of the manifest file and the certificate file SHALL be as defined by the OVF specification [OVF]. [PDP-10]

---

**TA\_Id:** CAMP11-409b

**NormativeSource:** PDP-10 (section: [Validating Integrity](#))

**Target:** A PDP artifact.

**Prerequisite:** the PDP contains a certificate (named “camp.cert”) at its root.

**Predicate:** the certificate (named “camp.cert”) at the root of the PDP conforms to the structure defined in OVF [DSP0243] for OVF certificate files.

**PrescriptionLevel:** mandatory

**Tag:** conformance=PDP

## 3.3.2 Plan Test Assertions

### 3.3.2.1 Plan File Content (1) (CAMP11-405b)

Addressing normative statement:

A Plan file SHALL contain a single instance of a Plan. [PLAN-03]

---

**TA\_Id:** CAMP11-405b

**NormativeSource:** PLAN-03 (PDP-11) (section: [Plan](#))

**Target:** A Plan file.

**Predicate:** the Plan file contains a single `yaml plan` node and satisfies the `yaml` schema for this node.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Plan

### 3.3.2.2 Plan CAMP version (CAMP11-406b)

Addressing normative statement:

For Plans that conform to this document, the value of this node (`camp_version`) SHALL be as defined in Section **Error! Reference source not found.** “[Specification Version](#)”. [\[PLAN-05\]](#)

---

**TA\_Id:** CAMP11-406b

**NormativeSource:** PLAN-05 (PLAN-03) (section: [campVersion](#))

**Target:** A Plan file.

**Predicate:** the Plan file has a `yaml` node that has a `camp_version` tag with value “CAMP 1.1”.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Plan

### 3.3.2.3 Plan and Unique Service IDs (CAMP11-430b)

Addressing normative statement:

Plans SHALL use id values that are unique within the scope of the Plan. [\[PLAN-06\]](#)

---

**TA\_Id:** CAMP11-430b

**NormativeSource:** PLAN-06 (section: [ServiceSpecification](#))

**Target:** A Plan file.

**Predicate:** the `services` array (`ServiceSpecification[]`) contained in the Plan file does NOT have two `ServiceSpecification` items with same id node value.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Plan

### 3.3.2.4 Plan References (CAMP11-431b)

Addressing normative statement:

If a Consumer includes this node in a Plan, the value of this node SHALL reference a Consumer-visible resource within the target Platform. [\[RMR-01\]](#)

---

**TA\_Id:** CAMP11-431b

**NormativeSource:** RMR-01 (section: [ServiceSpecification](#))

**Target:** A Plan file.

**Prerequisite:** the Plan is originating on Consumer side.

**Predicate:** Any `ServiceSpecification` items that has an `href` node in the `services` array (`ServiceSpecification[]`) contained in the Plan file identified in this POST, has the `href` value resolve to an existing resource on the target platform.

**PrescriptionLevel:** mandatory

**Tag:** conformance=Plan

### 3.3.2.5 Plan Artifact integrity (CAMP11-407b)

Addressing normative statement:

The Plan file SHALL conform to the description provided in this section. [\[PLAN-09\]](#)

---

**TA\_Id:** CAMP11-407b

**NormativeSource:** PLAN-09 (section: [ContentSpecification](#))

**Target:** A Plan file.

**Predicate:** in the Plan file, every `ArtifactSpecification` item (`artifacts` array) has a `content` node that has either an `href` node, or a `data` node but not both.

**PrescriptionLevel:** mandatory

**Tag:** conformance= Plan

---

## 4 Conformance

### 4.1 Implementations

Implementations of this specification are **test suites** that are derived from (or exercise) all or parts of the test assertions defined in this document. Such Implementations are called here CAMP test suites.

**Note:** Implementations of this CAMP Test Assertions specification are NOT to be confused with implementations of the CAMP specification, which are programs or parts of a system implementing the CAMP Provider functions, or the CAMP Consumer functions, or yet data artifacts such as a CAMP PDP or a CAMP Plan. However, these four types of CAMP implementations (CAMP Provider, CAMP Consumer, PDP, Plan) are useful to partition the related Test assertions, and to define related conformance profiles for test suites.

A test suite is typically composed of test cases. According to the definition in [TAG] adopted here, a test case is:

*“A set of a test tools, software or files (data, programs, scripts, or instructions for manual operations) that verifies the adherence of a test assertion target to one or more normative statements in the specification.”*

A test suite is said to implement a test assertion if it contains one or more test cases that exercise this test assertion, with the ability to assess whether an actual test target (i.e. an instance of the “target” of the test assertion) fulfills the associated normative CAMP requirement (as identified by the “normativeSource” of the test assertion). This means that the test case(s) related to a test assertion, must be able to either “pass” or “fail” most test targets, under expected usage conditions.

#### Identification of test restrictions:

- A conforming CAMP test suite that is unable to assess a subset of test targets for a particular test assertion, **MUST** clearly identify or characterize this subset, regardless whether this limitation is intentional or not.
- A conforming CAMP test suite that is unable to assess test targets under specific conditions or within a specific context for a particular test assertion, **MUST** clearly identify these conditions and/or context, regardless whether this limitation is intentional or not.

Four **conformance profiles** are defined for CAMP test suites:

1. CAMP test suite for CAMP Provider (or “CAMP Provider test suite”)
2. CAMP test suite for CAMP Consumer (or “CAMP Consumer test suite”)
3. CAMP test suite for PDP (or “CAMP PDP test suite”)
4. CAMP test suite for Plan (or “CAMP Plan test suite”)

A CAMP test suite may claim conformance to more than one of the above conformance profiles.

### 4.2 CAMP Provider Test Suite Conformance Profile

In order to claim conformance to the CAMP Provider test suite conformance profile, a CAMP test suite **MUST** do both of the following:

- Satisfy the above “Identification of test restrictions” requirements,
- Implement all test assertions (in the sense defined in Section 2) that are tagged with a “conformance” tag of value “Provider”.

Such a test suite is qualified for verifying conformance of a CAMP implementation to the CAMP Provider profile.

### 4.3 CAMP Consumer Test Suite Conformance Profile

In order to claim conformance to the CAMP Consumer test suite conformance profile, a CAMP test suite MUST do both of the following:

- Satisfy the above “Identification of test restrictions” requirements,
- Implement all test assertions (in the sense defined in Section 2) that are tagged with a “conformance” tag of value “Consumer”.

Such a test suite is qualified for verifying conformance of a CAMP implementation to the CAMP Consumer profile.

### 4.4 CAMP PDP Test Suite Conformance Profile

In order to claim conformance to the CAMP PDP test suite conformance profile, a CAMP test suite MUST do both of the following:

- Satisfy the above “Identification of test restrictions” requirements,
- Implement all test assertions (in the sense defined in Section 2) that are tagged with a “conformance” tag of value “PDP”.

Such a test suite is qualified for verifying conformance of a CAMP implementation to the CAMP PDP profile.

### 4.5 CAMP Plan Test Suite Conformance Profile

In order to claim conformance to the CAMP Plan test suite conformance profile, a CAMP test suite MUST do both of the following:

- Satisfy the above “Identification of test restrictions” requirements,
- Implement all test assertions (in the sense defined in Section 2) that are tagged with a “conformance” tag of value “Plan”.

Such a test suite is qualified for verifying conformance of a CAMP implementation to the CAMP Plan profile.

---

## Appendix A. Acknowledgments

This section is informative. The following individuals have participated in the creation of this specification and are gratefully acknowledged:

**Participants:**

Roshan Agrawal	Rackspace Hosting, Inc.
Michael Behrens	US Department of Defense (DoD)
Bhaskar Reddy Byreddy	Software AG, Inc.
Mark Carlson	Oracle
Martin Chapman	Oracle
Francesco D'Andria	Cloud4SOA
Jacques Durand	Fujitsu Limited
Panagiotis Gouvas	Cloud4SOA
Keith Grange	JumpSoft
Alex Heneveld	Cloudsoft Corporation Limited
Gershon Janssen	Individual Member
David Jilk	Standing Cloud, Inc.
Duncan Johnston-Watt	Cloudsoft Corporation Limited
Anish Karmarkar	Oracle
Tobias Kunze	Red Hat
Eugene Luster	US Department of Defense (DoD)
Ashok Malhotra	Oracle
Alex McDonald	NetApp
Rich Miller	Cloudsoft Corporation Limited
Jeff Mischkinsky	Oracle
Adrian Otto	Rackspace Hosting, Inc.
Derek Palma	Vnomic
Gilbert Pilz	Oracle
Krishna Raman	Red Hat
Tom Rutt	Fujitsu Limited
Zhexuan Song	Huawei Technologies Co., Ltd.
Charles Tupitza	JumpSoft
Jeffrey West	Oracle
Prasad Yendluri	Software AG, Inc.

---

## Appendix B. Revision History

Revision	Date	Editor	Changes Made
Wd18	Feb 4, 2014	Jacques Durand	First complete set of test assertions matching CAMP WD37
Wd19	Feb 7, 2014	Jacques Durand	Several edits from Wd18 (see diffs) <ul style="list-style-type: none"><li>- OASIS references set to the right citation format for OASIS refs.</li><li>- Missing hyperlinks for cross-references (bookmarks)</li><li>- Various minor edits in Section 2.</li><li>- Improved section 2.3 (avoid redundancies, add more complete explanations.)</li><li>- Improved on several PUT test assertions (more appropriate set of resources, for their variables)</li><li>- Various minor edits and typos in TAs fixed.</li><li>- Added missing TA (CAMP11-105)</li><li>- Improved on the Conformance clause.</li></ul>
WD20	Feb 10, 2014	Gilbert Pilz	Editorial cleanups and formatting.
WD21	Feb 11, 2014	Jacques Durand	Editorial fixes.
WD22	Jul 15, 2014	Jacques Durand	(see diffs) Added CAMP11-222a, -222b, -222c to address new PR-76. Other edits to match wording changes in some normative statements in CAMP11-206 to -209