

KMIP Suite B Profile Version 1.0

Candidate OASIS Standard 01

03 February 2015

Specification URIs

This version:

<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/cos01/kmip-suite-b-profile-v1.0-cos01.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/cos01/kmip-suite-b-profile-v1.0-cos01.html>
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/cos01/kmip-suite-b-profile-v1.0-cos01.pdf>

Previous version:

<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/csprd01/kmip-suite-b-profile-v1.0-csprd01.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/csprd01/kmip-suite-b-profile-v1.0-csprd01.html>
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/csprd01/kmip-suite-b-profile-v1.0-csprd01.pdf>

Latest version:

<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/kmip-suite-b-profile-v1.0.doc> (Authoritative)
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/kmip-suite-b-profile-v1.0.html>
<http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/kmip-suite-b-profile-v1.0.pdf>

Technical Committee:

OASIS Key Management Interoperability Protocol (KMIP) TC

Chairs:

Saikat Saha (saikat.saha@oracle.com), Oracle
Tony Cox (tjc@cryptsoft.com), Cryptsoft

Editors:

Kelley Burgin (kwburgi@tycho.ncsc.mil), National Security Agency
Tim Hudson (tjh@cryptsoft.com), Cryptsoft

Related work:

This specification is related to:

- *Key Management Interoperability Protocol Profiles Version 1.0*. Edited by Robert Griffin and Subhash Sankuratipati. Latest version: <http://docs.oasis-open.org/kmip/profiles/v1.0/kmip-profiles-1.0.html>.
- *Key Management Interoperability Protocol Profiles Version 1.1*. Edited by Robert Griffin and Subhash Sankuratipati. Latest version: <http://docs.oasis-open.org/kmip/profiles/v1.1/kmip-profiles-v1.1.html>.
- *Key Management Interoperability Protocol Profiles Version 1.2*. Edited by Tim Hudson and Robert Lockhart. Latest version: <http://docs.oasis-open.org/kmip/profiles/v1.2/kmip-profiles-v1.2.html>.

- *Key Management Interoperability Protocol Specification Version 1.1*. Edited by Robert Haas and Indra Fitzgerald. Latest version: <http://docs.oasis-open.org/kmip/spec/v1.1/kmip-spec-v1.1.html>.
- *Key Management Interoperability Protocol Specification Version 1.2*. Edited by Kiran Thota and Kelley Burgin. Latest version: <http://docs.oasis-open.org/kmip/spec/v1.2/kmip-spec-v1.2.html>.
- *Key Management Interoperability Protocol Test Cases Version 1.2*. Edited by Tim Hudson and Faisal Faruqi. Latest version: <http://docs.oasis-open.org/kmip/testcases/v1.2/kmip-testcases-v1.2.html>.
- *Key Management Interoperability Protocol Usage Guide Version 1.2*. Edited by Indra Fitzgerald and Judith Furlong. Latest version: <http://docs.oasis-open.org/kmip/ug/v1.2/kmip-ug-v1.2.html>.

Abstract:

Describes a profile for KMIP clients and KMIP servers using Suite B cryptography that has been approved by NIST for use by the U.S. Government and specified in NIST standards or recommendations.

Status:

This document was last revised or approved by the OASIS Key Management Interoperability Protocol (KMIP) TC on the above date. The level of approval is also listed above. Check the "Latest version" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=kmip#technical.

Technical Committee members should send comments on this specification to the Technical Committee's email list. Others should send comments to the Technical Committee by using the "Send A Comment" button on the Technical Committee's web page at <https://www.oasis-open.org/committees/kmip/>.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the Technical Committee web page (<https://www.oasis-open.org/committees/kmip/ipr.php>).

Citation format:

When referencing this specification the following citation format should be used:

[kmip-suite-b-v1.0]

KMIP Suite B Profile Version 1.0. Edited by Kelley Burgin and Tim Hudson. 03 February 2015. OASIS Candidate OASIS Standard 01. <http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/cos01/kmip-suite-b-profile-v1.0-cos01.html>. Latest version: <http://docs.oasis-open.org/kmip/kmip-suite-b-profile/v1.0/kmip-suite-b-profile-v1.0.html>.

Notices

Copyright © OASIS Open 2015. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

Table of Contents

1	Introduction.....	6
1.1	Terminology	7
1.2	Normative References	7
2	Suite B minLOS_128 Profile.....	8
2.1	Authentication Suite.....	8
2.1.1	Protocols.....	8
2.1.2	Cipher Suites	8
2.1.3	Client Authenticity.....	8
2.1.4	Object Owner.....	8
2.1.5	KMIP Port Number	8
2.2	Suite B minLOS_128 - Client.....	8
2.3	Suite B minLOS_128 - Server	9
3	Suite B minLOS_128 Test Cases.....	11
3.1	Mandatory Suite B minLOS_128 Test Cases KMIP 1.0	11
3.1.1	SUITEB_128-M-1-10 - Query.....	11
3.2	Mandatory Suite B minLOS_128 Test Cases KMIP 1.1	12
3.2.1	SUITEB_128-M-1-11 - Query.....	12
3.3	Mandatory Suite B minLOS_128 Test Cases KMIP 1.2	14
3.3.1	SUITEB_128-M-1-12 - Query.....	14
4	Suite B minLOS_192 Profile.....	16
4.1	Authentication Suite.....	16
4.1.1	Protocols.....	16
4.1.2	Cipher Suites	16
4.1.3	Client Authenticity.....	16
4.1.4	Object Owner.....	16
4.1.5	KMIP Port Number	16
4.2	Suite B minLOS_192 - Client.....	16
4.3	Suite B minLOS_192 - Server	17
5	Suite B minLOS_192 Test Cases.....	19
5.1	Mandatory Suite B minLOS_192 Test Cases - KMIP v1.0	19
5.1.1	SUITEB_192-M-1-10 - Query.....	19
5.2	Mandatory Suite B minLOS_192 Test Cases KMIP 1.1	20
5.2.1	SUITEB_192-M-1-11 - Query.....	20
5.3	Mandatory Suite B minLOS_192 Test Cases KMIP 1.2	22
5.3.1	SUITEB_192-M-1-12 - Query.....	22
6	Conformance	24
6.1	Suite B minLOS_128 Client KMIP V1.0 Profile Conformance.....	24
6.2	Suite B minLOS_128 Client KMIP V1.1 Profile Conformance.....	24
6.3	Suite B minLOS_128 Client KMIP V1.2 Profile Conformance.....	24
6.4	Suite B minLOS_128 Server KMIP V1.0 Profile Conformance	24
6.5	Suite B minLOS_128 Server KMIP V1.1 Profile Conformance	24
6.6	Suite B minLOS_128 Server KMIP V1.2 Profile Conformance	24
6.7	Suite B minLOS_192 Client KMIP V1.0 Profile Conformance.....	24

6.8 Suite B minLOS_192 Client KMIP V1.1 Profile Conformance.....	25
6.9 Suite B minLOS_192 Client KMIP V1.2 Profile Conformance.....	25
6.10 Suite B minLOS_192 Server KMIP V1.0 Profile Conformance	25
6.11 Suite B minLOS_192 Server KMIP V1.1 Profile Conformance	25
6.12 Suite B minLOS_192 Server KMIP V1.2 Profile Conformance	25
6.13 Permitted Test Case Variations	25
6.13.1 Variable Items	25
6.13.2 Variable behavior	27
Appendix A. Acknowledgments	28
Appendix B. KMIP Specification Cross Reference	31
Appendix C. Revision History	36

1 Introduction

For normative definition of the elements of KMIP see the [KMIP Specification](#) [KMIP-SPEC] and the [KMIP Profiles](#) [KMIP-PROF].

Suite B [SuiteB] requires that key establishment and signature algorithms be based upon Elliptic Curve Cryptography and that the encryption algorithm be AES [FIPS197]. Suite B includes:

Encryption	Advanced Encryption Standard (AES) (key sizes of 128 and 256 bits)
Digital Signature	Elliptic Curve Digital Signature Algorithm (ECDSA) (using the curves with 256-bit and 384-bit prime moduli)
Key Exchange	Elliptic Curve Diffie-Hellman (ECDH), (using the curves with 256-bit and 384-bit prime moduli)
Hashes	SHA-256 and SHA-384

Suite B provides for two levels of cryptographic security, namely a 128-bit minimum level of security (minLOS_128) and a 192-bit minimum level of security (minLOS_192). Each level defines a minimum strength that all cryptographic algorithms must provide. A KMIP product configured at a minimum level of security of 128 bits provides adequate protection for classified information up to the SECRET level. A KMIP product configured at a minimum level of security of 192 bits is required to protect classified information at the TOP SECRET level.

The Suite B non-signature primitives are divided into two columns as shown below.

	Column 1	Column 2
Encryption	AES-128	AES-256
Key Agreement	ECDH on P-256	ECDH on P-384
Hash for PRF/MAC	SHA-256	SHA-384

At the 128-bit minimum level of security, the non-signature primitives MUST either come exclusively from Column 1 or exclusively from Column 2.

At the 192-bit minimum level of security, the non-signature primitives MUST come exclusively from Column 2.

Digital signatures using ECDSA MUST be used for authentication. Following the direction of RFC 4754, ECDSA-256 represents an instantiation of the ECDSA algorithm using the P-256 curve and the SHA-256 hash function. ECDSA-384 represents an instantiation of the ECDSA algorithm using the P-384 curve and the SHA-384 hash function.

If configured at a minimum level of security of 128 bits, a KMIP product MUST use either ECDSA-256 or ECDSA-384 for authentication. It is allowable for one party to authenticate with ECDSA-256 and the other party to authenticate with ECDSA-384. This flexibility will allow interoperability between a KMIP client and server that have different sizes of ECDSA authentication keys. KMIP products configured at a minimum level of security of 128 bits MUST be able to verify ECDSA-256 signatures and SHOULD be able to verify ECDSA-384 signatures. If configured at a minimum level of security of 192 bits, ECDSA-384 MUST be used by both the KMIP client and server for authentication. KMIP products configured at a minimum level of security of 192 bits MUST be able to verify ECDSA-384 signatures.

32 KMIP products, at both minimum levels of security, MUST each use an X.509 certificate that complies
33 with the "Suite B Certificate and Certificate Revocation List (CRL) Profile" [RFC5759] and that contains an
34 elliptic curve public key with the key usage bit set for digital signature.

35 1.1 Terminology

36 The key words "MUST", "SHALL", "SHOULD", and "MAY" in this document are to be interpreted as
37 described in [RFC2119].

38 1.2 Normative References

- 39 **[CNSSP-15]** N.S.A., "National Information Assurance Policy on the Use of Public Standards
40 for the Secure Sharing of Information Among National Security Systems", 1
41 October 2013,
42 [https://www.cnss.gov/Assets/pdf/CNSSP_No%2015_minorUpdate1_Oct12012.p](https://www.cnss.gov/Assets/pdf/CNSSP_No%2015_minorUpdate1_Oct12012.pdf)
43 [df](https://www.cnss.gov/Assets/pdf/CNSSP_No%2015_minorUpdate1_Oct12012.pdf).
- 44 **[RFC2119]** Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP
45 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.
- 46 **[KMIP-ENCODE]** *KMIP Additional Message Encodings Version 1.0*. Edited by Tim Hudson. Latest
47 version: [http://docs.oasis-open.org/kmip/kmip-addtl-msg-enc/v1.0/kmip-addtl-](http://docs.oasis-open.org/kmip/kmip-addtl-msg-enc/v1.0/kmip-addtl-msg-enc-v1.0.doc)
48 [msg-enc-v1.0.doc](http://docs.oasis-open.org/kmip/kmip-addtl-msg-enc/v1.0/kmip-addtl-msg-enc-v1.0.doc).
- 49 **[RFC5246]** Dierks, T. and E. Rescorla, *The Transport Layer Security (TLS) Protocol Version*
50 *1.2*, IETF RFC 5246, August 2008, <http://www.ietf.org/rfc/rfc5246.txt>.
- 51 **[KMIP-SPEC]** One or more of [KMIP-SPEC-1_0], [KMIP-SPEC-1_1], [KMIP-SPEC-1_2]
52 **[KMIP-SPEC-1_0]** *Key Management Interoperability Protocol Specification Version 1.0*,
53 <http://docs.oasis-open.org/kmip/spec/v1.0/os/kmip-spec-1.0-os.doc>,
54 OASIS Standard, 1 October 2010.
- 55 **[KMIP-SPEC-1_1]** *Key Management Interoperability Protocol Specification Version 1.1*,
56 <http://docs.oasis-open.org/kmip/spec/v1.1/os/kmip-spec-v1.1-os.doc>,
57 OASIS Standard, 24 January 2013.
- 58 **[KMIP-SPEC-1_2]** *Key Management Interoperability Protocol Specification Version 1.2*. Edited by
59 Kiran Thota and Kelley Burgin. Latest version: [http://docs.oasis-](http://docs.oasis-open.org/kmip/spec/v1.2/kmip-spec-v1.2.doc)
60 [open.org/kmip/spec/v1.2/kmip-spec-v1.2.doc](http://docs.oasis-open.org/kmip/spec/v1.2/kmip-spec-v1.2.doc).
- 61 **[KMIP-PROF]** One or more of [KMIP-PROF-1_0], [KMIP-PROF-1_1], [KMIP-PROF-1_2]
62 **[KMIP-PROF-1_0]** *Key Management Interoperability Protocol Profiles Version 1.0*, [http://docs.oasis-](http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc)
63 [open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc](http://docs.oasis-open.org/kmip/profiles/v1.0/os/kmip-profiles-1.0-os.doc),
64 OASIS Standard, 1 October 2010.
- 65 **[KMIP-PROF-1_1]** *Key Management Interoperability Protocol Profiles Version 1.1*,
66 <http://docs.oasis-open.org/kmip/profiles/v1.1/os/kmip-profiles-v1.1-os.doc>,
67 OASIS Standard 01, 24 January 2013.
- 68 **[KMIP-PROF-1_2]** *Key Management Interoperability Protocol Profiles Version 1.2*. Edited by Tim
69 Hudson and Robert Lockhart. Latest version: [http://docs.oasis-](http://docs.oasis-open.org/kmip/profiles/v1.2/kmip-profiles-v1.2.doc)
70 [open.org/kmip/profiles/v1.2/kmip-profiles-v1.2.doc](http://docs.oasis-open.org/kmip/profiles/v1.2/kmip-profiles-v1.2.doc).
- 71 **[SuiteB]** *Suite B Cryptography / Cryptographic Interoperability*,
72 http://www.nsa.gov/ia/programs/suiteb_cryptography/
73

2 Suite B minLOS_128 Profile

The Suite B minLOS_128 Profile describes a KMIP client interacting with a KMIP server as an information assurance product to provide a minimum level of security of 128 bits.
(http://www.nsa.gov/ia/programs/suiteb_cryptography/)

2.1 Authentication Suite

Implementations conformant to this profile SHALL use TLS to negotiate a mutually-authenticated connection.

2.1.1 Protocols

Conformant KMIP clients and servers SHALL support:

- TLS v1.2 [RFC5246]

2.1.2 Cipher Suites

Conformant KMIP servers SHALL support the following cipher suites:

- TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256

2.1.3 Client Authenticity

Conformant KMIP servers and clients SHALL handle client authenticity in accordance with section 3.2.3 of the TLS 1.2 Authentication Suite [KMIP-PROF].

2.1.4 Object Owner

Conformant KMIP servers and clients SHALL handle object owner in accordance with section 3.2.4 of the TLS 1.2 Authentication Suite [KMIP-PROF].

2.1.5 KMIP Port Number

Conformant KMIP servers and clients SHALL handle the KMIP port number in accordance with section 3.2.5 of the TLS 1.2 Authentication Suite [KMIP-PROF].

2.2 Suite B minLOS_128 - Client

KMIP clients conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the [KMIP-SPEC-1_0]

KMIP clients conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Client Clause* (section 5.12) of [KMIP-PROF-1_1]

KMIP clients conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Client* (section 5.2) of [KMIP-PROF-1_2]

KMIP clients conformant to this profile:

4. SHALL restrict use of the enumerated types listed in item 8 of the server list in section 2.3 to the values noted against each item
5. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause within this section 2.2.
6. MAY support extensions outside the scope of this standard (e.g., vendor extensions, conformance clauses) that do not conflict with any KMIP or [CNSSP-15] requirements.

2.3 Suite B minLOS_128 - Server

KMIP servers conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the [KMIP-SPEC-1_0]

KMIP servers conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Server* of [KMIP-PROF-1_1]

KMIP servers conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Server* of [KMIP-PROF-1_2]

KMIP servers conformant to this profile:

4. SHALL support the following *Objects* [KMIP-SPEC]

- a. *Certificate* [KMIP-SPEC]

- b. *Symmetric Key* [KMIP-SPEC]

- c. *Public Key* [KMIP-SPEC]

- d. *Private Key* [KMIP-SPEC]

5. SHALL support the following *Attributes* [KMIP-SPEC]

- a. *Cryptographic Algorithm* [KMIP-SPEC]

- b. *Cryptographic Length* [KMIP-SPEC] value :

- i. 128-bit (combined with AES)

- ii. 256-bit (combined with SHA, ECDH or ECDSA)

6. MAY support the following *Attributes* [KMIP-SPEC]

- a. *Cryptographic Length* [KMIP-SPEC] value :

- i. 256-bit (combined with AES)

- ii. 384-bit bit (combined with SHA, ECDH or ECDSA)

7. SHALL support the following *Client-to-Server Operations* [KMIP-SPEC]:

- a. *Create* [KMIP-SPEC]

- b. *Create Key Pair* [KMIP-SPEC]

- c. *Register* [KMIP-SPEC]

- d. *Re-key* [KMIP-SPEC]

- e. *Re-key Key Pair* [KMIP-SPEC]

8. SHALL support the following *Message Encoding* [KMIP-SPEC]:

- a. *Recommended Curve Enumeration* [KMIP-SPEC] value:

- i. P-256 (SECP256R1)

- b. *Certificate Type Enumeration* [KMIP-SPEC] value:

- i. X.509

- c. *Cryptographic Algorithm Enumeration* [KMIP-SPEC] value:

- i. AES

- ii. ECDSA

- iii. ECDH

- iv. HMAC-SHA256

- d. *Hashing Algorithm Enumeration* [KMIP-SPEC]

- i. SHA-256

- e. *Object Type Enumeration* [KMIP-SPEC] value:

- i. Certificate

- ii. Symmetric Key
- iii. Public Key
- iv. Private Key
- f. *Key Format Type Enumeration* [KMIP-SPEC] value:
 - i. Raw
 - ii. ECPrivateKey
 - iii. X.509
 - iv. Transparent ECDSA Private Key
 - v. Transparent ECDSA Public Key
 - vi. Transparent ECDH Private Key
 - vii. Transparent ECDH Public Key
- g. *Digital Signature Algorithm Enumeration* [KMIP-SPEC] value:
 - i. ECDSA with SHA256 (on P-256)
- 9. MAY support the following *Message Encoding* [KMIP-SPEC]:
 - a. *Recommended Curve* [KMIP-SPEC] value:
 - i. P-384 (SECP384R1)
 - b. *Cryptographic Algorithm Enumeration* [KMIP-SPEC] value:
 - i. HMAC-SHA384
 - c. *Hashing Algorithm Enumeration* [KMIP-SPEC]
 - i. SHA-384
 - d. Digital Signature Algorithm Enumeration
 - i. ECDSA with SHA384 (on P-384)
- 10. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause within this section 2.3.
- 11. MAY support extensions outside the scope of this standard (e.g., vendor extensions, conformance clauses) that do not conflict with any KMIP or [CNSSP-15] requirements.

3 Suite B minLOS_128 Test Cases

The test cases define a number of request-response pairs for KMIP operations. Each test case is provided in the XML format specified in [KMIP-ENCODE] intended to be both human-readable and usable by automated tools. The time sequence (starting from 0) for each request-response pair is noted and line numbers are provided for ease of cross-reference for a given test sequence.

Each test case has a unique label (the section name) which includes indication of mandatory (-M-) or optional (-O-) status and the protocol version major and minor numbers as part of the identifier.

The test cases may depend on a specific configuration of a KMIP client and server being configured in a manner consistent with the test case assumptions.

Where possible the flow of unique identifiers between tests, the date-time values, and other dynamic items are indicated using symbolic identifiers – in actual request and response messages these dynamic values will be filled in with valid values.

Note: the values for the returned items and the custom attributes are illustrative. Actual values from a real client or server system may vary as specified in section 6.10

3.1 Mandatory Suite B minLOS_128 Test Cases KMIP 1.0

3.1.1 SUITEB_128-M-1-10 - Query

Perform a Query operation, querying the Operations and Objects supported by the server, and get a successful response.

The specific list of operations and object types returned in the response MAY vary.

The TLS protocol version and cipher suite SHALL be as specified in section 2.1

```
# TIME 0
0001 <RequestMessage>
0002   <RequestHeader>
0003     <ProtocolVersion>
0004       <ProtocolVersionMajor type="Integer" value="1"/>
0005       <ProtocolVersionMinor type="Integer" value="0"/>
0006     </ProtocolVersion>
0007     <BatchCount type="Integer" value="1"/>
0008   </RequestHeader>
0009   <BatchItem>
0010     <Operation type="Enumeration" value="Query"/>
0011   <RequestPayload>
0012     <QueryFunction type="Enumeration" value="QueryOperations"/>
0013     <QueryFunction type="Enumeration" value="QueryObjects"/>
0014   </RequestPayload>
0015 </BatchItem>
0016 </RequestMessage>
0017 <ResponseMessage>
0018   <ResponseHeader>
0019     <ProtocolVersion>
0020       <ProtocolVersionMajor type="Integer" value="1"/>
0021       <ProtocolVersionMinor type="Integer" value="0"/>
0022     </ProtocolVersion>
0023     <TimeStamp type="DateTime" value="2013-06-26T09:09:17+00:00"/>
0024     <BatchCount type="Integer" value="1"/>
0025   </ResponseHeader>
0026   <BatchItem>
0027     <Operation type="Enumeration" value="Query"/>
```

0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>
0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>
0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="Certify"/>
0053	<Operation type="Enumeration" value="ReCertify"/>
0054	<Operation type="Enumeration" value="Notify"/>
0055	<Operation type="Enumeration" value="Put"/>
0056	<ObjectType type="Enumeration" value="Certificate"/>
0057	<ObjectType type="Enumeration" value="SymmetricKey"/>
0058	<ObjectType type="Enumeration" value="SecretData"/>
0059	<ObjectType type="Enumeration" value="PublicKey"/>
0060	<ObjectType type="Enumeration" value="PrivateKey"/>
0061	<ObjectType type="Enumeration" value="Template"/>
0062	<ObjectType type="Enumeration" value="OpaqueObject"/>
0063	<ObjectType type="Enumeration" value="SplitKey"/>
0064	</ResponsePayload>
0065	</BatchItem>
0066	</ResponseMessage>

198

199 3.2 Mandatory Suite B minLOS_128 Test Cases KMIP 1.1

200 3.2.1 SUITEB_128-M-1-11 - Query

201 Perform a Query operation, querying the Operations and Objects supported by the server, and get a
202 successful response.

203 The specific list of operations and object types returned in the response MAY vary.

204 The TLS protocol version and cipher suite SHALL be as specified in section 2.1

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="1"/>
0006	</ProtocolVersion>

0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	</RequestPayload>
0015	</BatchItem>
0016	</RequestMessage>
0017	<ResponseMessage>
0018	<ResponseHeader>
0019	<ProtocolVersion>
0020	<ProtocolVersionMajor type="Integer" value="1"/>
0021	<ProtocolVersionMinor type="Integer" value="1"/>
0022	</ProtocolVersion>
0023	<TimeStamp type="DateTime" value="2014-06-11T09:22:39+00:00"/>
0024	<BatchCount type="Integer" value="1"/>
0025	</ResponseHeader>
0026	<BatchItem>
0027	<Operation type="Enumeration" value="Query"/>
0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>
0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>
0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="ReKeyKeyPair"/>
0053	<Operation type="Enumeration" value="Certify"/>
0054	<Operation type="Enumeration" value="ReCertify"/>
0055	<Operation type="Enumeration" value="DiscoverVersions"/>
0056	<Operation type="Enumeration" value="Notify"/>
0057	<Operation type="Enumeration" value="Put"/>
0058	<ObjectType type="Enumeration" value="Certificate"/>
0059	<ObjectType type="Enumeration" value="SymmetricKey"/>
0060	<ObjectType type="Enumeration" value="SecretData"/>
0061	<ObjectType type="Enumeration" value="PublicKey"/>
0062	<ObjectType type="Enumeration" value="PrivateKey"/>
0063	<ObjectType type="Enumeration" value="Template"/>
0064	<ObjectType type="Enumeration" value="OpaqueObject"/>

0065	<ObjectType type="Enumeration" value="SplitKey"/>
0066	</ResponsePayload>
0067	</BatchItem>
0068	</ResponseMessage>

205

206 3.3 Mandatory Suite B minLOS_128 Test Cases KMIP 1.2

207 3.3.1 SUITEB_128-M-1-12 - Query

208 Perform a Query operation, querying the Operations and Objects supported by the server, and get a
209 successful response.

210 The specific list of operations and object types returned in the response MAY vary.

211 The TLS protocol version and cipher suite SHALL be as specified in section 2.1

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="2"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	</RequestPayload>
0015	</BatchItem>
0016	</RequestMessage>
0017	<ResponseMessage>
0018	<ResponseHeader>
0019	<ProtocolVersion>
0020	<ProtocolVersionMajor type="Integer" value="1"/>
0021	<ProtocolVersionMinor type="Integer" value="2"/>
0022	</ProtocolVersion>
0023	<TimeStamp type="DateTime" value="2014-06-11T09:23:21+00:00"/>
0024	<BatchCount type="Integer" value="1"/>
0025	</ResponseHeader>
0026	<BatchItem>
0027	<Operation type="Enumeration" value="Query"/>
0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>
0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>

0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="ReKeyKeyPair"/>
0053	<Operation type="Enumeration" value="Certify"/>
0054	<Operation type="Enumeration" value="ReCertify"/>
0055	<Operation type="Enumeration" value="DiscoverVersions"/>
0056	<Operation type="Enumeration" value="Notify"/>
0057	<Operation type="Enumeration" value="Put"/>
0058	<Operation type="Enumeration" value="RNGRetrieve"/>
0059	<Operation type="Enumeration" value="RNGSeed"/>
0060	<Operation type="Enumeration" value="Encrypt"/>
0061	<Operation type="Enumeration" value="Decrypt"/>
0062	<Operation type="Enumeration" value="Sign"/>
0063	<Operation type="Enumeration" value="SignatureVerify"/>
0064	<Operation type="Enumeration" value="MAC"/>
0065	<Operation type="Enumeration" value="MACVerify"/>
0066	<Operation type="Enumeration" value="Hash"/>
0067	<Operation type="Enumeration" value="CreateSplitKey"/>
0068	<Operation type="Enumeration" value="JoinSplitKey"/>
0069	<ObjectType type="Enumeration" value="Certificate"/>
0070	<ObjectType type="Enumeration" value="SymmetricKey"/>
0071	<ObjectType type="Enumeration" value="SecretData"/>
0072	<ObjectType type="Enumeration" value="PublicKey"/>
0073	<ObjectType type="Enumeration" value="PrivateKey"/>
0074	<ObjectType type="Enumeration" value="Template"/>
0075	<ObjectType type="Enumeration" value="OpaqueObject"/>
0076	<ObjectType type="Enumeration" value="SplitKey"/>
0077	<ObjectType type="Enumeration" value="PGPKey"/>
0078	</ResponsePayload>
0079	</BatchItem>
0080	</ResponseMessage>

4 Suite B minLOS_192 Profile

The Suite B minLOS_192 Profile describes a KMIP client interacting with a KMIP server as an information assurance product to provide a minimum level of security of 192 bits.
(http://www.nsa.gov/ia/programs/suiteb_cryptography/)

4.1 Authentication Suite

Implementations conformant to this profile SHALL use TLS to negotiate a mutually-authenticated connection.

4.1.1 Protocols

Conformant KMIP clients and servers SHALL support:

- TLS v1.2 [RFC5246]

4.1.2 Cipher Suites

Conformant KMIP servers SHALL support the following cipher suites:

- TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384

4.1.3 Client Authenticity

Conformant KMIP servers and clients SHALL handle client authenticity in accordance with section 3.2.3 of the TLS 1.2 Authentication Suite [KMIP-PROF].

4.1.4 Object Owner

Conformant KMIP servers and clients SHALL handle object owner in accordance with section 3.2.4 of the TLS 1.2 Authentication Suite [KMIP-PROF].

4.1.5 KMIP Port Number

Conformant KMIP servers and clients SHALL handle the KMIP port number in accordance with section 3.2.5 of the TLS 1.2 Authentication Suite [KMIP-PROF].

4.2 Suite B minLOS_192 - Client

KMIP clients conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the [KMIP-SPEC-1_0]

KMIP clients conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Client Clause* (section 5.12) of [KMIP-PROF-1_1]

KMIP clients conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Client* (section 5.2) of [KMIP-PROF-1_2]

KMIP clients conformant to this profile under [KMIP-SPEC]:

4. SHALL restrict use of the enumerated types listed in item 7 of the server list in section 4.3 to the values noted against each item
5. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause within this section 4.2.
6. MAY support extensions outside the scope of this standard (e.g., vendor extensions, conformance clauses) that do not conflict with any KMIP or [CNSSP-15] requirements.

4.3 Suite B minLOS_192 - Server

KMIP servers conformant to this profile under [KMIP-SPEC-1_0]:

1. SHALL conform to the [KMIP-SPEC-1_0]

KMIP servers conformant to this profile under [KMIP-SPEC-1_1]:

2. SHALL conform to the *Baseline Server* of [KMIP-PROF-1_1]

KMIP servers conformant to this profile under [KMIP-SPEC-1_2]:

3. SHALL conform to the *Baseline Server* of [KMIP-PROF-1_2]

KMIP servers conformant to this profile under [KMIP-SPEC]:

4. SHALL support the following *Objects* [KMIP-SPEC]

- a. *Certificate* [KMIP-SPEC]

- b. *Symmetric Key* [KMIP-SPEC]

- c. *Public Key* [KMIP-SPEC]

- d. *Private Key* [KMIP-SPEC]

5. SHALL support the following *Attributes* [KMIP-SPEC]

- e. *Cryptographic Algorithm* [KMIP-SPEC]

- f. *Cryptographic Length* [KMIP-SPEC] value:

- i. 384-bit bit (combined with SHA, ECDH or ECDSA)

6. SHALL support the following *Client-to-Server Operations* [KMIP-SPEC]:

- g. *Create* [KMIP-SPEC]

- h. *Create Key Pair* [KMIP-SPEC]

- i. *Register* [KMIP-SPEC]

- j. *Re-key* [KMIP-SPEC]

- k. *Re-key Key Pair* [KMIP-SPEC]

7. SHALL support the following *Message Encoding* [KMIP-SPEC]:

- l. *Recommended Curve Enumeration* [KMIP-SPEC] value:

- i. P-384 (SECP384R1)

- m. *Certificate Type Enumeration* [KMIP-SPEC] value:

- i. X.509

- n. *Cryptographic Algorithm Enumeration* [KMIP-SPEC] value:

- i. AES

- ii. ECDSA

- iii. ECDH

- iv. HMAC-SHA384

- o. *Hashing Algorithm Enumeration* [KMIP-SPEC]

- i. SHA-384

- p. *Object Type Enumeration* [KMIP-SPEC] value:

- i. Certificate

- ii. Symmetric Key

- iii. Public Key

- iv. Private Key

- q. *Key Format Type Enumeration* [KMIP-SPEC] value:

- i. Raw

- 291 ii. ECPrivateKey
- 292 iii. X.509
- 293 iv. Transparent ECDSA Private Key
- 294 v. Transparent ECDSA Public Key
- 295 vi. Transparent ECDH Private Key
- 296 vii. Transparent ECDH Public Key
- 297 r. *Digital Signature Algorithm Enumeration* [KMIP-SPEC] value:
- 298 i. ECDSA with SHA384 (on P-384)
- 299 8. MAY support any clause within [KMIP-SPEC] provided it does not conflict with any other clause
- 300 within this section 4.3.
- 301 9. MAY support extensions outside the scope of this standard (e.g., vendor extensions,
- 302 conformance clauses) that do not conflict with any KMIP or [CNSSP-15] requirements.

5 Suite B minLOS_192 Test Cases

The test cases define a number of request-response pairs for KMIP operations. Each test case is provided in the XML format specified in [KMIP-ENCODE] intended to be both human-readable and usable by automated tools. The time sequence (starting from 0) for each request-response pair is noted and line numbers are provided for ease of cross-reference for a given test sequence.

Each test case has a unique label (the section name) which includes indication of mandatory (-M-) or optional (-O-) status and the protocol version major and minor numbers as part of the identifier.

The test cases may depend on a specific configuration of a KMIP client and server being configured in a manner consistent with the test case assumptions.

Where possible the flow of unique identifiers between tests, the date-time values, and other dynamic items are indicated using symbolic identifiers – in actual request and response messages these dynamic values will be filled in with valid values.

Note: the values for the returned items and the custom attributes are illustrative. Actual values from a real client or server system may vary as specified in section 6.10

5.1 Mandatory Suite B minLOS_192 Test Cases - KMIP v1.0

This section documents the test cases that a client or server conformant to this profile SHALL support.

5.1.1 SUITEB_192-M-1-10 - Query

Perform a Query operation, querying the Operations and Objects supported by the server, and get a successful response.

The specific list of operations and object types returned in the response MAY vary.

The TLS protocol version and cipher suite SHALL be as specified in section 4.1

	<i># TIME 0</i>
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="0"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	</RequestPayload>
0015	</BatchItem>
0016	</RequestMessage>
0017	<ResponseMessage>
0018	<ResponseHeader>
0019	<ProtocolVersion>
0020	<ProtocolVersionMajor type="Integer" value="1"/>
0021	<ProtocolVersionMinor type="Integer" value="0"/>
0022	</ProtocolVersion>
0023	<TimeStamp type="DateTime" value="2013-06-26T09:09:17+00:00"/>
0024	<BatchCount type="Integer" value="1"/>
0025	</ResponseHeader>

0026	<BatchItem>
0027	<Operation type="Enumeration" value="Query"/>
0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>
0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>
0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="Certify"/>
0053	<Operation type="Enumeration" value="ReCertify"/>
0054	<Operation type="Enumeration" value="Notify"/>
0055	<Operation type="Enumeration" value="Put"/>
0056	<ObjectType type="Enumeration" value="Certificate"/>
0057	<ObjectType type="Enumeration" value="SymmetricKey"/>
0058	<ObjectType type="Enumeration" value="SecretData"/>
0059	<ObjectType type="Enumeration" value="PublicKey"/>
0060	<ObjectType type="Enumeration" value="PrivateKey"/>
0061	<ObjectType type="Enumeration" value="Template"/>
0062	<ObjectType type="Enumeration" value="OpaqueObject"/>
0063	<ObjectType type="Enumeration" value="SplitKey"/>
0064	</ResponsePayload>
0065	</BatchItem>
0066	</ResponseMessage>

324

325 5.2 Mandatory Suite B minLOS_192 Test Cases KMIP 1.1

326 5.2.1 SUITEB_192-M-1-11 - Query

327 Perform a Query operation, querying the Operations and Objects supported by the server, and get a
328 successful response.

329 The specific list of operations and object types returned in the response MAY vary.

330 The TLS protocol version and cipher suite SHALL be as specified in section 4.1

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>

0005	<ProtocolVersionMinor type="Integer" value="1"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	</RequestPayload>
0015	</BatchItem>
0016	</RequestMessage>
0017	<ResponseMessage>
0018	<ResponseHeader>
0019	<ProtocolVersion>
0020	<ProtocolVersionMajor type="Integer" value="1"/>
0021	<ProtocolVersionMinor type="Integer" value="1"/>
0022	</ProtocolVersion>
0023	<TimeStamp type="DateTime" value="2014-06-11T09:22:39+00:00"/>
0024	<BatchCount type="Integer" value="1"/>
0025	</ResponseHeader>
0026	<BatchItem>
0027	<Operation type="Enumeration" value="Query"/>
0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>
0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>
0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="ReKeyKeyPair"/>
0053	<Operation type="Enumeration" value="Certify"/>
0054	<Operation type="Enumeration" value="ReCertify"/>
0055	<Operation type="Enumeration" value="DiscoverVersions"/>
0056	<Operation type="Enumeration" value="Notify"/>
0057	<Operation type="Enumeration" value="Put"/>
0058	<ObjectType type="Enumeration" value="Certificate"/>
0059	<ObjectType type="Enumeration" value="SymmetricKey"/>
0060	<ObjectType type="Enumeration" value="SecretData"/>
0061	<ObjectType type="Enumeration" value="PublicKey"/>
0062	<ObjectType type="Enumeration" value="PrivateKey"/>

0063	<ObjectType type="Enumeration" value="Template"/>
0064	<ObjectType type="Enumeration" value="OpaqueObject"/>
0065	<ObjectType type="Enumeration" value="SplitKey"/>
0066	</ResponsePayload>
0067	</BatchItem>
0068	</ResponseMessage>

331

332 5.3 Mandatory Suite B minLOS_192 Test Cases KMIP 1.2

333 5.3.1 SUITEB_192-M-1-12 - Query

334 Perform a Query operation, querying the Operations and Objects supported by the server, and get a
335 successful response.

336 The specific list of operations and object types returned in the response MAY vary.

337 The TLS protocol version and cipher suite SHALL be as specified in section 4.1

	# TIME 0
0001	<RequestMessage>
0002	<RequestHeader>
0003	<ProtocolVersion>
0004	<ProtocolVersionMajor type="Integer" value="1"/>
0005	<ProtocolVersionMinor type="Integer" value="2"/>
0006	</ProtocolVersion>
0007	<BatchCount type="Integer" value="1"/>
0008	</RequestHeader>
0009	<BatchItem>
0010	<Operation type="Enumeration" value="Query"/>
0011	<RequestPayload>
0012	<QueryFunction type="Enumeration" value="QueryOperations"/>
0013	<QueryFunction type="Enumeration" value="QueryObjects"/>
0014	</RequestPayload>
0015	</BatchItem>
0016	</RequestMessage>
0017	<ResponseMessage>
0018	<ResponseHeader>
0019	<ProtocolVersion>
0020	<ProtocolVersionMajor type="Integer" value="1"/>
0021	<ProtocolVersionMinor type="Integer" value="2"/>
0022	</ProtocolVersion>
0023	<TimeStamp type="DateTime" value="2014-06-11T09:23:21+00:00"/>
0024	<BatchCount type="Integer" value="1"/>
0025	</ResponseHeader>
0026	<BatchItem>
0027	<Operation type="Enumeration" value="Query"/>
0028	<ResultStatus type="Enumeration" value="Success"/>
0029	<ResponsePayload>
0030	<Operation type="Enumeration" value="Query"/>
0031	<Operation type="Enumeration" value="Locate"/>
0032	<Operation type="Enumeration" value="Destroy"/>
0033	<Operation type="Enumeration" value="Get"/>
0034	<Operation type="Enumeration" value="Create"/>
0035	<Operation type="Enumeration" value="Register"/>
0036	<Operation type="Enumeration" value="GetAttributes"/>
0037	<Operation type="Enumeration" value="GetAttributeList"/>
0038	<Operation type="Enumeration" value="AddAttribute"/>
0039	<Operation type="Enumeration" value="ModifyAttribute"/>

0040	<Operation type="Enumeration" value="DeleteAttribute"/>
0041	<Operation type="Enumeration" value="Activate"/>
0042	<Operation type="Enumeration" value="Revoke"/>
0043	<Operation type="Enumeration" value="Poll"/>
0044	<Operation type="Enumeration" value="Cancel"/>
0045	<Operation type="Enumeration" value="Check"/>
0046	<Operation type="Enumeration" value="GetUsageAllocation"/>
0047	<Operation type="Enumeration" value="CreateKeyPair"/>
0048	<Operation type="Enumeration" value="ReKey"/>
0049	<Operation type="Enumeration" value="Archive"/>
0050	<Operation type="Enumeration" value="Recover"/>
0051	<Operation type="Enumeration" value="ObtainLease"/>
0052	<Operation type="Enumeration" value="ReKeyKeyPair"/>
0053	<Operation type="Enumeration" value="Certify"/>
0054	<Operation type="Enumeration" value="ReCertify"/>
0055	<Operation type="Enumeration" value="DiscoverVersions"/>
0056	<Operation type="Enumeration" value="Notify"/>
0057	<Operation type="Enumeration" value="Put"/>
0058	<Operation type="Enumeration" value="RNGRetrieve"/>
0059	<Operation type="Enumeration" value="RNGSeed"/>
0060	<Operation type="Enumeration" value="Encrypt"/>
0061	<Operation type="Enumeration" value="Decrypt"/>
0062	<Operation type="Enumeration" value="Sign"/>
0063	<Operation type="Enumeration" value="SignatureVerify"/>
0064	<Operation type="Enumeration" value="MAC"/>
0065	<Operation type="Enumeration" value="MACVerify"/>
0066	<Operation type="Enumeration" value="Hash"/>
0067	<Operation type="Enumeration" value="CreateSplitKey"/>
0068	<Operation type="Enumeration" value="JoinSplitKey"/>
0069	<ObjectType type="Enumeration" value="Certificate"/>
0070	<ObjectType type="Enumeration" value="SymmetricKey"/>
0071	<ObjectType type="Enumeration" value="SecretData"/>
0072	<ObjectType type="Enumeration" value="PublicKey"/>
0073	<ObjectType type="Enumeration" value="PrivateKey"/>
0074	<ObjectType type="Enumeration" value="Template"/>
0075	<ObjectType type="Enumeration" value="OpaqueObject"/>
0076	<ObjectType type="Enumeration" value="SplitKey"/>
0077	<ObjectType type="Enumeration" value="PGPKey"/>
0078	</ResponsePayload>
0079	</BatchItem>
0080	</ResponseMessage>

6 Conformance

6.1 Suite B minLOS_128 Client KMIP V1.0 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.2 of this profile.
3. SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.0 (3.1)

6.2 Suite B minLOS_128 Client KMIP V1.1 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.2 of this profile.
3. SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.1 (3.2)

6.3 Suite B minLOS_128 Client KMIP V1.2 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.2 of this profile.
3. SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.2 (3.3)

6.4 Suite B minLOS_128 Server KMIP V1.0 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.3 of this profile.
3. SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.0 (3.1)

6.5 Suite B minLOS_128 Server KMIP V1.1 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.3 of this profile.
3. SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.1 (3.2)

6.6 Suite B minLOS_128 Server KMIP V1.2 Profile Conformance

KMIP server implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 2.1 of this profile.
2. SHALL support the conditions as specified in Section 2.3 of this profile.
- SHALL support all the Mandatory Suite B minLOS_128 Test Cases KMIP 1.2 (3.3)

6.7 Suite B minLOS_192 Client KMIP V1.0 Profile Conformance

KMIP client implementations conformant to this profile:

1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.

- 373 2. SHALL support the conditions as specified in Section 4.2 of this profile.
374 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases - KMIP v1.0 (5.1)

375 **6.8 Suite B minLOS_192 Client KMIP V1.1 Profile Conformance**

376 KMIP client implementations conformant to this profile:

- 377 1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.
378 2. SHALL support the conditions as specified in Section 4.2 of this profile.
379 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases KMIP 1.1(5.2)

380 **6.9 Suite B minLOS_192 Client KMIP V1.2 Profile Conformance**

381 KMIP client implementations conformant to this profile:

- 382 1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.
383 2. SHALL support the conditions as specified in Section 4.2 of this profile.
384 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases KMIP 1.2 (5.3)

385 **6.10 Suite B minLOS_192 Server KMIP V1.0 Profile Conformance**

386 KMIP server implementations conformant to this profile:

- 387 1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.
388 2. SHALL support the conditions as specified in Section 4.3 of this profile.
389 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases - KMIP v1.0 (5.1)

390 **6.11 Suite B minLOS_192 Server KMIP V1.1 Profile Conformance**

391 KMIP server implementations conformant to this profile:

- 392 1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.
393 2. SHALL support the conditions as specified in Section 4.3 of this profile.
394 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases KMIP 1.1(5.2)

395 **6.12 Suite B minLOS_192 Server KMIP V1.2 Profile Conformance**

396 KMIP server implementations conformant to this profile:

- 397 1. SHALL support the Authentication Suite conditions as specified in Section 4.1 of this profile.
398 2. SHALL support the conditions as specified in Section 4.3 of this profile.
399 3. SHALL support all the Mandatory Suite B minLOS_192 Test Cases KMIP 1.2 (5.3)

400 **6.13 Permitted Test Case Variations**

401 Whilst the test cases provided in this Profile define the allowed request and response content, some
402 inherent variations MAY occur and are permitted within a successfully completed test case.

403 Each test case MAY include allowed variations in the description of the test case in addition to the
404 variations noted in this section.

405 Other variations not explicitly noted in this Profile SHALL be deemed non-conformant.

406 **6.13.1 Variable Items**

407 An implementation conformant to this Profile MAY vary the following values:

- 408 1. UniqueIdentifier

- 409 2. PrivateKeyUniqueIdentifier
- 410 3. PublicKeyUniqueIdentifier
- 411 4. UniqueBatchItemIdentifier
- 412 5. AsynchronousCorrelationValue
- 413 6. TimeStamp
- 414 7. KeyValue / KeyMaterial including:
 - 415 a. key material content returned for managed cryptographic objects which are generated by
 - 416 the server
 - 417 b. wrapped versions of keys where the wrapping key is dynamic or the wrapping contains
 - 418 variable output for each wrap operation
- 419 8. For response containing the output of cryptographic operation in Data / SignatureData/ MACData
- 420 / IVCounterNonce where:
 - 421 a. the managed object is generated by the server; or
 - 422 b. the operation inherently contains variable output
- 423 9. For the following DateTime attributes where the value is not specified in the request as a fixed
- 424 DateTime value:
 - 425 a. ActivationDate
 - 426 b. ArchiveDate
 - 427 c. CompromiseDate
 - 428 d. CompromiseOccurrenceDate
 - 429 e. DeactivationDate
 - 430 f. DestroyDate
 - 431 g. InitialDate
 - 432 h. LastChangeDate
 - 433 i. ProtectStartDate
 - 434 j. ProcessStopDate
 - 435 k. ValidityDate
 - 436 l. OriginalCreationDate
- 437 10. LinkedObjectIdentifier
- 438 11. DigestValue
 - 439 a. For those managed cryptographic objects which are dynamically generated
- 440 12. KeyFormatType
 - 441 a. The key format type selected by the server when it creates managed objects
- 442 13. Digest
 - 443 a. The HashingAlgorithm selected by the server when it calculates the digest for a managed
 - 444 object for which it has access to the key material
 - 445 b. The Digest Value
- 446 14. Extensions reported in Query for ExtensionList and ExtensionMap
- 447 15. Application Namespaces reported in Query
- 448 16. Object Types reported in Query other than those noted as required in this profile
- 449 17. Operation Types reported in Query other than those noted as required in this profile (or any
- 450 referenced profile documents)
- 451 18. For TextString attribute values containing test identifiers:
 - 452 a. Additional vendor or application prefixes

19. Additional attributes beyond those noted in the response

An implementation conformant to this Profile MAY allow the following response variations:

20. Object Group values – May or may not return one or more Object Group values not included in the requests
21. y-CustomAttributes – May or may not include additional server-specific associated attributes not included in requests
22. Message Extensions – May or may not include additional (non-critical) vendor extensions
23. TemplateAttribute – May or may not be included in responses where the Template Attribute response is noted as optional in [KMIP-SPEC]
24. AttributeIndex – May or may not include Attribute Index value where the Attribute Index value is 0 for Protocol Versions 1.1 and above.
25. ResultMessage – May or may not be included in responses and the value (if included) may vary from the text contained within the test case.
26. The list of Protocol Versions returned in a DiscoverVersion response may include additional protocol versions if the request has not specified a list of client supported Protocol Versions.
27. VendorIdentification - The value (if included) may vary from the text contained within the test case.

6.13.2 Variable behavior

An implementation conformant to this Profile SHALL allow variation of the following behavior:

1. A test may omit the clean-up requests and responses (containing Revoke and/or Destroy) at the end of the test provided there is a separate mechanism to remove the created objects during testing.
2. A test may omit the test identifiers if the client is unable to include them in requests. This includes the following attributes:
 - a. Name; and
 - b. x-ID
3. A test MAY perform requests with multiple batch items or as multiple requests with a single batch item provided the sequence of operations are equivalent
4. A request MAY contain an optional *Authentication* [KMIP_SPEC] structure within each request

Appendix A. Acknowledgments

The following individuals have participated in the creation of this specification and are gratefully acknowledged:

Participants:

483 Hal Aldridge, Sypris Electronics
484 Mike Allen, Symantec
485 Gordon Arnold, IBM
486 Todd Arnold, IBM
487 Richard Austin, Hewlett-Packard
488 Lars Bagnert, PrimeKey
489 Elaine Barker, NIST
490 Peter Bartok, Venafi, Inc.
491 Tom Benjamin, IBM
492 Anthony Berglas, Cryptsoft
493 Mathias Björkqvist, IBM
494 Kevin Bocket, Venafi
495 Anne Bolgert, IBM
496 Alan Brown, Thales e-Security
497 Tim Bruce, CA Technologies
498 Chris Burchett, Credant Technologies, Inc.
499 Kelley Burgin, National Security Agency
500 Robert Burns, Thales e-Security
501 Chuck Castleton, Venafi
502 Kenli Chong, QuintessenceLabs
503 John Clark, Hewlett-Packard
504 Tom Clifford, Symantec Corp.
505 Doron Cohen, SafeNet, Inc
506 Tony Cox, Cryptsoft
507 Russell Dietz, SafeNet, Inc
508 Graydon Dodson, Lexmark International Inc.
509 Vinod Duggirala, EMC Corporation
510 Chris Dunn, SafeNet, Inc.
511 Michael Duren, Sypris Electronics
512 James Dzierzanowski, American Express CCoE
513 Faisal Faruqui, Thales e-Security
514 Stan Feather, Hewlett-Packard
515 David Finkelstein, Symantec Corp.
516 James Fitzgerald, SafeNet, Inc.
517 Indra Fitzgerald, Hewlett-Packard
518 Judith Furlong, EMC Corporation
519 Susan Gleeson, Oracle
520 Robert Griffin, EMC Corporation
521 Paul Grojean, Individual
522 Robert Haas, IBM
523 Thomas Hardjono, M.I.T.
524 ChengDong He, Huawei Technologies Co., Ltd.
525 Steve He, Vormetric
526 Kurt Heberlein, Hewlett-Packard
527 Larry Hofer, Emulex Corporation
528 Maryann Hondo, IBM
529 Walt Hubis, NetApp
530 Tim Hudson, Cryptsoft
531 Jonas Iggbom, Venafi, Inc.

532 Sitaram Inguva, American Express CCoE
 533 Jay Jacobs, Target Corporation
 534 Glen Jaquette, IBM
 535 Mahadev Karadiguddi, NetApp
 536 Greg Kazmierczak, Wave Systems Corp.
 537 Marc Kenig, SafeNet, Inc.
 538 Mark Knight, Thales e-Security
 539 Kathy Kriese, Symantec Corporation
 540 Mark Lambiase, SecureAuth
 541 John Leiseboer, Quintessence Labs
 542 Hal Lockhart, Oracle Corporation
 543 Robert Lockhart, Thales e-Security
 544 Anne Luk, Cryptsoft
 545 Sairam Manidi, Freescale
 546 Luther Martin, Voltage Security
 547 Neil McEvoy, iFOSSF
 548 Marina Milshtein, Individual
 549 Dale Moberg, Axway Software
 550 Jishnu Mukeri, Hewlett-Packard
 551 Bryan Olson, Hewlett-Packard
 552 John Peck, IBM
 553 Rob Philpott, EMC Corporation
 554 Denis Pochuev, SafeNet, Inc.
 555 Reid Poole, Venafi, Inc.
 556 Ajai Puri, SafeNet, Inc.
 557 Saravanan Ramalingam, Thales e-Security
 558 Peter Reed, SafeNet, Inc.
 559 Bruce Rich, IBM
 560 Christina Richards, American Express CCoE
 561 Warren Robbins, Dell
 562 Peter Robinson, EMC Corporation
 563 Scott Rotondo, Oracle
 564 Saikat Saha, SafeNet, Inc.
 565 Anil Saldhana, Red Hat
 566 Subhash Sankuratipati, NetApp
 567 Boris Schumperli, Cryptomathic
 568 Greg Singh, QuintessenceLabs
 569 David Smith, Venafi, Inc
 570 Brian Spector, Certivox
 571 Terence Spies, Voltage Security
 572 Deborah Steckroth, RouteOne LLC
 573 Michael Stevens, QuintessenceLabs
 574 Marcus Streets, Thales e-Security
 575 Satish Sundar, IBM
 576 Kiran Thota, VMware
 577 Somanchi Trinath, Freescale Semiconductor, Inc.
 578 Nathan Turajski, Thales e-Security
 579 Sean Turner, IECA, Inc.
 580 Paul Turner, Venafi, Inc.
 581 Rod Wideman, Quantum Corporation
 582 Steven Wierenga, Hewlett-Packard
 583 Jin Wong, QuintessenceLabs
 584 Sameer Yami, Thales e-Security
 585 Peter Yee, EMC Corporation
 586 Krishna Yellepeddy, IBM
 587 Catherine Ying, SafeNet, Inc.
 588 Tatu Ylonen, SSH Communications Security (Tectia Corp)

589 Michael Yoder, Vormetric. Inc.
590 Magda Zdunkiewicz, Cryptsoft
591 Peter Zelechowski, Election Systems & Software

Appendix B. KMIP Specification Cross Reference

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
1 Introduction			
<i>Non-Normative References</i>	1.3.	1.3.	1.3.
<i>Normative References</i>	1.2.	1.2.	1.2.
<i>Terminology</i>	1.1.	1.1.	1.1.
2 Objects			
<i>Attribute</i>	2.1.1.	2.1.1.	2.1.1.
<i>Base Objects</i>	2.1.	2.1.	2.1.
<i>Certificate</i>	2.2.1.	2.2.1.	2.2.1.
<i>Credential</i>	2.1.2.	2.1.2.	2.1.2.
<i>Data</i>	-	-	2.1.10.
<i>Data Length</i>	-	-	2.1.11.
<i>Extension Information</i>	-	2.1.9.	2.1.9.
<i>Key Block</i>	2.1.3.	2.1.3.	2.1.3.
<i>Key Value</i>	2.1.4.	2.1.4.	2.1.4.
<i>Key Wrapping Data</i>	2.1.5.	2.1.5.	2.1.5.
<i>Key Wrapping Specification</i>	2.1.6.	2.1.6.	2.1.6.
<i>MAC Data</i>	-	-	2.1.13.
<i>Managed Objects</i>	2.2.	2.2.	2.2.
<i>Nonce</i>	-	-	2.1.14.
<i>Opaque Object</i>	2.2.8.	2.2.8.	2.2.8.
<i>PGP Key</i>	-	-	2.2.9.
<i>Private Key</i>	2.2.4.	2.2.4.	2.2.4.
<i>Public Key</i>	2.2.3.	2.2.3.	2.2.3.
<i>Secret Data</i>	2.2.7.	2.2.7.	2.2.7.
<i>Signature Data</i>	-	-	2.1.12.
<i>Split Key</i>	2.2.5.	2.2.5.	2.2.5.
<i>Symmetric Key</i>	2.2.2.	2.2.2.	2.2.2.
<i>Template</i>	2.2.6.	2.2.6.	2.2.6.
<i>Template-Attribute Structures</i>	2.1.8.	2.1.8.	2.1.8.
<i>Transparent DH Private Key</i>	2.1.7.6.	2.1.7.6.	2.1.7.6.
<i>Transparent DH Public Key</i>	2.1.7.7.	2.1.7.7.	2.1.7.7.
<i>Transparent DSA Private Key</i>	2.1.7.2.	2.1.7.2.	2.1.7.2.
<i>Transparent DSA Public Key</i>	2.1.7.3.	2.1.7.3.	2.1.7.3.
<i>Transparent ECDH Private Key</i>	2.1.7.10.	2.1.7.10.	2.1.7.10.
<i>Transparent ECDH Public Key</i>	2.1.7.11.	2.1.7.11.	2.1.7.11.
<i>Transparent ECDSA Private Key</i>	2.1.7.8.	2.1.7.8.	2.1.7.8.
<i>Transparent ECDSA Public Key</i>	2.1.7.9.	2.1.7.9.	2.1.7.9.
<i>Transparent ECMQV Private Key</i>	2.1.7.12.	2.1.7.12.	2.1.7.12.
<i>Transparent ECMQV Public Key</i>	2.1.7.13.	2.1.7.13.	2.1.7.13.
<i>Transparent Key Structures</i>	2.1.7.	2.1.7.	2.1.7.
<i>Transparent RSA Private Key</i>	2.1.7.4.	2.1.7.4.	2.1.7.4.
<i>Transparent RSA Public Key</i>	2.1.7.5.	2.1.7.5.	2.1.7.5.
<i>Transparent Symmetric Key</i>	2.1.7.1.	2.1.7.1.	2.1.7.1.
3 Attributes			
<i>Activation Date</i>	3.19.	3.24.	3.24.
<i>Alternative Name</i>	-	-	3.40.
<i>Application Specific Information</i>	3.30.	3.36.	3.36.
<i>Archive Date</i>	3.27.	3.32.	3.32.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Attributes</i>	3	3	3
<i>Certificate Identifier</i>	3.9.	3.13.	3.13.
<i>Certificate Issuer</i>	3.11.	3.15.	3.15.
<i>Certificate Length</i>	-	3.9.	3.9.
<i>Certificate Subject</i>	3.10.	3.14.	3.14.
<i>Certificate Type</i>	3.8.	3.8.	3.8.
<i>Compromise Date</i>	3.25.	3.30.	3.30.
<i>Compromise Occurrence Date</i>	3.24.	3.29.	3.29.
<i>Contact Information</i>	3.31.	3.37.	3.37.
<i>Cryptographic Algorithm</i>	3.4.	3.4.	3.4.
<i>Cryptographic Domain Parameters</i>	3.7.	3.7.	3.7.
<i>Cryptographic Length</i>	3.5.	3.5.	3.5.
<i>Cryptographic Parameters</i>	3.6.	3.6.	3.6.
<i>Custom Attribute</i>	3.33.	3.39.	3.39.
<i>Deactivation Date</i>	3.22.	3.27.	3.27.
<i>Default Operation Policy</i>	3.13.2.	3.18.2.	3.18.2.
<i>Default Operation Policy for Certificates and Public Key Objects</i>	3.13.2.2.	3.18.2.2.	3.18.2.2.
<i>Default Operation Policy for Secret Objects</i>	3.13.2.1.	3.18.2.1.	3.18.2.1.
<i>Default Operation Policy for Template Objects</i>	3.13.2.3.	3.18.2.3.	3.18.2.3.
<i>Destroy Date</i>	3.23.	3.28.	3.28.
<i>Digest</i>	3.12.	3.17.	3.17.
<i>Digital Signature Algorithm</i>	-	3.16.	3.16.
<i>Fresh</i>	-	3.34.	3.34.
<i>Initial Date</i>	3.18.	3.23.	3.23.
<i>Key Value Location</i>	-	-	3.42.
<i>Key Value Present</i>	-	-	3.41.
<i>Last Change Date</i>	3.32.	3.38.	3.38.
<i>Lease Time</i>	3.15.	3.20.	3.20.
<i>Link</i>	3.29.	3.35.	3.35.
<i>Name</i>	3.2.	3.2.	3.2.
<i>Object Group</i>	3.28.	3.33.	3.33.
<i>Object Type</i>	3.3.	3.3.	3.3.
<i>Operation Policy Name</i>	3.13.	3.18.	3.18.
<i>Operations outside of operation policy control</i>	3.13.1.	3.18.1.	3.18.1.
<i>Original Creation Date</i>	-	-	3.43.
<i>Process Start Date</i>	3.20.	3.25.	3.25.
<i>Protect Stop Date</i>	3.21.	3.26.	3.26.
<i>Revocation Reason</i>	3.26.	3.31.	3.31.
<i>State</i>	3.17.	3.22.	3.22.
<i>Unique Identifier</i>	3.1.	3.1.	3.1.
<i>Usage Limits</i>	3.16.	3.21.	3.21.
<i>X.509 Certificate Identifier</i>	-	3.10.	3.10.
<i>X.509 Certificate Issuer</i>	-	3.12.	3.12.
<i>X.509 Certificate Subject</i>	-	3.11.	3.11.
4 Client-to-Server Operations			
<i>Activate</i>	4.18.	4.19.	4.19.
<i>Add Attribute</i>	4.13.	4.14.	4.14.
<i>Archive</i>	4.21.	4.22.	4.22.
<i>Cancel</i>	4.25.	4.27.	4.27.
<i>Certify</i>	4.6.	4.7.	4.7.
<i>Check</i>	4.9.	4.10.	4.10.
<i>Create</i>	4.1.	4.1.	4.1.
<i>Create Key Pair</i>	4.2.	4.2.	4.2.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Create Split Key</i>	-	-	4.38.
<i>Decrypt</i>	-	-	4.30.
<i>Delete Attribute</i>	4.15.	4.16.	4.16.
<i>Derive Key</i>	4.5.	4.6.	4.6.
<i>Destroy</i>	4.20.	4.21.	4.21.
<i>Discover Versions</i>	-	4.26.	4.26.
<i>Encrypt</i>	-	-	4.29.
<i>Get</i>	4.10.	4.11.	4.11.
<i>Get Attribute List</i>	4.12.	4.13.	4.13.
<i>Get Attributes</i>	4.11.	4.12.	4.12.
<i>Get Usage Allocation</i>	4.17.	4.18.	4.18.
<i>Hash</i>	-	-	4.37.
<i>Join Split Key</i>	-	-	4.39.
<i>Locate</i>	4.8.	4.9.	4.9.
<i>MAC</i>	-	-	4.33.
<i>MAC Verify</i>	-	-	4.34.
<i>Modify Attribute</i>	4.14.	4.15.	4.15.
<i>Obtain Lease</i>	4.16.	4.17.	4.17.
<i>Poll</i>	4.26.	4.28.	4.28.
<i>Query</i>	4.24.	4.25.	4.25.
<i>Re-certify</i>	4.7.	4.8.	4.8.
<i>Recover</i>	4.22.	4.23.	4.23.
<i>Register</i>	4.3.	4.3.	4.3.
<i>Re-key</i>	4.4.	4.4.	4.4.
<i>Re-key Key Pair</i>	-	4.5.	4.5.
<i>Revoke</i>	4.19.	4.20.	4.20.
<i>RNG Retrieve</i>	-	-	4.35.
<i>RNG Seed</i>	-	-	4.36.
<i>Sign</i>	-	-	4.31.
<i>Signature Verify</i>	-	-	4.32.
<i>Validate</i>	4.23.	4.24.	4.24.
5 Server-to-Client Operations			
<i>Notify</i>	5.1.	5.1.	5.1.
<i>Put</i>	5.2.	5.2.	5.2.
6 Message Contents			
<i>Asynchronous Correlation Value</i>	6.8.	6.8.	6.8.
<i>Asynchronous Indicator</i>	6.7.	6.7.	6.7.
<i>Attestation Capable Indicator</i>	-	-	6.17.
<i>Batch Count</i>	6.14.	6.14.	6.14.
<i>Batch Error Continuation Option</i>	6.13.	6.13.	6.13.
<i>Batch Item</i>	6.15.	6.15.	6.15.
<i>Batch Order Option</i>	6.12.	6.12.	6.12.
<i>Maximum Response Size</i>	6.3.	6.3.	6.3.
<i>Message Extension</i>	6.16.	6.16.	6.16.
<i>Operation</i>	6.2.	6.2.	6.2.
<i>Protocol Version</i>	6.1.	6.1.	6.1.
<i>Result Message</i>	6.11.	6.11.	6.11.
<i>Result Reason</i>	6.10.	6.10.	6.10.
<i>Result Status</i>	6.9.	6.9.	6.9.
<i>Time Stamp</i>	6.5.	6.5.	6.5.
<i>Unique Batch Item ID</i>	6.4.	6.4.	6.4.
7 Message Format			

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Message Structure</i>	7.1.	7.1.	7.1.
<i>Operations</i>	7.2.	7.2.	7.2.
8 Authentication			
<i>Authentication</i>	8	8	8
9 Message Encoding			
<i>Alternative Name Type Enumeration</i>	-	-	9.1.3.2.34.
<i>Attestation Type Enumeration</i>	-	-	9.1.3.2.36.
<i>Batch Error Continuation Option Enumeration</i>	9.1.3.2.29.	9.1.3.2.30.	9.1.3.2.30.
<i>Bit Masks</i>	9.1.3.3.	9.1.3.3.	9.1.3.3.
<i>Block Cipher Mode Enumeration</i>	9.1.3.2.13.	9.1.3.2.14.	9.1.3.2.14.
<i>Cancellation Result Enumeration</i>	9.1.3.2.24.	9.1.3.2.25.	9.1.3.2.25.
<i>Certificate Request Type Enumeration</i>	9.1.3.2.21.	9.1.3.2.22.	9.1.3.2.22.
<i>Certificate Type Enumeration</i>	9.1.3.2.6.	9.1.3.2.6.	9.1.3.2.6.
<i>Credential Type Enumeration</i>	9.1.3.2.1.	9.1.3.2.1.	9.1.3.2.1.
<i>Cryptographic Algorithm Enumeration</i>	9.1.3.2.12.	9.1.3.2.13.	9.1.3.2.13.
<i>Cryptographic Usage Mask</i>	9.1.3.3.1.	9.1.3.3.1.	9.1.3.3.1.
<i>Defined Values</i>	9.1.3.	9.1.3.	9.1.3.
<i>Derivation Method Enumeration</i>	9.1.3.2.20.	9.1.3.2.21.	9.1.3.2.21.
<i>Digital Signature Algorithm Enumeration</i>	-	9.1.3.2.7.	9.1.3.2.7.
<i>Encoding Option Enumeration</i>	-	9.1.3.2.32.	9.1.3.2.32.
<i>Enumerations</i>	9.1.3.2.	9.1.3.2.	9.1.3.2.
<i>Examples</i>	9.1.2.	9.1.2.	9.1.2.
<i>Hashing Algorithm Enumeration</i>	9.1.3.2.15.	9.1.3.2.16.	9.1.3.2.16.
<i>Item Length</i>	9.1.1.3.	9.1.1.3.	9.1.1.3.
<i>Item Tag</i>	9.1.1.1.	9.1.1.1.	9.1.1.1.
<i>Item Type</i>	9.1.1.2.	9.1.1.2.	9.1.1.2.
<i>Item Value</i>	9.1.1.4.	9.1.1.4.	9.1.1.4.
<i>Key Compression Type Enumeration</i>	9.1.3.2.2.	9.1.3.2.2.	9.1.3.2.2.
<i>Key Format Type Enumeration</i>	9.1.3.2.3.	9.1.3.2.3.	9.1.3.2.3.
<i>Key Role Type Enumeration</i>	9.1.3.2.16.	9.1.3.2.17.	9.1.3.2.17.
<i>Key Value Location Type Enumeration</i>	-	-	9.1.3.2.35.
<i>Link Type Enumeration</i>	9.1.3.2.19.	9.1.3.2.20.	9.1.3.2.20.
<i>Name Type Enumeration</i>	9.1.3.2.10.	9.1.3.2.11.	9.1.3.2.11.
<i>Object Group Member Enumeration</i>	-	9.1.3.2.33.	9.1.3.2.33.
<i>Object Type Enumeration</i>	9.1.3.2.11.	9.1.3.2.12.	9.1.3.2.12.
<i>Opaque Data Type Enumeration</i>	9.1.3.2.9.	9.1.3.2.10.	9.1.3.2.10.
<i>Operation Enumeration</i>	9.1.3.2.26.	9.1.3.2.27.	9.1.3.2.27.
<i>Padding Method Enumeration</i>	9.1.3.2.14.	9.1.3.2.15.	9.1.3.2.15.
<i>Put Function Enumeration</i>	9.1.3.2.25.	9.1.3.2.26.	9.1.3.2.26.
<i>Query Function Enumeration</i>	9.1.3.2.23.	9.1.3.2.24.	9.1.3.2.24.
<i>Recommended Curve Enumeration for ECDSA, ECDH, and ECMQV</i>	9.1.3.2.5.	9.1.3.2.5.	9.1.3.2.5.
<i>Result Reason Enumeration</i>	9.1.3.2.28.	9.1.3.2.29.	9.1.3.2.29.
<i>Result Status Enumeration</i>	9.1.3.2.27.	9.1.3.2.28.	9.1.3.2.28.
<i>Revocation Reason Code Enumeration</i>	9.1.3.2.18.	9.1.3.2.19.	9.1.3.2.19.
<i>Secret Data Type Enumeration</i>	9.1.3.2.8.	9.1.3.2.9.	9.1.3.2.9.
<i>Split Key Method Enumeration</i>	9.1.3.2.7.	9.1.3.2.8.	9.1.3.2.8.
<i>State Enumeration</i>	9.1.3.2.17.	9.1.3.2.18.	9.1.3.2.18.
<i>Storage Status Mask</i>	9.1.3.3.2.	9.1.3.3.2.	9.1.3.3.2.
<i>Tags</i>	9.1.3.1.	9.1.3.1.	9.1.3.1.
<i>TTLV Encoding</i>	9.1.	9.1.	9.1.
<i>TTLV Encoding Fields</i>	9.1.1.	9.1.1.	9.1.1.
<i>Usage Limits Unit Enumeration</i>	9.1.3.2.30.	9.1.3.2.31.	9.1.3.2.31.

Reference Term	KMIP 1.0	KMIP 1.1	KMIP 1.2
<i>Validity Indicator Enumeration</i>	9.1.3.2.22.	9.1.3.2.23.	9.1.3.2.23.
<i>Wrapping Method Enumeration</i>	9.1.3.2.4.	9.1.3.2.4.	9.1.3.2.4.
<i>XML Encoding</i>	9.2.	-	-
10 Transport			
<i>Transport</i>	10	10	10
12 KMIP Server and Client Implementation Conformance			
<i>Conformance clauses for a KMIP Server</i>	12.1.	-	-
<i>KMIP Client Implementation Conformance</i>	-	12.2.	12.2.
<i>KMIP Server Implementation Conformance</i>	-	12.1.	12.1.

592

Appendix C. Revision History

Revision	Date	Editor	Changes Made
wd01	10 July 2013	Kelley Burgin / Tim Hudson	Initial Draft
wd02	8 August 2013	Kelley Burgin	Editorial updates and inclusion of a corresponding restriction on client enumeration usage
wd03	10 August 2013	Tim Hudson	Updated Permitted Test Case Variations
wd03a	24-October-2013	Tim Hudson	Editorial update to include VendorIdentification in the list of allowed variations as per TC motion.
pr01update	11-June-2014	Tim Hudson	Updated following Public Review

593