



Electronic Court Filing Web Services Service Interaction Profile Version 4.1

Committee Specification Draft 02

17 July 2023

This stage:

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd02/ecf-webservices-v4.1-csd02.docx> (Authoritative)

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd02/ecf-webservices-v4.1-csd02.html>

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd02/ecf-webservices-v4.1-csd02.pdf>

Previous stage:

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd01/ecf-webservices-v4.1-csd01.docx> (Authoritative)

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd01/ecf-webservices-v4.1-csd01.html>

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd01/ecf-webservices-v4.1-csd01.pdf>

Latest stage:

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/ecf-webservices-v4.1.docx> (Authoritative)

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/ecf-webservices-v4.1.html>

<https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/ecf-webservices-v4.1.pdf>

Technical Committee:

OASIS LegalXML Electronic Court Filing TC

Chair:

James Cabral (jim.cabral@infotrack.com), InfoTrack US

Editors:

James Cabral (jim.cabral@infotrack.com), InfoTrack US

Gary Graham (GGraham@courts.az.gov), Arizona Supreme Court

Philip Baughman (Philip.Baughman@tylertech.com), Tyler Technologies, Inc.

Additional artifacts:

This document is one component of a Work Product that also includes:

- WSDL files: <https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd02/wSDL/>
 - [CourtRecordMDE.wsdl](#)
 - [FilingAssemblyMDE.wsdl](#)
 - [FilingReviewMDE.wsdl](#)
 - [ServiceMDE.wsdl](#)
- WSDL example files: <https://docs.oasis-open.org/legalxml-courtfilling/ecf-webservices/v4.1/csd02/wSDL/examples/>
 - [CourtRecordMDE-ImplementationExample.wsdl](#)
 - [FilingAssemblyMDE-ImplementationExample.wsdl](#)

- [FilingReviewMDE-ImplementationExample.wsdl](#)
- [ServiceMDE-ImplementationExample.wsdl](#)

Related work:

This specification replaces or supersedes:

- *Web Services Messaging Profile 1.0 Specification*. Edited by Roger Winters. November 15, 2005. <https://docs.oasis-open.org/legalxml-court filing/specs/ecf/v3.0/ecf-v3.0-webservices-spec/ecf-v3.0-webservices-spec-cd01.doc>
- *Web Services Service Interaction Profile 1.1 Specification*. Edited by Roger Winters. July 10, 2007. <http://www.oasis-open.org/committees/download.php/29417/ecf-v3.1-webservices-spec-cd01.zip>
- *Electronic Court Filing 4.0 Web Services Service Interaction Profile Version 2.0*. Edited by Adam Angione. 21 September 2008. <http://docs.oasis-open.org/legalxml-court filing/specs/ecf/v4.0/ecf-v4.0-webservices-spec/ecf-v4.0-webservices-v2.0-spec-cd01.html>
- *Electronic Court Filing 4.0 Web Services Service Interaction Profile Version 2.01*. Edited by Adam Angione. 09 August 2011. <http://docs.oasis-open.org/legalxml-court filing/specs/ecf/v4.0/ecf-v4.0-webservices-spec/v2.01/ecf-v4.0-webservices-spec-v2.01.html>

This specification is related to:

- *Electronic Court Filing Version 4.1*. Edited by James Cabral, Gary Graham, and Philip Baughman. Latest stage: <https://docs.oasis-open.org/legalxml-court filing/ecf/v4.1/ecf-v4.1.html>.

Declared XML namespaces:

- urn:oasis:names:tc:legalxml-court filing:schema:wsdl:CourtRecordMDE-4.1
- urn:oasis:names:tc:legalxml-court filing:schema:wsdl:FilingAssemblyMDE-4.1
- urn:oasis:names:tc:legalxml-court filing:schema:wsdl:FilingReviewMDE-4.1
- urn:oasis:names:tc:legalxml-court filing:schema:wsdl:ServiceMDE-4.1

Abstract:

This document defines a Service Interaction Profile, as defined in section 5 of the LegalXML Electronic Court Filing 4.1 (ECF 4.1) specification. The Web Services Service Interaction Profile may be used to transmit ECF 4.1 messages between Internet-connected systems.

Status:

This document was last revised or approved by the OASIS LegalXML Electronic Court Filing TC on the above date. The level of approval is also listed above. Check the "Latest stage" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=legalxml-court filing#technical.

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list, after subscribing to it by following the instructions at the "Send A Comment" button on the TC's web page at <https://www.oasis-open.org/committees/legalxml-court filing/>.

This specification is provided under the [RF on Limited Terms Mode](#) of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/legalxml-court filing/ipr.php>).

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this document, the following citation format should be used:

[ECF-WS-SIP-v4.1]

Electronic Court Filing Web Services Service Interaction Profile Version 4.1. Edited by James Cabral, Gary Graham, and Philip Baughman. 17 July 2023. OASIS Committee Specification Draft 02. <https://docs.oasis-open.org/legalxml-court filing/ecf-webservices/v4.1/csd02/ecf-webservices-v4.1-csd02.html>. Latest stage: <https://docs.oasis-open.org/legalxml-court filing/ecf-webservices/v4.1/ecf-webservices-v4.1.html>.

Notices:

Copyright © OASIS Open 2023. All Rights Reserved.

Distributed under the terms of the OASIS IPR Policy, [<https://www.oasis-open.org/policies-guidelines/ipr/>].
For complete copyright information please see the full Notices section in Appendix E below.

Table of Contents

1	Introduction.....	5
1.1	Relationship to ECF 4.1 Specifications	5
1.2	Relationship to other XML Specifications	5
1.2.1	W3C XML Schema 1.0.....	5
1.2.2	W3C Namespaces in XML	6
1.2.3	W3C Simple Object Access Protocol (SOAP) 1.1.....	6
1.2.4	W3C Web Services Description Language (WSDL) 1.1	6
1.2.5	W3C XML- <i>Signature Syntax and Processing</i>	6
1.2.6	WS-I Basic Profile 1.1	6
1.2.7	W3C SOAP 1.1 Binding for MTOM 1.0	6
1.2.8	WS-I Basic Security Profile 1.0	7
1.2.9	WS-ReliableMessaging Version 1.1.....	7
1.3	Terms and Definitions.....	7
1.4	Symbols and Abbreviations	8
1.5	Normative References	9
1.6	Non-Normative References	10
2	Profile Design	11
2.1	Service Interaction Profile Identifier	11
2.2	Transport Protocol	11
2.3	MDE Addressing	12
2.4	Operation Addressing	12
2.5	Request and Operation Invocation	13
2.6	Synchronous Mode Response	13
2.7	Asynchronous Mode Response.....	13
2.8	Message/Attachment Delimiters.....	13
2.9	Message Identifiers.....	13
2.10	Message Non-repudiation.....	13
2.11	Message Integrity	13
2.12	Message Confidentiality.....	13
2.13	Message Authentication	14
2.14	Message Reliability.....	14
2.15	Message Splitting and Assembly.....	14
2.16	Transmission Auditing	14
3	Service Definitions.....	15
4	Conformance	16
	Appendix A. (Informative) Acknowledgments	17
	Appendix B. (Informative) Revision History	18
	Appendix C. (Informative) Example Implementation	19
	Appendix D. (Informative) Example Transmissions	20
	D.1 Operation Invocation	20
	D.2 Synchronous Response	21
	D.3 Asynchronous Response	22
	Appendix E. Notices.....	23

1 Introduction

This document defines a Service Interaction Profile, as called for in section 5 of **[ECF-v4.1]**. The purpose of the Web Services Service Interaction Profile is to provide a web service-based system in conformance with the WS-I Basic Profile 1.1 (**[WS-I BP 1.1]**) and Basic Security Profile 1.0 (**[WS-I BP 1.0]**) for use with the **[ECF-v4.1]** specification. This version improves security support for tokens, attachments, and rights management through inclusion of WS-Security 1.1 and adds supports for message splitting and assembly through inclusion of WS-Reliable Messaging 1.0. This specification requires an active network connection between the sending and receiving MDEs.

1.1 Relationship to ECF 4.1 Specifications

The ECF 4.1 specification describes the technical architecture and the functional features of an electronic court filing system, that is, features needed to accomplish electronic filing in a court, pointing out both normative (required) and non-normative (optional) business processes it supports. The non-functional requirements associated with electronic filing transactions, and actions and services needed to accomplish the transactions, such as network structures and security infrastructures, are defined in related specifications, namely:

- Service interaction profile specifications defining communications infrastructures within which electronic filing transactions can take place.
- Document signature profile specifications that define mechanisms for stating or proving that a person signed a particular document.

This specification represents an ECF 4.1 service interaction profile based on web-services. It is intended for implementation in conjunction with the ECF 4.1 specification and at least one ECF 4.1 document signature profile specification. Specifically, in this service interaction profile, the implementation details for each of the Major Design Elements (MDEs), operations, and messages defined in the ECF 4.1 specification, are defined in Web Services Description Language (WSDL).

1.2 Relationship to other XML Specifications

Consistent with the ECF 4.1 principle of leveraging other existing, non-proprietary XML specifications wherever possible, this service interaction profile specification leverages previous specifications for web services messaging and security including the following:

- W3C XML Schema 1.0 (**[Schema Part 1, Schema Part 2]**).
- W3C Namespaces in XML (**[Namespaces]**).
- W3C Simple Object Access Protocol (SOAP) 1.1 (**[SOAP 1.1]**).
- W3C Web WSDL 1.1 (**[WSDL 1.1]**).
- W3C XML-Signature Syntax and Processing (**[XMLSIG]**).
- W3C SOAP 1.1 Binding for MTOM 1.0
- WS-I Basic Profile Version 1.1.
- WS-I Basic Security Profile Version 1.0.
- OASIS WS-Reliable Messaging 1.0.

The use of each of these specifications is described below.

1.2.1 W3C XML Schema 1.0

The W3C XML Schema 1.0 (**[Schema Part 1, Schema Part 2]**) specification defines an application protocol for imposing constraints on the storage layout and logical structure of data objects using text tags

43 or “markup.” Compliance with the requirements of the XML Schema 1.0 specification is REQUIRED for
44 compliance with this service interaction profile.

45 **1.2.2 W3C Namespaces in XML**

46 The W3C Namespaces in XML (**[Namespaces]**) specification defines conventions for defining and
47 referring to separate XML tags. Compliance with the requirements of the Namespaces in XML
48 specification is REQUIRED for compliance with this service interaction profile.

49 **1.2.3 W3C Simple Object Access Protocol (SOAP) 1.1**

50 The W3C SOAP 1.1 (**[SOAP 1.1]**) specification defines message exchange patterns and message
51 structures for use with XML. Compliance with the requirements of the SOAP 1.1 specification is
52 REQUIRED for compliance with this service interaction profile.

53 **1.2.4 W3C Web Services Description Language (WSDL) 1.1**

54 The W3C WSDL (**[WSDL 1.1]**) specification enables the description of services as sets of endpoints
55 operating on messages. Compliance with the requirements of the WSDL 1.1 specification is REQUIRED
56 for compliance with this service interaction profile.

57 An MDE implementation MUST consist of a **[SOAP 1.1]** web service that implements the SOAP HTTP
58 binding for that MDE’s portType from the corresponding MDE WSDL document provided with this
59 specification (e.g. *CourtRecordMDE.wsdl*). Further, the implementation MUST be accompanied by an
60 implementation-specific WSDL document that imports the namespace defined in the MDE WSDL, and
61 defines a `<wsdl:service>` element containing a `<soap:address>` element with a `location` attribute
62 whose value provides an HTTP URL at which the MDE implementation can be invoked.

63 (Note that in the previous paragraph, a namespace prefix of “wsdl” is assumed to map to the
64 <http://schemas.xmlsoap.org/wsdl/> namespace, while the namespace prefix of “soap” is
65 assumed to map to the <http://schemas.xmlsoap.org/wsdl/soap/> namespace.)

66 An example (non-normative) implementation-specific WSDL document for each MDE (e.g.
67 *wsdl/examples/CourtRecordMDE-ImplementationExample.wsdl*) is provided with this
68 specification.

69 **1.2.5 W3C XML-Signature Syntax and Processing**

70 The W3C XML Signature Syntax and Processing (**[XMLSIG]**) specification defines representations of
71 signatures of Web resources, portions of protocol messages (anything that may be referenced by a URI),
72 and procedures for computing and verifying such signatures. Compliance with the requirements of the
73 XML Signature Syntax and Processing specification is REQUIRED for compliance with this service
74 interaction profile.

75 **1.2.6 WS-I Basic Profile 1.1**

76 The WS-Interoperability Basic Profile 1.1 (**[WS-I BP 1.1]**) specification defines a set of best practices for
77 implementing interoperable web services. Compliance with the requirements of the **[WS-I BP 1.1]**, with
78 the exceptions noted in Section 1.2.7, is REQUIRED for compliance with this service interaction profile.

79 **1.2.7 W3C SOAP 1.1 Binding for MTOM 1.0**

80 The SOAP 1.1 Binding for MTOM 1.0 (**[SOAP MTOM 1.0]**) defines a set of best practices for
81 implementing interoperable serialization of the SOAP envelope and its representation in the message.
82 This binding MUST be used as a replacement for the WS-I Attachments Profile 1.0 and the W3C Simple
83 SOAP Binding Profile in the WS-I Basic Profile **[WS-I BP 1.1]**. Compliance with the requirements of the **[**
84 **SOAP MTOM 1.0]** and the specifications that this binding references, the SOAP Message Transmission
85 Optimization Mechanism (MTOM) (**[MTOM]**) and the W3C XML-binary Optimized Packaging (XOP)
86 specifications (**[XOP]**), is REQUIRED for compliance with the web services service interaction profile.

87 1.2.8 WS-I Basic Security Profile 1.0

88 The WS-Interoperability Basic Security Profile Version 1.0 ([WS-I BSP 1.0]) complements [WS-I BP 1.0]
89 and defines a set of best practices for implementing interoperable and secure web services. With the
90 exception of the requirements for use of the WS-I Attachments Profile 1.0 and the W3C Simple SOAP
91 Binding Profile 1.0, compliance with the requirements of [WS-I BSP 1.0] is REQUIRED for compliance
92 with this service interaction profile. However, in many cases, [WS-I BSP 1.0] is underspecified. The
93 following options in [WS-I BSP 1.0] are REQUIRED for compliance with this web services service
94 interaction profile:

- 95 • E0002 - Security Tokens - Security tokens MUST be specified in additional security token profiles.
96 (NOTE: This will be determined in Court Policy)
- 97 • R3103 - A SIGNATURE MUST be a Detached Signature as defined by the XML Signature
98 specification.

99 1.2.9 WS-ReliableMessaging Version 1.1

100 The WS-Reliability 1.1 ([WS-RM 1.1]) specification complements [WS-I BP 1.1] and defines a set of
101 extensions for exchanging SOAP messages with guaranteed delivery, no duplicates, and guaranteed
102 message ordering.

103 1.3 Terms and Definitions

104 The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD
105 NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described
106 in [RFC2119].

107

108 The key terms used in this specification include:

109 **Attachment**

110 Information transmitted between MDEs that is of an arbitrary format, and is related to the ECF 4.1
111 message(s) in the transmission in a manner defined in the ECF 4.1 specification. An attachment
112 may be in XML format, non-XML text format, encoded binary format, or un-encoded binary
113 format.

114 **Callback message**

115 A message transmission returned by some operations some time after the operation was invoked
116 (asynchronously).

117 **Document**

118 Represents an electronic version of the paper that would have been sent as paper.

119 **Docketing**

120 The process invoked when a court receives a pleading, order, or notice, when no errors in
121 transmission or in presence of required content have occurred, and when the pleading, order, or
122 notice is recorded as a part of the official record.

123 **Filer**

124 Attorneys or pro se litigants are individuals who assemble and submit Filings (data and
125 documents).

126 **Filing**

127 Electronic document collection that has been assembled for filing on a designated court case.

128 **Major Design Element (MDE)**

129 A logical grouping of operations representing a significant business process supported by ECF
130 4.1. Each MDE operation receives one or more ECF 4.1 messages, returns a ECF 4.1

131 synchronous response message, and optionally sends an ECF 4.1 asynchronous response
132 message back to the original sender.

133 **Message**

134 Information transmitted between MDEs that consists of a well-formed XML document that is valid
135 against one of the defined message structure schemas in the ECF 4.1 specification. A message
136 may be related to one or more attachments in a manner defined in the ECF 4.1 specification.

137 **Message Transmission**

138 The sending of one or more ECF 4.1 messages and associated attachments to an MDE. Each
139 transmission must invoke or respond to an operation on the receiving MDE, as defined in the
140 ECF 4.1 specification.

141 **Operation (or MDE Operation)**

142 A function provided by an MDE upon receipt of one or more ECF 4.1 messages. The function
143 provided by the operation represents a significant step in the court filing business process. A
144 sender invokes an operation on an MDE by transmitting a set of ECF 4.1 messages to that MDE,
145 addressed to that operation.

146 **Operation signature**

147 A definition of the ECF 4.1 input message(s) and ECF 4.1 synchronous response message
148 associated with an operation. Each SOAP message is given a name and a type by the operation.
149 The type is defined by a single one of the structures defined in the ECF 4.1 specification.

150 **Receiving MDE**

151 In an Electronic Court Filing operation, the MDE that receives the request with the operation
152 invocation performs the operation and sends the response.

153 **Sending MDE**

154 In an Electronic Court Filing operation, the MDE that sends the request including the operation
155 invocation and receives the response with the results of the operation.

156 **Synchronous response**

157 A message transmission returned immediately (synchronously) as the result of an operation.
158 Every operation has a synchronous response.

159 **1.4 Symbols and Abbreviations**

160 The key symbols and abbreviations used in this specification include:

161 **ECF 4.1**

162 OASIS LegalXML Electronic Court Filing 4.1

163 **MDE**

164 Major Design Element

165 **OASIS**

166 Organization for the Advancement of Structured Information Standards

167 **SOAP**

168 Simple Object Access Protocol

169 **XML**

170 eXtensible Markup Language

171 **W3C**

172 World Wide Web Consortium

173 **WSDL**

174 Web Services Description Language
175 **WS-I**
176 Web Services Interoperability Organization

177 **1.5 Normative References**

178 **[ECF-v4.1]**

179 *Electronic Court Filing Version 4.1*. Edited by James Cabral, Gary Graham, and Philip Baughman. Latest
180 stage: <https://docs.oasis-open.org/legalxml-courtfilling/ecf/v4.1/ecf-v4.1.html>.

181 **[MTOM]**

182 M. Gudgin, N Mendelsohn, M Nottingham, H Ruellan, SOAP Message Transmission Optimization
183 Mechanism, <http://www.w3.org/TR/soap12-mtom/>, W3C Recommendation, January 2005.

184 **[Namespaces]**

185 T. Bray, *Namespaces in XML*, <http://www.w3.org/TR/xml-names/>, W3C Recommendation, December
186 2009.

187 **[RFC2045]**

188 N. Freed, *Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies*,
189 <http://www.ietf.org/rfc/rfc2045.txt>, IETF RFC 2045, November 1996.

190 **[RFC2046]**

191 N. Freed, *Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types*,
192 <http://www.ietf.org/rfc/rfc2046>, IETF RFC 2046, November 1996.

193 **[RFC2119]**

194 S. Bradner, *Key words for use in RFCs to Indicate Requirement Levels*, <http://www.ietf.org/rfc/rfc2119>,
195 IETF RFC 2119, March 1997.

196 **[RFC2616]**

197 R. Fielding, et al., *Hypertext Transfer Protocol -- HTTP/1.1*, <http://www.ietf.org/rfc/rfc2616>, IETF RFC
198 2616, June 1999.

199 **[RFC2617]**

200 J. Franks, P. Hallam-Baker, J. Hostetler, S. Lawrence, P. Leach, A. Luotonen, E. Sink, and L. Stewart,
201 *HTTP Authentication: Basic and Digest Access Authentication*, <http://www.ietf.org/rfc/rfc2617>, RFC 2617,
202 June 1999.

203 **[RFC4122]**

204 Leach, et al., *A Universally Unique IDentifier (UUID) URN Namespace*, <http://www.ietf.org/rfc/rfc4122.txt>,
205 IETF RFC 4112, July 2005.

206 **[Schema Part 1]**

207 H. S. Thompson, D. Beech, M. Maloney, N. Mendelsohn, *XML Schema Part 1: Structures Second Edition*,
208 <http://www.w3.org/TR/xmlschema-1/>, W3C Recommendation, October 28, 2004.

209 **[Schema Part 2]**

210 P. Biron, A. Malhotra, *XML Schema Part 2: Datatypes Second Edition*, <http://www.w3.org/TR/xmlschema-2/>,
211 W3C Recommendation, October 28, 2004.

212 **[SOAP 1.1]**

213 D. Box, et. al., *Simple Object Access Protocol (SOAP) 1.1*, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508>,
214 W3C Note, May 8, 2000.

215 **[SOAP MTOM 1.0]**

216 D. Angelov, C. Ferris, A Karmarkar, C Liu, J Marsh, J Mischinsky, A Nadalin, U Yalçınalp, *SOAP 1.1*
217 *Binding for MTOM 1.0*, <http://www.w3.org/Submission/soap11mtom10/>, W3C Member Submission, April
218 05, 2006.

- 219 **[WSDL 1.1]**
220 E. Christensen, F Curbera, G Meredith, S. Weerawarana, *Web Services Description Language 1.1*,
221 <http://www.w3.org/TR/wsdl>, W3C Note, March 15, 2001.
- 222 **[WS-I BP1.1]**
223 K. Ballinger, D. Ehnebuske, C. Ferris, M. Gudgin, M. Nottingham, C. K. Liu, P. Yendluri, *Basic Profile*
224 *Version 1.1 (Final Material)*, <http://www.ws-i.org/Profiles/BasicProfile-1.1-2006-04-10.html>, WS-I
225 Organization, April 10 2006.
- 226 **[WS-I BSP 1.1]**
227 M. McIntosh, M. Gudgin, K. Scott Morrison, A. Barbir, *Basic Security Profile Version 1.1 (Final Material)*,
228 <http://www.ws-i.org/Profiles/BasicSecurityProfile-1.1.html>, WS-I Organization, January 2010.
- 229 **[WS-RM 1.1]**
230 *WS-ReliableMessaging 1.1*, 15 November 2004, OASIS Standard, [http://docs.oasis-open.org/wsrn/ws-](http://docs.oasis-open.org/wsrn/ws-reliability/v1.1/wsrn-ws_reliability-1.1-spec-os.pdf)
231 [reliability/v1.1/wsrn-ws_reliability-1.1-spec-os.pdf](http://docs.oasis-open.org/wsrn/ws-reliability/v1.1/wsrn-ws_reliability-1.1-spec-os.pdf)
- 232 **[XML 1.0]**
233 T. Bray, et al., *Extensible Markup Language (XML) 1.0 (Fifth Edition)*, <http://www.w3.org/TR/xml/>, W3C
234 Recommendation, November 2008.
- 235 **[XMLENC]**
236 D. Eastlake, J. Reagle, *XML Encryption Syntax and Processing*, <http://www.w3.org/TR/xmlenc-core/>,
237 W3C Recommendation, December 2002.
- 238 **[XMLSIG]**
239 D. Eastlake., J. Reagle, D. Solo, *XML-Signature Syntax and Processing*, [http://www.w3.org/TR/xmlsig-](http://www.w3.org/TR/xmlsig-core/)
240 [core/](http://www.w3.org/TR/xmlsig-core/), W3C Recommendation, June 2008.
- 241 **[XOP]**
242 M. Gudgin, N Mendelsohn, M Nottingham, H Ruellan, *XML-binary Optimized Packaging*,
243 <http://www.w3.org/TR/2005/REC-xop10-20050125/>), W3C Recommendation, January 2005.

244 **1.6 Non-Normative References**

- 245 **[JRA WS-SIP]**
246 *Global Justice Reference Architecture Web Services Service Interaction Profile 1.1*,
247 https://bj.a.ojp.gov/sites/g/files/xyckuh186/files/media/document/ws-sip_aug_31_version_1_1_final3.pdf,
248 Global Infrastructure/Standards Working Group, August 1, 2007
- 249

250 2 Profile Design

251 This section describes the design of the Web Services Service Interaction Profile and identifies how it
252 satisfies the requirements of a document signature profile listed in Section 5 of the [ECF-v4.1]
253 specification. In addition, this profile is intended for compatibility with the Global Justice Reference
254 Architecture Web Services Service Interaction Profile [JRA WS-SIP].

255 2.1 Service Interaction Profile Identifier

256 Each ECF 4.1 service interaction profile MUST be identified with a unique URI which is used in the ECF
257 4.1 court policy to identify the service interaction profile(s) that a given MDE supports. The ECF 4.1 Web
258 Services Service Interaction Profile will be identified by the following URI:

259 `urn:oasis:names:tc:legalxml-courtfiling:schema:xsd:WebServices-4.1`

260 With the exception of **PaymentMessage** and **PaymentReceiptMessage**, all ECF 4.1 messages sent via
261 this service interaction profile MUST include this URI in the `<SendingMDEProfileCode>` element. In
262 addition, any court supporting this service interaction profile MUST include this URI in the
263 `<SupportedMessageProfile>` element in the **CourtPolicyResponseMessage**.


264 2.2 Transport Protocol

265 Each ECF 4.1 message transmission sent using this service interaction profile MUST be encapsulated in
266 a SOAP message over the HTTP 1.1 protocol as defined in the [WSI-I BP 1.1] and [SOAP MTOM]
267 specifications. Figure 1 illustrates the containment of ECF 4.1 messages and attachments within a SOAP
268 Message Package. For compliance with this specification, a SOAP envelope MUST contain one or more
269 ECF 4.1 messages and MAY contain one or more attachments.

270

271

Figure 1. SOAP Envelope with ECF 4.1 Messages and Attachments



272

273 2.3 MDE Addressing

274 Each ECF message transmission sent using this service interaction profile MUST identify the sending and
 275 receiving MDEs with universally unique address identifiers. The identifier for each MDE will be assigned
 276 by the organization that manages the MDE and MUST be the HyperText Transfer Protocol (HTTP) or
 277 HTTP over Secure Socket Layer (SSL) permanent URL for the MDE web service.

278 This URL MUST be the value of the `location` attribute of the `<soap:address>` element contained within
 279 the `<wsdl:service>` element that binds the MDE's portType to a service, and that is defined in the
 280 implementation-specific WSDL document discussed in section 1.2.4 above.

281 For instance, a conformant MDE ID of a web service at `courts.wa.gov` using HTTP over SSL on port 8000
 282 would be as follows:

283 `https://courts.wa.gov:8000`

284 2.4 Operation Addressing

285 Each message transmission MUST either identify the operation being invoked or be a synchronous
 286 response to a previous request. Each operation MUST be either a REQUIRED operation as defined in
 287 the ECF 4.1 specification or an OPTIONAL operation identified as supported by the court through the
 288 current machine-readable court policy. The response to a request for an operation not supported by the
 289 court MUST be reported using the ECF 4.1 `<ErrorCode>` element in the core message and MAY also
 290 include a `SOAPFault` in the SOAP envelope.

291 2.5 Request and Operation Invocation

292 Each message transmission MUST identify the operation being invoked within the SOAP Body only; the
293 (qualified) operation name MUST be the qualified name of the first child element of the SOAP body
294 element, as called for in section 7.1 of the **[SOAP 1.1]** specification.

295 An MDE implementation MAY allow message transmissions that include a SOAPAction HTTP header.

296 In compliance with the **[WSI-I BP 1.1]** specification, a receiving MDE MAY NOT rely on the value of the
297 SOAPAction HTTP header in processing the message.

298 2.6 Synchronous Mode Response

299 Synchronous responses to requests MUST be encoded using the MIME binding defined in Section 3 of
300 the **[SOAP MTOM 1.0]** specification.

301 2.7 Asynchronous Mode Response

302 The receiving MDE MUST deliver the asynchronous response to a request sent using the web services
303 service interaction profile by sending the asynchronous response to the sending MDE via the web
304 services service interaction profile. The response message transmission MUST conform to the rules for
305 message transmissions established in section 2.5 of this specification above.

306 2.8 Message/Attachment Delimiters

307 The ECF 4.1 messages MUST be encapsulated in the SOAP Body. All other attachments MUST be
308 included in separate MIME parts as shown in Figure 1. The delimiters between the message and the first
309 attachment, and between attachments, MUST comply with the rules for delimiting MIME parts as defined
310 in **[RFC2045]**.

311 2.9 Message Identifiers

312 Each MIME part that includes an attachment MUST have a unique "Content-ID" as defined in **[RFC2045]**
313 that uniquely identifies the content within that part.

314 2.10 Message Non-repudiation

315 The SOAP message MAY include a digital signature applied to the SOAP Body and all MIME parts that
316 contain messages or attachments. The digital signature MUST be conformant with Section 8 of the **[WS-I
317 BSP 1.0]** specification which references the **[XMLSIG]** specification. The algorithms defined by
318 **[XMLSIG]** support non-repudiation of the signer and signing date through a digital signature created
319 using the signer's private key. Because the sender is the only one with access to the private key and the
320 date is included in the signature, receivers can be reasonably assured of the signer and signing date.

321 2.11 Message Integrity

322 The algorithms defined by **[XMLSIG]** support message integrity through inclusion of a public-key-based
323 digital signature. Because the signing date and message hash are included in the signature and the
324 entire signature is computed using the sender's private key, the receiver can compare the hashes to
325 verify that the message has not been altered since it left the control of the sender on the specified date.

326 2.12 Message Confidentiality

327 If the Filing Review MDE supports the filing of confidential filings and publishes the court's public key in
328 court policy, messages and attachments MAY be encrypted for filing into the court according to Section 9
329 of the **[WS-I BSP 1.0]** specification which references the **[XMLENC]** specification. Because the Filing
330 Review MDE is the only one with access to the court's private key, filers can be reasonably assured that
331 only the Filing Review MDE will be able to read the message or attachment.

332 This mechanism MAY be used to protect sensitive or confidential information in a filing such as the
333 **PaymentMessage** However, this specification does NOT support the transmission of messages and
334 attachments encrypted with the court's public key to other parties in the case. Any messages and
335 attachments transmitted to other parties MUST be either encrypted with the party's public key or not
336 encrypted. This specification and the ECF 4.1 specification do NOT define the exchange or publication of
337 public keys by persons or organizations other than the court.

338 2.13 Message Authentication

339 Each MDE MAY define HTTP credentials for authentication to access the operations supported by that
340 MDE. If authentication is required, the sending MDE MUST include the credentials in the request as
341 defined in [RFC2617].

342 For instance, the Filing Review MDE MAY assign user ID and password pairs to each supported Filing
343 Assembly MDE, and require authentication for ReviewFiling operations but not query operations. In that
344 case, each Filing Assembly MDE would include the user ID and password assigned to them in each filing.

345 2.14 Message Reliability

346 If a court expresses support for message reliability in human-readable court policy, a sending MDE MAY
347 include reliability extensions to the SOAP envelope as defined in the [WS-RM 1.1] specification. An MDE
348 that receives a request with a SOAP envelope that includes reliability extensions MUST include reliability
349 extensions as defined by [WS-RM 1.1] in the response.

350 2.15 Message Splitting and Assembly

351 WS-Reliable Messaging defines mechanisms by which messages MAY be split into multiple pieces that
352 are assigned sequence numbers and transmitted separately by the RM Source (sending MDE) and
353 reassembled into the complete message by the RM Destination (receiving MDE).

354

355 2.16 Transmission Auditing

356 An implementation of the web services message profile MUST ensure that the complete SOAP message,
357 including the SOAP envelope, any attachments, and signatures, is available to the receiving MDE for
358 persisting and auditing purposes.

359

360

3 Service Definitions

361

Implementation by each MDE of this service interaction profile MUST be described in WSDL file that imports the service definitions from the corresponding MDE WSDL file included with this specification.

362

363

364

These WSDL files import the xsd/wrappers.xsd schema file provided in **[ECF-v4.1]**.

365

366

4 Conformance

367
368
369

An implementation conforms with the ECF 4.1 Web Services SIP if the implementation meets the requirements identified by capitalized key words [RFC2119] in Sections 1 and 2 and publishes a WSDL as required in Section 3.

370 **Appendix A. (Informative) Acknowledgments**

371 The following individuals have participated in the creation of this specification and are gratefully
372 acknowledged:

373 **Participants:**

- 374 Philip Baughman, Tyler Technologies, Inc.
- 375 James Cabral, InfoTrack US
- 376 Eric Eastman, InfoTrack US
- 377 Ryan Foley, i3-ImageSoft, LLC
- 378 Gary Graham, Arizona Supreme Court
- 379 Barbara Holmes, National Center for State Courts
- 380 George Knecht, InfoTrack US
- 381 James McMillan, National Center for State Courts
- 382 Enrique Othon, Tyler Technologies, Inc.
- 383 Jim Price, Arizona Supreme Court
- 384 Brock Rogers, File & ServeXpress

Appendix B. (Informative) Revision History

Revision	Date	Editor	Changes Made
Wd01	2022-06-18	James Cabral	Changes to ECF 4.01 Web Services SIP 2.01: Split the previous WSDL into separate files for each MDE; changed the WSDLs to use document literals, (aligning operation names and root elements) and include a SOAP action in the binding; fixed reference to MTOM specification.
Wd02	2022-08-23	James Cabral Gary Graham	Replace references to ECF 4.0 with 4.1.
Wd03	2022-09-12	James Cabral Gary Graham	Minor changes to front matter, section 2,5 and D-1.
WD04	2022-11-17	James Cabral Gary Graham	Minor typo change to 2.5.
CSD01	2022-12-07	James Cabral Gary Graham	Committee Specification Draft approved for public review
WD05	2023-05-10	James Cabral Gary Graham	Added a README.txt file in /wsdl. Fixed broken link in Section 1.6, defined namespaces and references to Related Work in the front matter, citations to ECF 4.1 throughout, and names of specific messages. Clarified references to ECF 4.1 vs SOAP messages throughout. Added guidance in Appendix C for linking the WSDL files and wrappers.xsd. Updated Figure 1. Clarified the user of xsd/wrappers.xsd in Section 3.
WD06	2023-06-23	James Cabral Gary Graham	Removed reference to support for bulk filing in Section 1.

387

Appendix C. (Informative) Example Implementation

388

This non-normative section provides an example WSDL implementation of this service interaction profile.

389

This is also included in the `CourtRecordMDE-ImplementationExample.wsdl` file included with this specification. Note that the following is for illustrative purposes only.

390
391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

```
<definitions
  targetNamespace="urn:oasis:names:tc:legalxml-courtfiling:schema:wsdl:CourtRecordMDE-
ImplementationExample-4.1"
  xmlns:wsmpt="urn:oasis:names:tc:legalxml-courtfiling:schema:wsdl:CourtRecordMDE-4.1"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
  xmlns="http://schemas.xmlsoap.org/wsdl/">

  <import namespace="urn:oasis:names:tc:legalxml-
courtfiling:schema:wsdl:CourtRecordMDE-4.1" location="CourtRecordMDE.wsdl"/>

  <service name="CourtRecordMDEService">
    <port name="CourtRecordMDE" binding="wsmpt:CourtRecordMDESoap">
      <soap:address location="https://localhost/..."/>
    </port>
  </service>
</definitions>
```

413

414

The WSDL files provided in the `/wsdl` folder on this specification import the `wrappers.xsd` file provided in

415

the `/xsd` folder of the Core specification. The `<import>` statements in the WSDL files assume that the

416

`/xsd` folder and `/wsdl` folder share a common parent folder. If not, it will be necessary to update the

417

`<import>` statements in the provided WSDL files.

418 Appendix D. (Informative) Example Transmissions

419 This non-normative section provides an example transmission that demonstrates an operation invocation,
420 a synchronous response, and an asynchronous response using this service interaction profile. Note that
421 these examples are for illustrative purposes only.

422 D.1 Operation Invocation

423 This is an example of a request including a ReviewFiling operation invocation.
424

```
425 MIME-Version: 1.0
426 Content-Type: Multipart/Related; boundary=boundary;
427     type="application/xop+xml";
428     start="Envelope"
429     start-info="text/xml"
430
431 --boundary
432 Content-Type: application/xop+xml;
433     text/xml; charset="UTF-8"
434 Content-Transfer-Encoding: 8bit
435 Content-ID: Envelope
436
437 <?xml version='1.0' ?>
438 <env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
439     <env:Body xmlns:types="http://example.com/some-namespace">
440         <wrappers:ReviewFiling>
441             <wrappers:ReviewFilingRequest>
442                 <core:CoreFilingMessage>
443                     ...
444                 </core:CoreFilingMessage>
445                 <payment:PaymentMessage>
446                     ...
447                 </payment:PaymentMessage>
448             </wrappers:ReviewFilingRequest>
449         </wrappers:ReviewFiling>
450     </env:Body>
451 </env:Envelope>
452
453 --boundary
454 Content-Type: application/pdf
455 Content-Transfer-Encoding: binary
456 Content-ID: Attachment1
457
458 ...Lead Document...
459 --boundary-
460 Content-Type: application/pdf
461 Content-Transfer-Encoding: binary
462 Content-ID: Attachment2
463
464 ...Connected Document...
465 --boundary--
466
467
```

468

469

470 D.2 Synchronous Response

471 This is an example of a MessageReceiptMessage synchronous response.

```
472 MIME-Version: 1.0
473 Content-Type: Multipart/Related; boundary=boundary;
474     type="application/xop+xml";
475     start="Envelope"
476     start-info="text/xml"
477
478 --boundary
479 Content-Type: application/xop+xml;
480     text/xml; charset="UTF-8"
481 Content-Transfer-Encoding: 8bit
482 Content-ID: Envelope
483
484 <?xml version='1.0' ?>
485 <env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
486     <env:Body xmlns:types="http://example.com/some-namespace">
487         <wrappers:ReviewFilingResponse>
488
489             <message:MessageReceiptMessage>
490                 ...
491             </message:MessageReceiptMessage>
492
493         </wrappers:ReviewFilingResponse>
494     </env:Body>
495 </env:Envelope>
496
```

497

498

499 D.3 Asynchronous Response

500 This is an example of a NotifyFilingReviewComplete asynchronous response.

501

```
502 MIME-Version: 1.0
503 Content-Type: Multipart/Related; boundary=boundary;
504     type="application/xop+xml";
505     start="Envelope"
506     start-info="text/xml"
507
508 --boundary
509 Content-Type: application/xop+xml;
510     text/xml; charset="UTF-8"
511 Content-Transfer-Encoding: 8bit
512 Content-ID: Envelope
513
514 <?xml version='1.0' ?>
515 <env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
516     <env:Body xmlns:types="http://example.com/some-namespace">
517         <wrappers:NotifyFilingReviewComplete>
518             <wrappers:NotifyFilingReviewCompleteRequest>
519                 <reviewcb:ReviewFilingCallbackMessage>
520                     ...
521                 </reviewcb:ReviewFilingCallbackMessage>
522
523                 <receipt:PaymentReceiptMessage>
524                     ...
525                 </receipt:PaymentReceiptMessage>
526             </wrappers:NotifyFilingReviewCompleteRequest>
527         </wrappers:NotifyFilingReviewComplete>
528     </env:Body>
529 </env:Envelope>
530
531 --boundary
532 Content-Type: application/pdf
533 Content-Transfer-Encoding: binary
534 Content-ID: Attachment1
535
536 ...Lead Document...
537 --boundary-
538 Content-Type: application/pdf
539 Content-Transfer-Encoding: binary
540 Content-ID: Attachment2
541
542 ...Connected Document...
543 --boundary--
544
```

545

546

Appendix E. Notices

547 Copyright © OASIS Open 2023. All Rights Reserved.

548 All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual
549 Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website:
550 [<https://www.oasis-open.org/policies-guidelines/ipr/>].

551 This document and translations of it may be copied and furnished to others, and derivative works that
552 comment on or otherwise explain it or assist in its implementation may be prepared, copied, published,
553 and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice
554 and this section are included on all such copies and derivative works. However, this document itself may
555 not be modified in any way, including by removing the copyright notice or references to OASIS, except as
556 needed for the purpose of developing any document or deliverable produced by an OASIS Technical
557 Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must
558 be followed) or as required to translate it into languages other than English.

559 The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors
560 or assigns.

561 This document and the information contained herein is provided on an "AS IS" basis and OASIS
562 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY
563 WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY
564 OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A
565 PARTICULAR PURPOSE. OASIS AND ITS MEMBERS WILL NOT BE LIABLE FOR ANY DIRECT,
566 INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THIS
567 DOCUMENT OR ANY PART THEREOF.

568 As stated in the OASIS IPR Policy, the following three paragraphs in brackets apply to OASIS Standards
569 Final Deliverable documents (Committee Specifications, OASIS Standards, or Approved Errata).

570 [OASIS requests that any OASIS Party or any other party that believes it has patent claims that would
571 necessarily be infringed by implementations of this OASIS Standards Final Deliverable, to notify OASIS
572 TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims
573 in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this
574 deliverable.]

575 [OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of
576 any patent claims that would necessarily be infringed by implementations of this OASIS Standards Final
577 Deliverable by a patent holder that is not willing to provide a license to such patent claims in a manner
578 consistent with the IPR Mode of the OASIS Technical Committee that produced this OASIS Standards
579 Final Deliverable. OASIS may include such claims on its website, but disclaims any obligation to do so.]

580 [OASIS takes no position regarding the validity or scope of any intellectual property or other rights that
581 might be claimed to pertain to the implementation or use of the technology described in this OASIS
582 Standards Final Deliverable or the extent to which any license under such rights might or might not be
583 available; neither does it represent that it has made any effort to identify any such rights. Information on
584 OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS
585 Technical Committee can be found on the OASIS website. Copies of claims of rights made available for
586 publication and any assurances of licenses to be made available, or the result of an attempt made to
587 obtain a general license or permission for the use of such proprietary rights by implementers or users of
588 this OASIS Standards Final Deliverable, can be obtained from the OASIS TC Administrator. OASIS
589 makes no representation that any information or list of intellectual property rights will at any time be
590 complete, or that any claims in such list are, in fact, Essential Claims.]

591 The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this document, and should be
592 used only to refer to the organization and its official outputs. OASIS welcomes reference to, and
593 implementation and use of, documents, while reserving the right to enforce its marks against misleading
594 uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark/> for above guidance.

595