



OSLC PROMCODE Version 1.0. Part 2: Vocabulary

Committee Specification Draft 01

28 April 2021

This stage:

<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-vocab.html> (Authoritative)
<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-vocab.pdf>

Previous stage:

N/A

Latest stage:

<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/promcode-vocab.html> (Authoritative)
<https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/promcode-vocab.pdf>

Latest editor's draft:

<http://tools.oasis-open.org/version-control/browse/wsvn/oslc-promcode/shape/trunk/vocab.html>

Technical Committee:

[OASIS OSLC Lifecycle Integration for Project Management of Contracted Delivery \(OSLC PROMCODE\) TC](#)

Chair:

Tom Kamimura (tomk@nanzan.jp), [Nanzan University](#)

Editors:

Mikio Aoyama (amikio@nanzan.jp), [Nanzan University](#)
Yoshio Horiuchi (hoy@jp.ibm.com), [IBM](#)
Tom Kamimura (tomk@nanzan.jp), [Nanzan University](#)
Shinji Matsuoka (matuoka.sinji@jp.fujitsu.com), [Fujitsu Limited](#)
Shigeaki Matsumoto (shigeaki.m@nec.com), [NEC Corporation](#)
Masaki Wakao (wakao@jp.ibm.com), [IBM](#)
Kazuo Yabuta (yabuta@nanzan.jp), [Nanzan University](#)
Hiroyuki Yoshida (yhryuki@nanzan-u.ac.jp), [Nanzan University](#)

Additional artifacts:

This specification is one component of a Work Product that also includes:

- *OSLC PROMCODE Version 1.0. Part 1: Specification.* <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-spec.html>.
- *OSLC PROMCODE Version 1.0. Part 2: Vocabulary* (this document). <https://docs.oasis-open.org/oslc->

Standards Track Work Product

- [promcode/promcode/v1.0/csd01/promcode-vocab.html](https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-vocab.html).
- *OSLC PROMCODE Version 1.0. Part 3: Constraints*. <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-shapes.html>.
- Machine-readable vocabulary terms: <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-vocab.ttl>.
- Machine-readable constraints: <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-shapes.ttl>.

Related work:

This document is related to:

- *OSLC PROMCODE Use Cases*. Work in progress. Latest editor's draft accessible at <http://tools.oasis-open.org/version-control/browse/wsvn/oslc-promcode/shape/trunk/usecase.html>. To be published at: <https://docs.oasis-open.org/oslc-promcode/usecase/v1.0/usecase-v1.0.html>.

Abstract:

This document describes vocabulary terms of the OSLC PROMCODE specification.

Status:

This document was last revised or approved by the [OASIS OSLC Lifecycle Integration for Project Management of Contracted Delivery \(OSLC PROMCODE\) TC](#) on the above date. The level of approval is also listed above. Check the "Latest stage" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=oslc-promcode#technical.

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list oslc-promcode-comment@lists.oasis-open.org, after subscribing to it by following the instructions at the "Send A Comment" button on the TC's web page at <https://www.oasis-open.org/committees/oslc-promcode/>.

This specification is provided under the [RF on Limited Terms](#) Mode of the [OASIS IPR Policy](#), the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/oslc-promcode/ipr.php>).

Note that any machine-readable content ([Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this specification, the following citation format should be used:

[OSLC-PROMCODE-v1.0-Vocab]

OSLC PROMCODE Version 1.0. Part 2: Vocabulary. Edited by Mikio Aoyama, Yoshio Horiuchi, Tom Kamimura, Shinji Matsuoka, Shigeaki Matsumoto, Masaki Wakao, Kazuo Yabuta, and Hiroyuki Yoshida. 28 April 2021. OASIS Committee Specification Draft 01. <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/csd01/promcode-vocab.html>. Latest stage: <https://docs.oasis-open.org/oslc-promcode/promcode/v1.0/promcode-vocab.html>.

Notices

Copyright © OASIS Open 2021. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

Table of Contents

- 1. [Introduction](#)
- 2. [Terminology](#)
- 3. [Vocabulary](#)
 - 3.1 [Vocabulary Details](#)
- 4. [Conformance](#)
- Appendix A. [References](#)
 - A.1 [Normative references](#)

1. Introduction

This section is non-normative.

This specification describes the vocabulary of OSLC PROMCODE specification. Class as defined in [\[rdf-schema\]](#) is used as a grouping of resources in PROMCODE. Every PROMCODE resource is a member of some class defined in PROMCODE. Properties are instances of Class `rdf:Property` defined in [\[rdf-schema\]](#) and describe a relation between subject resources and object resources. PROMCODE specification introduces fourteen classes and twenty nine properties. Among the fourteen classes, two classes are used as "abstract class" of other classes as "subclasses". More specifically, `ManagedItem` is an abstract class that has `Scopeltem`, `WorkItem`, `Artifact`, `Issue` and `Risk` classes as subclasses. Also, `ManagedItemCollection` is an abstract class with `Plan`, `Report`, `RiskCollection` and `IssueCollection` classes as subclasses.

2. Terminology

This section is non-normative.

Terminology is based on OSLC Core Overview [[OSLCCore3](#)], W3C Linked Data Platform [[LDP](#)], W3C's Architecture of the World Wide Web [[WEBARCH](#)], Hyper-text Transfer Protocol [[HTTP11](#)]. Terminology for this specification is defined in part 1 of the multi-part specification.

3. Vocabulary

3.1 Vocabulary Details

The namespace URI for this vocabulary is: <http://open-services.net/ns/promcode#>

All vocabulary URIs defined in The OSLC PROMCODE namespace.

3.1.1 RDFS Classes in this namespace

[Artifact](#), [Issue](#), [IssueCollection](#), [ManagedItem](#), [ManagedItemCollection](#), [Measure](#), [Measurement](#), [Plan](#), [Project](#), [Report](#), [Risk](#), [RiskCollection](#), [Scopeltem](#), [WorkItem](#)

3.1.2 RDF Properties in this namespace

[actualEndDate](#), [actualSize](#), [actualStartDate](#), [belongsTo](#), [collects](#), [correspondsTo](#), [identifiedBy](#), [identifiedDate](#), [includes](#), [isPartOf](#), [measures](#), [metricOfMeasure](#), [metricOfScopeltemSize](#), [observes](#), [plannedEndDate](#), [plannedSize](#), [plannedStartDate](#), [producedFor](#), [raisedBy](#), [raisedDate](#), [representedBy](#), [requiredBy](#), [sequenceNumber](#), [stateOfIssue](#), [stateOfRisk](#), [targets](#), [unitOfMeasure](#), [unitOfScopeltemSize](#), [valueOfMeasure](#)

3.1.3 Artifact

<http://open-services.net/ns/promcode#Artifact>

Artifact is an RDFS class.

Artifact is a subclass of ManagedItem class. An Artifact resource is a work product that is produced in a project such as design documents, source code, test report, and so on.

3.1.4 Issue

<http://open-services.net/ns/promcode#Issue>

Issue is an RDFS class.

Issue is a subclass of ManagedItem. An Issue resource represents a situation that must be resolved in order to meet the objectives of a project. Issue resources shared between an acquirer and a supplier must be managed. Internal issues which must be resolved by a supplier alone may not be shared. Failure to resolve the situation may result in negative consequences for the project, such as a schedule delay.

3.1.5 IssueCollection

<http://open-services.net/ns/promcode#IssueCollection>

IssueCollection is an RDFS class.

IssueCollection is a subclass of ManagedItemCollection. An IssueCollection resource is a collection of Issue resources. Once an Issue resource is collected, it continues to be included in the collection regardless of its state value. Depending on the situation, a collection may collect all Issues resources to be shared in the project on a specific date, or it may collect only certain Issues resources of some categories, such as certain status, priority, those related to a Scopeltem resource, and so on.

3.1.6 ManagedItem

<http://open-services.net/ns/promcode#ManagedItem>

ManagedItem is an RDFS class.

ManagedItem is a super class which abstracts its five concrete subclasses, that are, *ScopelItem*, *WorkItem*, *Artifact*, *Issue*, and *Risk*.

3.1.7 ManagedItemCollection

<http://open-services.net/ns/promcode#ManagedItemCollection>

ManagedItemCollection is an RDFS class.

A *ManagedItemCollection* resource is a collection of *ManagedItem* resources of a specific interest. A resource in the collection can be a resource of any subclass of *ManagedItems*, that is, *ScopelItem*, *WorkItem*, *Artifact*, *Issue*, or *Risk*. *ManagedItemCollection* has four concrete subclasses which are *Plan*, *Report*, *IssueCollection*, and *RiskCollection*. A *ManagedItemCollection* resource is linked to a *Project* resource it belongs to.

3.1.8 Measure

<http://open-services.net/ns/promcode#Measure>

Measure is an RDFS class.

A *Measure* resource represents an observation of some measurable aspect of an *Artifact*.

3.1.9 Measurement

<http://open-services.net/ns/promcode#Measurement>

Measurement is an RDFS class.

A *Measurement* resource has a link to an *Artifact* resource and a link to *measure* resources that represent actual measures of the *Artifact*. It also has the date on which the measures are taken.

3.1.10 Plan

<http://open-services.net/ns/promcode#Plan>

Plan is an RDFS class.

A *Plan* resource is a collection of *ScopelItem* resources, *WorkItem* resources and *Artifact* resources with associated *Measure* resources. A *Plan* resource represents a project plan that is agreed on between an acquirer and a supplier at project initiation. *Plan* is a subclass of *ManagedItemCollection*.

3.1.11 Project

<http://open-services.net/ns/promcode#Project>

Project is an RDFS class.

A *Project* resource represents the information on the project including the name of the project, the descriptions of the project, and start and end dates, both planned and actual, of the project. A *Project* resource also specifies the metric and the unit type of size of *ScopelItem* resources because they should be unique in a project.

3.1.12 Report

<http://open-services.net/ns/promcode#Report>

Report is an RDFS class.

A Report resource represents a project status information reported by a supplier to an acquirer at agreed timing as a project report. It is a ManagedItemCollection resource that collects Scopeltem resources, WorkItem resources, and Artifact resources whose properties are reported in the report. It is also linked to Measurement resources that represent the quality data of the Artifact resources collected in the ManagedItemCollection resource.

3.1.13 Risk

<http://open-services.net/ns/promcode#Risk>

Risk is an RDFS class.

Risk is a subclass of ManagedItem. A Risk resource represents a potential problem that must be controlled in order to meet the objectives of a project. Shared risks between an acquirer and a supplier must be managed. Internal risks which must be resolved by a supplier alone may not be shared. Failure to control the potential problem may result in negative consequences for the project, such as a schedule delay.

3.1.14 RiskCollection

<http://open-services.net/ns/promcode#RiskCollection>

RiskCollection is an RDFS class.

RiskCollection is a subclass of ManagedItemCollection. A RiskCollection resource is a collection, or a snapshot of shared risks. Shared risks of resolved status continue to be included in the collection. Only Risk resources can be collected in a RiskCollection resource. Examples are a collection of all Risk resources of the project on a specific date, a collection of Risk resources of some category, such as certain status, certain priority, related Scopeltem, and so on.

3.1.15 Scopeltem

<http://open-services.net/ns/promcode#Scopeltem>

Scopeltem is an RDFS class.

Scopeltem is a subclass of ManagedItem. A Scopeltem resource defines the scope of the work to be included in a project. It defines the binding between an acquirer and a supplier for the project.

3.1.16 WorkItem

<http://open-services.net/ns/promcode#WorkItem>

WorkItem is an RDFS class.

WorkItem is a subclass of ManagedItem. A WorkItem resource describes the work to be performed in a contract. It adds details to the description of the work that is described by a Scopeltem resource. These details typically include cost, schedule, and resource requirements. The set of all WorkItem resources in a project may form a work breakdown structure.

3.1.17 actualEndDate

<http://open-services.net/ns/promcode#actualEndDate>

actualEndDate is an RDF property.

actualEndDate is either a property of a WorkItem resource or a Project resource. It is the actual end date of the work described by the WorkItem resource or of the project described by the Project resource. Its value is a dateTime.

3.1.18 actualSize

<http://open-services.net/ns/promcode#actualSize>

actualSize is an RDF property.

actualSize is a property actual development size of the scope described by the *ScopItem* resource.

3.1.19 *actualStartDate*

<http://open-services.net/ns/promcode#actualStartDate>

actualStartDate is an RDF property.

actualStartDate is either a property of a *WorkItem* resource or a *Project* resource. It is the actual start date of the work described by the *WorkItem* resource or of the project described by the *Project* resource. Its value is a *dateTime*.

3.1.20 *belongsTo*

<http://open-services.net/ns/promcode#belongsTo>

belongsTo is an RDF property.

belongsTo is a relation between *ManagedItemCollections* and a *Project* resource. An acquirer and a supplier may operate multiple projects in parallel. This relation is used to identify which collection belongs to which project.

3.1.21 *collects*

<http://open-services.net/ns/promcode#collects>

collects is an RDF property.

collects is a relation between a *ManagedItemCollection* resource and *ManagedItem* resources. A *Plan* resource and a *Report* resource collect any combination of resources of *ScopItem*, *WorkItem* and *Artifact*. An *IssueCollection* resource collects only *Issue* resources and a *RiskCollection* collects only *Risk* resources.

3.1.22 *correspondsTo*

<http://open-services.net/ns/promcode#correspondsTo>

correspondsTo is an RDF property.

correspondsTo is a relation between a *Plan* resource and a *Report* resource. A *Report* resource has at most one *correspondsTo* relation to a *Plan* resource. If a new *Plan* resource is created, a *Report* resource may need to be related to the new *Plan* resource.

3.1.23 *identifiedBy*

<http://open-services.net/ns/promcode#identifiedBy>

identifiedBy is an RDF property.

identifiedBy is a relation between a *Risk* resource and *ManagedItem* resources. A *Risk* may be identified by one or more *ManagedItem* resources.

3.1.24 *identifiedDate*

<http://open-services.net/ns/promcode#identifiedDate>

identifiedDate is an RDF property.

identifiedDate is an optional property of a Risk resource. It is the identified date of the Risk resource. Its value is a dateTime.

3.1.25 includes

<http://open-services.net/ns/promcode#includes>

includes is an RDF property.

includes is a relation between a Report resource and Measurement resources. A Measurement resource linked from the Report resource measures a quality value of the Artifact resource in the collection of the ManagedItem resources of the Report resource.

3.1.26 isPartOf

<http://open-services.net/ns/promcode#isPartOf>

isPartOf is an RDF property.

isPartOf is a relation between a resource of type Artifact, ScopeItem or WorkItem and other resources of the same type. It represents the parent and child relationship of ManagedItem resources of the same type.

3.1.27 measures

<http://open-services.net/ns/promcode#measures>

measures is an RDF property.

measures is a relation between a Measurement resource and an Artifact resource. A Measurement measures an Artifact.

3.1.28 metricOfMeasure

<http://open-services.net/ns/promcode#metricOfMeasure>

metricOfMeasure is an RDF property.

metricOfMeasure is a relation between a Measure resource and a Metric resource. It defines a metric of Measure.

3.1.29 metricOfScopeItemSize

<http://open-services.net/ns/promcode#metricOfScopeItemSize>

metricOfScopeItemSize is an RDF property.

metricOfScopeItemSize is a relation between a Project resource and a Metric resource. It defines a metric of the size which all the ScopeItem resources in the project refer to.

3.1.30 observes

<http://open-services.net/ns/promcode#observes>

observes is an RDF property.

observes is a relation between a Measurement resource and a Measure resource. One Measurement observes zero or many Measures.

3.1.31 plannedEndDate

<http://open-services.net/ns/promcode#plannedEndDate>

plannedEndDate is an RDF property.

plannedEndDate is either a property of a *WorkItem* resource or a *Project* resource. It is the planned end date of the work described by the *WorkItem* resource or of the project described by the *Project* resource. Its value is a *dateTime*.

3.1.32 *plannedSize*

<http://open-services.net/ns/promcode#plannedSize>

plannedSize is an RDF property.

plannedSize is a property on the estimated development size of the scope described by a *Scopeltem* resource.

3.1.33 *plannedStartDate*

<http://open-services.net/ns/promcode#plannedStartDate>

plannedStartDate is an RDF property.

plannedStartDate is either a property of a *WorkItem* resource or of a *Project* resource. It is the planned start date of the work described by the *WorkItem* resource or of the project described by the *Project* resource. Its value is a *dateTime*.

3.1.34 *producedFor*

<http://open-services.net/ns/promcode#producedFor>

producedFor is an RDF property.

producedFor is a relation between an *Artifact* resource and a *Scopeltem* resource or a *WorkItem* resource. *Artifact* resources are produced as deliverables of the scope defined by a *Scopeltem* resource or the result of implementing the work described by a *WorkItem* resource.

3.1.35 *raisedBy*

<http://open-services.net/ns/promcode#raisedBy>

raisedBy is an RDF property.

raisedBy is a relation between an *Issue* resource and *ManagedItem* resources. An *Issue* may be raised by one or more *ManagedItem* resources.

3.1.36 *raisedDate*

<http://open-services.net/ns/promcode#raisedDate>

raisedDate is an RDF property.

raisedDate is an optional property of an *Issue* resource. It is the raised date of the *Issue* resource. Its value is a *dateTime*.

3.1.37 *representedBy*

<http://open-services.net/ns/promcode#representedBy>

representedBy is an RDF property.

`requiredBy` is a relation between a `WorkItem` resource and a person in charge. A work item may be represented by a person who acts as the contact for the work item. This person is responsible for the progress of the work described by the `WorkItem` resource. This person may or may not actually do the required work.

3.1.38 `requiredBy`

<http://open-services.net/ns/promcode#requiredBy>

`requiredBy` is an RDF property.

`requiredBy` is a relation either between a `WorkItem` resource and an `Artifact` resource, or between a `WorkItem` resource and a `Scopeltem` resource. A `WorkItem` resource, such as reviewing the design, is required by producing an `Artifact` resource such as a review record. A `WorkItem` resource may also be required to implement the scope described by a `Scopeltem` resource.

3.1.39 `sequenceNumber`

<http://open-services.net/ns/promcode#sequenceNumber>

`sequenceNumber` is an RDF property.

`sequenceNumber` is a unique number which represents the position of the resource in a sequential order of all the resources of each subclass of `ManagedItem`.

3.1.40 `stateOfIssue`

<http://open-services.net/ns/promcode#stateOfIssue>

`stateOfIssue` is an RDF property.

`stateOfIssue` is a relation between an `Issue` resource and a `State` resource. The `State` resource defines a set of values which represent the state of an issue resource.

3.1.41 `stateOfRisk`

<http://open-services.net/ns/promcode#stateOfRisk>

`stateOfRisk` is an RDF property.

`stateOfRisk` is a relation between a `Risk` resource and a `State` resource. The `State` resource defines a set of values which represent the state of a `Risk` resource.

3.1.42 `targets`

<http://open-services.net/ns/promcode#targets>

`targets` is an RDF property.

`targets` is a relation between an `Artifact` resource and a `Measure` resource. The `Measure` resource represents a target goal of quality measure of the `Artifact` resource.

3.1.43 `unitOfMeasure`

<http://open-services.net/ns/promcode#unitOfMeasure>

`unitOfMeasure` is an RDF property.

`unitOfMeasure` is a relation between a `Measure` resource and a `Unit` resource. It is a unit of volume. If an acquirer sums

up the same type of measures in a report, the value should be converted according to the unit.

3.1.44 **unitOfScopeltemSize**

<http://open-services.net/ns/promcode#unitOfScopeltemSize>

unitOfScopeltemSize is an RDF property.

unitOfScopeltemSize is a relation between a Project resource and a Unit resource. It defines a unit of size which all the Scopeltem resources refer to in the project.

3.1.45 **valueOfMeasure**

<http://open-services.net/ns/promcode#valueOfMeasure>

valueOfMeasure is an RDF property.

valueOfMeasure is a property that represents a value for a Measure resource.

4. Conformance

PROMCODE servers **MUST** follow the constraints defined here where required, and with the meanings defined here.

PROMCODE servers **MAY** provide additional constraints for specific purposes.

Appendix A. References

A.1 Normative references

[HTTP11]

R. Fielding, Ed.; J. Reschke, Ed.. *Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing*. June 2014. Proposed Standard. URL: <https://httpwg.org/specs/rfc7230.html>

[LDP]

Steve Speicher; John Arwe; Ashok Malhotra. *Linked Data Platform 1.0*. 26 February 2015. W3C Recommendation. URL: <https://www.w3.org/TR/ldp/>

[OSLCCore3]

Jim Amsden; Martin Sarabura. *OSLC Core 3.0*. URL: <https://docs.oasis-open-projects.org/oslc-op/core/v3.0/ps01/oslc-core.html>

[WEBARCH]

Ian Jacobs; Norman Walsh. *Architecture of the World Wide Web, Volume One*. 15 December 2004. W3C Recommendation. URL: <https://www.w3.org/TR/webarch/>

[rdf-schema]

Dan Brickley; Ramanathan Guha. *RDF Schema 1.1*. 25 February 2014. W3C Recommendation. URL: <https://www.w3.org/TR/rdf-schema/>