



SAML V2.0 Subject Identifier Attributes Profile Version 1.0

~~Committee Specification Draft 03/~~
~~Public Review Draft 03~~01

~~25 September 2018~~

16 January 2019

Specification URIs

This version:

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/cs01/saml-subject-id-attr-v1.0-cs01.odt> (Authoritative)

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/cs01/saml-subject-id-attr-v1.0-cs01.html>

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/cs01/saml-subject-id-attr-v1.0-cs01.pdf>

Previous version:

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd03/saml-subject-id-attr-v1.0-csprd03.odt> (Authoritative)

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd03/saml-subject-id-attr-v1.0-csprd03.html>

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd03/saml-subject-id-attr-v1.0-csprd03.pdf> other format

Previous version:

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd02/saml-subject-id-attr-v1.0-csprd02.odt> (Authoritative)

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd02/saml-subject-id-attr-v1.0-csprd02.html>

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd02/saml-subject-id-attr-v1.0-csprd02.pdf>

Latest version:

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.odt> (Authoritative)

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.html>

<http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.pdf>

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.odt> (Authoritative)

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.html>

<https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.pdf>

Technical Committee:

OASIS Security Services (SAML) TC

Chair:

Thomas Hardjono (hardjono@mit.edu), M.I.T.

Editors:

Scott Cantor (cantor.2@osu.edu), Internet2

Additional artifacts:

This prose specification is one component of a Work Product that also includes:

XML schema: <http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd03/schema/saml-subject-id-attr-v1.0.xsd>

- XML schema: <https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/cs01/schema/saml-subject-id-attr-v1.0.xsd>

Related work:

This specification is related to:

- eduPerson Object Class Specification (201602)
<http://software.internet2.edu/eduperson/internet2-mace-dir-eduperson-201602.html>.

Declared XML namespaces:

- urn:mace:shibboleth:metadata:1.0

Abstract:

This specification standardizes two new SAML Attributes to identify security subjects, as a replacement for long-standing inconsistent practice with the `<saml:NameID>` and `<saml:Attribute>` constructs, and to address recognized deficiencies with the SAML V2.0 `urn:oasis:names:tc:SAML:2.0:nameid-format:persistent` Name Identifier format.

Status:

This document was last revised or approved by the OASIS Security Services (SAML) TC on the above date. The level of approval is also listed above. Check the "Latest version" location noted above for possible later revisions of this document. Any other numbered Versions and other technical work produced by the Technical Committee (TC) are listed at https://www.oasis-open.org/committees/tc_home.php?wg_abbrev=security#technical.

TC members should send comments on this specification to the TC's email list. Others should send comments to the TC's public comment list, after subscribing to it by following the instructions at the "[Send A Comment](#)" button on the Technical Committee's web page at <https://www.oasis-open.org/committees/security/>.

~~This Committee Specification Public Review Draft~~ [This specification](#) is provided under the RF on RAND Terms Mode of the OASIS IPR Policy, the mode chosen when the Technical Committee was established. For information on whether any patents have been disclosed that may be essential to implementing this Work Product, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/security/ipr.php>).

Note that any machine-readable content (aka [Computer Language Definitions](#)) declared Normative for this Work Product is provided in separate plain text files. In the event of a discrepancy between any such plain text file and display content in the Work Product's prose narrative document(s), the content in the separate plain text file prevails.

Citation format:

When referencing this Work Product the following citation format should be used:

[SAML-SubjectID-v1.0]

SAML V2.0 Subject Identifier Attributes Profile Version 1.0. Edited by Scott Cantor. ~~25 September 2018.~~ **16 January 2019**. OASIS Committee Specification ~~Draft 03 / Public Review Draft 03-01.~~ <http://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/csprd03/saml-subject-id-attr-v1.0-csprd03.html>. <https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/cs01/saml-subject-id-attr-v1.0-cs01.html>. Latest version: <https://docs.oasis-open.org/security/saml-subject-id-attr/v1.0/saml-subject-id-attr-v1.0.html>.

Notices

Copyright © OASIS Open 2018⁹. All Rights Reserved.

All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual Property Rights Policy (the "OASIS IPR Policy"). The full [Policy](#) may be found at the OASIS website.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this section are included on all such copies and derivative works. However, this document itself may not be modified in any way, including by removing the copyright notice or references to OASIS, except as needed for the purpose of developing any document or deliverable produced by an OASIS Technical Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be followed) or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and OASIS DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

OASIS requests that any OASIS Party or any other party that believes it has patent claims that would necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification.

OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any patent claims that would necessarily be infringed by implementations of this specification by a patent holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced this specification. OASIS may include such claims on its website, but disclaims any obligation to do so.

OASIS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS Standard, can be obtained from the OASIS TC Administrator. OASIS makes no representation that any information or list of intellectual property rights will at any time be complete, or that any claims in such list are, in fact, Essential Claims.

The name "OASIS" is a trademark of [OASIS](#), the owner and developer of this specification, and should be used only to refer to the organization and its official outputs. OASIS welcomes reference to, and implementation and use of, specifications, while reserving the right to enforce its marks against misleading uses. Please see <https://www.oasis-open.org/policies-guidelines/trademark> for above guidance.

Table of Contents

1	Introduction	5
1.1	IPR Policy	5
1.2	Terminology and Notation.....	5
1.3	Normative References	5
1.4	Non-Normative References	6
2	Motivation	7
2.1	Problem Statement.....	7
2.2	Relationship to Existing Work.....	8
3	SAML V2.0 Subject Identifier Attributes Profile Version 1.0	9
3.1	Required Information	9
3.2	Overview	9
3.3	General Purpose Subject Identifier.....	9
3.3.1	Syntax and Handling	10 9
3.3.2	Semantics and Practices.....	10
3.3.3	Example.....	11 10
3.4	Pairwise Subject Identifier	11
3.4.1	Syntax and Handling	11
3.4.2	Semantics and Practices.....	11
3.4.3	Implementation Strategies.....	12
3.4.4	Differences from "persistent" NameIDs.....	12
3.4.5	Example.....	12
3.5	Considerations for SAML Profiles.....	13 12
3.5.1	Requirements Signaling	13 12
3.5.2	Scope Filtering	13
3.5.2.1	Element <shibmd:Scope>	14
3.5.2.2	Usage Considerations.....	15 14
3.5.3	NameID Considerations	15
3.5.4	Security Considerations	15
4	Conformance.....	17 16
4.1	Conformance Clause 1: Asserting Party Implementations	17 16
4.2	Conformance Clause 2: Relying Party Implementations	17 16
Appendix A	Acknowledgments	18 17
Appendix B	Revision History.....	19 18

1 Introduction

1.1 IPR Policy

This specification is provided under the RF on RAND Terms Mode of the OASIS IPR Policy, the mode chosen when the Technical Committee was established.

For information on whether any patents have been disclosed that may be essential to implementing this specification, and any offers of patent licensing terms, please refer to the Intellectual Property Rights section of the TC's web page (<https://www.oasis-open.org/committees/security/ipr.php>).

1.2 Terminology and Notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Conventional XML namespace prefixes are used throughout the listings in this specification to stand for their respective namespaces as follows, whether or not a namespace declaration is present in the example:

Prefix	XML Namespace	Comments
saml:	urn:oasis:names:tc:SAML:2.0:assertion	This is the SAML V2.0 assertion namespace [SAML2Core].
samlp:	urn:oasis:names:tc:SAML:2.0:protocol	This is the SAML V2.0 protocol namespace [SAML2Core].
md:	urn:oasis:names:tc:SAML:2.0:metadata	This is the SAML V2.0 metadata namespace [SAML2Meta].
mdattr:	urn:oasis:names:tc:SAML:metadata:attributes	This is the SAML V2.0 metadata extension for entity attributes namespace [MetaAttr].
shibmd:	urn:mace:shibboleth:metadata:1.0	This is a SAML V2.0 metadata extension namespace defined by this document and its accompanying schema.
xsd:	http://www.w3.org/2001/XMLSchema	This namespace is defined in the W3C XML Schema specification [XMLSCHEMA-2].

This specification uses the following typographical conventions in text: `<ns:Element>`, *Attribute*, **Datatype**, *OtherCode*.

This specification uses the following typographical conventions in XML listings:

```
Listings of XML schemas appear like this.
```

```
Listings of XML examples appear like this. These listings are non-normative.
```

1.3 Normative References

- [RFC2119]** Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997. <http://www.ietf.org/rfc/rfc2119.txt>.
- [RFC2234]** Crocker, D, Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 2234, November 1997. <http://www.ietf.org/rfc/rfc2234.txt>.
- [SAML2Core]** *Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0*. Edited by Scott Cantor, John Kemp, Rob Philpott, Eve Maler. 15 March 2005. OASIS Standard. <http://docs.oasis-open.org/security/saml/v2.0/saml-core-2.0-os.pdf>

- [MetaAttr]** *SAML V2.0 Metadata Extension for Entity Attributes Version 1.0*. Edited by Scott Cantor. 4 August 2009. OASIS Committee Specification. <http://docs.oasis-open.org/security/saml/Post2.0/sstc-metadata-attr-cs-01.pdf>. Latest version: <http://docs.oasis-open.org/security/saml/Post2.0/sstc-metadata-attr.pdf>.
- [SAML2Errata]** *SAML V2.0 Errata*. Edited by Scott Cantor. 1 May 2012. OASIS Approved Errata. <http://docs.oasis-open.org/security/saml/v2.0/errata05/os/saml-v2.0-errata05-os.pdf>. Latest version: <http://docs.oasis-open.org/security/saml/v2.0/sstc-saml-approved-errata-2.0.pdf>
- [SAML2Meta]** *Metadata for the OASIS Security Assertion Markup Language (SAML) V2.0*. Edited by Scott Cantor, Jahan Moreh, Rob Philpot, Eve Maler. 15 **March 2005**. OASIS Standard. <http://docs.oasis-open.org/security/saml/v2.0/saml-metadata-2.0-os.pdf>
- [SAML2Prof]** *Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0*. Edited by John Hughes, Scott Cantor, Jeff Hodges, Frederick Hirsch, Prateek Mishra, Rob Philpot, Eve Maler. 15 **March 2005**. OASIS Standard. <http://docs.oasis-open.org/security/saml/v2.0/saml-profiles-2.0-os.pdf>
- [XMLSCHEMA-2]** *XML Schema Part 2: Datatypes Second Edition*. Paul V. Biron, A. Malhotra, Editors. W3C Recommendation. October 28, 2004. <http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>. Latest version: <http://www.w3.org/TR/xmlschema-2/>.

22 1.4 Non-Normative References

- [eduPerson]** Internet2, “eduPerson Object Class Specification (201602)”, February 2016. <http://software.internet2.edu/eduperson/internet2-mace-dir-eduperson-201602.html>.
- [RFC4648]** Josefson, S., “The Base16, Base32, and Base64 Data Encodings”, RFC 4648, October 2006. <http://www.ietf.org/rfc/rfc4648.txt>.
- [ShibMetaExt]** Shibboleth Project, “Shibboleth Metadata Extensions V1.0”, July 2018. <https://wiki.shibboleth.net/confluence/x/QACt>.

23 2 Motivation

24 2.1 Problem Statement

25 Identification of subjects in security protocols and applications has a fraught history of inconsistent syntax,
26 bugs, terrible but deeply cemented practices such as misuse of email addresses, vertical market-specific
27 approaches, and failure to precisely communicate intended semantics and constraints. These problems
28 lead to overly complex burdens on both asserting and relying parties to issue and consume a variety of
29 different identifiers in different formats, many of which work poorly with off the shelf applications. Much of
30 this is self-inflicted fragmentation due to the constant tension between fixing problems with new solutions
31 and avoiding new solutions to ensure wider adoption.

32 SAML itself has its origins in a design philosophy that tried to avoid breaking new ground in this area, and
33 instead attempted to design for generality, which is valuable, but did not ease adoption due to a lack of
34 guidance. SAML also complicates itself by providing an optional, singly-appearing construct for
35 identification (the `<saml:NameID>` element) *and* a more general multiply-appearing
36 `<saml:Attribute>` construct that inherently overlap.

37 This, together with inconsistent technical precision by implementers and deployers, creates complexity.
38 Deployment experience has shown that use of the NameID feature is confusing in many implementations.
39 It also, through its presence in the SAML Single Logout protocol, potentially appears (indirectly but
40 recoverably) in web access logs, leading to the added complexity of encryption when privacy is a
41 consideration.

42 There is a general consensus by most federated identity practitioners around a few common
43 requirements:

- 44 • Identifiers should be as stable as possible and should have little or no risk of reassignment to
45 different subjects due to the lack of tight synchronization¹ inherent between loosely-coupled
46 systems.
- 47 • Opaque (i.e., superficially random) identifiers are inherently more stable than name-based
48 identifiers or email addresses in many organizations.
- 49 • Identifiers should be compact and simple to handle and manipulate.
- 50 • The ability to clearly express the scope of an identifier's uniqueness and enforce policy stipulating
51 the asserting parties permitted to issue an identifier is crucial to federated systems and the lack of
52 such policy has led to widely-publicized breaches.

53 Another requirement perhaps more common to education and research is the ability for different asserting
54 parties to issue the same identifier. This is facilitated by ensuring the scope of an identifier is part of its
55 value and not implicit in a protocol-specific construct specific to an asserting party.

56 SAML does not define an identifier that meets all of these requirements well. It does standardize a kind of
57 NameID termed "persistent" that meets some of them in the particular case of so-called "pairwise"
58 identification, where for a given subject's identifier varies by relying party. It has seen minimal adoption
59 outside of a few contexts, and fails at the "compact" and "simple to handle" criteria above, on top of the
60 disadvantages inherent with all NameID usage.

61 Pairwise identification may help meet certain privacy and regulatory requirements (though this is far from
62 clear to date), but does not address many common use cases that demand cross-system correlation
63 without the friction of complex linking protocols and the involvement of the data subject.

64 In addition, it has come to light that many, if not most, applications have a predisposition to handle
65 identifiers case-insensitively, partly due to a long-standing, though factually untrue, assumption that e-
66 mail address mailbox names are case-insensitive data. SAML's "persistent" NameID definition explicitly
67 requires case-sensitive handling, making them impossible to use safely with such applications without
68 resorting to additional layers of profiling. Note that any other specification promulgating such identifiers is
69 potentially unsafe in combination with such applications and should be used with caution.

¹It's worth noting that SAML actually defines a protocol for managing changes to NameID values, but it has seen very little adoption, further demonstrating the lack of value of NameID usage.

70 For all of these reasons, this profile attacks these problems by taking a clean-slate approach that
71 abandons existing practice instead of attempting to layer more profiling and out of band agreements on
72 top of existing solutions, an approach that has seemingly reached its breaking point.

73 **2.2 Relationship to Existing Work**

74 A clean slate notwithstanding, this profile is based on a thorough review of practice within the higher
75 education sector, which has seen extensive adoption of SAML and partially-successful efforts to
76 standardize subject identification and avoid the “email address” trap that most of the technical world fell
77 into many years ago.

78 Among the significant work in this space, the [eduPerson] schema includes a number of identifier
79 attributes, some widely adopted and some less so. This profile is particularly influenced by:

- 80 • Experience with the SAML “persistent” NameID construct and the related eduPersonTargetedID
81 attribute.
- 82 • The eduPersonPrincipalName and eduPersonUniqueid attributes, the former successful but
83 deeply flawed, the latter less successful but more carefully defined.
- 84 • Success with DNS domain-based scoping of values and managing policy around their use in
85 SAML.
- 86 • Challenges in the adoption of profiles required to accommodate the limitations of widely deployed
87 identifiers.

88 Portions of this specification are borrowed liberally from the [eduPerson] specification in a deliberate
89 desire to remain consistent with the formulation of the eduPersonUniqueid attribute.

90 This specification also incorporates the relevant subset of a SAML Metadata extension schema, originally
91 defined by the Shibboleth Project [ShibMetaExt]. This extension has seen extensive adoption, and is
92 included here to support centralizing and automating policy for authorizing asserting parties to issue
93 identifiers in particular scopes. The XML namespace of this extension (a URN issued by the Shibboleth
94 Project) is maintained to remain compatible with existing implementations and deployments dating back
95 many years.

3 SAML V2.0 Subject Identifier Attributes Profile Version 1.0

3.1 Required Information

Identification: urn:oasis:names:tc:SAML:profiles:subject-id

Contact information: security-services-comment@lists.oasis-open.org

Description: Given below.

Updates: None.

3.2 Overview

This profile defines a pair of SAML Attributes providing for unique identification of security subjects (which are generally but not exclusively people). One is designed for general use as a correlatable globally-unique identifier, and the other is a pairwise identifier suitable for more specialized uses.

Both SAML Attributes are limited to a single value when expressed in SAML assertions and other constructs. They may be mapped to and from other technical forms (e.g., LDAP attributes) but this profile does not include such mappings.

In the terminology used in this profile:

- "asserting party" refers to a uniquely-named SAML entity that issues assertions containing one or both of these Attributes
- "relying party" refers to one or more uniquely-named SAML entities that receive assertions containing one or both of these Attributes

In addition, this profile defines a signaling mechanism for a relying party to express its subject identification requirements via SAML metadata [SAML2Meta], by means of the `<mdattr:EntityAttributes>` extension [MetaAttr]. This allows asserting parties to unambiguously understand the requirements of a peer and facilitates deployment profiles that wish to mandate support for one or both of these Attributes, while maintaining appropriate privacy expectations.

Finally, this profile incorporates and re-publishes in a standards-based context an existing SAML metadata extension element that documents attribute "scopes" an asserting party is authorized to use for its SAML Attributes (according to the issuer of that metadata).

3.3 General Purpose Subject Identifier

For general purpose identification of subjects, the following SAML Attribute is defined:

Name: urn:oasis:names:tc:SAML:attribute:subject-id

NameFormat: urn:oasis:names:tc:SAML:2.0:attrname-format:uri

This is a long-lived, non-reassignable, omni-directional identifier suitable for use as a globally-unique external key. Its value for a given subject is independent of the relying party to whom it is given.

3.3.1 Syntax and Handling

The `<saml:Attribute>` element MUST contain exactly one `<saml:AttributeValue>` element, whose `xsi:type` SHOULD be absent or if present MUST BE bound to the XML Schema `xsd:string` data type [XMLSCHEMA-2].

Any leading or trailing whitespace, as defined by XML (ASCII 32, ASCII 9, ASCII 10, ASCII 13), present in the `<saml:AttributeValue>` element's content is not significant and MUST be stripped by the relying party prior to evaluation or comparison.

The value consists of two substrings (termed a "unique ID" and a "scope" in the remainder of this definition) separated by an @ symbol (ASCII 64) as an inline delimiter.

138 The unique ID consists of 1 to 127 ASCII characters, each of which is either an alphanumeric ASCII
139 character, an equals sign (ASCII 61), or a hyphen (ASCII 45). The first character MUST be alphanumeric.

140 The scope consists of 1 to 127 ASCII characters, each of which is either an alphanumeric ASCII
141 character, a hyphen (ASCII 45), or a period (ASCII 46). The first character MUST be alphanumeric. The
142 scope deliberately resembles, and often is, a DNS domain name, but is drawn from a more limited
143 character set due to case folding considerations, and no attempt is made to limit the allowable grammar
144 to legal domain names (e.g., it allows consecutive periods).

145 The ABNF [RFC2234] grammar is therefore:

```
146     <value> = <uniqueID> "@" <scope>  
147     <uniqueID> = (ALPHA / DIGIT) 0*126(ALPHA / DIGIT / "=" / "-")  
148     <scope> = (ALPHA / DIGIT) 0*126(ALPHA / DIGIT / "-" / ".")
```

149 Value comparison MUST be performed case-insensitively (that is, values that differ only by case are the
150 same, and MUST refer to the same subject).

151 In the grammar above, ~~only~~ the ALPHA production contains characters that can be expressed in both
152 upper and lower case. It is RECOMMENDED that the unique ID be exclusively upper- or lower-case when
153 expressed or stored to facilitate ease of comparison. Further, it is RECOMMENDED that scopes be
154 expressed in lower case, since they are generally chosen independently of more “entrenched” decisions
155 and are frequently, though not required to be, in the form of DNS domains. [See also Section 3.5.2.2 for](#)
156 [additional motivation.](#)

157 3.3.2 Semantics and Practices

158 A value (the unique ID and scope together) MUST be bound to one and only one subject, but the same
159 unique ID given a different scope may refer to the same or (far more likely) a different subject.

160 The relationship between an asserting party and a scope is an arbitrary one and does not reflect any
161 assumed relationship between a scope in the form of a domain name and a domain found in a given
162 SAML entity identifier. This indirect relationship is formally expressible in SAML metadata via the
163 extension defined in Section 3.5.2.

164 A value MUST NOT be assigned to more than a single subject over its lifetime of use under any
165 circumstances. The unique ID should therefore be constructed in a fashion that reduces the probability of
166 non-technical or political considerations leading to a violation of this requirement, and any such violation
167 should be treated as a potential security risk to the relying parties to which the value may have been
168 given.

169 Relying parties should not treat this identifier as an email address for the subject as it is unlikely (though
170 not precluded) for it to be valid for that purpose. Most organizations will find that existing email address
171 values will not serve well as values for this Attribute.

172 The unique ID should not change as a result of a change to any other data associated with the subject
173 (e.g., name, email address, age, organizational role).

174 A given value MUST identify the same subject regardless of the context of use or the relying parties to
175 which the Attribute is given. It is therefore to be assumed by relying parties that receive a given value that
176 the same subject has been identified.

177 Note that, policy permitting, a given value could be provided by any asserting party, and the requirement
178 still holds: identical values correspond to the same subject. While it will be common in many deployments
179 to limit values with a given scope to a single asserting party, this is ultimately left to the discretion of the
180 relying party and the use case.

181 A single subject MAY be identified simultaneously by a single asserting party by multiple values, but this
182 should be minimized to the extent possible.

183 3.3.3 Example

184 The following is an example of the SAML Attribute defined in this section:

```
185     <saml:Attribute Name="urn:oasis:names:tc:SAML:attribute:subject-id"  
186         NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">  
187         <saml:AttributeValue>idm123456789@example.com</saml:AttributeValue>
```

189 3.4 Pairwise Subject Identifier

190 For pairwise identification of subjects, the following SAML Attribute is defined:

191 **Name:** urn:oasis:names:tc:SAML:attribute:pairwise-id

192 **NameFormat:** urn:oasis:names:tc:SAML:2.0:attrname-format:uri

193 This is a long-lived, non-reassignable, uni-directional identifier suitable for use as a unique external key
194 specific to a particular relying party. Its value for a given subject depends upon the relying party to whom
195 it is given, thus preventing unrelated systems from using it as a basis for correlation.

196 3.4.1 Syntax and Handling

197 The requirements for this Attribute are identical to those described in Section 3.3.1. That is, values of this
198 Attribute are indistinguishable, lacking the context, from the other.

199 3.4.2 Semantics and Practices

200 Given a particular relying party, a value (the unique ID and scope together) MUST be bound to only one
201 subject, but the same unique ID given a different scope may refer to the same or (far more likely) a
202 different subject. The same value provided to different relying parties MAY refer to different subjects, and
203 indeed that is the primary distinguishing characteristic of this identifier Attribute.

204 The relationship between an asserting party and a scope is an arbitrary one and does not reflect any
205 assumed relationship between a scope in the form of a domain name and a domain found in a given
206 SAML entity identifier. This indirect relationship is formally expressible in SAML metadata via the
207 extension defined in Section 3.5.2.

208 A value MUST NOT be assigned to more than a single subject over its lifetime of use under any
209 circumstances. The unique ID should therefore be constructed in a fashion that reduces the probability of
210 non-technical or political considerations leading to a violation of this requirement, and any such violation
211 should be treated as a potential security risk to the relying parties to which the value may have been
212 given.

213 The value MUST NOT be mappable by a relying party into a non-pairwise identifier for the subject
214 through ordinary effort. This precludes the degenerate case of providing a non-pairwise value to all
215 relying parties for a given subject.

216 Relying parties should not treat this identifier as an email address for the subject as it is unlikely (though
217 not precluded) for it to be valid for that purpose. Most organizations will find that existing email address
218 values will not serve well as values for this Attribute.

219 The unique ID should not change as a result of a change to any other data associated with the subject
220 (e.g., name, email address, age, organizational role).

221 Assuming a particular scope, a given subject MUST be identified with a different, though consistent,
222 unique ID for each relying party to which a value is provided; however, the relationship between relying
223 parties and SAML entities is not defined by this profile and is interpreted from the perspective of the
224 asserting party. For example, in the context of the SAML Web Browser SSO profile [SAMLProf] it would
225 be typical for an Identity Provider to base its notion of a relying party boundary on a single Service
226 Provider's entity identifier, but that is not specifically required by this profile. The boundary MAY be larger
227 or even smaller, at the Identity Provider's discretion or as addressed by additional profiles.

228 While it will be common in many deployments to limit values with a given scope to a single asserting
229 party, this is ultimately left to the discretion of the relying party and the use case. It is unspecified by this
230 profile whether a given value provided by two or more asserting parties correspond to the same subject.
231 This would depend on out of band arrangements made between the parties. ~~But, in such cases, the~~
232 ~~"standard"~~ **If you want a relying party to understand that two or more asserting parties are referring to the**
233 **same subject, using the general-purpose** subject identifier defined in Section 3.3 is likely to be a much
234 better choice.

235 3.4.3 Implementation Strategies

236 Supporting pairwise identifiers typically involves either the generation and storage of random values, or
237 the computation of reproducible values that can be produced on demand but need not be stored. This
238 profile does not require any specific approach, but implementers should be aware that some techniques
239 for computing values may result in an unacceptable risk of case conflicts. For example, a salted hash
240 over a seed identifier together with a relying party identifier produces a "safe" generated value, but
241 becomes unsafe when encoded in Base64 [RFC4648] (and the allowable character set is defined in part
242 to preclude this choice). However, encoding hashes in Base32 [RFC4648] is a safe choice, and the
243 equals sign is included in the allowable character set to accommodate this.

244 3.4.4 Differences from "persistent" NameIDs

245 This Attribute is a direct replacement for the `urn:oasis:names:tc:SAML:2.0:nameid-`
246 `format:persistent` NameID Format defined in SAML [SAML2Core]. There are obvious syntactic
247 differences, in a deliberate attempt at simplification. The XML syntax and data "triple" are replaced with a
248 simpler id/scope pair encoded into a string, and the awkward use of a pair of URIs to qualify the value is
249 replaced with a simpler, shorter, and more flexible approach that more easily emulates the email address
250 syntax required by many applications, and decouples identifier scoping from SAML entity naming.

251 One functional gap is the interoperable mechanism of SAML "affiliations" to group entities for the purpose
252 of targeting pairwise identifiers to multiple Service Providers, which was ~~based~~ designed into the SAML
253 protocol. It has been left out of this profile due to the general lack of adoption by implementers or
254 deployers in the intervening years since the publication of the standard. Were there demand, it could be
255 incorporated into a future revision.

256 3.4.5 Example

257 The following is an example of the SAML Attribute defined in this section:

```
258 <saml:Attribute Name="urn:oasis:names:tc:SAML:attribute:pairwise-id"  
259     NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri">  
260     <saml:AttributeValue>  
261     HA2TKNZZGE2TOZDCGMZWKOLDHQBQWIMBSGM4TGZBYGUYGINRQHAYTINBZGYZDOZBZMZRGKNZTME3TMN  
262     BXGYTYIOBYGMYWKNLFFMYDAYY=@osu.edu  
263     </saml:AttributeValue>  
264 </saml:Attribute>
```

265 3.5 Considerations for SAML Profiles

266 The Attributes defined in this profile are designed to be used in conjunction with any SAML profiles that
267 support the use of SAML Attributes, though its predominant expected use is with the various SAML single
268 sign-on profiles [SAML2Prof] such as the Web Browser SSO Profile and Enhanced Client or Proxy (ECP)
269 Profile.

270 3.5.1 Requirements Signaling

271 In the event that SAML metadata [SAML2Meta] is used, a relying party MUST express its identifier
272 requirements by including an `<mdattr:EntityAttribute>` extension [MetaAttr] in its metadata
273 containing the following Attribute:

274 **Name:** `urn:oasis:names:tc:SAML:profiles:subject-id:req`

275 **NameFormat:** `urn:oasis:names:tc:SAML:2.0:attrname-format:uri`

276 This Attribute, MUST contain exactly one `<saml:AttributeValue>` element, whose `xsi:type`
277 SHOULD be absent or if present MUST BE bound to the XML Schema `xsd:string` data type
278 [XMLSCHEMA-2].

279 The value MUST be one of the following, signaling the corresponding requirement:

- 280 • `subject-id`
- 281 ◦ The relying party requires the standard identifier Attribute defined in Section 3.3.

- 282 • pairwise-id
- 283 ◦ The relying party requires the pair-wise identifier Attribute defined in Section 3.4.
- 284 • none
- 285 ◦ The relying party does not require any subject identifier and is designed to operate without a
- 286 specific user identity (e.g., with authorization based on non-identifying data).
- 287 • any
- 288 ◦ The relying party will accept any of the identifier Attributes defined in this profile but requires
- 289 at least one.

290 This profile does not define specific normative behavior on the part of asserting parties in response to this
291 metadata, but it is expected that other profiles will do so in the future.

292 This profile does not provide (nor preclude) any guidance around the use of the
293 <md:RequestedAttribute> element for signaling requirements, but notably it is impossible without
294 additional specification work to reflect the semantics of the any value defined above using that
295 mechanism.

296 3.5.2 Scope Filtering

297 A critical obligation of any federated relying party is to limit the ability of asserting parties to supply
298 identifiers they are not authorized to assert. While this is commonly done in SAML based on the asserting
299 party's entityID, that approach generally requires artificially combining an identifier's value with the
300 entityID for storage and comparison. The Attributes defined in this specification include a scope
301 expression in their values that makes this step unnecessary but introduce the need for a binding between
302 scopes and asserting parties.

303 In the event that SAML metadata [SAML2Meta] is used, an asserting party MUST express the scope(s)
304 within which it will issue subject identifiers by including one or more <shibmd:Scope> elements (defined
305 below) in its metadata.

306 The <shibmd:Scope> element MUST appear within the <md:Extensions> element of an
307 <md:EntityDescriptor> element or the <md:Extensions> element of an assertion-issuing role
308 descriptor element (such as <md:IDPSSODescriptor> or
309 <md:AttributeAuthorityDescriptor>). The use of the <shibmd:Scope> element outside of
310 these contexts is undefined.

311 When a <shibmd:Scope> element appears in the <md:Extensions> element of an
312 <md:EntityDescriptor> element it applies to all descendant role descriptor elements. That is to say,
313 this usage is equivalent to putting an identical <shibmd:Scope> on every descendant role descriptor.

314 In processing the identifiers defined in this specification, the scope component is intended to be
315 compared against the collection of scopes designated as permissible for the asserting party in its
316 metadata. Any values whose scope is not permissible SHOULD be discarded, thus ensuring that all
317 scoped identifier values accepted by the relying party and passed to an application will have permissible
318 scopes.

319 The final arbiter of any such policy is the relying party, and metadata-based policy via this extension MAY
320 be supplemented or overridden by local policy.

321 This profile does not mandate a particular exchange or trust model by which the metadata and its content
322 are expected to be verified, but it is common for metadata containing this extension to come from a
323 trusted third party able to independently validate an asserting party's right to the claimed scope(s).

324 For compatibility reasons, the matching between values of this extension and the scope component of the
325 identifiers defined in this specification is done in a case-sensitive manner. To avoid unintentional
326 mismatches, it is RECOMMENDED that scopes be expressed in lower case (both in this extension and in
327 the values themselves, per Section 3.3.1).

328 Finally, note that the concept of scope and scope filtering need not be limited to the Attributes defined in
329 this specification, but such applicability is outside the purview of this specification.

330 3.5.2.1 Element <shibmd:Scope>

331 This element extends the **xsd:string** schema type with the following attribute:

332 `regexp` [Optional]

333 Boolean regular expression indicator

334 Each <shibmd:Scope> element's text content identifies a permissible identifier scope for the issuing
335 entity/role, per the definition of "scope" in Section 3.3.1.

336 If `regexp` is "false" or "0" or absent, the text content of the <shibmd:Scope> element is interpreted
337 as the literal scope value (matched case-sensitively for compatibility reasons, see below).

338 If `regexp` is "true" or "1", the text content of the <shibmd:Scope> element is interpreted as
339 specifying a regular expression (also see below).

340 The schema for the <shibmd:Scope> element is as follows:

```
341 <element name="Scope">  
342   <complexType>  
343     <simpleContent>  
344       <extension base="string">  
345         <attribute name="regexp" type="boolean" use="optional"  
346         default="false"/>  
347       </extension>  
348     </simpleContent>  
349   </complexType>  
350 </element>
```

351 3.5.2.2 Usage Considerations

352 Because this extension has an extensive history of use, its definition is not optimal and there are some
353 important caveats.

354 Comparison of literal scope values expressed via this extension is defined to be case-sensitive, despite
355 the overall rule for comparison of the Attributes defined in this specification as case-insensitive. This is for
356 reasons of historical compatibility and generality, and is easily addressed by adhering to this
357 specification's guidance to express scopes in lower-case.

358 The XML Schema definition of the <shibmd:Scope> element includes an explicit default value for the
359 `regexp` attribute. One effect of this is that the meaning of an omitted `regexp` attribute will be different for
360 a schema-validating processor than for one which does not schema-validate. If a document containing a
361 <shibmd:Scope> element with an omitted `regexp` attribute is digitally signed, the signature value will
362 therefore depend on whether the signer schema-validates, and validation of such a signature will only
363 succeed if the validator has chosen to take the same approach.

364 To ensure interoperability between signers and validators no matter whether each schema validates or
365 does not, it is therefore strongly RECOMMENDED that any <shibmd:Scope> element appearing in a
366 metadata document that is to be digitally signed incorporate an explicit `regexp` attribute (i.e.,
367 `regexp="false"` or `regexp="0"` SHOULD always be used instead of an omitted `regexp` attribute).

368 Furthermore, great care should be taken in using `regexp="true"` as it is extremely easy to write regular
369 expressions which match the desired patterns but also permit additional, sometimes surprising, matches.
370 This can lead to an asserting party being permitted a wider range of scopes than intended. Common
371 mistakes are not appropriately quoting meta-characters such as ". ", and not appropriately anchoring the
372 ends of the match.

373 Additionally, regular expressions are implemented with a degree of inconsistency in specifics and
374 features and this extension does not include a formal reference to any single "standard" version of regular
375 expressions because it would be impractical to force SAML implementations to follow only one.

376 As a result, deployments SHOULD avoid the use of regular expressions and implementations MAY omit
377 support for this capability and reject its use. Its presence is again an issue of legacy compatibility
378 ~~more~~more-so than current practice.

379 3.5.3 NameID Considerations

380 While the Attributes defined in this profile have as a goal the explicit replacement of the `<saml:NameID>`
381 element as a means of subject identification, it is certainly possible to compose them with existing
382 NameID usage provided the same subject is being identified. This can also serve as a migration strategy
383 for existing applications.

384 Some profiles such as the Single Logout Profile [SAML2Prof] require the use of a `<saml:NameID>`
385 element, which implies the earlier use of a NameID. In such cases, it is RECOMMENDED that the
386 `urn:oasis:names:tc:SAML:2.0:nameid-format:transient` NameID Format be used.

387 This specification does not define any syntax by which the SAML Attributes defined within would be used
388 directly within the NameID construct. Such use is discouraged, but is not precluded by this specification.
389 In practice, the most appropriate mechanism to express any string-valued SAML Attribute in a
390 `<saml:NameID>` element is to express the Attribute's Name as a Format and omit any qualifiers, and
391 such an approach is safe to use with the Attributes defined in this specification.

392 3.5.4 Security Considerations

393 All identifiers have inherent and generally well-understood concerns; most applications traditionally
394 associate users directly with resources, privileges, and/or data by uniquely identifying those users and
395 remembering them during subsequent interactions. Federated protocols don't alter these concerns, but
396 can complicate them because of the particular issues introduced by multiple asserting parties that may
397 (but usually do not) share a common identifier namespace.

398 Applications not originally designed to support federation often treat each asserting party as a kind of silo
399 of identity, and the identifiers used are inherently segregated by these silos such that global uniqueness
400 (or lack thereof) is irrelevant. In such cases, the asserting party's own identifier acts as an implicit "scope"
401 for all of the identifiers it asserts. In some cases, a lack of this implicit enforcement of scope has led to
402 security vulnerabilities involving impersonation of users across asserting parties, demonstrating that, no
403 matter what kind of identifier is used, some form of scoping of user identifiers is an absolute necessity in
404 federated systems. This requirement is more obvious when applications are truly federated and combine
405 identifiers from multiple asserting parties within a data set.

406 The identifier attributes defined in this specification contain an explicit scope as part of their syntax,
407 providing globally uniqueness, but, more subtly, creating indirection between the scopes and the
408 asserting party or parties that provide them. That is, the scope is explicit, but the relationship between
409 that scope and an asserting party is indirect, at least when looking solely at the identifier. This indirection
410 adds power, in that use cases involving identity linking between asserting parties become simpler to
411 support, and it adds simplicity from the point of view of safe handling of identifier values since the scope
412 is harder to "lose" or ignore. But this also adds complexity because a policy decision is required to
413 authorize an asserting party to supply identifiers in a given scope.

414 As an example, consider an identifier such as "abcdef123@osu.edu"; SAML doesn't define anything in its
415 core machinery that associates "osu.edu" with the Identity Provider representing The Ohio State
416 University. Domain ownership proofs are of course a common and sensible practice to use to establish
417 this association, but nothing in SAML specifies that, so it's an additional step and is not represented "in-
418 band".

419 This specification does not impose a single such policy layer, but does standardize (in Section 3.5.2) a
420 long-standing SAML metadata extension that associates authorized scope values with asserting parties.
421 By using SAML metadata, the problem of self-assertion is addressed; if an asserting party were able to
422 self-authorize its ability to supply an identifier in a different asserting party's scope, impersonation
423 becomes easy. Communities that rely on curated, third-party sources of metadata have a vehicle for
424 automating policy around scopes, and for off-loading domain/scope verification. Thus, use of metadata in
425 this fashion and use of scoped identifiers become mutually reinforcing.

426 4 Conformance

427 4.1 Conformance Clause 1: Asserting Party Implementations

428 An asserting party implementation conforms to this specification if it can be configured to produce both
429 identifier Attributes conforming to the normative requirements in Sections 3.3 and 3.4.

430 If the asserting party implementation provides a mechanism for generation and/or publication of SAML
431 metadata, then it MUST support the inclusion of the extension defined in Section 3.5.2.

432 4.2 Conformance Clause 2: Relying Party Implementations

433 A relying party implementation conforms to this specification if it can be configured to consume neither,
434 either, and both of the two identifier Attributes conforming to the normative requirements in Sections 3.3
435 and 3.4.

436 If the relying party implementation provides a mechanism for generation and/or publication of SAML
437 metadata, then it MUST support the inclusion of the extension defined in Section 3.5.1.

438 If the relying party supports the consumption of SAML metadata, then it MUST support configuring its
439 acceptance of values of the Attributes defined in this specification based on authorization of their scopes
440 via the extension defined in Section 3.5.2.

441 Appendix A Acknowledgments

442 The following individuals have participated in the creation of this specification and are gratefully acknowl-
443 edged:

Scott Cantor, Internet2
Thomas Hardjono, MIT
Mohammad Jafari, Veterans Health Administration
Hal Lockhart, Oracle Corporation
Madalina Sultan, Connectis

Contributors to the InCommon Deployment Profile Working Group
Past contributors to the Shibboleth Project

444 Appendix B Revision History

Revision	Date	Editor	Changes Made
WD 01	30 Aug 2017	Scott Cantor	Initial draft
WD 02	13 Sep 2017	Scott Cantor	Added considerations for other profiles
WD 03	15 Sep 2017	Scott Cantor	Added hyphen as legal character in unique ID
WD 04	1 Feb 2018	Scott Cantor	Many nits, missing references, clarifying changes in response to public review
WD 05	3 Jul 2018	Scott Cantor	Second public review updates
WD 06	5 Sep 2018	Scott Cantor	Expansion of scope to include, umm, Scope
<u>WD 07</u>	<u>16 Nov 2018</u>	<u>Scott Cantor</u>	<u>Editorial nits and corrections for final vote</u>

445